



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05


Report Template Revision Date: 2021-11-03

Test Report


Report No.: CQASZ20231001943E-01
Applicant: Shenzhen Itian Technology Co.,LTD
Address of Applicant: 6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District, Shenzhen, China
Equipment Under Test (EUT):
Product: 3 in 1 Wireless Charger
Model No.: F16S, F16G, F16A
Test Model No.: F16S
Brand Name: ITIAN
FCC ID: 2AUDO-F16SF16GF16A
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2023-10-27
Date of Test: 2023-10-27 to 2023-11-21
Date of Issue: 2023-11-21
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above


Tested By:


(Joe Wang)

Reviewed By:


(Timo Lei)

Approved By:


(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20231001943E-01	Rev.01	Initial report	2023-11-21

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.215	ANSI C63.10 2013	PASS
Radiated Emission , Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.209	ANSI C63.10 2013	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
4.4 TEST ENVIRONMENT	6
4.5 DESCRIPTION OF SUPPORT UNITS	6
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
4.7 TEST LOCATION	7
4.8 TEST FACILITY	7
4.9 DEVIATION FROM STANDARDS	7
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
4.11 EQUIPMENT LIST	8
5 TEST RESULTS AND MEASUREMENT DATA	9
5.1 ANTENNA REQUIREMENT	9
5.2 CONDUCTED EMISSIONS	10
5.3 20dB OCCUPY BANDWIDTH	15
5.4 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS	17
5.4.1 <i>Spurious Emissions</i>	17
6 PHOTOGRAPHS - EUT TEST SETUP	24
6.1 RADIATED EMISSION	24
6.2 CONDUCTED EMISSION	25
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	26

4 General Information

4.1 Client Information

Applicant:	Shenzhen Itian Technology Co.,LTD
Address of Applicant:	6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen Itian Technology Co.,LTD
Address of Manufacturer:	6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District, Shenzhen, China
Factory:	Shenzhen Itian Technology Co.,LTD
Address of Factory:	6F, Building D, Phase 2nd, Anfeng Industrial Park, Dalang Street, Longhua District, Shenzhen, China

4.2 General Description of EUT

Product Name:	3 in 1 Wireless Charger
Model No.:	F16S, F16G, F16A
Test Model No.:	F16S
Brand Name:	ITIAN
Software Version:	F16-1024N-V1
Hardware Version:	F16-1024-5004-V12
Power Supply:	DC 5V=2A, 9V=2A

4.3 Product Specification subjective to this standard

Equipment Category:	Non-ISM frequency
Operation Frequency range:	110kHz~205kHz
Modulation Type:	ASK
Antenna Type:	Induction coil
Antenna Gain:	0dBi
Power:	Output: 28W(Max)

Note:

1. In section 15.31(m), regards to the operating frequency range less 1 MHz.

4.4 Test Environment

Operating Environment:	
Radiated Emissions:	
Temperature:	25.5 °C
Humidity:	53 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.5 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	27.1 °C
Humidity:	56 % RH
Atmospheric Pressure:	1009 mbar
Test Mode:	
Mode a:	Keep the EUT Wireless Charging pad for Galaxy Watch Out Put 3W
Mode b:	Keep the EUT Wireless Charging pad for Wireless1 Out Put 5W
Mode c:	Keep the EUT Wireless Charging pad for Wireless1 Out Put 7.5W
Mode d:	Keep the EUT Wireless Charging pad for Wireless1 Out Put 10W
Mode e:	Keep the EUT Wireless Charging pad for Wireless1 Out Put 15W (MAX)
Mode f:	Keep the EUT Wireless Charging pad for Wireless2 Out Put 5W
Mode g:	Keep the EUT Wireless Charging pad for Wireless2 Out Put 7.5W
Mode h:	Keep the EUT Wireless Charging pad for Wireless2 Out Put 10W (MAX)
Mode i:	Keep the EUT Wireless Charging pad for Wireless1+for Wireless2 +for Galaxy Watch Out Put 28W (Total MAX)
Note: The above test modes all include full load,empty load,and half load, The worst-case state reflected in this report is the fully loaded state	

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	/	LPL-C010050200Z	/	CQA
Wireless charge load	/	/	/	CQA
Samsung	Galaxy	Watch	/	CQA

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Occupied Bandwidth	1.1%	(1)
4	Temperature test	0.8℃	(1)
5	Humidity test	2.0%	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.7 Test Location

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

• A2LA (Certificate No. 4742.01)

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• FCC Registration No.: 522263

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Deviation from Standards

None.

4.10 Other Information Requested by the Customer


None.

4.11 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2023/9/8	2024/9/7
Spectrum analyzer	R&S	FSU26	CQA-038	2023/9/8	2024/9/7
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2023/9/8	2024/9/7
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/9/16	2024/9/15
Bilog Antenna	R&S	HL562	CQA-011	2021/9/16	2024/9/15
Horn Antenna	R&S	HF906	CQA-012	2021/9/16	2024/9/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/9/16	2024/9/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2023/9/8	2024/9/7
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2023/9/8	2024/9/7
Antenna Connector	CQA	RFC-01	CQA-080	2023/9/8	2024/9/7
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2023/9/8	2024/9/7
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2023/9/8	2024/9/7
EMI Test Receiver	R&S	ESR7	CQA-005	2023/9/8	2024/9/7
LISN	R&S	ENV216	CQA-003	2023/9/8	2024/9/7
Coaxial cable	CQA	N/A	CQA-C009	2023/9/8	2024/9/7
DC power	KEYSIGHT	E3631A	CQA-028	2023/9/8	2024/9/7

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	
The antenna is Induction coil. The best case gain of the antenna is 0dBi.	

5.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
Test Setup:			
Test Results:	Pass		

Measurement Data

The worst case:

Mode e:

Live line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.440	28.24	9.65	37.89	47.06	-9.17	Average	Line
2	0.440	30.80	9.65	40.45	57.06	-16.61	QP	Line
3 PP	0.880	27.18	9.78	36.96	46.00	-9.04	Average	Line
4 QP	0.880	29.87	9.78	39.65	56.00	-16.35	QP	Line
5	1.175	21.94	10.15	32.09	46.00	-13.91	Average	Line
6	1.175	26.51	10.15	36.66	56.00	-19.34	QP	Line
7	1.470	20.25	10.78	31.03	46.00	-14.97	Average	Line
8	1.470	25.08	10.78	35.86	56.00	-20.14	QP	Line
9	1.765	20.39	11.30	31.69	46.00	-14.31	Average	Line
10	1.765	24.67	11.30	35.97	56.00	-20.03	QP	Line
11	2.055	19.75	11.59	31.34	46.00	-14.66	Average	Line
12	2.055	23.30	11.59	34.89	56.00	-21.11	QP	Line


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

The worst case:

Mode e:

Neutral line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	28.07	9.68	37.75	55.46	-17.71	Average	Neutral
2	QP 0.160	39.50	9.68	49.18	65.46	-16.28	QP	Neutral
3	0.195	23.07	9.62	32.69	53.82	-21.13	Average	Neutral
4	QP 0.195	33.47	9.62	43.09	63.82	-20.73	QP	Neutral
5	PP 0.440	28.57	9.64	38.21	47.06	-8.85	Average	Neutral
6	QP 0.440	31.08	9.64	40.72	57.06	-16.34	QP	Neutral
7	0.735	25.98	9.88	35.86	46.00	-10.14	Average	Neutral
8	QP 0.735	28.93	9.88	38.81	56.00	-17.19	QP	Neutral
9	1.025	25.33	9.70	35.03	46.00	-10.97	Average	Neutral
10	QP 1.025	28.74	9.70	38.44	56.00	-17.56	QP	Neutral
11	1.615	17.50	9.73	27.23	46.00	-18.77	Average	Neutral
12	QP 1.615	22.57	9.73	32.30	56.00	-23.70	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

The worst case:

Mode i:

Live line:



	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.180	34.08	9.64	43.72	54.49	-10.77	Average	Line
2	0.180	39.17	9.64	48.81	64.49	-15.68	QP	Line
3	0.885	28.32	9.78	38.10	46.00	-7.90	Average	Line
4 QP	0.885	30.78	9.78	40.56	56.00	-15.44	QP	Line
5 PP	1.240	28.20	10.30	38.50	46.00	-7.50	Average	Line
6	1.240	30.23	10.30	40.53	56.00	-15.47	QP	Line
7	1.740	24.87	11.26	36.13	46.00	-9.87	Average	Line
8	1.740	27.54	11.26	38.80	56.00	-17.20	QP	Line
9	2.370	22.94	11.29	34.23	46.00	-11.77	Average	Line
10	2.370	25.15	11.29	36.44	56.00	-19.56	QP	Line
11	3.005	24.57	10.78	35.35	46.00	-10.65	Average	Line
12	3.005	26.02	10.78	36.80	56.00	-19.20	QP	Line


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

The worst case:

Mode i:

Neutral line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	31.34	9.70	41.04	56.00	-14.96	Average	Neutral
2 QP	0.150	44.82	9.70	54.52	66.00	-11.48	QP	Neutral
3	0.175	36.19	9.65	45.84	54.72	-8.88	Average	Neutral
4	0.175	40.69	9.65	50.34	64.72	-14.38	QP	Neutral
5	0.195	25.38	9.62	35.00	53.82	-18.82	Average	Neutral
6	0.195	35.71	9.62	45.33	63.82	-18.49	QP	Neutral
7	0.525	24.34	9.72	34.06	46.00	-11.94	Average	Neutral
8	0.525	27.95	9.72	37.67	56.00	-18.33	QP	Neutral
9	0.880	28.61	9.78	38.39	46.00	-7.61	Average	Neutral
10	0.880	29.64	9.78	39.42	56.00	-16.58	QP	Neutral
11 PP	1.230	32.36	9.71	42.07	46.00	-3.93	Average	Neutral
12	1.230	34.12	9.71	43.83	56.00	-12.17	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: Offset=Cable loss+ attenuation factor.</p>
Test Results:	Pass

Measurement Data

Mode e		
Test Frequency (kHz)	20dB Occupy Bandwidth (Hz)	Result
146.37	2435	Pass

Mode i		
Test Frequency (kHz)	20dB Occupy Bandwidth (Hz)	Result
143.41	2403	Pass

Test plot as follows:



5.4 Radiated Spurious Emission & Restricted bands

5.4.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the

	<p>measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Repeat above procedures until all frequencies measured was complete.</p>
Test Results:	Pass

Radiated Emission below 9k~30MHz	
the worst case	
Test mode:	Mode i

Frequency MHz	Detector	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) Peak	Limit dB(uV/m) Average	Margin dB	Pass/Fail
0.126	AV	40.91	19.80	60.71	105.57	-44.87	Pass
0.122	AV	39.04	19.80	58.84	105.90	-47.06	Pass
0.335	AV	38.51	19.80	58.31	97.12	-38.81	Pass
0.381	QP	38.18	19.80	57.98	95.99	-38.02	Pass
1.185	QP	16.58	19.70	36.28	66.13	-29.84	Pass
7.983	QP	10.39	19.70	30.09	69.54	-39.45	Pass

Note: No other emissions found between lowest internal used/generated frequencies to 30MHz. The peak level of the emission is less than the average limit, so the average level shall be less than 1 the limit without test.


Radiated Emission

30MHz~1GHz, the worst case

Test mode:

Mode e

Horizontal



	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	56.00	21.14	6.65	27.79	40.00	-12.21	Peak	HORIZONTAL
2	70.34	20.80	8.21	29.01	40.00	-10.99	Peak	HORIZONTAL
3	131.76	23.61	9.93	33.54	43.50	-9.96	Peak	HORIZONTAL
4	199.99	24.47	8.49	32.96	43.50	-10.54	Peak	HORIZONTAL
5	250.30	23.76	12.09	35.85	46.00	-10.15	Peak	HORIZONTAL
6 pp	356.68	22.51	15.11	37.62	46.00	-8.38	Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level = Receiver Reading + Antenna Factor + Cable Factor

30MHz~1GHz, the worst case

Test mode:

Mode e

Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	46.50	19.43	9.73	29.16	40.00	-10.84	Peak	VERTICAL
2	56.00	23.30	6.65	29.95	40.00	-10.05	Peak	VERTICAL
3 pp	66.50	25.72	7.05	32.77	40.00	-7.23	Peak	VERTICAL
4	130.38	20.61	10.23	30.84	43.50	-12.66	Peak	VERTICAL
5	252.06	13.81	12.14	25.95	46.00	-20.05	Peak	VERTICAL
6	833.32	9.98	23.97	33.95	46.00	-12.05	Peak	VERTICAL


Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor

30MHz~1GHz, the worst case

Test mode: Mode i Horizontal



	Read		Limit	Over			
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	57.39	24.46	6.08	30.54	40.00	-9.46 Peak	HORIZONTAL
2	71.83	23.31	8.45	31.76	40.00	-8.24 Peak	HORIZONTAL
3	135.51	28.73	9.07	37.80	43.50	-5.70 Peak	HORIZONTAL
4	271.32	25.38	12.78	38.16	46.00	-7.84 Peak	HORIZONTAL
5	298.27	26.43	13.68	40.11	46.00	-5.89 Peak	HORIZONTAL
6 pp	341.98	25.83	14.76	40.59	46.00	-5.41 Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level =Receiver Reading + Antenna Factor + Cable Factor

30MHz~1GHz, the worst case

Test mode:

Mode i

Vertical



	Read	Limit	Over					
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase	
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			
1	51.30	23.76	7.82	31.58	40.00	-8.42	Peak	VERTICAL
2	56.79	25.69	6.33	32.02	40.00	-7.98	Peak	VERTICAL
3 pp	66.73	28.39	7.13	35.52	40.00	-4.48	Peak	VERTICAL
4	109.80	19.58	10.18	29.76	43.50	-13.74	Peak	VERTICAL
5	130.38	21.93	10.23	32.16	43.50	-11.34	Peak	VERTICAL
6	290.02	16.19	13.40	29.59	46.00	-16.41	Peak	VERTICAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9kHz~30MHz:



30MHz~1GHz:



6.2 Conducted Emission



7 Photographs - EUT Constructional Details

