



# FCC Radio Test Report

**FCC ID: FSUGMZLB**

This report concerns (check one): ☒ Original Grant ☐ Class II Change

**Project No.** : 1407C024C  
**Equipment** : 2.4GHz Wireless Keyboard and Mouse Combo  
**Model Name** : GK-140001/R  
**Applicant** : KYE SYSTEMS CORP.  
**Address** : No.492, Sec.5, Chongxin Rd,  
Sanchong Dist, New Taipei City  
24160, Taiwan( R.O.C)

**Tested by:** BTL Inc. EMC Laboratory  
**Date of Receipt:** Jul. 01, 2014  
**Date of Test:** Jul. 01, 2014~ Jul. 10, 2014  
**Issued Date:** Jul. 11, 2014

**Testing Engineer** : David Mao  
(David Mao)

**Technical Manager** : Leo Hung  
(Leo Hung)

**Authorized Signatory** : Steven Lu  
(Steven Lu)

## BTL INC.

No.3, Jinshagang 1st Road, Shixia,  
Dalang Town, Dongguan, China.  
TEL: 0769-8318-3000 FAX: 0769-8319-6000



### **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (NML) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

### **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

| <b>Table of Contents</b>                                     | <b>Page</b> |
|--------------------------------------------------------------|-------------|
| <b>1 . CERTIFICATION</b>                                     | <b>7</b>    |
| <b>2 . SUMMARY OF TEST RESULTS</b>                           | <b>8</b>    |
| 2.1 TEST FACILITY                                            | 9           |
| 2.2 MEASUREMENT UNCERTAINTY                                  | 9           |
| <b>3 . GENERAL INFORMATION</b>                               | <b>10</b>   |
| 3.1 GENERAL DESCRIPTION OF EUT                               | 10          |
| 3.2 DESCRIPTION OF TEST MODES                                | 12          |
| 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING             | 12          |
| 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 13          |
| 3.5 DESCRIPTION OF SUPPORT UNITS                             | 14          |
| <b>4 . EMC EMISSION TEST</b>                                 | <b>15</b>   |
| 4.1 CONDUCTED EMISSION MEASUREMENT                           | 15          |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS                   | 15          |
| 4.1.2 TEST PROCEDURE                                         | 15          |
| 4.1.3 DEVIATION FROM TEST STANDARD                           | 15          |
| 4.1.4 TEST SETUP                                             | 16          |
| 4.1.5 EUT OPERATING CONDITIONS                               | 16          |
| 4.1.6 EUT TEST CONDITIONS                                    | 16          |
| 4.1.7 TEST RESULTS                                           | 16          |
| 4.2 RADIATED EMISSION MEASUREMENT                            | 17          |
| 4.2.1 RADIATED EMISSION LIMITS                               | 17          |
| 4.2.2 TEST PROCEDURE                                         | 18          |
| 4.2.3 DEVIATION FROM TEST STANDARD                           | 18          |
| 4.2.4 TEST SETUP                                             | 19          |
| 4.2.5 EUT OPERATING CONDITIONS                               | 20          |
| 4.2.6 EUT TEST CONDITIONS                                    | 20          |
| 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)                           | 20          |
| 4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)               | 21          |
| 4.2.9 TEST RESULTS (ABOVE 1000 MHZ)                          | 21          |
| <b>5 . NUMBER OF HOPPING CHANNEL</b>                         | <b>22</b>   |
| 5.1 APPLIED PROCEDURES                                       | 22          |
| 5.1.1 TEST PROCEDURE                                         | 22          |
| 5.1.2 DEVIATION FROM STANDARD                                | 22          |
| 5.1.3 TEST SETUP                                             | 22          |
| 5.1.4 EUT OPERATION CONDITIONS                               | 22          |
| 5.1.5 EUT TEST CONDITIONS                                    | 22          |
| 5.1.6 TEST RESULTS                                           | 22          |

**Table of Contents****Page**

|                                                   |           |
|---------------------------------------------------|-----------|
| <b>6 . AVERAGE TIME OF OCCUPANCY</b>              | <b>23</b> |
| <b>6.1 APPLIED PROCEDURES / LIMIT</b>             | <b>23</b> |
| 6.1.1 TEST PROCEDURE                              | 23        |
| 6.1.2 DEVIATION FROM STANDARD                     | 23        |
| 6.1.3 TEST SETUP                                  | 23        |
| 6.1.4 EUT OPERATION CONDITIONS                    | 24        |
| 6.1.5 EUT TEST CONDITIONS                         | 24        |
| 6.1.6 TEST RESULTS                                | 24        |
| <b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b> | <b>25</b> |
| <b>7.1 APPLIED PROCEDURES / LIMIT</b>             | <b>25</b> |
| 7.1.1 TEST PROCEDURE                              | 25        |
| 7.1.2 DEVIATION FROM STANDARD                     | 25        |
| 7.1.3 TEST SETUP                                  | 25        |
| 7.1.4 EUT TEST CONDITIONS                         | 25        |
| 7.1.5 TEST RESULTS                                | 25        |
| <b>8 . BANDWIDTH TEST</b>                         | <b>26</b> |
| <b>8.1 APPLIED PROCEDURES</b>                     | <b>26</b> |
| 8.1.1 TEST PROCEDURE                              | 26        |
| 8.1.2 DEVIATION FROM STANDARD                     | 26        |
| 8.1.3 TEST SETUP                                  | 26        |
| 8.1.4 EUT OPERATION CONDITIONS                    | 26        |
| 8.1.5 EUT TEST CONDITIONS                         | 26        |
| 8.1.6 TEST RESULTS                                | 26        |
| <b>9 . PEAK OUTPUT POWER TEST</b>                 | <b>27</b> |
| <b>9.1 APPLIED PROCEDURES / LIMIT</b>             | <b>27</b> |
| 9.1.1 TEST PROCEDURE                              | 27        |
| 9.1.2 DEVIATION FROM STANDARD                     | 27        |
| 9.1.3 TEST SETUP                                  | 27        |
| 9.1.4 EUT OPERATION CONDITIONS                    | 27        |
| 9.1.5 EUT TEST CONDITIONS                         | 27        |
| 9.1.6 TEST RESULTS                                | 27        |
| <b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>   | <b>28</b> |
| <b>10.1 APPLIED PROCEDURES / LIMIT</b>            | <b>28</b> |
| 10.1.1 TEST PROCEDURE                             | 28        |
| 10.1.2 DEVIATION FROM STANDARD                    | 28        |
| 10.1.3 TEST SETUP                                 | 28        |
| 10.1.4 EUT OPERATION CONDITIONS                   | 28        |
| 10.1.5 EUT TEST CONDITIONS                        | 28        |
| 10.1.6 TEST RESULTS                               | 28        |

| <b>Table of Contents</b>                                     | <b>Page</b> |
|--------------------------------------------------------------|-------------|
| <b>11 . MEASUREMENT INSTRUMENTS LIST</b>                     | <b>29</b>   |
| <b>12 . EUT TEST PHOTO</b>                                   | <b>31</b>   |
| <b>ATTACHMENT A - CONDUCTED EMISSION</b>                     | <b>35</b>   |
| <b>ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)</b>         | <b>38</b>   |
| <b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>   | <b>40</b>   |
| <b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>      | <b>47</b>   |
| <b>ATTACHMENT E - NUMBER OF HOPPING CHANNEL</b>              | <b>60</b>   |
| <b>ATTACHMENT F - AVERAGE TIME OF OCCUPANCY</b>              | <b>62</b>   |
| <b>ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT</b> | <b>65</b>   |
| <b>ATTACHMENT H - BANDWIDTH</b>                              | <b>69</b>   |
| <b>ATTACHMENT I - PEAK OUTPUT POWER</b>                      | <b>72</b>   |
| <b>ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>    | <b>75</b>   |

**REPORT ISSUED HISTORY**

| Issued No.           | Description     | Issued Date   |
|----------------------|-----------------|---------------|
| NEI-FCCP-1-1407C024C | Original Issue. | Jul. 11, 2014 |

## 1. CERTIFICATION

Equipment : 2.4GHz Wireless Keyboard and Mouse Combo  
Brand Name : Genius  
Model Name : GK-140001/R  
Applicant : KYE SYSTEMS CORP  
Manufacturer : SHENZHEN SENBIZ INDUSTRY CO.,LTD  
Address : Building 11-12,XinQiao XinFa Industrial Zone, Shajing town, Bao An district,  
Shenzhen Guangdong,China  
Factory : SHENZHEN SENBIZ INDUSTRY CO.,LTD  
Address : Building A, No.11,First row,Xinfa Industrial Zone, XinQiao,Shajing Town,Bao'an  
District,Shenzhen,Guangdong,China  
Date of Test : Jul. 01, 2014 ~Jul. 10, 2014  
Test Item : ENGINEERING SAMPLE  
Standard(s) : FCC Part15, Subpart C : 2013 (15.247) / ANSI C63.4 : 2009 /  
FCC Public Notice DA 00-705, March 30, 2000.  
Canada RSS-210: 2010  
RSS-GEN Issue 3, Dec 2010

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-1407C024C) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Note: This report only records the test datas of model: GK-140001/R, receive sample.

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| Applied Standard(s): 47 CFR Part 15, Subpart C: 2013; |                                     |          |        |
|-------------------------------------------------------|-------------------------------------|----------|--------|
| Standard(s) Section                                   | Test Item                           | Judgment | Remark |
| FCC                                                   |                                     |          |        |
| 15.207                                                | Conducted Emission                  | PASS     |        |
| 15.247(d)                                             | Antenna conducted Spurious Emission | PASS     |        |
| 15.247<br>(a)(1)                                      | Hopping Channel Separation          | PASS     |        |
| 15.247<br>(b)(1)                                      | Peak Output Power                   | PASS     |        |
| 15.247(d)<br>15.209                                   | Radiated Spurious Emission          | PASS     |        |
| 15.247<br>(a)(1)(iii)                                 | Number of Hopping Frequency         | PASS     |        |
| 15.247<br>(a)(1)(iii)                                 | Dwell Time                          | PASS     |        |
| 15.205                                                | Restricted Bands                    | PASS     |        |
| 15.203                                                | Antenna Requirement                 | PASS     |        |

Note:

(1)" N/A" denotes test is not applicable in this test report

(2) According to FCC Public Notice DA 00-705, March 30, 2000.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dong Guan, China.523792

BTL's test firm number for FCC: 319330

BTL's test firm number for IC: 4428B-1

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

### A. Conducted Measurement :

| Test Site | Method | Measurement Frequency Range | U , (dB) | Note |
|-----------|--------|-----------------------------|----------|------|
| DG-C02    | CISPR  | 150 KHz ~ 30MHz             | 1.94     |      |

### B. Radiated Measurement :

| Test Site | Method | Measurement Frequency Range | Ant. H / V | U , (dB) | Note |
|-----------|--------|-----------------------------|------------|----------|------|
| DG-CB03   | CISPR  | 9KHz~30MHz                  | V          | 3.79     |      |
|           |        | 9KHz~0MHz                   | H          | 3.57     |      |
|           |        | 30MHz ~ 200MHz              | V          | 3.82     |      |
|           |        | 30MHz ~ 200MHz              | H          | 3.60     |      |
|           |        | 200MHz ~ 1,000MHz           | V          | 3.86     |      |
|           |        | 200MHz ~ 1,000MHz           | H          | 3.94     |      |
|           |        | 1GHz~18GHz                  | V          | 3.12     |      |
|           |        | 1GHz~18GHz                  | H          | 3.68     |      |
|           |        | 18GHz~40GHz                 | V          | 4.15     |      |
|           |        | 18GHz~40GHz                 | H          | 4.14     |      |

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                        |                                          |               |
|------------------------|------------------------------------------|---------------|
| Equipment              | 2.4GHz Wireless Keyboard and Mouse Combo |               |
| Brand Name             | Genius                                   |               |
| Model Name             | GK-140001/R                              |               |
| Model Difference       | N/A                                      |               |
| Output Power (Max.)    | Operation Frequency                      | 2402~2480 MHz |
|                        | Modulation Technology                    | DFSK          |
|                        | Bit Rate of Transmitter                  | 1Mbps         |
|                        | Output Power Max.                        | -6.69 dBm     |
| Power Source           | Supplier from PC USB port                |               |
| Power Rating           | DC 5V                                    |               |
| Connecting I/O Port(s) | Please refer to the User's Manual        |               |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

| Channel List |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 01           | 2402            | 19      | 2430            | 37      | 2458            |
| 02           | 2403            | 20      | 2430            | 38      | 2461            |
| 03           | 2404            | 21      | 2431            | 39      | 2462            |
| 04           | 2405            | 22      | 2433            | 40      | 2465            |
| 05           | 2407            | 23      | 2434            | 41      | 2466            |
| 06           | 2409            | 24      | 2435            | 42      | 2467            |
| 07           | 2410            | 25      | 2437            | 43      | 2468            |
| 08           | 2411            | 26      | 2438            | 44      | 2469            |
| 09           | 2413            | 27      | 2439            | 45      | 2470            |
| 10           | 2414            | 28      | 2441            | 46      | 2471            |
| 11           | 2415            | 29      | 2443            | 47      | 2473            |
| 12           | 2418            | 30      | 2447            | 48      | 2475            |
| 13           | 2421            | 31      | 2449            | 49      | 2476            |
| 14           | 2422            | 32      | 2450            | 50      | 2476            |
| 15           | 2425            | 33      | 2451            | 51      | 2477            |
| 16           | 2426            | 34      | 2453            | 52      | 2478            |
| 17           | 2427            | 35      | 2454            | 53      | 2479            |
| 18           | 2429            | 36      | 2455            | 54      | 2480            |

3 Table for Filed Antenna

| Ant. | Manufacturer | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|--------------|------------|--------------|-----------|------------|
| 1    | N/A          | N/A        | printed      | N/A       | 0          |

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description             |
|--------------|-------------------------|
| Mode 1       | TX Mode <b>Note (1)</b> |

| For Conducted Emission |                         |
|------------------------|-------------------------|
| Final Test Mode        | Description             |
| Mode 1                 | TX Mode <b>Note (1)</b> |

| For Radiated Emission |                         |
|-----------------------|-------------------------|
| Final Test Mode       | Description             |
| Mode 1                | TX Mode <b>Note (1)</b> |

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

**Note:**


(1) The measurements are performed at the high, middle, low available channels.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

| Test software version | Bluetest |          |          |
|-----------------------|----------|----------|----------|
| Frequency             | 2402 MHz | 2441 MHz | 2480 MHz |
| Parameters-1Mbps      | N/A      | N/A      | N/A      |

### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | FCC ID | Series No.   | Note |
|------|-----------|-----------|----------------|--------|--------------|------|
| E-1  | Notebook  | DELL      | INSPIRON 1420  | DOC    | JX193A01SDC2 |      |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| -    | -             | -            | -      |      |

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| Frequency (MHz) | Class A (dBuV) |         | Class B (dBuV) |           | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
|                 | Quasi-peak     | Average | Quasi-peak     | Average   |          |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * | CISPR    |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | CISPR    |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | CISPR    |
|                 |                |         |                |           |          |
| 0.15 -0.5       | 79.00          | 66.00   | 66 - 56 *      | 56 - 46 * | FCC      |
| 0.50 -5.0       | 73.00          | 60.00   | 56.00          | 46.00     | FCC      |
| 5.0 -30.0       | 73.00          | 60.00   | 60.00          | 50.00     | FCC      |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 KHz    |


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

## 4.1.4 TEST SETUP



**Note: 1.**Support units were connected to second LISN.

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

## 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

## 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

## 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of "Note". If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009~0.490        | 2400/F(KHz)                          | 300                              |
| 0.490~1.705        | 24000/F(KHz)                         | 30                               |
| 1.705~30.0         | 30                                   | 30                               |
| 30~88              | 100                                  | 3                                |
| 88~216             | 150                                  | 3                                |
| 216~960            | 200                                  | 3                                |
| 960~1000           | 500                                  | 3                                |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | dB(uV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | Peak                   | Average |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) =20log Emission level (uV/m).

| Spectrum Parameter                         | Setting                                          |
|--------------------------------------------|--------------------------------------------------|
| Attenuation                                | Auto                                             |
| Start Frequency                            | 1000 MHz                                         |
| Stop Frequency                             | 10th carrier harmonic                            |
| RBW / VBW<br>(emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Spectrum Receiver Parameter | Setting                            |
|-----------------------------|------------------------------------|
| Attenuation                 | Auto                               |
| Start ~ Stop Frequency      | 9KHz ~90KHz for PK/AVG detector    |
| Start ~ Stop Frequency      | 90KHz ~110KHz for QP detector      |
| Start ~ Stop Frequency      | 110KHz ~490KHz for PK/AVG detector |
| Start ~ Stop Frequency      | 490KHz ~30MHz for QP detector      |
| Start ~ Stop Frequency      | 30MHz~1000MHz for QP detector      |


**4.2.2 TEST PROCEDURE**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

**4.2.3 DEVIATION FROM TEST STANDARD**

No deviation

(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### **4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)**

**Please refer to the Attachment C.**

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

#### **4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

**Please refer to the Attachment D.**

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode of the emission
- (3) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (4) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (5) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

| FCC Part15 (15.247) , Subpart C |                           |                       |        |
|---------------------------------|---------------------------|-----------------------|--------|
| Section                         | Test Item                 | Frequency Range (MHz) | Result |
| 15.247(a)(1)(iii)               | Number of Hopping Channel | 2400-2483.5           | PASS   |

| Spectrum Parameters | Setting                     |
|---------------------|-----------------------------|
| Attenuation         | Auto                        |
| Span Frequency      | > Operating Frequency Range |
| RBW                 | 100 KHz                     |
| VBW                 | 100 KHz                     |
| Detector            | Peak                        |
| Trace               | Max Hold                    |
| Sweep Time          | Auto                        |

#### 5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |                           |        |                       |        |
|---------------------------------|---------------------------|--------|-----------------------|--------|
| Section                         | Test Item                 | Limit  | Frequency Range (MHz) | Result |
| 15.247(a)(1)(iii)               | Average Time of Occupancy | 0.4sec | 2400-2483.5           | PASS   |


#### 6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for packet transmitting.
- Measure the maximum time duration of one single pulse.
- Dwell time = [spreading rate/16] x duty-cycle x 0.4 seconds

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

**Please refer to the Attachment F**

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

| Spectrum Parameter | Setting                                       |
|--------------------|-----------------------------------------------|
| Attenuation        | Auto                                          |
| Span Frequency     | > Measurement Bandwidth or Channel Separation |
| RBW                | 30 KHz                                        |
| VBW                | 100 KHz                                       |
| Detector           | Peak                                          |
| Trace              | Max Hold                                      |
| Sweep Time         | Auto                                          |


#### 7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Attachment G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

| FCC Part15 (15.247) , Subpart C |           |                       |
|---------------------------------|-----------|-----------------------|
| Section                         | Test Item | Frequency Range (MHz) |
| 15.247(a)(2)                    | Bandwidth | 2400-2483.5           |

| Spectrum Parameter | Setting                                                 |
|--------------------|---------------------------------------------------------|
| Attenuation        | Auto                                                    |
| Span Frequency     | > Measurement Bandwidth or Channel Separation           |
| RBW                | 30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)   |
| VBW                | 100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation) |
| Detector           | Peak                                                    |
| Trace              | Max Hold                                                |
| Sweep Time         | Auto                                                    |

#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Attachment H

## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |                   |                     |                       |        |
|---------------------------------|-------------------|---------------------|-----------------------|--------|
| Section                         | Test Item         | Limit               | Frequency Range (MHz) | Result |
| 15.247(b)(1)                    | Peak Output Power | 0.125 Watt or 21dBm | 2400-2483.5           | PASS   |


#### 9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 9.1.6 TEST RESULTS

Please refer to the Attachment I

## **10. ANTENNA CONDUCTED SPURIOUS EMISSION**

### **10.1 APPLIED PROCEDURES / LIMIT**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


#### **10.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### **10.1.2 DEVIATION FROM STANDARD**

No deviation.

#### **10.1.3 TEST SETUP**



#### **10.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **10.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **10.1.6 TEST RESULTS**

**Please refer to the Attachment J**

Remark :Hopping on and hopping off mode all have been tested ,hopping off mode is worse case ,and only worse case is reported shown in Attachement J.

## 11. MEASUREMENT INSTRUMENTS LIST

| Conducted Emission Measurement |                   |              |          |            |                  |
|--------------------------------|-------------------|--------------|----------|------------|------------------|
| Item                           | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                              | LISN              | EMCO         | 3816/2   | 00052765   | Mar. 29, 2015    |
| 2                              | LISN              | R&S          | ENV216   | 101447     | Mar. 29, 2015    |
| 3                              | Test Cable        | N/A          | C_17     | N/A        | Mar. 14, 2015    |
| 4                              | EMI TEST RECEIVER | R&S          | ESCS30   | 833364/017 | Mar. 29, 2015    |
| 5                              | 50Ω Terminator    | SHX          | TF2-3G-A | 08122902   | Mar. 29, 2015    |

| Radiated Emission Measurement |                     |              |           |            |                  |
|-------------------------------|---------------------|--------------|-----------|------------|------------------|
| Item                          | Kind of Equipment   | Manufacturer | Type No.  | Serial No. | Calibrated until |
| 1                             | Antenna             | Schwarbeck   | VULB9160  | 9160-3232  | Mar. 29, 2015    |
| 2                             | Amplifier           | HP           | 8447D     | 2944A09673 | Mar. 29, 2015    |
| 3                             | Test Receiver       | R&S          | ESCI      | 100382     | Mar. 29, 2015    |
| 4                             | Test Cable          | N/A          | C-01_CB03 | N/A        | Jul. 01, 2015    |
| 5                             | Antenna             | ETS          | 3115      | 00075789   | Mar. 29, 2015    |
| 6                             | Amplifier           | Agilent      | 8449B     | 3008A02274 | Mar. 29, 2015    |
| 7                             | Spectrum            | Agilent      | E4408B    | US39240143 | Nov. 09, 2014    |
| 8                             | Test Cable          | HUBER+SUHNER | C-45      | N/A        | Apr. 29, 2015    |
| 9                             | Controller          | CT           | SC100     | N/A        | N/A              |
| 10                            | Horn Antenna        | EMCO         | 3115      | 9605-4803  | Mar. 29, 2015    |
| 11                            | Active Loop Antenna | R&S          | HFH2-Z2   | 830749/020 | Mar. 29, 2015    |

### Number of Hopping Channel

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

### Average Time of Occupancy

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

### Hopping Channel Separation Measurement

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

### Bandwidth

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

### Peak Output Power

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

### Antenna Conducted Spurious Emission

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|
| 1    | Spectrum Analyzer | R&S          | FSP 40   | 100185     | Nov. 11, 2014    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.

## 12. EUT TEST PHOTO

### Conducted Measurement Photos



## Radiated Measurement Photos

9KHz to 30MHz



## Radiated Measurement Photos

30MHz to 1000MHz



## Radiated Measurement Photos

Above 1000MHz




## **ATTACHMENT A - CONDUCTED EMISSION**

Remark :Test at hopping off mode

Test Mode: TX


## Line



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1578       | 34.44                    | 9.52                    | 43.96                    | 65.58         | -21.62     | peak     |         |
| 2   |     | 0.2047       | 29.51                    | 9.54                    | 39.05                    | 63.42         | -24.37     | peak     |         |
| 3   |     | 0.4547       | 23.05                    | 9.68                    | 32.73                    | 56.79         | -24.06     | peak     |         |
| 4   |     | 0.9470       | 18.29                    | 9.69                    | 27.98                    | 56.00         | -28.02     | peak     |         |
| 5   | *   | 2.0211       | 25.52                    | 9.71                    | 35.23                    | 56.00         | -20.77     | peak     |         |
| 6   |     | 14.7813      | 17.94                    | 10.23                   | 28.17                    | 60.00         | -31.83     | peak     |         |

Test Mode: TX

## Neutral



| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measure-ment | Limit | Over   |          |         |
|-----|-----|--------|---------------|----------------|--------------|-------|--------|----------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV         | dBuV  | dB     | Detector | Comment |
| 1   | *   | 0.1617 | 34.24         | 9.63           | 43.87        | 65.38 | -21.51 | peak     |         |
| 2   |     | 0.1970 | 30.29         | 9.61           | 39.90        | 63.74 | -23.84 | peak     |         |
| 3   |     | 0.2594 | 25.90         | 9.62           | 35.52        | 61.45 | -25.93 | peak     |         |
| 4   |     | 0.4273 | 24.87         | 9.63           | 34.50        | 57.31 | -22.81 | peak     |         |
| 5   |     | 1.9977 | 23.90         | 9.74           | 33.64        | 56.00 | -22.36 | peak     |         |
| 6   |     | 7.5938 | 20.62         | 9.99           | 30.61        | 60.00 | -29.39 | peak     |         |

## **ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)**

Remark :Test at hopping off mode

Test Mode: TX Mode

| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0172         | 0°             | 76.35                 | 24.48                   | 100.83                   | 102.89                 | -2.07          | AVG  |
| 0.0172         | 0°             | 83.27                 | 24.48                   | 107.75                   | 122.89                 | -15.15         | PEAK |
| 0.0269         | 0°             | 56.14                 | 23.86                   | 80.00                    | 99.01                  | -19.01         | AVG  |
| 0.0269         | 0°             | 63.75                 | 23.86                   | 87.61                    | 119.01                 | -31.40         | PEAK |
| 0.0316         | 0°             | 54.35                 | 23.57                   | 77.92                    | 97.61                  | -19.70         | AVG  |
| 0.0316         | 0°             | 62.28                 | 23.57                   | 85.85                    | 117.61                 | -31.77         | PEAK |
| 0.0431         | 0°             | 59.25                 | 22.84                   | 82.09                    | 94.91                  | -12.83         | AVG  |
| 0.0431         | 0°             | 65.15                 | 22.84                   | 87.99                    | 114.91                 | -26.93         | PEAK |
| 0.4926         | 0°             | 19.27                 | 19.82                   | 39.09                    | 73.75                  | -34.67         | QP   |
| 1.7315         | 0°             | 19.13                 | 19.53                   | 38.66                    | 69.54                  | -30.88         | QP   |


| Freq.<br>(MHz) | Ant.<br>0°/90° | Reading(RA)<br>(dBuV) | Corr.Factor(CF)<br>(dB) | Measured(FS)<br>(dBuV/m) | Limits(QP)<br>(dBuV/m) | Margin<br>(dB) | Note |
|----------------|----------------|-----------------------|-------------------------|--------------------------|------------------------|----------------|------|
| 0.0187         | 90°            | 70.15                 | 24.30                   | 94.45                    | 122.17                 | -27.72         | AVG  |
| 0.0187         | 90°            | 78.86                 | 24.30                   | 103.16                   | 142.17                 | -39.01         | PEAK |
| 0.0435         | 90°            | 56.28                 | 22.81                   | 79.09                    | 114.83                 | -35.74         | AVG  |
| 0.0435         | 90°            | 64.75                 | 22.81                   | 87.56                    | 134.83                 | -47.27         | PEAK |
| 0.0354         | 90°            | 51.75                 | 23.32                   | 75.07                    | 116.62                 | -41.55         | AVG  |
| 0.0354         | 90°            | 58.25                 | 23.32                   | 81.57                    | 136.62                 | -55.05         | PEAK |
| 0.0418         | 90°            | 56.45                 | 22.92                   | 79.37                    | 115.18                 | -35.81         | AVG  |
| 0.0418         | 90°            | 67.55                 | 22.92                   | 90.47                    | 135.18                 | -44.71         | PEAK |
| 0.4965         | 90°            | 17.15                 | 19.81                   | 36.96                    | 73.69                  | -36.73         | QP   |
| 1.7138         | 90°            | 18.23                 | 19.53                   | 37.76                    | 69.54                  | -31.78         | QP   |

## **ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)**

Remark :Test at hopping off mode

Test Mode: TX 2402MHz\_CH01


## Vertical



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 51.3400      | 31.85                    | -14.23                  | 17.62                      | 40.00           | -22.38     | peak     |         |
| 2   |     | 216.2400     | 40.40                    | -15.13                  | 25.27                      | 46.00           | -20.73     | peak     |         |
| 3   |     | 304.5100     | 39.55                    | -11.13                  | 28.42                      | 46.00           | -17.58     | peak     |         |
| 4   |     | 436.4300     | 33.28                    | -8.94                   | 24.34                      | 46.00           | -21.66     | peak     |         |
| 5   |     | 646.9200     | 32.22                    | -5.37                   | 26.85                      | 46.00           | -19.15     | peak     |         |
| 6   | *   | 761.3800     | 35.46                    | -4.28                   | 31.18                      | 46.00           | -14.82     | peak     |         |

Test Mode: TX 2402MHz\_CH01


## Horizontal



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 167.7400 | 34.83         | -13.01         | 21.82       | 43.50  | -21.68 | peak     |         |
| 2   |     | 216.2400 | 47.37         | -15.13         | 32.24       | 46.00  | -13.76 | peak     |         |
| 3   | *   | 304.5100 | 45.09         | -11.13         | 33.96       | 46.00  | -12.04 | peak     |         |
| 4   |     | 406.3600 | 36.32         | -9.55          | 26.77       | 46.00  | -19.23 | peak     |         |
| 5   |     | 698.3300 | 35.06         | -4.96          | 30.10       | 46.00  | -15.90 | peak     |         |
| 6   |     | 797.2700 | 34.07         | -3.01          | 31.06       | 46.00  | -14.94 | peak     |         |

Test Mode: TX 2441MHz\_CH28


## Vertical



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit  | Over   |          |         |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|---------|
|     |     | MHz      | Level   | Factor  | ment     |        |        | Detector | Comment |
|     |     |          | dBuV    | dB      | dBuV/m   | dBuV/m | dB     |          |         |
| 1   |     | 216.2400 | 37.86   | -15.13  | 22.73    | 46.00  | -23.27 | peak     |         |
| 2   |     | 305.4800 | 32.67   | -11.12  | 21.55    | 46.00  | -24.45 | peak     |         |
| 3   |     | 408.3000 | 32.73   | -9.51   | 23.22    | 46.00  | -22.78 | peak     |         |
| 4   |     | 458.7400 | 32.40   | -8.99   | 23.41    | 46.00  | -22.59 | peak     |         |
| 5   | *   | 684.7500 | 33.25   | -5.03   | 28.22    | 46.00  | -17.78 | peak     |         |
| 6   |     | 974.7800 | 30.74   | -0.37   | 30.37    | 54.00  | -23.63 | peak     |         |

Test Mode: TX 2441MHz \_CH28


## Horizontal



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 167.7400     | 33.78                    | -13.01                  | 20.77                      | 43.50           | -22.73     | peak     |         |
| 2   | *   | 216.2400     | 47.88                    | -15.13                  | 32.75                      | 46.00           | -13.25     | peak     |         |
| 3   |     | 239.5200     | 45.16                    | -14.06                  | 31.10                      | 46.00           | -14.90     | peak     |         |
| 4   |     | 298.6900     | 39.44                    | -11.07                  | 28.37                      | 46.00           | -17.63     | peak     |         |
| 5   |     | 366.5900     | 33.91                    | -11.10                  | 22.81                      | 46.00           | -23.19     | peak     |         |
| 6   |     | 800.1800     | 31.22                    | -2.91                   | 28.31                      | 46.00           | -17.69     | peak     |         |

Test Mode: TX 2480MHz\_CH54


## Vertical



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 167.7400     | 30.85                    | -13.01                  | 17.84                      | 43.50           | -25.66     | peak     |         |
| 2   |     | 216.2400     | 37.98                    | -15.13                  | 22.85                      | 46.00           | -23.15     | peak     |         |
| 3   |     | 299.6600     | 32.22                    | -11.05                  | 21.17                      | 46.00           | -24.83     | peak     |         |
| 4   |     | 399.5700     | 31.52                    | -9.70                   | 21.82                      | 46.00           | -24.18     | peak     |         |
| 5   |     | 653.7100     | 30.74                    | -5.17                   | 25.57                      | 46.00           | -20.43     | peak     |         |
| 6   | *   | 765.2600     | 32.70                    | -4.14                   | 28.56                      | 46.00           | -17.44     | peak     |         |

Test Mode: TX 2480MHz \_CH54

## Horizontal




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 167.7400     | 34.51                    | -13.01                  | 21.50                      | 43.50           | -22.00     | peak     |         |
| 2   | *   | 216.2400     | 48.87                    | -15.13                  | 33.74                      | 46.00           | -12.26     | peak     |         |
| 3   |     | 240.4900     | 44.62                    | -14.06                  | 30.56                      | 46.00           | -15.44     | peak     |         |
| 4   |     | 298.6900     | 39.51                    | -11.07                  | 28.44                      | 46.00           | -17.56     | peak     |         |
| 5   |     | 402.4800     | 34.47                    | -9.62                   | 24.85                      | 46.00           | -21.15     | peak     |         |
| 6   |     | 738.1000     | 33.44                    | -4.74                   | 28.70                      | 46.00           | -17.30     | peak     |         |

## **ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)**

Remark :Test at hopping off mode


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2402MHz _CH01 |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment                         |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------------------------------|
| 1   |     | 2390.000     | 23.82                    | 33.38                   | 57.20                      | 74.00           | -16.80     | peak     |                                 |
| 2   |     | 2390.000     | 13.53                    | 33.38                   | 46.91                      | 54.00           | -7.09      | AVG      |                                 |
| 3   | X   | 2401.730     | 56.03                    | 33.41                   | 89.44                      | 74.00           | 15.44      | peak     | Fundamental frequency, no limit |
| 4   | *   | 2402.000     | 54.56                    | 33.41                   | 87.97                      | 54.00           | 33.97      | AVG      | Fundamental frequency, no limit |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2402MHz _CH01 |

## Vertical




| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m       | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 4803.820 | 28.24         | 6.39           | 34.63        | 54.00  | -19.37 | AVG      |         |
| 2   |     | 4804.050 | 37.38         | 6.39           | 43.77        | 74.00  | -30.23 | peak     |         |

|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2402MHz _CH01 |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment                         |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------------------------------|
| 1   |     | 2390.000     | 23.43                    | 33.38                   | 56.81                      | 74.00           | -17.19     | peak     |                                 |
| 2   |     | 2390.000     | 13.57                    | 33.38                   | 46.95                      | 54.00           | -7.05      | AVG      |                                 |
| 3   | X   | 2401.670     | 53.12                    | 33.41                   | 86.53                      | 74.00           | 12.53      | peak     | Fundamental frequency, no limit |
| 4   | *   | 2402.000     | 51.51                    | 33.41                   | 84.92                      | 54.00           | 30.92      | AVG      | Fundamental frequency, no limit |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2402MHz _CH01 |



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 4803.950 | 28.15         | 6.39           | 34.54       | 54.00  | -19.46 | AVG      |         |
| 2   |     | 4804.070 | 36.96         | 6.39           | 43.35       | 74.00  | -30.65 | peak     |         |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2441MHz _CH28 |

## Vertical




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment                         |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------------------------------|
| 1   | X   | 2440.700     | 54.74                    | 33.51                   | 88.25                      | 74.00           | 14.25      | peak     | Fundamental frequency, no limit |
| 2   | *   | 2441.000     | 53.20                    | 33.51                   | 86.71                      | 54.00           | 32.71      | AVG      | Fundamental frequency, no limit |

|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2441MHz _CH28 |



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 4881.930 | 27.37         | 6.57           | 33.94       | 54.00  | -20.06 | AVG      |         |
| 2   |     | 4882.050 | 37.13         | 6.57           | 43.70       | 74.00  | -30.30 | peak     |         |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2441MHz _CH28 |



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over  | Detector | Comment                         |
|-----|-----|----------|---------------|----------------|-------------|--------|-------|----------|---------------------------------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB    |          |                                 |
| 1   | X   | 2440.700 | 52.61         | 33.51          | 86.12       | 74.00  | 12.12 | peak     | Fundamental frequency, no limit |
| 2   | *   | 2441.000 | 51.05         | 33.51          | 84.56       | 54.00  | 30.56 | AVG      | Fundamental frequency, no limit |

|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2441MHz _CH28 |


## Horizontal



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 4881.990 | 38.21         | 6.57           | 44.78       | 74.00  | -29.22 | peak     |         |
| 2   | *   | 4881.990 | 27.37         | 6.57           | 33.94       | 54.00  | -20.06 | AVG      |         |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2480MHz _CH54 |

## Vertical




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment                         |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------------------------------|
| 1   | *   | 2480.000     | 52.23                    | 33.61                   | 85.84                      | 54.00           | 31.84      | AVG      | Fundamental frequency, no limit |
| 2   | X   | 2480.300     | 53.83                    | 33.61                   | 87.44                      | 74.00           | 13.44      | peak     | Fundamental frequency, no limit |
| 3   |     | 2483.500     | 24.09                    | 33.62                   | 57.71                      | 74.00           | -16.29     | peak     |                                 |
| 4   |     | 2483.500     | 13.63                    | 33.62                   | 47.25                      | 54.00           | -6.75      | AVG      |                                 |

|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2480MHz _CH54 |



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |                  |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|------------------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector Comment |
| 1   | *   | 4959.990 | 27.28         | 6.74           | 34.02       | 54.00  | -19.98 | AVG              |
| 2   |     | 4960.310 | 38.75         | 6.74           | 45.49       | 74.00  | -28.51 | peak             |


|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2480MHz _CH54 |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment                         |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------------------------------|
| 1   | X   | 2479.730     | 52.98                    | 33.61                   | 86.59                      | 74.00           | 12.59      | peak     | Fundamental frequency, no limit |
| 2   | *   | 2480.000     | 51.29                    | 33.61                   | 84.90                      | 54.00           | 30.90      | AVG      | Fundamental frequency, no limit |
| 3   |     | 2483.500     | 23.07                    | 33.62                   | 56.69                      | 74.00           | -17.31     | peak     |                                 |
| 4   |     | 2483.500     | 13.63                    | 33.62                   | 47.25                      | 54.00           | -6.75      | AVG      |                                 |

|                   |                  |
|-------------------|------------------|
| Orthogonal Axis : | X                |
| Test Mode :       | TX 2480MHz _CH54 |

## Horizontal



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   | *   | 4959.980 | 26.80         | 6.74           | 33.54       | 54.00  | -20.46 | AVG      |         |
| 2   |     | 4960.100 | 36.95         | 6.74           | 43.69       | 74.00  | -30.31 | peak     |         |


## **ATTACHMENT E - NUMBER OF HOPPING CHANNEL**

## Test Mode

## Hopping Mode

Number of Hopping Channel

16



Date: 9.JUL.2014 18:05:55


## ATTACHMENT F - AVERAGE TIME OF OCCUPANCY

| Test Mode: Hopping Mode                           |                                          |                  |                 |
|---------------------------------------------------|------------------------------------------|------------------|-----------------|
| Number of transmission in a<br>6.4(16Hopping*0.4) | Length of<br>transmission<br>time (msec) | Result<br>(msec) | Limit<br>(msec) |
| (5/1) *6.4=32 times <b>Note1</b>                  | 0.24                                     | 7.68             | 400             |


**Note1:** 5 times of occupied channels per 1 second

|                                                            | Results               |
|------------------------------------------------------------|-----------------------|
| Measured cycle (sec)                                       | 16 CH*0.4=6.4         |
| The total number of frequency-hopping per second           | ((5/1)*6.4)=32        |
| The number of occupied channels per second                 | 32/6.4=5 (number/sec) |
| occupied time for each channel(1)                          | 0.24 ms               |
| The total number of channels occupied within one cycle (2) | (5/1) *6.4=32 times   |
| The average time of occupancy within one cycle(1)*(2)      | 7.68 msec             |
| LIMIT (msec)                                               | 400msec               |

## Hopping Mode : 5 (times/1sec)



Date: 9.JUL.2014 18:06:39



Date: 9.JUL.2014 17:36:20




## **ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT**

## Test Mode: Hopping on \_CH07/41/54

| Frequency<br>MHz | Ch. Separation<br>(MHz) | Result   |
|------------------|-------------------------|----------|
| 2402             | 1.0000                  | Complies |
| 2410             | 4.0000                  | Complies |
| 2466             | 4.0000                  | Complies |
| 2480             | 2.0000                  | Complies |


Remark : Two-thirds of the 20 dB bandwidth ( 1.2MHz ) is 0.8MHz , so limit is >0.8MHz

### CH01




Date: 29.JUL.2014 14:23:47

## CH07




Date: 7.JUL.2014 23:49:34

## CH41



Date: 7.JUL.2014 23:52:05

## CH54




Date: 7.JUL.2014 23:55:51

## **ATTACHMENT H - BANDWIDTH**

Remark :Test at hopping off mode


## Test Mode: 1Mbps\_CH01/28/54

| Frequency<br>MHz | 20dB Bandwidth<br>(MHz) | 99% Occupied Bandwidth<br>(MHz) | Result |
|------------------|-------------------------|---------------------------------|--------|
| 2402             | 1.18                    | 1.01                            | PASS   |
| 2441             | 1.20                    | 1.03                            | PASS   |
| 2480             | 1.20                    | 1.05                            | PASS   |




Date: 7.JUL.2014 23:43:48

## CH28



Date: 7.JUL.2014 23:45:26

## CH54




Date: 7.JUL.2014 23:47:09

## **ATTACHMENT I - PEAK OUTPUT POWER**

Remark :Test at hopping off mode


## Test Mode: 1Mbps\_CH01/28/54

| Test Channel | Frequency (MHz) | Peak Output Power (dBm) | LIMIT (dBm) | LIMIT (W) |
|--------------|-----------------|-------------------------|-------------|-----------|
| CH01         | 2402            | -6.69                   | 21          | 0.125     |
| CH28         | 2441            | -6.70                   | 21          | 0.125     |
| CH54         | 2480            | -6.92                   | 21          | 0.125     |




Date: 7.JUL.2014 23:42:26

## CH28



Date: 7.JUL.2014 23:44:09


## CH54



Date: 7.JUL.2014 23:45:44


## **ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION**

## CH01 (Lower)




Date: 7.JUL.2014 23:29:58

## CH54 (Upper)




Date: 7.JUL.2014 23:33:34

## CH01 (30MHz~1GHz)




Date: 7.JUL.2014 23:30:31

## CH01 (1GHz~10<sup>th</sup> Harmonic)




Date: 7.JUL.2014 23:30:51

## CH28 (30MHz~1GHz)




Date: 7.JUL.2014 23:32:00

## CH28 (1GHz~10<sup>th</sup> Harmonic)




Date: 7.JUL.2014 23:32:19

## CH54 (30MHz~1GHz)



Date: 7.JUL.2014 23:33:59

## CH54 (1GHz~10<sup>th</sup> Harmonic)



Date: 7.JUL.2014 23:34:16