

FCC REPORT

Applicant: B mobile HK Limited

Address of Applicant: Ground floor, 144 Un Chau Street, Sham Shui Po, Hong Kong

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: C450

Trade mark: B mobile

FCC ID: ZSW-C450-S750

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 06 Mar., 2014

Date of Test: 06 Mar., to 13 Mar., 2014

Date of report issued: 14 Mar., 2014

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	14 Mar., 2014	Original

Prepared by:

Lisachen

Date:

14 Mar., 2014

Report Clerk

Reviewed by:

Aaron Fei

Date:

14 Mar., 2014

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE.....	5
5.4 DESCRIPTION OF SUPPORT UNITS	6
5.5 LABORATORY FACILITY.....	6
5.6 LABORATORY LOCATION	6
5.7 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	11
7 TEST SETUP PHOTO.....	17
8 EUT CONSTRUCTIONAL DETAILS.....	19

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Radiated Emission	Part15.109	Pass

Pass: *The EUT complies with the essential requirements in the standard.*

5 General Information

5.1 Client Information

Applicant:	B mobile HK Limited
Address of Applicant:	Ground floor, 144 Un Chau Street, Sham Shui Po, Hong Kong
Manufacturer/Factory:	Fortune Ship Technology (HK) Limited
Address of Manufacturer /Factory:	Rm.402, B District, TCL King Electronics Company, No.33th. NanhaiRoad,Nanshan District,Shenzhen,P.R.C.

5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	C450
Trade mark:	B mobile
Power supply:	Rechargeable Li-ion Battery DC3.7V 600mAh
AC adapter :	Input: AC100-240V 50/60Hz 0.15A Output: DC 5.0V 0.5A Max 500mAh

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode with PC (Worst case)
Charging+recording mode	Keep the EUT in Charging+recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: 0755-23118282

Fax: 0755-23116366

5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2013	June 08 2014
2	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	May 25 2013	May 24 2014
3	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 25 2013	May 24 2014
4	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
5	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2013	Mar. 31 2014
6	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2013	Mar. 31 2014
7	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2013	Mar. 31 2014
8	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2013	Mar. 31 2014
9	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2013	Mar. 31 2014
10	Amplifier(10kHz- 1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2013	Mar. 31 2014
11	Amplifier(1GHz- 18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2013	June 08 2014
12	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Apr. 01 2013	Mar. 31 2014
13	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2013	Mar. 29 2014
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A
16	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP	CCIS0023	May. 25 2013	May. 24 2014
17	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr 01 2013	Mar. 31 2014
18	Loop antenna	Laplace instrument	RF300	EMC0701	Aug. 12 2013	Aug. 11 2014
19	Universal radio communication tester	Rhode & Schwarz	CMU200	CCIS0069	May. 25 2013	May. 24 2014
20	Signal Analyzer	Rohde & Schwarz	FSIQ3	CCIS0088	May. 25 2013	May. 24 2014

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2013	June 08 2014
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2013	May. 24 2014
3	LISN	CHASE	MN2050D	CCIS0074	Apr. 01 2013	Mar. 31 2014
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2013	Mar. 31 2014


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150kHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9kHz, VBW=30kHz																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dB μ V)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
0.5-30	60	50															
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 																
Test environment:	Temp.:	23 °C	Humid.: 56% Press.: 1 01kPa														
Measurement Record:	Uncertainty: 3.28dB																
Test Instruments:	Refer to section 5.7 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																

Measurement data:


Line:



Site : CCIS Conducted Test Site
 Condition : FCC PART15 B QP LISN LINE
 Job. no : 098RF
 EUT : Mobile phone
 Model : C450
 Test Mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: aaron

Freq	Read	LISN	Cable	Limit	Over	Remark	
	MHz	Level	Factor	Loss	Level	Line	Limit
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	30.32	10.25	0.79	41.36	66.00	-24.64 QP
2	0.174	20.03	10.23	0.77	31.03	54.77	-23.74 Average
3	0.242	16.05	10.23	0.75	27.03	52.04	-25.01 Average
4	0.614	26.00	10.21	0.77	36.98	56.00	-19.02 QP
5	0.617	18.22	10.21	0.77	29.20	46.00	-16.80 Average
6	0.792	26.44	10.19	0.80	37.43	56.00	-18.57 QP
7	2.513	22.57	10.28	0.94	33.79	46.00	-12.21 Average
8	2.608	32.28	10.28	0.94	43.50	56.00	-12.50 QP
9	3.224	32.32	10.29	0.90	43.51	56.00	-12.49 QP
10	3.241	23.01	10.29	0.90	34.20	46.00	-11.80 Average
11	28.152	26.05	10.76	0.87	37.68	60.00	-22.32 QP
12	28.302	22.92	10.78	0.87	34.57	50.00	-15.43 Average

Neutral:



Site : CCIS Conducted Test Site
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job. no : 098RF
 EUT : Mobile phone
 Model : C450
 Test Mode : PC mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Huni:56% Atmos:101KPa
 Test Engineer: aaron

Freq	Read	LISN	Cable	Limit	Over	Remark	
	MHz	dBuV	Factor	Loss	Level	Line	Limit
1	0.174	29.17	10.25	0.77	40.19	64.77	-24.58 QP
2	0.178	22.69	10.25	0.77	33.71	54.59	-20.88 Average
3	0.614	25.36	10.21	0.77	36.34	56.00	-19.66 QP
4	0.614	17.53	10.21	0.77	28.51	46.00	-17.49 Average
5	2.487	31.17	10.27	0.95	42.39	56.00	-13.61 QP
6	2.567	20.88	10.27	0.94	32.09	46.00	-13.91 Average
7	3.276	31.68	10.28	0.90	42.86	56.00	-13.14 QP
8	3.328	20.66	10.28	0.90	31.84	46.00	-14.16 Average
9	15.388	23.44	10.24	0.90	34.58	50.00	-15.42 Average
10	16.398	26.93	10.26	0.91	38.10	60.00	-21.90 QP
11	27.562	25.32	10.72	0.87	36.91	60.00	-23.09 QP
12	27.855	22.71	10.74	0.87	34.32	50.00	-15.68 Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109								
Test Method:	ANSI C63.4:2003								
Test Frequency Range:	30MHz to 6000MHz								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	30MHz-1GHz	Quasi-peak	120 kHz	300 kHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit:	Frequency	Limit (dBuV/m @3m)		Remark					
	30MHz-88MHz	40.0		Quasi-peak Value					
	88MHz-216MHz	43.5		Quasi-peak Value					
	216MHz-960MHz	46.0		Quasi-peak Value					
	960MHz-1GHz	54.0		Quasi-peak Value					
	Above 1GHz	54.0		Average Value					
		74.0		Peak Value					
Test setup:	Below 1GHz								
	Above 1GHz								

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Measurement Record:	Uncertainty: 4.88dB					
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
EUT : mobile phone
Model : C450
Test mode : PC MODE
Power Rating : AC120W/60Hz
Environment : Temp:25.5°C Huni:55%
Test Engineer: aaron
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit		Over	Remark
	Freq	Level	Factor	Loss	Factor	Level	Line	
MHz	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	162.041	47.44	8.72	2.60	29.72	29.04	43.50	-14.46 QP
2	178.758	39.16	9.62	2.72	26.81	24.69	43.50	-18.81 QP
3	339.589	39.64	14.12	3.07	29.63	27.20	46.00	-18.80 QP
4	403.250	46.94	15.14	3.09	29.94	35.23	46.00	-10.77 QP
5	437.120	50.62	15.55	3.17	30.35	38.99	46.00	-7.01 QP
6	533.832	53.15	17.26	3.80	30.53	43.68	46.00	-2.32 QP

Vertical:




Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
EUT : mobile phone
Model : C450
Test mode : PC MODE
Power Rating : AC120V/60Hz
Environment : Temp:25.5°C Humi:55%
Test Engineer: aaron
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	Level	Factor	Loss			
1	44.743	34.05	13.55	1.28	27.77	21.11	40.00 -18.89 QP
2	167.824	48.30	8.90	2.64	29.01	30.83	43.50 -12.67 QP
3	180.017	43.45	9.68	2.73	26.51	29.35	43.50 -14.15 QP
4	401.839	43.11	15.10	3.08	29.92	31.37	46.00 -14.63 QP
5	437.120	49.07	15.55	3.17	30.35	37.44	46.00 -8.56 QP
6	528.246	52.18	17.15	3.77	30.53	42.57	46.00 -3.43 QP

Above 1GHz


Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
Jobi NO. : 098RF
EUT : Mobile phone
Model : C450
Test mode : PC Mode
Power Rating : AC 120V/60Hz
Environment : Temp:25.5°C Huni:55%
Test Engineer: aaron

Freq	ReadAntenna		Cable	Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1053.335	55.92	24.27	3.25	40.97	42.47	74.00 -31.53 Peak
2	1053.335	45.84	24.27	3.25	40.97	32.39	54.00 -21.61 Average
3	1996.946	52.83	26.13	4.83	40.84	42.95	74.00 -31.05 Peak
4	1996.946	42.91	26.13	4.83	40.84	33.03	54.00 -20.97 Average
5	5015.753	48.59	31.85	9.12	39.99	49.57	74.00 -24.43 Peak
6	5015.753	38.47	31.85	9.12	39.99	39.45	54.00 -14.55 Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 Jobi NO. : 098RF
 EUT : Mobile phone
 Model : C450
 Test mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Huni:55%
 Test Engineer: aaron

	ReadAntenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss Factor	Level	Line	Limit Remark
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	1111.504	56.94	24.50	3.36	40.93	43.87 74.00 -30.13 Peak
2	1111.504	46.82	24.50	3.36	40.93	33.75 54.00 -20.25 Average
3	1993.371	54.44	26.06	4.82	40.85	44.47 74.00 -29.53 Peak
4	1993.371	44.32	26.06	4.82	40.85	34.35 54.00 -19.65 Average
5	5585.026	48.95	32.08	9.21	40.37	49.87 74.00 -24.13 Peak
6	5585.026	38.87	32.08	9.21	40.37	39.79 54.00 -14.21 Average