



**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Led Lamp with Wireless Charging and Speaker

Model No.: INV00786

Trademark: N/A

FCC ID: 2A8CV-INV00786

Report No.: E01A22080489F00502

Issue Date: September 08, 2022

Prepared for

IDEA SOURCE MARKETING INC.

152 Madison Ave., Suite 901, New York, NY 10016

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

**1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake
Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr.,
China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Electronic Technology Co., Ltd.**

VERIFICATION OF COMPLIANCE

Applicant:	IDEA SOURCE MARKETING INC. 152 Madison Ave., Suite 901, New York, NY 10016
Manufacturer:	IDEA SOURCE MARKETING INC. 152 Madison Ave., Suite 901, New York, NY 10016
Product Description:	Led Lamp with Wireless Charging and Speaker
Trade Mark:	N/A
Model Number:	INV00786

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.209(2022).

Date of Test : August 23, 2022 to September 06, 2022

Prepared by : _____

Duke Liu / Editor

Reviewer &
Authorized Signer : _____

Tiger Xu / Supervisor



Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A22080489F00502

Table of Contents

1 GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION	4
1.2 RELATED SUBMITTAL(S) / GRANT(S)	5
1.3 TEST METHODOLOGY	5
1.4 SPECIAL ACCESSORIES	5
1.5 EQUIPMENT MODIFICATIONS	5
1.6 TEST FACILITY	5
2 SYSTEM TEST CONFIGURATION.....	6
2.1 EUT CONFIGURATION	6
2.2 EUT EXERCISE	6
2.3 TEST PROCEDURE	6
2.4 CONFIGURATION OF TESTED SYSTEM.....	7
3 SUMMARY OF TEST RESULTS.....	7
4 TEST SYSTEM UNCERTAINTY.....	8
5 CONDUCTED EMISSIONS TEST	9
5.1 MEASUREMENT PROCEDURE	9
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	9
5.3 MEASUREMENT EQUIPMENT USED.....	9
5.4 CONDUCTED EMISSION LIMIT	9
5.5 MEASUREMENT RESULT	10
5.6 CONDUCTED MEASUREMENT PHOTO.....	13
6 RADIATED EMISSION TEST.....	14
6.1 MEASUREMENT PROCEDURE	14
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	14
6.3 MEASUREMENT EQUIPMENT USED.....	15
6.4 RADIATED EMISSION LIMIT	15
6.5 MEASUREMENT RESULT	17
6.6 RADIATED MEASUREMENT PHOTOS.....	21
7 20DB BANDWIDTH.....	22
7.1 20dB BANDWIDTH LIMIT	22
7.2 TEST INSTRUMENTS.....	22
7.3 TEST PROCEDURE	22
7.4 TEST SETUP.....	22
7.5 TEST RESULT	22
8 ANTENNA APPLICATION	24
8.1 ANTENNA REQUIREMENT	24
8.2 RESULT	24

1 General Information

1.1 Product Description

Characteristics	Description
Product Name	Led Lamp with Wireless Charging and Speaker
Model number	INV00786
Operation Mode	Wireless Charging
Input Rating	DC 5V 3A, DC 9V 2.5A
Power Supply	AC120V/60Hz for adapter
Operating Frequency	127.7KHz
Wireless Charging Power	5W/7.5W/10W/15W
Modulation Technique	ASK
Antenna Type	Induction coil
Sample receipt date	August 23, 2022

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: 2A8CV-INV00786 filing to comply with the FCC Part 15, Subpart C Rules.

1.3 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description	:	
Name of Firm	:	Dong Guan Anci Electronic Technology Co., Ltd.
Site Location	:	1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, evelopment Zone, Dongguan City, Guangdong Pr., China.

2 System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the fixed in a particular direction according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trade Mark	Model No.	FCC ID	Note
1.	Led Lamp with Wireless Charging and Speaker	J5create	INV00786	2A8CV-INV00786	<i>EUT</i>
2	adapter	N/A	Model: PD23U-1TNA Input: AC 100-240V, 50/60Hz, 0.8A Max Output: DC 5V/3A, DC 9V/2.5A	N/A	<i>Support EUT</i>
3	iphone	Apple	A2176	N/A	<i>Support Equipment</i>

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.209	Radiated Emission	Compliant
§2.1049	20dB Bandwidth	Compliant
§15.203	Antenna Requirement	Compliant

4 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$


Remark: The coverage Factor ($k=2$), and measurement Uncertainty for a level of Confidence of 95%

5 Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2023-05-12
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2023-05-12
RF Cable	N/A	N/A	2#	2023-05-12
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2023-05-12
1# Shielded Room	chengyu	8m*4m*3.3m	N/A	2024-11-12
Test Software	Farad	EZ-EMC (Ver.ANCI-3A1)	N/A	N/A

5.4 Conducted Emission Limit

Conducted Emission

Frequency(MHz)

Quasi-peak

Average

0.15-0.5

66-56

56-46

0.5-5.0

56

46

5.0-30.0

60

50

Note: 1. The lower limit shall apply at the transition frequencies


2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

Operation Mode:	TX	Test Date :	2022/08/23
Frequency Range:	0.15MHz~30MHz	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %
Test By:	Best		


Pass

We pretested modes (Wireless Charging(15W), Wireless Charging(10W),Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst test data see follow the table.

Test mode: Wireless Charging 15W

Site:	843	Phase:	L1	Temperature(C):	26(C)
Limit:	FCC Part 18 C Conduction(QP)			Humidity(%):	60%
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:			2022/08/23
M/N.:	INV00786	Power Rating:		AC 120V/60Hz	
Mode:	Wireless Charging 15W	Test Engineer:		Jack	
Note:					

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1740	29.02	9.46	38.48	64.77	-26.29	QP	
2	0.1740	22.10	9.46	31.56	54.77	-23.21	AVG	
3	0.2620	26.96	9.74	36.70	61.37	-24.67	QP	
4	0.2620	20.18	9.74	29.92	51.37	-21.45	AVG	
5	0.3500	26.13	9.49	35.62	58.96	-23.34	QP	
6	0.3500	20.45	9.49	29.94	48.96	-19.02	AVG	
7	0.4780	24.51	9.74	34.25	56.37	-22.12	QP	
8	0.4780	19.17	9.74	28.91	46.37	-17.46	AVG	
9	0.6020	23.55	9.56	33.11	56.00	-22.89	QP	
10	0.6020	17.75	9.56	27.31	46.00	-18.69	AVG	
11	0.7780	28.28	9.71	37.99	56.00	-18.01	QP	
12	0.7780	22.65	9.71	32.36	46.00	-13.64	AVG	



Site:	843	Phase:	N	Temperature(C):	26(C)
Limit:	FCC Part 18 C Conduction(QP)			Humidity(%):	60%
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:	2022/08/23		
M/N.:	INV00786	Power Rating:	AC 120V/60Hz		
Mode:	Wireless Charging 15W	Test Engineer:	Jack		
Note:					

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1740	27.73	9.46	37.19	64.77	-27.58	QP	
2	0.1740	19.16	9.46	28.62	54.77	-26.15	AVG	
3	0.2700	24.53	9.75	34.28	61.12	-26.84	QP	
4	0.2700	18.57	9.75	28.32	51.12	-22.80	AVG	
5	0.3780	24.68	9.67	34.35	58.32	-23.97	QP	
6	0.3780	18.91	9.67	28.58	48.32	-19.74	AVG	
7	0.4780	22.62	9.74	32.36	56.37	-24.01	QP	
8	0.4780	17.03	9.74	26.77	46.37	-19.60	AVG	
9	0.5660	22.20	9.61	31.81	56.00	-24.19	QP	
10	0.5660	16.71	9.61	26.32	46.00	-19.68	AVG	
11	0.7940	28.67	9.74	38.41	56.00	-17.59	QP	
12	0.7940	22.28	9.74	32.02	46.00	-13.98	AVG	

5.6 Conducted Measurement Photo




6 Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



6.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022/11/12
2.	Pre-Amplifier	HP	8447D	2727A06172	2023-05-12
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2023-05-12
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022/11/12
5.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92 J-2m	N/A	2022/11/12
6.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92 J-0.3m	N/A	2022/11/12
7.	RF Cable	N/A	N/A	6#	2023-05-12
8.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2023-05-12
9.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	$2400 / F(\text{KHz})$	300m	$10000 * 2400/F(\text{KHz})$	$20\log 2400/F(\text{KHz}) + 80$
0.490 – 1.705	$24000 / F(\text{KHz})$	30m	$100 * 24000/F(\text{KHz})$	$20\log 24000/F(\text{KHz}) + 40$
1.705 – 30.00	30	30m	$100 * 30$	$20\log 30 + 40$
30.0 – 88.0	100	3m	100	$20\log 100$
88.0 – 216.0	150	3m	150	$20\log 150$
216.0 – 960.0	200	3m	200	$20\log 200$
Above 960.0	500	3m	500	$20\log 500$


15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark: 1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result

We pretested modes (Wireless Charging(15W), Wireless Charging(10W), Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst mode (Wireless Charging(15W)) test data see follow the table.



Site:	LAB	Antenna::Vertical	Temperature(C):23.4(C)
Limit:	FCC Part 15C 3m Radiation(QP)		Humidity(%):56.7%
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:	2022/08/23
M/N.:	INV00786	Power Rating:	AC 120V/60Hz
Mode:	Wireless Charging 15W	Test Engineer:	sunshine
Note:			

No	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	0.1280	79.33	6.20	85.53	105.39	-19.86	QP	100	236	
2	0.2555	61.03	5.60	66.63	99.42	-32.79	QP	100	254	
3	0.3830	53.09	5.97	59.06	95.92	-36.86	QP	100	120	
4	0.5090	50.34	6.31	56.65	73.47	-16.82	QP	100	103	
5 *	0.7638	50.82	6.50	57.32	69.95	-12.63	QP	100	271	
6	0.9743	44.53	6.09	50.62	67.85	-17.23	QP	100	152	

*:Maximum data x:Over limit !:over margin




Site:	LAB	Antenna::Horizontal	Temperature(C):23.4(C)
Limit:	FCC Part 15C 3m Radiation(QP)		
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:	Humidity(%):56.7%
M/N.:	INV00786	Power Rating:	AC 120V/60Hz
Mode:	Wireless Charging 15W	Test Engineer:	sunshine
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1	0.1282	77.33	6.20	83.53	105.37	-21.84	QP	100	236	
2	0.2555	64.03	5.60	69.63	99.42	-29.79	QP	100	254	
3	0.3830	57.59	5.97	63.56	95.92	-32.36	QP	100	120	
4	0.5090	50.84	6.31	57.15	73.47	-16.32	QP	100	103	
5 *	0.6764	48.60	6.46	55.06	71.01	-15.95	QP	100	271	
6	0.7953	43.74	6.44	50.18	69.60	-19.42	QP	100	152	

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) EUT lying on the table position is the worst case result in the report.

We pretested modes (Wireless Charging(15W),Wireless Charging(10W),Wireless Charging(7.5W), Wireless Charging(5W)) for EUT. The worst test data see follow the table.

Test mode: Wireless Charging 15W




Site:	LAB	Antenna::Vertical	Temperature(C):23.4(C)
Limit:	FCC Part 15 Class B 3m Radiation(QP)		Humidity(%):56.7%
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:	2022/08/23
M/N.:	INV00786	Power Rating:	AC 120V/60Hz
Mode:	Wireless Charging 15W	Test Engineer:	sunshine
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1 *	31.5095	44.98	-11.93	33.05	40.00	-6.95	QP	100	45	
2	35.3750	40.64	-11.06	29.58	40.00	-10.42	QP	100	45	
3	83.8156	39.43	-12.59	26.84	40.00	-13.16	QP	100	27	
4	90.5374	40.27	-13.13	27.14	43.50	-16.36	QP	100	27	
5	137.9028	40.50	-11.90	28.60	43.50	-14.90	QP	100	96	
6	177.5092	41.45	-11.72	29.73	43.50	-13.77	QP	100	96	

*:Maximum data x:Over limit !:over margin


ial Testing , Great Quality.



Site:	LAB	Antenna::Horizontal	Temperature(C):23.4(C)
Limit:	FCC Part 15 Class B 3m Radiation(QP)		Humidity(%):56.7%
EUT:	Led Lamp with Wireless Charging and Speaker	Test Time:	2022/08/23
M/N.:	INV00786	Power Rating:	AC 120V/60Hz
Mode:	Wireless Charging 15W	Test Engineer:	sunshine
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)	Remark
1 *	80.0806	40.41	-12.39	28.02	40.00	-11.98	QP	100	45	
2	84.7019	39.62	-12.81	26.81	40.00	-13.19	QP	100	45	
3	91.4949	40.25	-13.04	27.21	43.50	-16.29	QP	100	27	
4	163.1818	35.42	-11.54	23.88	43.50	-19.62	QP	100	27	
5	173.2051	38.78	-11.32	27.46	43.50	-16.04	QP	100	96	
6	188.4125	39.55	-11.39	28.16	43.50	-15.34	QP	100	96	

6.6 Radiated Measurement Photos



7 20db Bandwidth

7.1 20dB Bandwidth Limit

None: for reporting purposed only.


7.2 Test Instruments

Refer a test equipment and calibration data table in this test report.

7.3 Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1KHz RBW and 3KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


7.4 Test Setup



7.5 Test Result

Frequency (KHz)	20dB Bandwidth (KHz)	Results
115.94	2.1997	PASS

20 dB Bandwidth Test plot



8 Antenna Application


8.1 Antenna requirement



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



8.2 Result


The EUT's antenna, permanent attached antenna, used an Induction coil and integrated on PCB, The antenna's gain meets the requirement.

APPENDIX (Photos of EUT)









-----The end-----