FCC RF Test Report

APPLICANT : CASTLES TECHNOLOGY CO., LTD.

EQUIPMENT: Smart Module

BRAND NAME : CASTLES

MODEL NAME : CWM100

FCC ID : WIYCWM100001

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DSS) Spread Spectrum Transmitter

TEST DATE(S) : Nov. 21, 2024 ~ Dec. 26, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

JasonJia

Approved by: Jason Jia





Report No.: FR4N0518A

Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

Page Number : 1 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMAR	RY OF TEST RESULT	4
1	GENI	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	6
	1.6	Testing Location	6
	1.7	Test Software	6
	1.8	Applicable Standards	6
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	10
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	TEST	「 RESULT	11
	3.1	Number of Channel Measurement	11
	3.2	Hopping Channel Separation Measurement	12
	3.3	Dwell Time Measurement	13
	3.4	20dB and 99% Bandwidth Measurement	14
	3.5	Output Power Measurement	15
	3.6	Conducted Band Edges Measurement	16
	3.7	Conducted Spurious Emission Measurement	17
	3.8	Radiated Band Edges and Spurious Emission Measurement	18
	3.9	AC Conducted Emission Measurement	22
	3.10	Antenna Requirements	24
4	LIST	OF MEASURING EQUIPMENT	25
5	MEAS	SUREMENT UNCERTAINTY	26
ΑP	PEND	IX A. CONDUCTED TEST RESULTS	
ΑP	PEND	IX B. AC CONDUCTED EMISSION TEST RESULT	
ΑP	PEND	IX C. RADIATED SPURIOUS EMISSION	
ΑP	PEND	IX D. DUTY CYCLE PLOTS	
ΑP	PEND	IX E. SETUP PHOTOGRAPHS	

Report No. : FR4N0518A

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4N0518A	Rev. 01	Initial issue of report	Jan. 06, 2025

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 3 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No. : FR4N0518A

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.55 dB at 2483.51 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 21.46 dB at 0.171 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or
 in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of
 non-compliance that may potentially occur if measurement uncertainty is taken into account.
- 2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 4 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

1 General Description

1.1 Applicant

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.2 Manufacturer

CASTLES TECHNOLOGY CO., LTD.

6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Smart Module			
Brand Name	CASTLES TECHNOLOGY			
Model Name	CWM100			
FCC ID	WIYCWM100001			
SN Code	Conducted: 219b107d Conduction: 209b11f8 Radiation: 209b11f9			
EUT Stage	Identical Prototype			

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification				
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz			
Number of Channels	79			
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78			
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 10.82 dBm (0.0121 W) Bluetooth EDR (2Mbps) : 10.08 dBm (0.0102 W) Bluetooth EDR (3Mbps) : 10.31 dBm (0.0107 W)			
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.866MHz Bluetooth EDR (2Mbps) : 1.169MHz Bluetooth EDR (3Mbps) : 1.154MHz			
Antenna Type / Gain	PIFA Antenna type with gain 5.4 dBi			
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) :π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK			

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 5 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)					
	No. 1098, Pengxi North Road, Kunshan Economic Development Zone					
Test Site Location	Jiangsu Province 215300 People's Republic of China					
	TEL: +86-512-57900158					
	Sporton Site No.	FCC Designation No.	FCC Test Firm			
Test Site No.	Sporton Site No.	FCC Designation No.	Registration No.			
Test Site NU.	CO01-KS 03CH06-KS TH01-KS	CN1257	314309			

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 Sporton International Inc.(Kunshan)
 Page Number
 : 6 of 26

 TEL: +86-512-57900158
 Report Issued Date
 : Jan. 06, 2025

 FCC ID: WIYCWM100001
 Report Version
 : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Report No.: FR4N0518A

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
2400-2483.5 MHz	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 7 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases						
		Data Rate / Modulation					
Test Item	Bluetooth BR 1Mbps	Bluetooth EDR 2Mbps	Bluetooth EDR 3Mbps				
	GFSK	π/4-DQPSK	8-DPSK				
Conducted	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz				
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz				
Test Cases	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz				
		Bluetooth BR 1Mbps GFSK					
Radiated	Mode 1: CH00_2402 MHz						
Test Cases	Mode 2: CH39_2441 MHz						
	Mode 3: CH78_2480 MHz						
AC	AC						
Conducted	Mode 1 : WCDMA Band V + BT Link + WLAN Link(2.4G) + Test Jig + Adapter						
Emission							

Remark:

- 1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.
- 2. For Radiated Test Cases, The tests were performed with Adapter .

FCC ID: WIYCWM100001

Report Issued Date : Jan. 06, 2025 Report Version : Rev. 01

Page Number


Report Template No.: BU5-FR15CBT Version 2.0

: 8 of 26


Report No.: FR4N0518A

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 9 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	BT Base Station	R&S	СВТ	N/A	N/A	Unshielded, 1.8m
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	Shielded cable DC O/P 1.8m, Unshielded AC I/P cable 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Test Jig	N/A	N/A	N/A	N/A	N/A
7.	Antenna	N/A	N/A	N/A	N/A	N/A
8.	Adapter	N/A	N/A	N/A	N/A	N/A
9.	USB Cable	N/A	N/A	N/A	N/A	N/A
10.	Battery	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the BT Earphone under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.86 dB and 20dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 1.86 + 20 = 21.86 (dB)

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 10 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 7.8.3.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- 5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
- 6. The number of hopping frequency used is defined as the number of total channel.
- 7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

FCC ID: WIYCWM100001

Page Number : 11 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.2.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- Use the following spectrum analyzer settings:
 Span = wide enough to capture the peaks of two adjacent channels;
 RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
- 6. Measure and record the results in the test report.

3.2.4 Test Setup

FCC ID: WIYCWM100001



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

Sporton International Inc.(Kunshan)
TEL: +86-512-57900158

Report Issued Date : Jan. 06, 2025 Report Version : Rev. 01

Page Number

Report Template No.: BU5-FR15CBT Version 2.0

: 12 of 26

Report No.: FR4N0518A

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.4.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- 5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
- 6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 13 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;

The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;

Sweep = auto; Detector function = peak;

Trace = \max hold.

5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.

Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;


The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;

Sweep = auto; Detector function = peak;

Trace = max hold.

6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 14 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.5.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power with cable loss and record the results in the test report.
- 5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 15 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.6.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
- 4. Enable hopping function of the EUT and then repeat step 2. and 3.
- 5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

Sporton International Inc.(Kunshan) TEL: +86-512-57900158

FCC ID: WIYCWM100001

Page Number : 16 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 7.8.8.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 17 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 18 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.8.3 Test Procedures

- 1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 4. Set to the maximum power setting and enable the EUT transmit continuously.
- 5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds

On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.

Average Emission Level = Peak Emission Level + 20*log(Duty cycle)


- 6. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.


Report No.: FR4N0518A

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 20 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix D.

Sporton International Inc.(Kunshan) TEL: +86-512-57900158

FCC ID: WIYCWM100001

Page Number : 21 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Eroquency of emission (MUz)	Conducted limit (dBµV)		
Frequency of emission (MHz)	Quasi-peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

^{*}Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.9.3 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 22 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 23 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Sporton International Inc.(Kunshan)

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Page Number : 24 of 26
Report Issued Date : Jan. 06, 2025
Report Version : Rev. 01

Report No.: FR4N0518A

List of Measuring Equipment 4

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Jan. 02, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jan. 01, 2025	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574710 84	10Hz-44GHz	Jul. 04, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jul. 03, 2025	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Nov. 29, 2024~ Dec. 01, 2024	Sep. 07, 2025	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Sep. 03, 2024	Nov. 29, 2024~ Dec. 01, 2024	Sep. 02, 2025	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 11, 2024	Nov. 29, 2024~ Dec. 01, 2024	Apr. 10, 2025	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 06, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jan. 05, 2025	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	372171	9KHz ~1GHZ	Jan. 02, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jan. 01, 2025	Radiation (03CH06-KS)
Amplifier	EM	EM18G40GA	060728	18~40GHz	Jan. 02, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jan. 01, 2025	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2082395	1Ghz-18Ghz	Jan. 02, 2024	Nov. 29, 2024~ Dec. 01, 2024	Jan. 01, 2025	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY572801 19	500MHz~26.5G Hz	Oct. 09, 2024	Nov. 29, 2024~ Dec. 01, 2024	Oct. 08, 2025	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Nov. 29, 2024~ Dec. 01, 2024	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Nov. 29, 2024~ Dec. 01, 2024	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Nov. 29, 2024~ Dec. 01, 2024	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 18, 2024	Dec. 01, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Dec. 01, 2024	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr. 18, 2024	Dec. 01, 2024	Apr. 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Dec. 01, 2024	Oct. 08, 2025	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Nov. 21, 2024~ Dec. 26, 2024	Oct. 09, 2025	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 02, 2024	Nov. 21, 2024~ Dec. 26, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Nov. 21, 2024~ Dec. 26, 2024	Jan. 01, 2025	Conducted (TH01-KS)

NCR: No Calibration Required

Sporton International Inc.(Kunshan)

Page Number : 25 of 26 TEL: +86-512-57900158 Report Issued Date: Jan. 06, 2025 FCC ID: WIYCWM100001 Report Version : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Report No. : FR4N0518A

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.22 dB		
Occupied Channel Bandwidth	±0.1%		
Conducted Power	±0.50 dB		
Conducted Power Spectral Density	±0.90 dB		
Frequency	±0.04 Hz		

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.84 dB
of 95% (U = 2Uc(y))	2.04 UB

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	3.30 dB
of 95% (U = 2Uc(y))	3.30 UB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.06 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence	5.18 dB
of 95% (U = 2Uc(y))	3.10 u b

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence	5.38 dB
of 95% (U = 2Uc(y))	5.36 UB

----- THE END -----

 Sporton International Inc.(Kunshan)
 Page Number
 : 26 of 26

 TEL: +86-512-57900158
 Report Issued Date
 : Jan. 06, 2025

 FCC ID: WIYCWM100001
 Report Version
 : Rev. 01

Report Template No.: BU5-FR15CBT Version 2.0

Report No.: FR4N0518A

Appendix A. Conducted Test Results

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Report No. : FR4N0518A



FCC RF Test Report No.: FR4N0518A

Ambient Condition: $\underline{25}$ °C, $\underline{45}$ %RH


Test Date: 2024/11/21~12/26 Test Engineer: Jacob Zhang

20dB Emission Bandwidth

Test Result

TestMode	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	2402	0.95	2401.54	2402.48		
	2441	0.95	2440.54	2441.48		
	2480	0.95	2479.53	2480.48		
2DH1	2402	1.28	2401.35	2402.63		
	2441	1.28	2440.35	2441.63		
	2480	1.28	2479.35	2480.63		
3DH1	2402	1.24	2401.39	2402.63		
	2441	1.24	2440.39	2441.63		
	2480	1.24	2479.39	2480.63		


Test Graphs





TEL: +86-512-57900158 FCC ID: WIYCWM100001 : A2 of A43

Report No. : FR4N0518A









: A6 of A43

Report No. : FR4N0518A

Occupied Channel Bandwidth

Test Result

TestMode	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	2402	0.866	2401.5654	2402.4316		
	2441	0.863	2440.5684	2441.4316		
	2480	0.866	2479.5654	2480.4316		
2DH1	2402	1.169	2401.4066	2402.5754		
	2441	1.169	2440.4066	2441.5754		
	2480	1.169	2479.4066	2480.5754		
3DH1	2402	1.154	2401.4366	2402.5904		
	2441	1.151	2440.4366	2441.5874		
	2480	1.154	2479.4366	2480.5904		

TEL: +86-512-57900158 FCC ID: WIYCWM100001 Report No.: FR4N0518A

Test Graphs



TEL: +86-512-57900158 FCC ID: WIYCWM100001 : A8 of A43

Report No. : FR4N0518A



Report No.: FR4N0518A




: A10 of A43



: A11 of A43





Maximum conducted output power

Test Result Peak

TestMode	CH.	Peak Power (dBm)	Power Limit (dBm)	Pass/Fail
	0	10.68	20.97	Pass
DH5	39	10.82	20.97	Pass
	78	10.69	20.97	Pass
	0	9.82	20.97	Pass
2DH1	39	10.08	20.97	Pass
	78	9.89	20.97	Pass
	0	10.05	20.97	Pass
3DH1	39	10.31	20.97	Pass
	78	10.12	20.97	Pass

Note: The power setting is default.

TEL: +86-512-57900158 FCC ID: WIYCWM100001


FCC RF Test Report No. : FR4N0518A

Carrier frequency separation

Test Result

TestMode	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
	2402	1.004	≥0.633	PASS
DH5	2441	1	≥0.633	PASS
	2480	1.009	≥0.633	PASS
	2402	1.009	≥0.853	PASS
2DH1	2441	0.996	≥0.853	PASS
	2480	1	≥0.853	PASS
	2402	1	≥0.827	PASS
3DH1	2441	1.004	≥0.827	PASS
	2480	1.004	≥0.827	PASS

Test Graphs



TEL: +86-512-57900158 FCC ID: WIYCWM100001








: A18 of A43







Time of occupancy


Test Result

TestMode	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.8986	0.31	0.4	Pass
AFH	20	53.33	2.8986	0.15	0.4	Pass

Remark:

- 1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.
 - With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
 - Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67 \text{ hops}$.
- 2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
- 3. Hops Over Occupancy Time comes to $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$ hops. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test Graphs




TEL: +86-512-57900158 FCC ID: WIYCWM100001

Number of hopping channels

Test Result

TestMode	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH5	Нор	79	≥15	PASS

Test Graphs



TEL: +86-512-57900158 FCC ID: WIYCWM100001


Band edge measurements

Test Result


TestMode	ChNoma		RefLevel	Result	Limit	\/a ndiat
restivioue	ChName	Freq(MHz)	[dBm]	[dBm]	[dBm]	Verdict
	Low	2402	11.19	-40.86	≤-8.81	PASS
DH5	High	2480	10.82	-49.24	≤-9.18	PASS
פחט	Low	Hop_2402	11.15	-46.07	≤-8.85	PASS
	High	Hop_2480	10.75	-49.84	≤-9.25	PASS
	Low	2402	9.08	-43.94	≤-10.92	PASS
2DH1	High	2480	9.05	-50.06	≤-10.95	PASS
2טחו	Low	Hop_2402	9.25	-49.37	≤-10.75	PASS
	High	Hop_2480	9.14	-49.94	≤-10.86	PASS
	Low	2402	7.85	-45.45	≤-12.15	PASS
3DH1	High	2480	7.91	-50.01	≤-12.09	PASS
וחענ	Low	Hop_2402	7.89	-49.23	≤-12.11	PASS
	High	Hop_2480	8.02	-50.8	≤-11.98	PASS


TEL: +86-512-57900158 FCC ID: WIYCWM100001

Test Graphs





TEL: +86-512-57900158 FCC ID: WIYCWM100001






: A25 of A43








Conducted Spurious Emission

Test Result


To at Maria	F===(NALL=)	FreqRange	RefLevel	Result	Limit	\
TestMode	Freq(MHz)	[MHz]	[dBm]	[dBm]	[dBm]	Verdict
		Reference	10.26	10.26		PASS
	2402	30~1000	10.26	-56.67	≤-9.74	PASS
		1000~26500	10.26	-49.35	≤-9.74	PASS
		Reference	10.23	10.23		PASS
DH5	2441	30~1000	10.23	-55.7	≤-9.77	PASS
		1000~26500	10.23	-48.96	≤-9.77	PASS
		Reference	9.94	9.94		PASS
	2480	30~1000	9.94	-56.18	≤-10.06	PASS
		1000~26500	9.94	-48.88	≤-10.06	PASS
		Reference	7.89	7.89		PASS
	2402	30~1000	7.89	-56.07	≤-12.11	PASS
		1000~26500	7.89	-49.13	≤-12.11	PASS
	2441	Reference	7.86	7.86		PASS
2DH1		30~1000	7.86	-56.12	≤-12.14	PASS
		1000~26500	7.86	-48.67	≤-12.14	PASS
	2480	Reference	7.89	7.89		PASS
		30~1000	7.89	-56.48	≤-12.11	PASS
		1000~26500	7.89	-48.9	≤-12.11	PASS
		Reference	7.91	7.91		PASS
	2402	30~1000	7.91	-56.14	≤-12.09	PASS
		1000~26500	7.91	-48.6	≤-12.09	PASS
		Reference	6.40	6.40		PASS
3DH1	2441	30~1000	6.40	-56.53	≤-13.6	PASS
		1000~26500	6.40	-48.81	≤-13.6	PASS
		Reference	6.54	6.54		PASS
	2480	30~1000	6.54	-56.11	≤-13.46	PASS
		1000~26500	6.54	-49.52	≤-13.46	PASS


TEL: +86-512-57900158 FCC ID: WIYCWM100001

Test Graphs





TEL: +86-512-57900158 FCC ID: WIYCWM100001








: A32 of A43


















: A38 of A43











: A42 of A43





Appendix B. AC Conducted Emission Test Results



TEL: +86-512-57900158 FCC ID: WIYCWM100001



Tost Engineer:	Amos	Temperature :	25.3~26.2°C
Test Engineer :	Amos	Relative Humidity :	38~40%
Гest Voltage :	120Vac / 60Hz	Phase:	Neutral
Remark :	All emissions not reported here are mo	re than 10 dB below the pr	escribed limit.
80 Level	(dBuV)		
80			
70.0			
60.0		15	C RS\$247-QP
50.0 m (ka)		150	RSS247-AVG
	An an		
40.0	WIND WILLIAM PURCHAMAN MANAGAMAN	A sadden som known and	
30.0		And was to be still by the first of the same of the sa	CARROLLAND MATCHER CONTRACT
20.0	12		W
10.0			
0.15	2 .5 1 2 Frequency (I	5 10	20 30
Site Condition	: CO01-KS		
	Over Limit Read LISN Ca Freq Level Limit Line Level Factor L	ble oss Remark	
	MHz dBuV dB dBuV dBuV dB	dB	
2 3 4 5 6 7 8 9 10	$\begin{array}{cccccccccccccccccccccccccccccccccccc$.42 QP .42 Average .41 QP .41 Average .40 QP .40 Average .31 QP .31 Average .30 QP .30 Average .25 QP .25 Average	

Note:

- 1. Level(dB μ V) = Read Level(dB μ V) + LISN Factor(dB) + Cable Loss(dB)
- 2. Over Limit(dB) = Level(dB μ V) Limit Line(dB μ V)

TEL: +86-512-57900158 FCC ID: WIYCWM100001

Appendix C. Radiated Spurious Emission

Test Engineer :		Relative Humidity :	41~42%	
	Jerry Xu	Temperature :	22~23°C	

Radiated Spurious Emission Test Modes


Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	Bluetooth BR_GFSK	0	2402	1Mbps	-	-
Mode 2	2400-2483.5	Bluetooth BR_GFSK	39	2441	1Mbps	-	-
Mode 3	2400-2483.5	Bluetooth BR_GFSK	78	2480	1Mbps	-	-

Summary of each worse mode


Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	0	2389.82	56.81	74.00	-17.19	V	PEAK	Pass	Band Edge
1	Bluetooth BR_GFSK	0	4804.00	43.33	74.00	-30.67	V	PEAK	Pass	Harmonic
2	Bluetooth BR_GFSK	39	-	-	-	-	-	-	-	Band Edge
2	Bluetooth BR_GFSK	39	7323.00	44.66	74.00	-29.34	V	PEAK	Pass	Harmonic
3	Bluetooth BR_GFSK	78	2483.51	63.45	74.00	-10.55	Н	Peak	Pass	Band Edge
3	Bluetooth BR_GFSK	78	7440.00	44.74	74.00	-29.26	V	PEAK	Pass	Harmonic


Sporton International Inc.(Kunshan)
TEL: +86-512-57900158
FCC ID: WIYCWM100001

Report No.: FR4N0518A














3 Mode **Band Edge** 2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz Pol. Horizontal **Fundamental** 130 Level (dBuV/m) 130 Level (dBuV/m) 113.8 113.8 97.5 97.5 81.3 81.3 FCC PART 15C FCC PART 150 65.0 65.0 48.8 48.8 **Peak** 32.5 32.5 16.3 16.3

2500

Remark

deg

35 Peak

35 Average

1000

1400.

MHz dBuV/m dBuV/m dB dBuV dB/m

TEL: +86-512-57900158 FCC ID: WIYCWM100001

2441

2452.8

2464.6

MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB

2 2483.51 38.69 54.00 -15.31 25.59 32.60 6.73 32.23 6.00 128

1 2483.51 63.45 74.00 -10.55 50.35 32.60 6.73 32.23 6.00

Limit Over Read Ant Cable Preamp Aux APos TPos

Frequency (MHz)

2476.4

2488.2

Report No.: FR4N0518A

2600.

Remark

deg

35 PEAK

35 AVERAGE

Frequency (MHz)

Limit Over Read Ant Cable Preamp Aux APos TPos


Freq Level Line Limit Level Factor Loss Factor Factor

1 2480.00 109.39 ----- 96.31 32.58 6.73 32.23 6.00 128


2 2480.00 84.63 ----- 71.55 32.58 6.73 32.23 6.00 128

3000


SPORTON LAB. FCC RF Test Report



TEL: +86-512-57900158 FCC ID: WIYCWM100001



CC RF Test Report No.: FR4N0518A



3 Mode 30M-1G 2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz Pol. Horizontal Vertical 80 Level (dBuV/m) 80 Level (dBuV/m) 70.0 70.0 60.0 60.0 FCC PART 15C FCC PART 150 50.0 40.0 30.0 30.0 20.0 10.0 **Peak** 0.0 -10.0 300. 500. 60 Frequency (MHz) 100. 200. 300. 500. 600. 700. 800. 900. Frequency (MHz) Limit Over ReadAntenna Cable Preamp Aux Freq Level Lime Limit Level Factor Loss Factor Factor Limit Over ReadAntenna Cable Preamp Aux A/Pos T/Pos Freq Level Line Limit Level Factor Loss Factor Factor Aux A/Pos T/Pos MHz dBuV/m dBuV/m dB dBuV dB/m dB MHz dBuV/m dBuV/m dB dBuV dB/m dB deg cm deg 47.46 28.97 40.00 11.03 45.50 15.40 91.11 22.73 43.50 -20.77 38.00 15.35 148.34 20.26 43.50 -23.24 34.80 16.44 19.62 43.50 -23.24 34.00 16.44 325.65 20.93 46.00 -25.67 31.16 19.90 462.02 22.17 46.00 -23.83 28.57 23.22 1.01 32.94 0.00 1.43 32.85 0.00 1.84 32.82 0.00 2.13 32.84 0.00 2.75 32.88 0.00 3.35 32.97 0.00 46.49 21.85 40.00 18.15 38.06 15.76 0.99 32.96 102.75 20.45 43.50 -23.05 34.77 17.02 1.53 32.87 166.77 18.87 43.50 -24.63 33.67 16.08 1.95 32.83 212.36 22.00 43.50 -24.50 36.44 16.16 2.22 32.82 297.72 21.55 46.00 -24.45 32.46 19.28 2.63 32.82 340.40 26.77 46.00 -19.23 36.65 20.22 2.81 32.91 --- Peak --- Peak --- Peak --- Peak --- Peak 0.00 0.00 0.00 0.00 0.00 ---


TEL: +86-512-57900158 FCC ID: WIYCWM100001

Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39



Note:

- 1. Worst case Duty cycle = on time/100 milliseconds = $2 \times 2.89 / 100 = 5.78 \%$
- 2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.76 dB
- 3. DH5 has the highest duty cycle worst case and is reported.