


RF TEST REPORT



Report No.: 17071028-FCC-R

Supersede Report No.: N/A

Applicant	HONWA(HK) CORPORATION LIMITED	
Product Name	BLUETOOTH EARPHONE	
Model No.	MBH543	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	September 29 to October 23, 2017	
Issue Date	October 24, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17071028-FCC-R
Page	3 of 63

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 CHANNEL SEPARATION	9
6.3 20DB BANDWIDTH	13
6.4 PEAK OUTPUT POWER	17
6.5 NUMBER OF HOPPING CHANNEL	21
6.6 TIME OF OCCUPANCY (DWELL TIME)	23
6.7 BAND EDGE & RESTRICTED BAND	27
6.8 AC POWER LINE CONDUCTED EMISSIONS	35
6.9 RADIATED EMISSIONS & RESTRICTED BAND	41
ANNEX A. TEST INSTRUMENT	48
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	49
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	58
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	62
ANNEX E. DECLARATION OF SIMILARITY	63

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17071028-FCC-R	NONE	Original	October 24, 2017

2. Customer information

Applicant Name	HONWA(HK) CORPORATION LIMITED
Applicant Add	MAOGUANG INDUSTRIAL GURAO TOWN CHAOYANG DISTRICT SHANTOU
Manufacturer	HONWA(HK) CORPORATION LIMITED
Manufacturer Add	MAOGUANG INDUSTRIAL GURAO TOWN CHAOYANG DISTRICT SHANTOU

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	BLUETOOTH EARPHONE
Main Model:	MBH543
Serial Model:	N/A
Date EUT received:	September 28, 2017
Test Date(s):	September 29 to October 23, 2017
Equipment Category :	DSS
Antenna Gain:	0dBi
Antenna Type:	PCB Antenna
Type of Modulation:	GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	2402-2480 MHz
Max. Output Power:	6.174dBm
Number of Channels:	79CH
Port:	USB Port
Input Power:	Battery: Spec: 3.7V, 0.222wh USB: DC 5.0V
Trade Name :	MAGNAVOX
FCC ID:	2AIXC-HW-MBH543

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth, the gain is 0dBi for Bluetooth.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1014mbar
Test date :	October11, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.935	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.932	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.941	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.841	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.845	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.845	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.855	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.863	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.853	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1014mbar
Test date :	October11, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Measurement result


Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	0.935	0.8511
	Mid	2441	0.932	0.8524
	High	2480	0.941	0.8546
$\pi/4$ DQPSK	Low	2402	1.262	1.1677
	Mid	2441	1.267	1.1652
	High	2480	1.267	1.1676
8-DPSK	Low	2402	1.283	1.1758
	Mid	2441	1.294	1.1778
	High	2480	1.280	1.1702

Test Plots


20dB Bandwidth measurement result




GFSK - Low Channel




GFSK - Middle Channel




GFSK - High Channel




$\pi/4$ DPSK - Low Channel




$\pi/4$ DQPSK - Middle Channel




$\pi/4$ DQPSK - High Channel



8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1014mbar
Test date :	October11, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐

Test Setup	 Spectrum Analyzer EUT
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	---

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Peak Output Power measurement result


Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	4.933	1000	Pass
		Mid	2441	4.757	1000	Pass
		High	2480	4.405	1000	Pass
	$\pi/4$ DQPSK	Low	2402	6.058	125	Pass
		Mid	2441	5.527	125	Pass
		High	2480	5.184	125	Pass
	8-DPSK	Low	2402	6.174	125	Pass
		Mid	2441	5.965	125	Pass
		High	2480	5.541	125	Pass

Test Plots


Output Power measurement result




GFSK Output power - Low CH 2402




GFSK Output power - Mid CH 2441




GFSK Output power - High CH 2480




$\pi/4$ DQPSK Output power - Low CH 2402




$\pi/4$ DQPSK Output power - Mid CH 2441




$\pi/4$ DQPSK Output power - High CH 2480



8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1014mbar
Test date :	October11, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23°C
Relative Humidity	54%
Atmospheric Pressure	1014mbar
Test date :	October11, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.930	312.533	400	Pass
		Mid	2.950	314.667	400	Pass
		High	2.940	313.600	400	Pass
	π / 4 DQPSK	Low	2.930	312.533	400	Pass
		Mid	2.930	312.533	400	Pass
		High	2.950	314.667	400	Pass
	8-DPSK	Low	2.940	313.600	400	Pass
		Mid	2.930	312.533	400	Pass
		High	2.940	313.600	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						

Test Plots


Dwell Time measurement result




GFSK - Low CH 2402




GFSK - Mid CH 2441




GFSK - High CH 2480




$\pi/4$ DQPSK - Low CH 2402




$\pi/4$ DQPSK - Mid CH 2441




$\pi/4$ DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	October16, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒

Test Setup	
------------	--


Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,
----------------	--

	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail


Test Data ☐ Yes ☒ N/A
Test Plot ☒ Yes (See below) ☐ N/A

Test Plots


GFSK Mode:



Note: Both Horizontal and vertical polarities were investigated.



Date: 16.OCT.2017 14:59:27



Date: 16.OCT.2017 15:02:00

GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)


Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV

GFSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.


$\pi/4$ DQPSK Mode:



$\pi/4$ DQPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)



$\pi/4$ DQPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Hopping Left-AV

$\pi/4$ DQPSK-Hopping Right-AV


Note: Both Horizontal and vertical polarities were investigated.



Date: 16.OCT.2017 15:00:06

$\pi/4$ DQPSK-Left Side-PK
Note: F1 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)



Date: 16.OCT.2017 15:02:19

$\pi/4$ DQPSK-Right Side-PK
Note: F1 is frequency 2483.5MHz


Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Left Side-AV

$\pi/4$ DQPSK-Right Side-AV

Note: Both Horizontal and vertical polarities were investigated.


8-DPSK Mode:



8DPSK-Hopping Left Side-PK

Note: F1 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)



8DPSK-Hopping Right Side-PK


Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)


8DPSK-Hopping Left-AV

8DPSK-Hopping Right-AV

Note: Both Horizontal and vertical polarities were investigated.



Date: 16.OCT.2017 15:00:24



Date: 16.OCT.2017 15:02:40

8DPSK-Left Side-PK

Note: F1 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

8DPSK-Left Side-AV

8DPSK-Right Side-AV


Note: Both Horizontal and vertical polarities were investigated.

6.8 AC Power Line Conducted Emissions

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	October16, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
		0.5 ~ 5		56	46												
5 ~ 30	60	50															

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---


Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---

Test Report	17071028-FCC-R
Page	36 of 63

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2943	28.73	QP	10.02	38.75	60.40	-21.65
2	L1	0.2943	19.82	AVG	10.02	29.84	50.40	-20.56
3	L1	0.4581	40.31	QP	10.02	50.33	56.73	-6.40
4	L1	0.4581	31.60	AVG	10.02	41.62	46.73	-5.11
5	L1	1.2069	25.79	QP	10.03	35.82	56.00	-20.18
6	L1	1.2069	16.31	AVG	10.03	26.34	46.00	-19.66
7	L1	1.6281	25.73	QP	10.04	35.77	56.00	-20.23
8	L1	1.6281	15.72	AVG	10.04	25.76	46.00	-20.24
9	L1	2.5914	25.49	QP	10.05	35.54	56.00	-20.46
10	L1	2.5914	16.67	AVG	10.05	26.72	46.00	-19.28
11	L1	15.9870	17.24	QP	10.21	27.45	60.00	-32.55
12	L1	15.9870	5.54	AVG	10.21	15.75	50.00	-34.25

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2826	22.01	QP	10.02	32.03	60.74	-28.71
2	N	0.2826	11.64	AVG	10.02	21.66	50.74	-29.08
3	N	0.4620	32.55	QP	10.02	42.57	56.66	-14.09
4	N	0.4620	22.82	AVG	10.02	32.84	46.66	-13.82
5	N	0.9144	25.64	QP	10.03	35.67	56.00	-20.33
6	N	0.9144	9.88	AVG	10.03	19.91	46.00	-26.09
7	N	1.2537	29.22	QP	10.03	39.25	56.00	-16.75
8	N	1.2537	8.95	AVG	10.03	18.98	46.00	-27.02
9	N	2.5797	19.04	QP	10.05	29.09	56.00	-26.91
10	N	2.5797	8.70	AVG	10.05	18.75	46.00	-27.25
11	N	13.9317	17.86	QP	10.19	28.05	60.00	-31.95
12	N	13.9317	3.64	AVG	10.19	13.83	50.00	-36.17

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.4581	30.22	QP	10.02	40.24	56.73	-16.49
2	L1	0.4581	20.10	AVG	10.02	30.12	46.73	-16.61
3	L1	0.5523	25.17	QP	10.02	35.19	56.00	-20.81
4	L1	0.5523	11.41	AVG	10.02	21.43	46.00	-24.57
5	L1	1.3980	24.35	QP	10.03	34.38	56.00	-21.62
6	L1	1.3980	10.16	AVG	10.03	20.19	46.00	-25.81
7	L1	2.2014	23.45	QP	10.04	33.49	56.00	-22.51
8	L1	2.2014	9.76	AVG	10.04	19.80	46.00	-26.20
9	L1	3.2930	23.81	QP	10.05	33.86	56.00	-22.14
10	L1	3.2930	8.54	AVG	10.05	18.59	46.00	-27.41
11	L1	13.9512	20.36	QP	10.19	30.55	60.00	-29.45
12	L1	13.9512	9.91	AVG	10.19	20.10	50.00	-29.90

Test Mode: Bluetooth Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.4542	40.42	QP	10.02	50.44	56.80	-6.36
2	N	0.4542	31.25	AVG	10.02	41.27	46.80	-5.53
3	N	0.6375	27.75	QP	10.02	37.77	56.00	-18.23
4	N	0.6375	18.46	AVG	10.02	28.48	46.00	-17.52
5	N	1.3317	30.30	QP	10.03	40.33	56.00	-15.67
6	N	1.3317	20.04	AVG	10.03	30.07	46.00	-15.93
7	N	2.1546	28.94	QP	10.04	38.98	56.00	-17.02
8	N	2.1546	19.10	AVG	10.04	29.14	46.00	-16.86
9	N	3.1716	28.36	QP	10.05	38.41	56.00	-17.59
10	N	3.1716	18.65	AVG	10.05	28.70	46.00	-17.30
11	N	13.8303	25.89	QP	10.19	36.08	60.00	-23.92
12	N	13.8303	17.03	AVG	10.19	27.22	50.00	-22.78


6.9 Radiated Emissions & Restricted Band

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	October16, 2017
Tested By :	Evans He

Requirement(s):

Spec	Item	Requirement	Applicable	
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges		
		Frequency range (MHz)		Field Strength (µV/m)
		0.009~0.490		2400/F(KHz)
		0.490~1.705		24000/F(KHz)
		1.705~30.0		30
		30 – 88		100
		88 – 216		150
		216 960		200
		Above 960		500

Test Setup	The diagram illustrates the test setup for radiated emissions. It shows an Equipment Under Test (EUT) placed on a stand that is 0.8 meters high. A Loop Antenna is positioned 3 meters away from the EUT. The entire setup is on a Ground Plane. An RF Test Receiver is connected to the antenna.
------------	--

	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq.	Detection	Factor	Reading	Result	Limit@3m	Margin
(MHz)	value	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode: Bluetooth Mode

30MHz -1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	43.6585	27.96	peak	11.49	22.29	0.76	17.92	40.00	-22.08	100	294
2	H	52.5753	30.53	peak	8.12	22.39	0.79	17.05	40.00	-22.95	100	205
3	H	135.0319	30.04	peak	12.92	22.40	1.24	21.80	43.50	-21.70	100	161
4	H	272.2776	49.63	QP	12.38	22.29	1.74	41.46	46.00	-4.54	100	94
5	H	416.1791	45.25	QP	16.02	21.98	2.05	41.34	46.00	-4.66	100	281
6	H	938.8326	28.25	peak	22.69	20.81	3.15	33.28	46.00	-12.72	100	37

30MHz -1GHz

80.0 dBuV/m



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	52.3913	38.53	peak	8.14	22.39	0.79	25.07	40.00	-14.93	100	62
2	V	81.2117	38.63	peak	7.65	22.41	1.05	24.92	40.00	-15.08	200	62
3	V	134.0882	32.66	peak	12.98	22.40	1.23	24.47	43.50	-19.03	100	61
4	V	173.2051	36.25	peak	11.54	22.26	1.36	26.89	43.50	-16.61	100	306
5	V	272.2776	38.18	peak	12.38	22.29	1.74	30.01	46.00	-15.99	100	278
6	V	416.1791	43.67	peak	16.02	21.98	2.05	39.76	46.00	-6.24	100	224

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: 8-DPSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	39.45	AV	V	33.39	7.22	48.46	31.6	54	-22.40
4804	38.12	AV	H	33.39	7.22	48.46	30.27	54	-23.73
4804	51.24	PK	V	33.39	7.22	48.46	43.39	74	-30.61
4804	50.11	PK	H	33.39	7.22	48.46	42.26	74	-31.74
7495	28.16	AV	V	37.61	7.61	48.21	25.17	54	-28.83
7495	26.35	AV	H	37.61	7.61	48.21	23.36	54	-30.64
7495	43.51	PK	V	37.61	7.61	48.21	40.52	74	-33.48
7495	42.71	PK	H	37.61	7.61	48.21	39.72	74	-34.28

Middle Channel: 8-DPSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	40.25	AV	V	33.62	7.53	48.36	33.04	54	-20.96
4882	39.75	AV	H	33.62	7.53	48.36	32.54	54	-21.46
4882	53.62	PK	V	33.62	7.53	48.36	46.41	74	-27.59
4882	51.72	PK	H	33.62	7.53	48.36	44.51	74	-29.49
12033	28.45	AV	V	39.85	12.92	46.01	35.21	54	-18.79
12033	26.15	AV	H	39.85	12.92	46.01	32.91	54	-21.09
12033	43.77	PK	V	39.85	12.92	46.01	50.53	74	-23.47
12033	41.82	PK	H	39.85	12.92	46.01	48.58	74	-25.42

High Channel: 8-DPSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	40.11	AV	V	33.89	7.86	48.31	33.55	54	-20.45
4960	36.48	AV	H	33.89	7.86	48.31	29.92	54	-24.08
4960	52.17	PK	V	33.89	7.86	48.31	45.61	74	-28.39
4960	50.26	PK	H	33.89	7.86	48.31	43.7	74	-30.3
17512	21.05	AV	V	41.99	17	46.01	34.03	54	-19.97
17512	19.43	AV	H	41.99	17	46.01	32.41	54	-21.59
17512	38.45	PK	V	41.99	17	46.01	51.43	74	-22.57
17512	36.55	PK	H	41.99	17	46.01	49.53	74	-24.47

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

4, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	☒
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	☒
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	☒
ISN	ISN T800	34373	09/23/2017	09/22/2018	☐
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	☒
Power Splitter	1#	1#	08/30/2017	08/29/2018	☒
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	☒
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☒
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	☒
Active Antenna (9kHz-30MHz)	AL-130	121031	10/13/2016	10/12/2017	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	☒
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	☒


Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo


Whole Package View




EUT - Front View




EUT - Rear View




EUT - Top View




EUT - Bottom View



EUT - Left View



EUT - Right View




Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard - Front View



Mainboard – Rear View



Antenna View




Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
DCA	Adaptor	E2164A	N/A
Lenovo	Laptop	E40	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A