

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)
Report No.: RFBBQZ-WTW-P24040119-2
FCC ID: PY324100619
Product: Orbi 11BE WiFi 7 Tri-band Router & Orbi 11BE WiFi 7 Tri-band Satellite
(Refer to item 3.1 for the more details)
Brand: NETGEAR
Model No.: RBE871
Series Model: RBE870 (Refer to item 3.1 for the more details)
Received Date: 2024/4/8
Test Date: 2024/4/12 ~ 2024/9/25
Issued Date: 2024/10/29

Applicant and Manufacturer: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose CA 95134

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by: Jeremy Lin, **Date:** 2024/10/29
Jeremy Lin / Project Engineer

This test report consists of 56 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vera Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Antenna Description of EUT	9
3.3 Channel List.....	10
3.4 Test Mode Applicability and Tested Channel Detail.....	11
3.5 Duty Cycle of Test Signal.....	12
3.6 Test Program Used and Operation Descriptions	14
3.7 Connection Diagram of EUT and Peripheral Devices	14
3.8 Configuration of Peripheral Devices and Cable Connections	14
4 Test Instruments	15
4.1 RF Output Power.....	15
4.2 Power Spectral Density	15
4.3 6 dB Bandwidth	15
4.4 AC Power Conducted Emissions	16
4.5 Unwanted Emissions below 1 GHz	16
4.6 Unwanted Emissions above 1 GHz.....	17
5 Limits of Test Items.....	18
5.1 RF Output Power.....	18
5.2 Power Spectral Density	18
5.3 6 dB Bandwidth	18
5.4 AC Power Conducted Emissions	18
5.5 Unwanted Emissions below 1 GHz	19
5.6 Unwanted Emissions above 1 GHz.....	19
6 Test Arrangements.....	20
6.1 RF Output Power.....	20
6.1.1 Test Setup	20
6.1.2 Test Procedure.....	20
6.2 Power Spectral Density	21
6.2.1 Test Setup	21
6.2.2 Test Procedure.....	21
6.3 6 dB Bandwidth	22
6.3.1 Test Setup	22
6.3.2 Test Procedure.....	22
6.4 AC Power Conducted Emissions	22
6.4.1 Test Setup	22
6.4.2 Test Procedure.....	22
6.5 Unwanted Emissions below 1 GHz	23
6.5.1 Test Setup	23
6.5.2 Test Procedure.....	24
6.6 Unwanted Emissions above 1 GHz.....	25
6.6.1 Test Setup	25
6.6.2 Test Procedure.....	25
7 Test Results of Test Item	26
7.1 RF Output Power.....	26
7.2 Power Spectral Density	28
7.3 6 dB Bandwidth	31
7.4 AC Power Conducted Emissions	33
7.5 Unwanted Emissions below 1 GHz	37

7.6	Unwanted Emissions above 1 GHz.....	41
8	Pictures of Test Arrangements	55
9	Information of the Testing Laboratories	56

Release Control Record

Issue No.	Description	Date Issued
RFBBQZ-WTW-P24040119-2	Original Release	2024/10/29

1 Certificate

Product: Orbi 11BE WiFi 7 Tri-band Router & Orbi 11BE WiFi 7 Tri-band Satellite
(Refer to item 3.1 for the more details)

Brand: NETGEAR

Test Model: RBE871

Series Model: RBE870 (Refer to item 3.1 for the more details)

Sample Status: Engineering sample

Applicant and Manufacturer: NETGEAR, INC.

Test Date: 2024/4/12 ~ 2024/9/25

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Measurement procedure: ANSI C63.10-2013
KDB 291074 D02 EMC Measurement v01
KDB 789033 D02 General UNII Test Procedure New Rules v02r01
KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Clause	Test Item	Result	Remark
15.407(a)(3)	RF Output Power	Pass	Meet the requirement of limit.
15.407(a)(3)	Power Spectral Density	Pass	Meet the requirement of limit.
15.407(b)(9)	AC Power Conducted Emissions	Pass	Minimum passing margin is -10.24 dB at 0.43800 MHz
15.407(b)(9)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -4.6 dB at 486.88 MHz
15.407(b)(5) 15.407(b)(10)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.1 dB at 5650.00 MHz
15.407(e)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	1 GHz ~ 18 GHz	2.29 dB
Power Spectral Density	1 GHz ~ 18 GHz	2.29 dB
6 dB Bandwidth	-	206.5 Hz
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.64 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Orbi 11BE WiFi 7 Tri-band Router & Orbi 11BE WiFi 7 Tri-band Satellite
Brand	NETGEAR
Test Model	RBE871
Series Model	RBE870
Model Difference	Refer to Note
Status of EUT	Engineering sample
Power Supply Rating	Refer to Note as below
Modulation Type	64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode 1024QAM for OFDMA in 11ax HE mode 4096QAM for OFDMA in 11be EHT mode
Modulation Technology	OFDM, OFDMA
Transfer Rate	802.11a: up to 54 Mbps 802.11n: up to 600 Mbps 802.11ac: up to 3466.7 Mbps 802.11ax: up to 4803.9 Mbps 802.11be: up to 5764 Mbps
Operating Frequency	5.815 GHz ~ 5.885 GHz
Number of Channel	802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20), 802.11be (EHT20): 3 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40), 802.11be (EHT40): 2 802.11ac (VHT80), 802.11ax (HE80), 802.11be (EHT80): 1 802.11ac (VHT160), 802.11ax (HE160), 802.11be (EHT160): 1
Output Power	EIRP: 3732.502 mW (35.72 dBm)
EUT Category	Indoor access point

Note:

1. All models are listed as below.

Brand	Product	Model	Difference
NETGEAR	Orbi 11BE WiFi 7 Tri-band Router	RBE871	DFS Function: Master With 10G Internet port*1, Lan port*4
	Orbi 11BE WiFi 7 Tri-band Satellite	RBE870	DFS Function: Master & Client (Easy Mesh) With Lan port*4

2. The EUT uses following accessories.

Item	Brand	Model	Part Number	Specification
AC Adapter 1	NETGEAR	2AEJ042FC-VII	332-11727-01 (white) & 332-11726-01 (black)	AC Input : 100-240V 50-60Hz 1.3A DC Output : 12.0V 3.5A 42.0W DC Output Cable : 1.83M / 0core Plug : US/EU/UK/AU Manufacturer : CWT
AC Adapter 2	NETGEAR	ADS-45FIC-12N 12042E	332-11729-01 (white) & 332-11728-01 (black)	AC Input : 100-240V 50/60Hz 1.5A DC Output : 12.0V 3.5A 42.0W DC Output Cable : 1.82M / 0core Plug : US/EU/UK/AU Manufacturer : HNR
AC Adapter 3	NETGEAR	AD2150F10	332-11093-02	AC Input : 100-120V 50/60Hz 1.0A DC Output : 12.0V 3.5A DC Output Cable : 1.8M / 0core Plug : US Manufacturer : PI ELETRONICS (VIETNAM) COMPANY LIMITED
AC Adapter 4	NETGEAR	AD2150M20	332-11099-06	AC Input : 100-240V 50/60Hz 1.0A DC Output : 12.0V 3.5A 42.0W DC Output Cable : 1.8M / 0core Plug : US/EU/AU Manufacturer : PI ELETRONICS (VIETNAM) COMPANY LIMITED
Ethernet Cable	NETGEAR	N/A	-	Signal Line : 0.95M

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna Type	Connector Type	Frequency Range	Antenna Gain (dBi)			
			Chain 0	Chain 1	Chain 2	Chain 3
Dipole	ipex(MHF)	5850 ~ 5895 MHz	3.68	2.79	3.35	2.56

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a MIMO function:

5 GHz Band			
Modulation Mode	Beamforming Mode	TX & RX Configuration	
802.11a	Not Support	4TX	4RX
802.11n (HT20)	Support	4TX	4RX
802.11n (HT40)	Support	4TX	4RX
802.11ac (VHT20)	Support	4TX	4RX
802.11ac (VHT40)	Support	4TX	4RX
802.11ac (VHT80)	Support	4TX	4RX
802.11ac (VHT160)	Support	4TX	4RX
802.11ax (HE20)	Support	4TX	4RX
802.11ax (HE40)	Support	4TX	4RX
802.11ax (HE80)	Support	4TX	4RX
802.11ax (HE160)	Support	4TX	4RX
802.11be (EHT20)	Support	4TX	4RX
802.11be (EHT40)	Support	4TX	4RX
802.11be (EHT80)	Support	4TX	4RX
802.11be (EHT160)	Support	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11a modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20 MHz (40 MHz), 802.11ac mode for 20 MHz (40 MHz, 80 MHz, 160 MHz), 802.11ax mode for 20 MHz (40 MHz, 80 MHz, 160 MHz) and 802.11be mode for 20 MHz (40 MHz, 80 MHz, 160 MHz), therefore the manufacturer will control the power for 802.11n/ac/ax mode is same as the 802.11be mode or more lower than it and investigated worst case to representative mode in test report.
4. The EUT device modulation technique OFDMA does not support partial RUs (resource units) and channel puncturing/bandwidth reduction mechanisms.

3.3 Channel List

3 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency
*169	5845 MHz	173	5865 MHz	177	5885 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency
*167	5835 MHz	175	5875 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency
*171	5855 MHz

1 channel is provided for 802.11ac (VHT160), 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency
*163	5815 MHz

Note: * U-NII-3 & -4 span channels.

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	Pre-scan AC Adapter 1 / AC Adapter 2 / AC Adapter 3 / AC Adapter 4 and find the worst case as a representative test condition.
Worst Case:	1. AC Adapter Worst Condition: AC Adapter 1 2. The EUT is usually used standing that and was therefore chosen for Unwanted Emissions.

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	A	802.11a	CDD	169, 173, 177	BPSK	6Mb/s
		802.11be (EHT20)	Beamforming	169, 173, 177	BPSK	MCS0
		802.11be (EHT40)	Beamforming	167, 175	BPSK	MCS0
		802.11be (EHT80)	Beamforming	171	BPSK	MCS0
		802.11be (EHT160)	Beamforming	163	BPSK	MCS0
Power Spectral Density	A	802.11a	CDD	169, 173, 177	BPSK	6Mb/s
		802.11be (EHT20)	Beamforming	169, 173, 177	BPSK	MCS0
		802.11be (EHT40)	Beamforming	167, 175	BPSK	MCS0
		802.11be (EHT80)	Beamforming	171	BPSK	MCS0
		802.11be (EHT160)	Beamforming	163	BPSK	MCS0
6 dB Bandwidth	A	802.11a	CDD	169, 173, 177	BPSK	6Mb/s
		802.11be (EHT20)	Beamforming	169, 173, 177	BPSK	MCS0
		802.11be (EHT40)	Beamforming	167, 175	BPSK	MCS0
		802.11be (EHT80)	Beamforming	171	BPSK	MCS0
		802.11be (EHT160)	Beamforming	163	BPSK	MCS0
AC Power Conducted Emissions	A, B	802.11be (EHT40)	Beamforming	167	BPSK	MCS0
Unwanted Emissions below 1 GHz	A, B	802.11be (EHT40)	Beamforming	167	BPSK	MCS0
Unwanted Emissions above 1 GHz	A	802.11a	CDD	169, 173, 177	BPSK	6Mb/s
		802.11be (EHT20)	Beamforming	169, 173, 177	BPSK	MCS0
		802.11be (EHT40)	Beamforming	167, 175	BPSK	MCS0
		802.11be (EHT80)	Beamforming	171	BPSK	MCS0
		802.11be (EHT160)	Beamforming	163	BPSK	MCS0
EUT Configure Mode:	A	EUT (Model: RBE871) powered by Adapter 1				
	B	EUT (Model: RBE870) powered by Adapter 1				

3.5 Duty Cycle of Test Signal


802.11a: Duty cycle = $1.985 \text{ ms} / 1.99 \text{ ms} \times 100\% = 99.7\%$

802.11be (EHT20): Duty cycle = $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$


802.11be (EHT40): Duty cycle = $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$

802.11be (EHT80): Duty cycle = $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$

802.11be (EHT160): Duty cycle = $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$




802.11a




802.11be (EHT20)

Duty Cycle Analysis




802.11be (EHT40)

Duty Cycle Analysis



802.11be (EHT80)

Duty Cycle Analysis



802.11be (EHT160)

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
EMI Test Receiver R&S	ESR3	102782	2023/12/7	2024/12/6
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-408	2023/11/12	2024/11/11
Preamplifier Keysight	83017A	MY53270295	2024/5/1	2025/4/30
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03(250724)	2024/5/1	2025/4/30
		MY 13380+295012/04	2024/5/1	2025/4/30
Signal & Spectrum Analyzer R&S	FSW43	101582	2024/4/12	2025/4/11
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2024/9/19

4.2 Power Spectral Density

Refer to section 4.1 to get the tested date and information of the instruments.

4.3 6 dB Bandwidth

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101105	2024/2/27	2025/2/26
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/9/19

4.4 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance HUBER+SUHNER	E1-011315	13	2023/11/22	2024/11/21
50 ohm terminal resistance	E1-011279	04	2023/11/22	2024/11/21
	E1-011280	05	2023/11/22	2024/11/21
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2023/11/7	2024/11/6
EMI Test Receiver R&S	ESCI	100613	2023/12/4	2024/12/3
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2024/1/6	2025/1/5
LISN R&S	ENV216	101826	2024/3/25	2025/3/24
	ESH3-Z5	100116	2024/2/21	2025/2/20
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2024/1/6	2025/1/5
Software BVADT	BVADT_Conf_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2024/8/28	2025/8/27

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2024/9/25

4.5 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-155	2023/10/13	2024/10/12
EMI Test Receiver R&S	ESR3	102782	2023/12/7	2024/12/6
Loop Antenna TESEQ	HLA 6121	45745	2024/8/21	2025/8/20
Preamplifier Agilent	8447D	2944A10631	2024/5/1	2025/4/30
Preamplifier EMCI	EMC001340	980201	2024/9/24	2025/9/23
RF Coaxial Cable Woken	8D-FB	Cable-CH4-01	2024/7/6	2025/7/5
Signal & Spectrum Analyzer R&S	FSW43	101582	2024/4/12	2025/4/11
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2024/9/24 ~ 2024/9/25

4.6 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
EMI Test Receiver R&S	ESR3	102782	2023/12/7	2024/12/6
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-408	2023/11/12	2024/11/11
	BBHA 9170	9170-480	2023/11/12	2024/11/11
		BBHA9170241	2023/10/16	2024/10/15
		BBHA9170243	2023/11/12	2024/11/11
Preamplifier EMCI	EMC 184045	980116	2023/9/27	2024/9/26
Preamplifier Keysight	83017A	MY53270295	2023/5/7 2024/5/1	2024/5/6 2025/4/30
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2023/7/8 2024/7/6	2024/7/7 2025/7/5
	EMC102-KM-KM-3000	150929	2023/7/8 2024/7/6	2024/7/7 2025/7/5
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03(250724)	2023/5/7 2024/5/1	2024/5/6 2025/4/30
		MY 13380+295012/04	2023/5/7 2024/5/1	2024/5/6 2025/4/30
Signal & Spectrum Analyzer R&S	FSW43	101582	2024/4/12	2025/4/11
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2024/4/12 ~ 2024/9/20

5 Limits of Test Items

5.1 RF Output Power

Device Category	Limit (Max Average Power)
Indoor access point	EIRP 36 dBm
Subordinate device	EIRP 36 dBm
Client device	EIRP 30 dBm
Note: For all U-NII-4 and U-NII-3 & -4 span channels shall met above EIRP values.	

5.2 Power Spectral Density

Device Category	Limit
Indoor access point	EIRP 20 dBm/MHz
Subordinate device	EIRP 20 dBm/MHz
Client device	EIRP 14 dBm/MHz
Note: For all U-NII-4 and U-NII-3 & -4 span channels shall met above EIRP values.	

5.3 6 dB Bandwidth

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.4 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.5 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.6 Unwanted Emissions above 1 GHz

- (i) For an indoor access point or subordinate device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of -7 dBm/MHz at or above 5.925 GHz.
- (ii) For a client device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of -5 dBm/MHz and shall decrease linearly to an e.i.r.p. of -27 dBm/MHz at or above 5.925 GHz.
- (iii) For a client device or indoor access point or subordinate device, all emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

Note:


The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.
- Follow ANSI C63.10 section 12.7.3, $EIRP \text{ Value (dBm)} = \text{Field Strength Value (dBuV / m)} + \text{Correction Factor @ 3 m}$.
- $\text{Correction Factor (dB) @ 3 m} = 20\log(D) - 104.77 = -95.23 \text{ dB}$; where D is the measurement distance @3 m.

Spectrum analyzer setting as below:


Method SA-1

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

Note: When measuring power, use compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function, with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.

6.2 Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.
- Follow ANSI C63.10 section 12.7.3, $EIRP \text{ Value (dBm)} = \text{Field Strength Value (dBuV/m)} + \text{Correction Factor @ 3 m}$.
- $\text{Correction Factor (dB) @ 3 m} = 20\log(D) - 104.77$; where D is the measurement distance @3 m = -95.23 dB


Spectrum analyzer setting as below:

Method SA-1

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 AC Power Conducted Emissions

6.4.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.4.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.5 Unwanted Emissions below 1 GHz

6.5.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.6 Unwanted Emissions above 1 GHz

6.6.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
169	5845	124.94	-95.23	935.406	29.71	36	Pass
173	5865	124.95	-95.23	937.562	29.72	36	Pass
177	5885	124.93	-95.23	933.254	29.70	36	Pass

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
169	5845	128.63	-95.23	2187.762	33.40	36	Pass
173	5865	128.89	-95.23	2322.737	33.66	36	Pass
177	5885	128.60	-95.23	2172.701	33.37	36	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
167	5835	130.95	-95.23	3732.502	35.72	36	Pass
175	5875	130.78	-95.23	3589.219	35.55	36	Pass


802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
171	5855	130.47	-95.23	3341.95	35.24	36	Pass

802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
163	5815	128.13	-95.23	1949.845	32.90	36	Pass

Spectrum Plot of Maximum Value



7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
169	5845	115.18	-95.23	19.95	20	Pass
173	5865	115.20	-95.23	19.97	20	Pass
177	5885	115.11	-95.23	19.88	20	Pass

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
169	5845	115.03	-95.23	19.80	20	Pass
173	5865	115.05	-95.23	19.82	20	Pass
177	5885	115.04	-95.23	19.81	20	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
167	5835	114.20	-95.23	18.97	20	Pass
175	5875	114.15	-95.23	18.92	20	Pass


802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
171	5855	111.00	-95.23	15.77	20	Pass

802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
163	5815	105.88	-95.23	10.65	20	Pass

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

802.11a

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
169	5845	16.39	16.36	16.37	16.37	0.5	Pass
173	5865	16.36	16.42	16.36	16.38	0.5	Pass
177	5885	16.37	16.38	16.36	16.38	0.5	Pass

802.11be (EHT20) Beamforming

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
169	5845	19.01	19.04	19.03	19.02	0.5	Pass
173	5865	19.04	19.08	19.02	19.01	0.5	Pass
177	5885	19.06	19.04	19.01	18.99	0.5	Pass

802.11be (EHT40) Beamforming

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
167	5835	38.20	38.20	38.20	38.15	0.5	Pass
175	5875	38.22	38.22	38.19	38.21	0.5	Pass


802.11be (EHT80) Beamforming

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
171	5855	78.23	77.99	78.02	77.83	0.5	Pass


802.11be (EHT160) Beamforming

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
163	5815	158.30	158.29	158.39	158.23	0.5	Pass


Spectrum Plot of Minimum Value




802.11a / Chain 0 : CH 173




802.11be (EHT20) Beamforming / Chain 3 : CH 177



802.11be (EHT40) Beamforming / Chain 3 : CH 167



802.11be (EHT80) Beamforming / Chain 3 : CH 171



802.11be (EHT160) Beamforming / Chain 3 : CH 163

7.4 AC Power Conducted Emissions


Mode A

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17000	9.69	34.11	24.42	43.80	34.11	64.96	54.96	-21.16	-20.85
2	0.19400	9.70	30.26	22.43	39.96	32.13	63.86	53.86	-23.90	-21.73
3	0.24200	9.73	29.27	24.25	39.00	33.98	62.03	52.03	-23.03	-18.05
4	0.33800	9.78	25.99	20.93	35.77	30.71	59.25	49.25	-23.48	-18.54
5	0.43800	9.82	29.98	23.29	39.80	33.11	57.10	47.10	-17.30	-13.99
6	0.89800	9.84	29.90	23.11	39.74	32.95	56.00	46.00	-16.26	-13.05

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.68	37.23	24.77	46.91	34.45	66.00	56.00	-19.09	-21.55
2	0.17400	9.69	35.12	23.27	44.81	32.96	64.77	54.77	-19.96	-21.81
3	0.19400	9.70	32.26	22.50	41.96	32.20	63.86	53.86	-21.90	-21.66
4	0.43800	9.84	32.91	27.02	42.75	36.86	57.10	47.10	-14.35	-10.24
5	0.95000	9.89	29.59	23.20	39.48	33.09	56.00	46.00	-16.52	-12.91
6	1.79000	9.94	26.74	20.17	36.68	30.11	56.00	46.00	-19.32	-15.89

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode B

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16200	9.68	35.02	23.35	44.70	33.03	65.36	55.36	-20.66	-22.33
2	0.18600	9.69	30.40	20.99	40.09	30.68	64.21	54.21	-24.12	-23.53
3	0.21000	9.71	32.11	23.49	41.82	33.20	63.21	53.21	-21.39	-20.01
4	0.26600	9.74	28.71	22.70	38.45	32.44	61.24	51.24	-22.79	-18.80
5	0.35000	9.79	29.45	23.83	39.24	33.62	58.96	48.96	-19.72	-15.34
6	0.83000	9.84	27.24	21.16	37.08	31.00	56.00	46.00	-18.92	-15.00

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.68	36.03	24.71	45.71	34.39	66.00	56.00	-20.29	-21.61
2	0.17000	9.69	34.12	23.24	43.81	32.93	64.96	54.96	-21.15	-22.03
3	0.19400	9.70	32.82	23.96	42.52	33.66	63.86	53.86	-21.34	-20.20
4	0.26600	9.75	29.82	23.12	39.57	32.87	61.24	51.24	-21.67	-18.37
5	0.44600	9.84	31.76	24.95	41.60	34.79	56.95	46.95	-15.35	-12.16
6	0.93800	9.89	28.44	20.74	38.33	30.63	56.00	46.00	-17.67	-15.37

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.5 Unwanted Emissions below 1 GHz


Mode A

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	134.03	26.2 QP	43.5	-17.3	1.49 H	267	35.8	-9.6
2	266.17	25.1 QP	46.0	-20.9	1.00 H	249	33.4	-8.3
3	373.01	35.3 QP	46.0	-10.7	1.00 H	133	41.1	-5.8
4	447.52	39.8 QP	46.0	-6.2	1.49 H	294	44.2	-4.4
5	486.88	41.4 QP	46.0	-4.6	1.49 H	358	45.2	-3.8
6	516.41	36.5 QP	46.0	-9.5	1.49 H	53	39.7	-3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	59.52	32.8 QP	40.0	-7.2	1.01 V	345	42.1	-9.3
2	162.14	27.1 QP	43.5	-16.4	1.01 V	16	35.6	-8.5
3	360.36	36.2 QP	46.0	-9.8	1.49 V	213	42.3	-6.1
4	439.09	39.9 QP	46.0	-6.1	1.01 V	251	44.4	-4.5
5	496.72	38.9 QP	46.0	-7.1	1.01 V	24	42.5	-3.6
6	582.48	33.3 QP	46.0	-12.7	1.01 V	334	35.0	-1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode B

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.62	29.4 QP	40.0	-10.6	1.50 H	215	39.5	-10.1
2	162.14	26.4 QP	43.5	-17.1	1.00 H	102	34.9	-8.5
3	247.90	28.6 QP	46.0	-17.4	1.00 H	63	37.9	-9.3
4	343.49	36.9 QP	46.0	-9.1	1.00 H	135	43.5	-6.6
5	493.91	33.4 QP	46.0	-12.6	1.50 H	150	37.1	-3.7
6	730.09	36.4 QP	46.0	-9.6	1.00 H	52	34.7	1.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	59.52	32.4 QP	40.0	-7.6	1.00 V	17	41.7	-9.3
2	94.67	24.5 QP	43.5	-19.0	1.00 V	286	38.6	-14.1
3	150.90	26.4 QP	43.5	-17.1	1.49 V	165	35.1	-8.7
4	349.12	40.1 QP	46.0	-5.9	1.49 V	190	46.6	-6.5
5	474.23	38.5 QP	46.0	-7.5	1.00 V	352	42.5	-4.0
6	780.70	37.9 QP	46.0	-8.1	1.00 V	104	35.1	2.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.6 Unwanted Emissions above 1 GHz

RF Mode	802.11a	Channel	CH 169 : 5845 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.0 PK	68.2	-7.2	2.04 H	324	47.7	13.3
2	*5845.00	119.0 PK			2.04 H	324	74.3	44.7
3	*5845.00	109.8 AV			2.04 H	324	65.1	44.7
4	#5895.00	61.5 PK	110.2	-48.7	2.04 H	324	47.5	14.0
5	11690.00	62.8 PK	74.0	-11.2	1.95 H	162	40.2	22.6
6	11690.00	49.3 AV	54.0	-4.7	1.95 H	162	26.7	22.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.1 PK	68.2	-6.1	1.74 V	359	48.8	13.3
2	*5845.00	123.5 PK			1.74 V	359	78.8	44.7
3	*5845.00	113.8 AV			1.74 V	359	69.1	44.7
4	#5895.00	62.6 PK	110.2	-47.6	1.74 V	359	48.6	14.0
5	11690.00	62.9 PK	74.0	-11.1	1.68 V	135	40.3	22.6
6	11690.00	49.5 AV	54.0	-4.5	1.68 V	135	26.9	22.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 173 : 5865 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.2 PK	68.2	-7.0	2.04 H	324	47.9	13.3
2	*5865.00	118.1 PK			2.04 H	324	73.4	44.7
3	*5865.00	108.7 AV			2.04 H	324	64.0	44.7
4	#5895.00	61.7 PK	110.2	-48.5	2.04 H	324	47.7	14.0
5	11730.00	62.1 PK	74.0	-11.9	1.99 H	168	39.8	22.3
6	11730.00	48.8 AV	54.0	-5.2	1.99 H	168	26.5	22.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.2 PK	68.2	-6.0	1.81 V	356	48.9	13.3
2	*5865.00	123.6 PK			1.81 V	356	78.9	44.7
3	*5865.00	113.8 AV			1.81 V	356	69.1	44.7
4	#5895.00	62.8 PK	110.2	-47.4	1.81 V	356	48.8	14.0
5	11730.00	62.5 PK	74.0	-11.5	1.64 V	133	40.2	22.3
6	11730.00	49.1 AV	54.0	-4.9	1.64 V	133	26.8	22.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 177 : 5885 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.2 PK	68.2	-7.0	2.04 H	322	47.9	13.3
2	*5885.00	117.8 PK			2.04 H	322	73.1	44.7
3	*5885.00	108.4 AV			2.04 H	322	63.7	44.7
4	#5895.00	91.2 PK	110.2	-19.0	2.04 H	322	77.2	14.0
5	11770.00	61.5 PK	74.0	-12.5	1.85 H	170	39.7	21.8
6	11770.00	48.3 AV	54.0	-5.7	1.85 H	170	26.5	21.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.0 PK	68.2	-6.2	1.75 V	356	48.7	13.3
2	*5885.00	122.7 PK			1.75 V	356	78.0	44.7
3	*5885.00	113.1 AV			1.75 V	356	68.4	44.7
4	#5895.00	94.0 PK	110.2	-16.2	1.75 V	356	80.0	14.0
5	11770.00	62.0 PK	74.0	-12.0	1.62 V	139	40.2	21.8
6	11770.00	48.6 AV	54.0	-5.4	1.62 V	139	26.8	21.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT20) Beamforming	Channel	CH 169 : 5845 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.1 PK	68.2	-7.1	2.04 H	340	47.8	13.3
2	*5845.00	122.7 PK			2.04 H	340	78.0	44.7
3	*5845.00	109.3 AV			2.04 H	340	64.6	44.7
4	#5895.00	61.9 PK	110.2	-48.3	2.04 H	340	47.9	14.0
5	11690.00	62.3 PK	74.0	-11.7	1.98 H	174	39.7	22.6
6	11690.00	49.0 AV	54.0	-5.0	1.98 H	174	26.4	22.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.0 PK	68.2	-6.2	1.75 V	355	48.7	13.3
2	*5845.00	126.8 PK			1.75 V	355	82.1	44.7
3	*5845.00	113.5 AV			1.75 V	355	68.8	44.7
4	#5895.00	62.7 PK	110.2	-47.5	1.75 V	355	48.7	14.0
5	11690.00	63.0 PK	74.0	-11.0	1.69 V	141	40.4	22.6
6	11690.00	49.4 AV	54.0	-4.6	1.69 V	141	26.8	22.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT20) Beamforming	Channel	CH 173 : 5865 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.2 PK	68.2	-7.0	2.04 H	339	47.9	13.3
2	*5865.00	120.7 PK			2.04 H	339	76.0	44.7
3	*5865.00	108.5 AV			2.04 H	339	63.8	44.7
4	#5895.00	61.9 PK	110.2	-48.3	2.04 H	339	47.9	14.0
5	11730.00	62.5 PK	74.0	-11.5	1.99 H	184	40.2	22.3
6	11730.00	48.8 AV	54.0	-5.2	1.99 H	184	26.5	22.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.2 PK	68.2	-6.0	1.75 V	356	48.9	13.3
2	*5865.00	125.3 PK			1.75 V	356	80.6	44.7
3	*5865.00	113.0 AV			1.75 V	356	68.3	44.7
4	#5895.00	62.8 PK	110.2	-47.4	1.75 V	356	48.8	14.0
5	11730.00	62.8 PK	74.0	-11.2	1.72 V	138	40.5	22.3
6	11730.00	49.1 AV	54.0	-4.9	1.72 V	138	26.8	22.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT20) Beamforming	Channel	CH 177 : 5885 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.1 PK	68.2	-7.1	2.04 H	339	47.8	13.3
2	*5885.00	120.9 PK			2.04 H	339	76.2	44.7
3	*5885.00	108.5 AV			2.04 H	339	63.8	44.7
4	#5895.00	104.4 PK	110.2	-5.8	2.04 H	339	90.4	14.0
5	11770.00	61.7 PK	74.0	-12.3	1.99 H	186	39.9	21.8
6	11770.00	48.5 AV	54.0	-5.5	1.99 H	186	26.7	21.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.5 PK	68.2	-5.7	1.75 V	355	49.2	13.3
2	*5885.00	125.3 PK			1.75 V	355	80.6	44.7
3	*5885.00	113.7 AV			1.75 V	355	69.0	44.7
4	#5895.00	107.2 PK	110.2	-3.0	1.75 V	355	93.2	14.0
5	11770.00	62.3 PK	74.0	-11.7	1.77 V	136	40.5	21.8
6	11770.00	48.6 AV	54.0	-5.4	1.77 V	136	26.8	21.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 167 : 5835 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.2 PK	68.2	-7.0	2.03 H	342	47.9	13.3
2	*5835.00	121.2 PK			2.03 H	342	76.5	44.7
3	*5835.00	107.9 AV			2.03 H	342	63.2	44.7
4	#5905.00	73.0 PK	102.9	-29.9	2.03 H	342	58.9	14.1
5	11670.00	62.2 PK	74.0	-11.8	1.99 H	174	39.7	22.5
6	11670.00	49.0 AV	54.0	-5.0	1.99 H	174	26.5	22.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.9 PK	68.2	-5.3	1.78 V	355	49.6	13.3
2	*5835.00	124.7 PK			1.78 V	355	80.0	44.7
3	*5835.00	112.0 AV			1.78 V	355	67.3	44.7
4	#5900.00	77.7 PK	106.5	-28.8	1.78 V	355	63.5	14.2
5	11670.00	62.7 PK	74.0	-11.3	1.74 V	136	40.2	22.5
6	11670.00	49.3 AV	54.0	-4.7	1.74 V	136	26.8	22.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT40) Beamforming	Channel	CH 175 : 5875 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	61.4 PK	68.2	-6.8	2.03 H	342	48.1	13.3
2	*5875.00	120.0 PK			2.01 H	324	75.3	44.7
3	*5875.00	107.7 AV			2.01 H	324	63.0	44.7
4	#5895.00	97.9 PK	110.2	-12.3	2.03 H	342	83.9	14.0
5	#5925.00	74.1 PK	88.2	-14.1	2.03 H	342	60.0	14.1
6	11750.00	61.6 PK	74.0	-12.4	1.85 H	186	39.7	21.9
7	11750.00	48.3 AV	54.0	-5.7	1.85 H	186	26.4	21.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	64.0 PK	68.2	-4.2	1.79 V	356	50.7	13.3
2	*5875.00	124.7 PK			1.79 V	356	80.0	44.7
3	*5875.00	112.3 AV			1.79 V	356	67.6	44.7
4	#5912.50	90.1 PK	97.4	-7.3	1.79 V	356	76.0	14.1
5	#5928.00	74.4 PK	88.2	-13.8	1.79 V	356	60.2	14.2
6	11750.00	62.2 PK	74.0	-11.8	1.70 V	148	40.3	21.9
7	11750.00	48.7 AV	54.0	-5.3	1.70 V	148	26.8	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT80) Beamforming	Channel	CH 171 : 5855 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	60.8 PK	68.2	-7.4	2.03 H	325	47.5	13.3
2	*5855.00	117.1 PK			2.03 H	325	72.4	44.7
3	*5855.00	105.0 AV			2.03 H	325	60.3	44.7
4	#5895.00	96.7 PK	110.2	-13.5	2.03 H	325	82.7	14.0
5	#5933.40	81.9 PK	88.2	-6.3	2.03 H	325	67.7	14.2
6	11710.00	62.4 PK	74.0	-11.6	1.86 H	170	40.0	22.4
7	11710.00	48.7 AV	54.0	-5.3	1.86 H	170	26.3	22.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	64.6 PK	68.2	-3.6	1.79 V	356	51.3	13.3
2	*5855.00	121.0 PK			1.79 V	356	76.3	44.7
3	*5855.00	109.0 AV			1.79 V	356	64.3	44.7
4	#5895.00	99.5 PK	110.2	-10.7	1.79 V	356	85.5	14.0
5	#5928.90	87.9 PK	88.2	-0.3	1.79 V	356	73.7	14.2
6	11710.00	62.8 PK	74.0	-11.2	1.74 V	136	40.4	22.4
7	11710.00	49.2 AV	54.0	-4.8	1.74 V	136	26.8	22.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11be (EHT160) Beamforming	Channel	CH 163 : 5815 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Luis Lee		




Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	62.5 PK	68.2	-5.7	2.02 H	322	49.2	13.3
2	*5815.00	111.6 PK			2.02 H	322	66.8	44.8
3	*5815.00	100.0 AV			2.02 H	322	55.2	44.8
4	#5895.00	89.6 PK	110.2	-20.6	2.02 H	322	75.6	14.0
5	#5925.00	64.7 PK	88.2	-23.5	2.02 H	322	50.6	14.1
6	11630.00	62.5 PK	74.0	-11.5	1.85 H	172	39.8	22.7
7	11630.00	48.7 AV	54.0	-5.3	1.85 H	172	26.0	22.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.00	68.1 PK	68.2	-0.1	1.79 V	357	54.8	13.3
2	*5815.00	116.5 PK			1.79 V	357	71.7	44.8
3	*5815.00	104.0 AV			1.79 V	357	59.2	44.8
4	#5895.00	94.8 PK	130.2	-35.4	1.79 V	357	80.8	14.0
5	#5931.00	71.0 PK	108.2	-37.2	1.79 V	357	56.8	14.2
6	11630.00	63.1 PK	74.0	-10.9	1.69 V	132	40.4	22.7
7	11630.00	49.2 AV	54.0	-4.8	1.69 V	132	26.5	22.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.


Plot of Band Edge

Frequency Range	5.55 GHz ~ 6.025 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	----------------------	-------------------------------	----------------------------------




Frequency Range	5.55 GHz ~ 6.025 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	----------------------	-------------------------------	----------------------------------


802.11be (EHT20) Beamforming Channel 169



802.11be (EHT20) Beamforming Channel 173




802.11be (EHT20) Beamforming Channel 177




Frequency Range	5.55 GHz ~ 6.025 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	----------------------	-------------------------------	----------------------------------

802.11be (EHT40) Beamforming Channel 167




Horizontal (Peak)




Vertical (Peak)

802.11be (EHT40) Beamforming Channel 175




Horizontal (Peak)



Vertical (Peak)


Frequency Range	5.55 GHz ~ 6.025 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	----------------------	-------------------------------	----------------------------------

802.11be (EHT80) Beamforming Channel 171



Frequency Range	5.55 GHz ~ 6.025 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	----------------------	-------------------------------	----------------------------------

802.11be (EHT160) Beamforming Channel 163



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---