Compliance Certification Services Inc. Report No: C140425S02-SF

FCC ID: QDS-BRCM1076 IC: 4324A-BRCM1076

Date of Issue :June 24, 2014

Output power test

LIST OF MEASURING EQUIPMENT:

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due	Remark
Spectrum Analyzer	RS	FSU26	200789	2014-8-19	Radiation
MIMO Power Measurement Test Set	Aglient	U2021XA	MY53120005	2014-9-13	Conducted

2.4G Conducted output power(dBm):

Test Configuration



TEST PROCEDURE

- Set span to encompass the entire emission bandwidth (EBW) of the signal. 1
- 2 Set RBW = 1 MHz.
- Set VBW \geq 3 MHz. 3
- Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 4 RBW. Otherwise use peak detector mode.
- Use a video trigger with the trigger level set to enable triggering only on full power pulses. 5 Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to ôhichfree runöhich.
- Trace average 100 traces in power averaging mode. 6
- 7 Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

Mode	Channel	Frequence	Chain0 Peak power(dBm)	Chain1 Peak power (dBm)
	1	2412 MHZ	17.50	16.90
802.11 b	6	2437 MHZ	17.50	16.90
	11	2462 MHZ	17.50	16.90
	1	2412 MHZ	17.45	16.83
802.11 g	6	2437 MHZ	17.47	16.85
	11	2462 MHZ	17.41	16.82
802.11 n HT20	1	2412 MHZ	17.38	16.73
	6	2437 MHZ	17.36	16.75
	11	2462 MHZ	17.37	16.77

ComplianceCertificationServicesInc.Report No: C140425S02-SFFCC ID: QDS-BRCM1076Date of Issue :JulIC: 4324A-BRCM1076

Date of Issue :June 24, 2014

Ва	nd	5.	8	G

Mode	Channel	Frequence	Chain0 output power(dBm)	Chain1 output power(dBm)
	149	5745	17.9	17.8
	153	5765	17.9	17.8
802.11 a	157	5785	17.9	17.8
	161	5805	17.9	17.8
	165	5825	17.9	17.8
	149	5745	17.8	17.7
000 44	153	5765	17.8	17.7
802.11 h (HT20)	157	5785	17.8	17.7
(1120)	161	5805	17.8	17.7
	165	5825	17.8	17.7
802.11 n	151	5755	17.8	17.7
(HT40)	159	5795	17.8	17.7
802.11 ac (VHT80)	155	5755	18.2	18







This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Page 3 of 13



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Page 4 of 13



Page 5 of 13 This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Compliance Certification Services Inc.

FCC ID: QDS-BRCM1076 IC: 4324A-BRCM1076 Date of Issue :June 24, 2014

5G WLAN Conducted output power(dBm):

Report No: C140425S02-SF



Set span to encompass the entire emission bandwidth (EBW) of the signal.

Set RBW = 1 MHz / Set VBW = 3 MHz. Detector RMS

Trace average 100 traces in power averaging mode. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

Mode	Channel	Frequence	Chain0 output power(dBm)	Chain1 output power(dBm)
	36	5180 MHZ	13.12	12.92
902 11 2	40	5200 MHZ	13.10	12.94
002.11 a	44	5220 MHZ	13.13	12.91
	48	5240 MHZ	13.08	12.91
	36	5180 MHZ	13.00	12.80
802.11 n	40	5200 MHZ	13.00	12.80
(HT20)	44	5220 MHZ	13.00	12.80
	48	5240 MHZ	13.00	12.80
802.11 n	38	5180 MHZ	13.04	12.85
(HT40)	46	5230 MHZ	13.07	12.87
802.11 ac (VHT80)	42	5210 MHZ	13.50	13.91

Band 5.2G

Band 5.3G

Mode	Channel	Frequence	Chain0 output power(dBm)	Chain1 output power(dBm)
	52	5260 MHZ	12.90	15
902 11 2	56	5280MHZ	12.90	15
002.11 a	60	5300 MHZ	12.90	15
	64	5320 MHZ	12.90	15
	52	5260 MHZ	12.80	14.90
802.11 n	56	5280MHZ	12.80	14.90
(HT20)	60	5300 MHZ	12.80	14.90
	64	5320 MHZ	12.80	14.90
802.11 n	54	5270 MHZ	12.80	14.90
(HT40)	62	5310 MHZ	12.80	14.90
802.11 ac (VHT80)	58	5290 MHZ	14.30	14.50

Compliance Certification Services Inc. Report No: C140425S02-SF FCC ID: QDS-BRCM1076 Date of Issue :Jul IC: 4324A-BRCM1076 Date of Issue :Jul

Date of Issue :June 24, 2014

Band	5.5G
Dana	0.00

Mode	Channel	Frequence MHZ	Chain0 output power(dBm)	Chain1 output power(dBm)
	100	5500	14.5	15
	104	5520	14.5	15
	108	5540	14.5	15
	112	5560	14.5	15
	116	5580	14.5	15
802.11 a	120	5600	14.5	15
	124	5620	14.5	15
	128	5640	14.5	15
	132	5660	14.5	15
	136	5680	14.5	15
	140	5700	14.5	15
	100	5500	14.4	14.9
	104	5520	14.4	14.9
	108	5540	14.4	14.9
	112	5560	14.4	14.9
000.44	116	5580	14.4	14.9
802.11 h (HT20)	120	5600	14.4	14.9
(1120)	124	5620	14.4	14.9
	128	5640	14.4	14.9
	132	5660	14.4	14.9
	136	5680	14.4	14.9
	140	5700	14.4	14.9
000.44	102	5510	14.4	14.9
802.11 h (HT40)	110	5550	14.4	14.9
(134	5670	14.4	14.9
000.44.55	106	5530	12.3	12.9
802.11 ac (VHT80)	122	5610	12.3	12.9
(11100)	138	5690	12.3	12.9



LVL

3DB

Span 45 MHz

13.07 dBm

1 RM MAXH

-10

-20 31 40 -50 60

-70

Center 5.23 GHz

Tx Channel

Bandwidth

Page 8 of 13

4.5 MHz/

Power

40 MHz



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.





Page 10 of 13



This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

Page 11 of 13



Page 12 of 13 This report shall not be reproduced except in full, without the written approval of Compliance Certification Services.

ComplianceCertificationServicesInc.Report No: C140425S02-SFFCC ID: QDS-BRCM1076Date of Issue :JulIC: 4324A-BRCM1076

Date of Issue :June 24, 2014

Bluetooth3.0 Conducted output power(dBm):

Test Configuration



Test data

Mode	СН	Frequency	Average power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)
	CH00	2402MHZ	5.1	4.2+1/-2	5.2
V3.0 + EDR, GFSK	CH39	2441MHZ	4.9	4.2+1/-2	5.2
	CH78	2480MHZ	4.9	4.2+1/-2	5.2
	CH00	2402MHZ	5.2	4.2+1/-2	5.2
V3.0 + EDR, 8-DPSK	CH39	2441MHZ	5.0	4.2+1/-2	5.2
	CH78	2480MHZ	4.8	4.2+1/-2	5.2

BLE4.0 Conducted output power(dBm):

Mode	СН	Frequency	Average power(dBm)	Turn up tolerance (dBm)	Maximum Turn up power (dBm)
	CH00	2402MHZ	-2.17	-2+1/-2	-1
GFSK	CH19	2440MHZ	-2.46	-2+1/-2	-1
	CH40	2480MHZ	-2.89	-2+1/-2	-1