



### RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06 and and part 2.1093  
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

#### For 2.4G WIFI

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
2462	9.17	8.26	5	2.59	3.0

#### For 5.2G WIFI

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
5180	7.74	5.94	5	2.71	3.0

#### For 5.8G WIFI

Frequency (MHz)	Max power (dBm)	Max power (mW)	Min. distance (mm)	Calculation Value	Threshold Value
5785	7.72	5.91	5	2.84	3.0

So SAR test is not required