	TEST REPORT		
	IEC 60950-1		
Information t	echnology equipment – Safety –		
Part	1: General requirements		
Report Number:	071-75942209-000		
Date of issue:	2018-09-25		
Total number of pages	24		
A			
Applicant's name:			
Address	4, rue Pierre Fauchard, 21 des Cing Chemins, CS 10028, Le Hirgoat, 56520, Guidel, France		
Test specification:			
Standard:	IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013		
Test procedure:	Private		
Non-standard test method::	N/A		
Test Report Form No	IEC60950_1F		
Test Report Form(s) Originator :	SGS Fimko Ltd		
Master TRF:	Dated 2014-02		
Copyright © 2014 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System), All rights reserved.			
This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting rom the reader's interpretation of the reproduced material due to its placement and context.			
f this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.			
This report is not valid as a CB Test and appended to a CB Test Certificat	Report unless signed by an approved CB Testing Laboratory te issued by an NCB in accordance with IECEE 02.		
General disclaimer:			
The test results presented in this report This report shall not be reproduced, exc	relate only to the object tested.		

This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Test item description:	GPS F	Personal Locator Beacon		
Trade Mark:	MCML	JRDO or KANNAD Marine		
Manufacturer:	Orolia			
Model/Type reference	МСМ	JRDO brand: Fast Find 22	20 PLB	
	KANN	AD Marine: Safe Link Sol	0	
Ratings:	12Vdc	(battery powered only)		
-				
Testing procedure and testing locati	on:			
CB Testing Laboratory:		TÜV SÜD Product Serv	ice	
Testing location/ address	:	Concorde Way, Segens PO15 5RL, UK	sworth North, Fareham, Hampshire,	
Associated CB Testing Laborat	ory:			
Testing location/ address	:			
Tested by (name + signature)	:	Rebecca Dyke	A	
Approved by (name + signature)	:	Matt Emery	Moth Ener	
Testing procedure: TMP/CTF St	age 1:			
Testing location/ address	:			
Tested by (name + signature)	:			
Approved by (name + signature)	:			
Testing procedure: WMT/CTF S	tage 2:			
Testing location/ address	:			
Tested by (name + signature)	:			
Witnessed by (name + signature)	:			
Approved by (name + signature)	:			
Testing procedure: SMT/CTF Stage 3 or 4:				
Testing location/ address	:			
Tested by (name + signature)	:			
Witnessed by (name + signature)	:			
Approved by (name + signature):				
Supervised by (name + signature)	:			



List of Attachments (including a total number of pages in each attachment):			
Attachment 1 – European group differences and national differences (19 pages)			
Attachment 2 – Record Photographs (6 pages)			
ndards listed below.			
Testing location: TÜV SÜD Product Service Concorde Way, Segensworth North, Fareham Hampshire, PO15 5RL, UK			
es:			
☑ The product fulfils the requirements of : IEC 60950-1:2005+A1:2009+A2:2013 EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013			











Test item particulars:	
Equipment mobility	[] movable [x] hand-held [] transportable [] stationary [] for building-in [] direct plug-in
Connection to the mains:	[] pluggable equipment [] type A [] type B [] permanent connection [] detachable power supply cord [] non-detachable power supply cord [x] not directly connected to the mains
Operating condition:	[x] continuous [] rated operating / resting time:
Access location	[x] operator accessible [] restricted access location
Over voltage category (OVC):	[] OVC I [] OVC II [] OVC III [] OVC IV [x] other: battery powered
Mains supply tolerance (%) or absolute mains	
supply values	N/A
Tested for IT power systems	[] Yes [x] No
IT testing, phase-phase voltage (V)	N/A
Class of equipment	[] Class I [] Class II [x] Class III [] Not classified
Considered current rating of protective device as	
part of the building installation (A)	N/A
Pollution degree (PD)	[] PD 1 [x] PD 2 [] PD 3
IP protection class	IPx0
Altitude during operation (m)	<2000m
Altitude of test laboratory (m)	<200m
Mass of equipment (kg)	0.152kg

Possible test case verdicts:	
- test case does not apply to the test object	N/A
- test object does meet the requirement:	P (Pass)
- test object does not meet the requirement:	F (Fail)
Testing	
Date of receipt of test item:	2018-07-10
Date (s) of performance of tests	2018-07-09 to 2018-07-12



General remarks:			
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.			
Throughout this report a \Box comma / $igsquare$ point is u	sed as the decimal separator.		
The unit is supplied from 4 X 3V CR 123A consumer g have been assessed as a Limited power source as a p	rade lithium battery cells connected in series which ack.		
The unit has been assessed for a rated operating amb	ient of +55°C.		
User instructions assessed were English language ver	sion of:		
 Fast Find 220 PLB User Manual, Documents i 	number 91-240-001 Issue 4.		
 Safelink Solo PLB User Manual, Document nu 	mber DOC18012A		
The hardware assessed was:1001488 Issue A.			
Manufacturer's Declaration per sub-clause 4.2.5 of	IECEE 02:		
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	 ☐ Yes ☑ Not applicable 		
When differences exist; they shall be identified in t	he General product information section.		
Name and address of factory (ies)	Orolia Ltd.		
	Silver Point,		
	Airport Service Road,		
	Portsmouth,		
	PO3 5PB,		
	UK		
General product information:			
The FastFind/SOLO Personal Locator Beacon (PLB) uses the dedicated 406MHz frequency to transmit a unique ID and precise GNSS location to the global network of search and rescue satellites. It also integrates a 121.5MHz homing transmission to help local rescue researches.			
Abbreviations used in the report: None			



Page	8	of	24	
------	---	----	----	--

IEC	60950-1
-----	---------

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

1	GENERAL	Р

1.5	Components		Р
1.5.1	General		Р
	Comply with IEC 60950-1 or relevant component standard	(see appended tables 1.5.1)	Р
1.5.2	Evaluation and testing of components		Р
1.5.3	Thermal controls		N/A
1.5.4	Transformers		N/A
1.5.5	Interconnecting cables		N/A
1.5.6	Capacitors bridging insulation		N/A
1.5.7	Resistors bridging insulation		N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		N/A
1.5.8	Components in equipment for IT power systems		N/A
1.5.9	Surge suppressors		N/A
1.5.9.1	General		N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A

1.6	Power interface	Р
1.6.1	AC power distribution systems	N/A
1.6.2	Input current	N/A
1.6.3	Voltage limit of hand-held equipment	Р
1.6.4	Neutral conductor	N/A

1.7	Marking and instructions		Р
1.7.1	Power rating and identification markings	Not connected to the mains	N/A
1.7.1.1	Power rating marking		N/A
	Multiple mains supply connections	-	N/A



_	Page 9 of 24	Report No.: 071-75942	209-000
	IEC 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
	-	·	T
	Rated voltage(s) or voltage range(s) (V)	-	N/A
	Symbol for nature of supply, for d.c. only:	-	N/A
	Rated frequency or rated frequency range (Hz):	-	N/A
	Rated current (mA or A)	-	N/A
1.7.1.2	Identification markings		Р
	Manufacturer's name or trade-mark or identification mark	Mucmurdo / Kannad Marine	Р
	Model identification or type reference	Fast Find 220 / Safelink Solo	Р
	Symbol for Class II equipment only	-	N/A
	Other markings and symbols	-	N/A
1.7.1.3	Use of graphical symbols		N/A
1.7.2	Safety instructions and marking		Р
1.7.2.1	General		Р
1.7.2.2	Disconnect devices		N/A
1.7.2.3	Overcurrent protective device		N/A
1.7.2.4	IT power distribution systems		N/A
1.7.2.5	Operator access with a tool		N/A
1.7.2.6	Ozone		N/A
1.7.3	Short duty cycles		N/A
1.7.4	Supply voltage adjustment	-	N/A
	Methods and means of adjustment; reference to installation instructions	-	N/A
1.7.5	Power outlets on the equipment	-	N/A
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference)	-	N/A
1.7.7	Wiring terminals		N/A
1.7.7.1	Protective earthing and bonding terminals	-	N/A
1.7.7.2	Terminals for a.c. mains supply conductors		N/A
1.7.7.3	Terminals for d.c. mains supply conductors		N/A
1.7.8	Controls and indicators		N/A
1.7.8.1	Identification, location and marking	-	N/A
1.7.8.2	Colours:	-	N/A
1.7.8.3	Symbols according to IEC 60417:		N/A
1.7.8.4	Markings using figures	-	N/A
1.7.9	Isolation of multiple power sources	-	N/A
1.7.10	Thermostats and other regulating devices	-	N/A
1.7.11	Durability		Р



Report No.: 071-75942209-000

N/A

Page 10 of 24

IEC	60950-1

Clause	Requirement + Test	Result - Remark	Verdict
1.7.12	Removable parts		N/A
1.7.13	Replaceable batteries:	Not user replacable	N/A
	Language(s):	-	

_

Equipment for restricted access locations.....:

2	PROTECTION FROM HAZARDS		Р
2.1	Protection from electric shock and energy hazards		Р
2.1.1	Protection in operator access areas		Р
2.1.1.1	Access to energized parts		Р
	Test by inspection	SELV only	Р
	Test with test finger (Figure 2A)	-	N/A
	Test with test pin (Figure 2B)	-	N/A
	Test with test probe (Figure 2C)	-	N/A
2.1.1.2	Battery compartments	Not user replaceable	N/A
2.1.1.3	Access to ELV wiring		N/A
	Working voltage (Vpeak or Vrms); minimum distance through insulation (mm)		
2.1.1.4	Access to hazardous voltage circuit wiring		N/A
2.1.1.5	Energy hazards	No accessible circuits	N/A
2.1.1.6	Manual controls		N/A
2.1.1.7	Discharge of capacitors in equipment		N/A
	Measured voltage (V); time-constant (s)	-	
2.1.1.8	Energy hazards – d.c. mains supply		N/A
	a) Capacitor connected to the d.c. mains supply:		N/A
	b) Internal battery connected to the d.c. mains supply :		N/A
2.1.1.9	Audio amplifiers	-	N/A
2.1.2	Protection in service access areas		Р
2.1.3	Protection in restricted access locations		N/A

2.2	SELV circuits		Р
2.2.1	General requirements	(see appended table 2.2)	Р
2.2.2	Voltages under normal conditions (V)	12Vdc	Р
2.2.3	Voltages under fault conditions (V)	12Vdc	Р
2.2.4	Connection of SELV circuits to other circuits:	No connections	N/A

2.3 TNV circuits

1.7.14

N/A



	Page 11 of	24 Report No	Report No.: 071-75942209-00	
	IEC 6095	i0-1		
Clause Requirement	+ Test	Result - Remark	Verdict	

2.4 Limited current circuits

2.5	Limited power sources		Р
	a) Inherently limited output	(see appended table 2.5)	Р
	b) Impedance limited output		N/A
	c) Regulating network or IC current limiter, limits output under normal operating and single fault condition		N/A
	Use of integrated circuit (IC) current limiters		N/A
	d) Overcurrent protective device limited output		N/A
	Max. output voltage (V), max. output current (A), max. apparent power (VA):	-	
	Current rating of overcurrent protective device (A) .:	-	

2.6	Provisions for earthing and bonding	N/A
-----	-------------------------------------	-----

2.7	Overcurrent and earth fault protection in primary circuits
-----	--

2.8 Safety interlocks

2.9	Electrical insulation		Р
2.9.1	Properties of insulating materials		Р
2.9.2	Humidity conditioning		N/A
	Relative humidity (%), temperature (°C):	-	
2.9.3	Grade of insulation	Functional	Р
2.9.4	Separation from hazardous voltages		N/A
	Method(s) used:	-	

2.10	Clearances, creepage distances and distances through insulation	N/A
3	WIRING, CONNECTIONS AND SUPPLY	Р
3.1	General	Р
3.1.1	Current rating and overcurrent protection	Р
3.1.2	Protection against mechanical damage	Р
3.1.3	Securing of internal wiring	Р
3.1.4	Insulation of conductors	N/A



N/A

N/A

N/A

	Page 12 of 24	Report No.: 07	1-75942209-000
	IEC 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
		-	
3.1.5	Beads and ceramic insulators		N/A
3.1.6	Screws for electrical contact pressure		N/A
3.1.7	Insulating materials in electrical connections		N/A
3.1.8	Self-tapping and spaced thread screws		N/A
3.1.9	Termination of conductors		N/A
	10 N pull test		N/A
3.1.10	Sleeving on wiring		N/A

3.2 Connection to a mains supply	N/A
----------------------------------	-----

3.3	Wiring terminals for connection of external conductors	N/A
-----	--	-----

Disconnection from the mains supply 3.4 N/A

3.5	Interconnection of equipment		N/A
3.5.1	General requirements	No external connections	N/A
3.5.2	Types of interconnection circuits:		N/A
3.5.3	ELV circuits as interconnection circuits		N/A
3.5.4	Data ports for additional equipment		N/A

4	PHYSICAL REQUIREMENTS		Р
4.1	Stability		N/A
	Angle of 10°		N/A
	Test force (N)	-	N/A

4.2	Mechanical strength		Р
4.2.1	General		Р
	Rack-mounted equipment.	Not rack mounted	N/A
4.2.2	Steady force test, 10 N		N/A
4.2.3	Steady force test, 30 N		N/A
4.2.4	Steady force test, 250 N		Р
4.2.5	Impact test		N/A
	Fall test		N/A
	Swing test		N/A
4.2.6	Drop test; height (mm)	1000	Р
4.2.7	Stress relief test		Р



Page 13 of 24

Clause	Requirement + Test	Result - Remark	Verdict
4.2.8	Cathode ray tubes		N/A
	Picture tube separately certified	-	N/A
4.2.9	High pressure lamps		N/A
4.2.10	Wall or ceiling mounted equipment; force (N):	-	N/A

4.3	Design and construction		Р
4.3.1	Edges and corners		Р
4.3.2	Handles and manual controls; force (N):		N/A
4.3.3	Adjustable controls		N/A
4.3.4	Securing of parts		N/A
4.3.5	Connection by plugs and sockets		N/A
4.3.6	Direct plug-in equipment	Not connected to the mains	N/A
	Torque:	-	
	Compliance with the relevant mains plug standard	-	N/A
4.3.7	Heating elements in earthed equipment		N/A
4.3.8	Batteries	(see appended tables 4.3.8)	Р
	- Overcharging of a rechargeable battery	Non-rechargeable battery only	N/A
	- Unintentional charging of a non-rechargeable battery	Primary battery only	N/A
	- Reverse charging of a rechargeable battery	Non-rechargeable battery only	N/A
	- Excessive discharging rate for any battery		Р
4.3.9	Oil and grease		N/A
4.3.10	Dust, powders, liquids and gases		N/A
4.3.11	Containers for liquids or gases		N/A
4.3.12	Flammable liquids	-	N/A
	Quantity of liquid (I)	none	N/A
	Flash point (°C)	-	N/A
4.3.13	Radiation		Р
4.3.13.1	General		N/A
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg)	-	
	Measured high-voltage (kV)	-	
	Measured focus voltage (kV):	-	
	CRT markings	-	
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A



Page 14 of 24

Report No.: 071-75942209-000

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	-	-	
	Part, property, retention after test, flammability classification	-	N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation:	-	N/A
4.3.13.5	Lasers (including laser diodes) and LEDs		Р
4.3.13.5.1	Lasers (including laser diodes)		N/A
	Laser class	-	
4.3.13.5.2	Light emitting diodes (LEDs)		
4.3.13.6	Other types		N/A

ſ	4.4	Protection against hazardous moving parts	No moving parts	N/A
L		r rotootion againot nazaraoao moving parto		

4.5	Thermal requirements		Р
4.5.1	General		Р
4.5.2	Temperature tests		Р
	Normal load condition per Annex L	7	
4.5.3	Temperature limits for materials	(see appended table 4.5)	Р
4.5.4	Touch temperature limits	(see appended table 4.5)	Р
4.5.5	Resistance to abnormal heat:	-	N/A

4.6	Openings in enclosures		
4.6.1	Top and side openings	No openings	Р
	Dimensions (mm):	-	
4.6.2	Bottoms of fire enclosures	No fire enclosure required	N/A
	Construction of the bottomm, dimensions (mm) :	-	
4.6.3	Doors or covers in fire enclosures		N/A
4.6.4	Openings in transportable equipment		N/A
4.6.4.1	Constructional design measures		N/A
	Dimensions (mm):	-	
4.6.4.2	Evaluation measures for larger openings		N/A
4.6.4.3	Use of metallized parts		N/A
4.6.5	Adhesives for constructional purposes		N/A
	Conditioning temperature (°C), time (weeks) :	-	

4.7	Resistance to fire		Р
4.7.1	Reducing the risk of ignition and spread of flame		Р
	Method 1, selection and application of components wiring and materials	(see appended table 4.7)	Р



Report No.: 071-75942209-000

Page	15	of	24
------	----	----	----

Clause	Requirement + Test	Result - Remark	Verdict
F			1
	Method 2, application of all of simulated fault condition tests		N/A
4.7.2	Conditions for a fire enclosure		Р
4.7.2.1	Parts requiring a fire enclosure	Supplied by limited power source	N/A
4.7.2.2	Parts not requiring a fire enclosure		Р
4.7.3	Materials		Р
4.7.3.1	General		Р
4.7.3.2	Materials for fire enclosures		N/A
4.7.3.3	Materials for components and other parts outside fire enclosures		Р
4.7.3.4	Materials for components and other parts inside fire enclosures		N/A
4.7.3.5	Materials for air filter assemblies		N/A
4.7.3.6	Materials used in high-voltage components		N/A

5	ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS	Р
5.1	Touch current and protective conductor current	N/A

|--|

5.3	Abnormal operating and fault conditions		Р
5.3.1	Protection against overload and abnormal operation	(see appended table 5.3)	Р
5.3.2	Motors		N/A
5.3.3	Transformers		N/A
5.3.4	Functional insulation	Method c)	Р
5.3.5	Electromechanical components		N/A
5.3.6	Audio amplifiers in ITE	-	N/A
5.3.7	Simulation of faults		Р
5.3.8	Unattended equipment		N/A
5.3.9	Compliance criteria for abnormal operating and fault conditions		N/A
5.3.9.1	During the tests		Р
5.3.9.2	After the tests		N/A

6	CONNECTION TO TELECOMMUNICATION NETWORKS	N/A
7	CONNECTION TO CABLE DISTRIBUTION SYSTEMS	N/A

		Page 16 of 24	4 Report No.: 071-75942209-000		
	IEC 60950-1				
Clause	Requirement + Test		Result - Remark	Verdict	

Α ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE N/A В ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and N/A 5.3.2) С ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3) N/A D ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS N/A (see 5.1.4) Е ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13) N/A

F	ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)	N/A

G	ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES	N/A
---	---	-----

|--|

J	ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)	N/A
	Metal(s) used	

|--|

L	ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)	Ρ
L.1	Typewriters	N/A
L.2	Adding machines and cash registers	N/A
L.3	Erasers	N/A
L.4	Pencil sharpeners	N/A
L.5	Duplicators and copy machines	N/A
L.6	Motor-operated files	N/A
L.7	Other business equipment	Р

М

ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)

N/A



N/A

Page	17	of 24	
i ugo		0121	

	IEC 60950-1		
Clause	Requirement + Test	Result - Remark	Verdict
Ν	ANNEX N, IMPULSE TEST GENERATORS (see 17.3.2, 7.4.3 and Clause G.5)	.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1,	N/A
Р	ANNEX P, NORMATIVE REFERENCES		

Q	ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)	N/A

R	ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES	N/A
---	---	-----

S	ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)	N/A

т	ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)	N/A

U	ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED
	INSULATION (see 2.10.5.4)

|--|

W	ANNEX W, SUMMATION OF TOUCH CURRENTS	N/A
X	ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)	N/A

Y ANNEX Y, ULTRAVIOLET LIGHT CONI	DNING TEST (see 4.3.13.3) N/A
-----------------------------------	-------------------------------

Z ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2) N/
--

AA	ANNEX AA, MANDREL TEST (see 2.10.5.8)	
----	---------------------------------------	--

BB	ANNEX BB, CHANGES IN THE SECOND EDITION	
СС	ANNEX CC, Evaluation of integrated circuit (IC) current limiters	N/A
DD	ANNEX DD, Requirements for the mounting means of rack-mounted equipment	N/A
EE	ANNEX EE, Household and home/office document/media shredders	N/A



N/A

N/A

N/A

		Page 18 of 24	Report No.: 071-7594	2209-000
IEC 60950-1				
Clause	Requirement + Test		Result - Remark	Verdict

r							
1.5.1	TABLE: List of critical components						
Object/part N	0.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Marl confc	<(s) of prmity ¹)
Battery Pack (containing 4 cells, 4S		GP	CR123A	Cell: 3V, 1400mAh, +60°C	UL CCN: BBCV2 UL CCN: BBFS2	UL (MH UL (MH	l46184) l25972)
LED 2		AVAGO	ASMT-QWBF- NKL0E	3.5V Max, 150mA, 120℃	IEC 62471	TÜV SÜ Report: 719103 EEC12-	ÜD 8919- CMF ²

Supplementary information:

- 1) Provided evidence ensures the agreed level of compliance. See OD-CB2039.
- 2) Variant declaration submitted by manufacturer.

1.5.1	TABLE: Opto Electronic Devices	N/A			
Manufacturer					
Туре					
Separately tes	sted				
Bridging insula	Bridging insulation				
External creepage distance: -					
Internal creepage distance					
Distance through insulation: -					
Tested under the following conditions: -					
Input: -					
Output					
supplementar	y information				

1.6.2	TABLE: Electrical data (in normal conditions)							
U (V)	I (A)	Irated (A)	P (W)	Fuse #	lfuse (A)	Condition/statu	S	
12	0.395	-	-	-	-	Peak when in alert (information only)		
Supplomor	Cumplementary information: For information only							

Supplementary information: For information only

2.1.1.5 c) 1)	TABLE: max. V, A, VA test					
Voltage (rated) (V)		Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (ma: (VA)	x.)
-		-	-	-	-	
supplementary information:						



Page 19 of 24

Report No.: 071-75942209-000

IEC 60950-1

Clause	Requirement + Test	Result - Remark	Verdict

2.1.1.5 c) 2)	TABLE: stored energy					
Capacitance C (μF) Voltage U (V) Energy E (J)						
supplementary information:						

2.2	TABLE: evaluation of voltage limiting	E: evaluation of voltage limiting components in SELV circuits				
Component (measured between)		max. voltage (V) (normal operation)		Voltage Limiting Com	ponents	
		V peak	V d.c.			
	-	-	-	-		
Fault test pe	Vol	tage measi (V p	ured (V) in SELV circuit beak or V d.c.)	ts		
	-			-		
supplement	ary information:					

2.5	TABLE: Limited power sources					Р
Circuit output tested: Battery Pack						
Note: Measured Uoc (V) with all load circuits disconnected:						
Component	s Test condition	Uoc (V) I _{sc} (A)		VA		
	(Single lauit)		Meas.	Limit	Meas.	Limit
Battery Pac	k SC	12	3.0	8	9.6	100
supplementary information:						
Sc=Short circuit, Oc=Open circuit						

2.10.2	Table: working voltage measurement				N/A
Location		RMS voltage (V)	Peak voltage (V)	Comments	
	-	-	-	-	
supplementary information:					

2.10.3 and 2.10.4	TABLE: Clearance	TABLE: Clearance and creepage distance measurements					N/A	
Clearance (distance (cr)	cl) and creepage) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)		cr (mm)
-		-	-	-	-	-	-	
Supplementary information:								



Page 20 of 24			Report No.: 07	71-75942209-000
		IEC 60950-1		
Clause	Requirement + Test		Result - Remark	Verdict

2.10.5	ABLE: Distance through insulation measurements					
Distance through insulation (DTI) at/of:		U peak (V)	U rms (V)	Test voltage (V)	Required DTI (mm)	DTI (mm)
	-	-	-	-	-	-
Supplementary information:						

4.3.8	TABLE:	Batteries							Р
The tests o data is not	The tests of 4.3.8 are applicable only when appropriate battery data is not available						N/A		
Is it possibl	le to install	the battery	in a reverse p	polarity pos	sition?	Not user re	placeable		N/A
	Non-re	chargeable	e batteries			Rechargeal	ole batterie	s	
	Disch	arging	Un- intentional	Chai	rging	Disch	arging	Reve charç	rsed ging
	Meas. current	Manuf. Specs.	charging	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.
Max. current during normal condition	39mA	<2A	25mA	-	-	-	-	-	-
Max. current during fault condition	2.8	-	-	-	-	-	-	-	-
									I
Test results	s:								Verdict
- Chemical leaks									Р
- Explosion of the battery									Р
- Emission of flame or expulsion of molten metal									Р
- Electric st	- Electric strength tests of equipment after completion of tests					N/A			
Supplemen	Supplementary information:								



Page 21 of 24

Report No.: 071-75942209-000

IEC 60950-1

Clause	Requirement + Test	Result - Remark	Verdict

4.3.8	TABLE: Batteries		Р
Battery category:		(Lithium)	
Manufacture	er:	GP	
Type / mode	əl:	CR123A	
Voltage	:	3V	
Capacity:		1400mAh	
Tested and Certified by (incl. Ref. No.) :		UL (MH46184)	
Circuit protection diagram:		N/A	

MARKINGS AND INSTRUCTIONS (1.7.13)			
Location of replaceable battery			
Language(s)	-		
Close to the battery	-		
In the servicing instructions	-		
In the operating instructions	-		

4.5	TABLE: Thermal requirements						Р
	Supply voltage (Vdc):	12.0	-	-	-	-	
	Ambient T _{min} (°C):	22.5	-	-	-	-	_
	Ambient T _{max} (°C):	22.5	-	-	-	-	_
Maximum measured temperature T of part/at:				T (°C)			Allowed T _{max} (°C)
PCB adj Antenna 1		61.6	-	-	-	-	105
PCB adj IC1		62.0	-	-	-	-	105
PCB adj IC	9	62.0	-	-	-	-	105
L12 windin	g	61.8	-	-	-	-	130
PCB adj IC	2	62.2	-	-	-	-	105
L1 surface temp		60.5	-	-	-	-	130
PCB adj battery connectors		60.3	-	-	-	-	105
Internal Ambient		57.0 ¹	-	-	-	-	60
Enclosure Silicone button		58.8	-	-	-	-	85
Enclosure	olastic	61.5	-	-	-	-	75

Supplementary information:

Note 1: Our MU for temperature readings is 3.5°C. Because this temperature is within this limit we are unable to confirm if this is a pass or fail. Responsibility for the acceptance of this falls with Orolia. Temperatures adjusted for a rated opertaing ambient of +55°C



Page 22 of 24

Report No.: 071-75942209-000

IEC	60950-1
	00000 1

Clause	Requirement + Test	Result - Remark	Verdict

4.5.5	TABLE: Ball pressure test of thermoplastic parts				
	Allowed impression diameter (mm)	≤ 2 mm			
Part		Test temperature (°C)	Impression (mm	diameter 1)	
-		-	-		
Supplement	tary information:				

4.7	TABLE:	Resistance to fire					Р	
Part		Manufacturer of material	Type of material	Thickness (mm)	Flammability class	Ev	idence	
Enclosure (Main)	Sabic Innovative Plastics	C1200	2.1	UL 94 HB	UL (E	45329)	
Keypad	ypad Midgold GF-151 2.0 UL 94 HB		UL 94 HB	UL (E	312893)			
Main housir	ng top	Sabic Innovative Plastics	C1200	2.0	UL 94 HB	UL (E	45329)	
Main enclosure lid		Coverstro deutschland AG	Makrolon 2807	2.1	UL 94 HB	UL (E	41613)	
PCB Q&D Circuits M2-A		M2-A	0.52	UL 94 V0	UL (E	251497)		
PCB Interchangeable		Interchangeable	Interchangeable	-	UL 94 V0	UL*		
Supplementary information:								

5.1	TABLE: touch current measurement					
Measured b	etween:	Measured (mA)	Limit (mA)	Comments/conditions		
	-	-	-	-		
supplement	ary information:					

5.2	TABLE: Electric strength tests, impulse tests and voltage surge tests					
Test voltage applied between:		Voltage shape (AC, DC, impulse, surge)	Test voltage (V)	Breakdo wn Yes / No		
-		-	-	-		
Supplement	ary information:					



Page 23 of 24	Report No.: 071-75942209-000			
IEC 60950-1				
Clause Requirement + Test	Result - Remark	Verdict		

5.3	TABLE: Fault condition tests							Р
	Ambient temperat	ure (°C)				22.3°0)	
	Power source for EUT: Manufacturer, model/type, output rating: DC PSU TTI CPX400A (Current limit set at 12Vdc, 3A)							
Component No.	Fault	Supply voltage (V)	Test time	Fuse #	l Cl	Fuse urrent (A)	Observation	
C48	SC	3.3	0:05:00	-		-	Slight temperature rise or which peaked around 30°	n L14 °C
C50	SC	12	0:15:00	-		-	Temperature rise on L11 or hazard observed.	, no fire
Supplement	ary information:							

C.2	TABLE: transforme	TABLE: transformers						
Loc.	Tested insulation	Working voltage peak / V (2.10.2)	Working voltage rms / V (2.10.2)	Required electric strength (5.2)	Required clearance / mm (2.10.3)	Required creepage distance / mm (2.10.4)	Req dista insu (2.1	uired ance thr. I. 0.5)
-	-	-	-	-	-	-		-
Loc.	Tested insulation			Test voltage/ V	Measured clearance / mm	Measured creepage dist./ mm	Mea dista insu num laye	asured ance thr. I. / mm; Iber of Irs
-	-			-	-	-		-
supplement	supplementary information:							

C.2	TABLE: transformers	N/A
Transformer		

TUV

Blank Page



IEC60950_1F - ATTACHMENT					
Clause	Requirement + Test		Result - Remark	Verdict	

ATTACHMENT TO TEST REPORT IEC 60950-1 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Information technology equipment – Safety –

Part 1: General requirements

Differences according to	EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013
Attachment Form No	EU_GD_IEC60950_1F
Attachment Originator	SGS Fimko Ltd
Master Attachment	Date 2014-02

Copyright © 2014 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.

EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013 - CENELEC COMMON MODIFICATIONS

	IEC 60950-1, GROU	JP DIFFERE	NCES (CENE	LEC commo	on modifications EN)	
Clause	Requirement + Te	st		Resu	lt - Remark	Verdict
	Clauses, subclauses, notes, tables and figures which are additional to those in IEC60950-1 and it's amendmets are prefixed "Z"					
Contents	Add the following	annexes:				Р
	Annex ZA (normative)		Normative r publications publications	references to s with their co s	international prresponding European	
(A2:2013)	Annex ZB (normative)Special national conditionsAnnex ZD (informative)IEC and CENELEC code designations for flexible cords					
General	Delete all the "cou according to the for 1.4.8 Note 2 1.5.8 Note 2 2.2.3 Note 2.3.2.1 Note 2 2.7.1 Note 3.2.1.1 Note 4.3.6 Note 1 & 2 4.7.3.1Note 2 6 Note 2 & 5 6.2.2 Note	intry" notes in blowing list: 1.5.1 1.5.9.4 2.2.4 2.3.4 2.10.3.2 3.2.4 4.7 5.1.7.1 6.1.2.1 6.2.2.1	n the reference Note 2 & 3 Note Note 2 Note 2 Note 2 Note 3. Note 4 Note 3 & 4 Note 2 Note 2 Note 2	e document (1.5.7.1 1.7.2.1 2.3.2 2.6.3.3 2.10.5.13 2.5.1 4.7.2.2 5.3.7 6.1.2.2 6.2.2.2	IEC 60950-1:2005) Note Note 4, 5 & 6 Note Note 2 & 3 Note 2 Note 3 Note 2 Note Note Note 1 Note Note	P
	G.2.1 Note 2	7.2 Annex H	Note 2	7.3	NOLE I & 2	
General (A1:2010)	Delete all the "cou 1:2005/A1:2010) a 1.5.7.1 Note 6.2.2.1 Note	intry" notes in according to 2	n the reference the following lis 6.1.2.1 EE.3	e document (st: Note 2 Note	IEC 60950-	P

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

I	EC 60950-1, GROUP DIFFERENCES (CENELEC co	ommon modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
General (A2:2013)	Delete all the "country" notes in the reference docur1:2005/A2:2013) according to the following list:2.7.1Note *2.10.3.1Note6.2.2.Note* Note of secretary: Text of Common Modification remains unch	ment (IEC 60950- 2 anged.	Р
1.1.1 (A1:2010)	Replace the text of NOTE 3 by the following. NOTE 3 The requirements of EN 60065 may also be used to me equipment. See IEC Guide 112, Guide on the safety of multimed 60065 applies.	eet safety requirements for multimedia dia equipment. For television sets EN	N/A
1.3.Z1	Add the following subclause: 1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones. NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for "one package equipment", and in EN 50332-2, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Guidelines to associate sets with headphones coming from different manufacturers.		N/A
(A12:2011)	In EN 60950-1:2006/A12:2011 Delete the addition of 1.3.Z1 / EN 60950-1:2006 Delete the definition 1.2.3.Z1 / EN 60950-1:2006 /A1:2010		Р
1.5.1 (Added info*)	Add the following NOTE: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC. New Directive 2011/65/11 *		Р
1.7.2.1 (A1:2010)	In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N/A
1.7.2.1 (A12.2011)	In EN 60950-1:2006/A12:2011 Delete NOTE Z1 and the addition for Portable Sound System. Add the following clause and annex to the existing standard and amendments.		N/A

	IEC60950_1F - ATTACHMENT			
Clause	Vause Requirement + Test Result - Remark			
IEC 60050-1 GBOUD DIFFERENCES (CENELEC common modifications EN)				

Clause	Requirement + Test	Result - Remark	Verdict
	Zx Protection against excessive sound pres players	sure from personal music	N/A
	Zx.1 General		N/A
	This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players.		
	A personal music player is a portable equipment for personal use, that:		
	 is designed to allow the user to listen to recorded or broadcast sound or video; and 		
	 primarily uses headphones or earphones that can be worn in or on or around the ears; and 		
	 allows the user to walk around while in use. 		
	NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment.		
	A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause.		
	The requirements in this sub-clause are valid for music or video mode only.		
	The requirements do not apply:		
	 while the personal music player is connected to an external amplifier; or 		
	 while the headphones or earphones are not used. 		
	NOTE 2 An external amplifier is an amplifier which is not part of the personal music player or the listening device, but which is intended to play the music as a standalone music player.		
	The requirements do not apply to:		
	 hearing aid equipment and professional equipment; 		
	NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.		

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

I	IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict	
	 analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015. 		N/A	
	NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies.			
	For equipment which is clearly designed or intended for use by young children, the limits of EN 71-1 apply.			
	Zx.2 Equipment requirements		N/A	
	No safety provision is required for equipment that complies with the following:			
	 equipment provided as a package (personal music player with its listening device), where 			
	the acoustic output $L_{Aeq,T}$ is ≤ 85 dBA measured while playing the fixed "programme simulation noise" as described in EN 50332-1; and			
	 a personal music player provided with an analogue electrical output socket for a listening device, where the electrical output is ≤ 27 mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" as described in EN 50332-1. 			
	NOTE 1 Wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level $L_{Aeq,T}$ is meant. See also Zx.5 and Annex Zx.			
	All other equipment shall:			
	 a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and 			
	 b) have a standard acoustic output level not exceeding those mentioned above, and 			
	automatically return to an output level not exceeding those mentioned above when the power is switched off; and			

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test	Result - Remark	Verdict	

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	 c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and 		N/A
	NOTE 2 Examples of means include visual or audible signals. Action from the user is always required. NOTE 3 The 20 h listening time is the accumulative listening time, independent how often and how long the personal music		
	player has been switched off.		
	a) have a warning as specified in $2x.3$; and e) not exceed the following:		
	 equipment provided as a package (player with Its listening device), the acoustic output shall be ≤ 100 dBA measured while playing the fixed "programme simulation noise" described in EN 50332-1; and 		
	2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be ≤ 150 mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" described in EN 50332-1.		
	For music where the average sound pressure (long term L _{Aeq,T}) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song. NOTE 4 Classical music typically has an average sound pressure (long term L _{Aeq,T}) which is much lower than the average programme simulation noise. Therefore, if the player is canable to analyse the song and compare it with the		
	programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA		

	IEC60950_1F - ATTACHME	INT	
Clause	Requirement + Test	Result - Remark	Verdict
	IEC 60950-1, GROUP DIFFERENCES (CENELEC c	ommon modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.3 Warning The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following: – the symbol of Figure 1 with a minimum height of 5 mm; and – the following wording, or similar: "To prevent possible hearing damage, do not listen at high volume levels for long periods." Figure 1 – Warning label (IEC 60417-6044) Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the		N/A
	Zx.4 Requirements for listening devices (headp	hones and earphones)	N/A
	 Zx.4.1 Wired listening devices with analogue input With 94 dBA sound pressure output LAeq,T, the input voltage of the fixed "programme simulation noise" described in EN 50332-2 shall be ≥ 75 mV. This requirement is applicable in any mode where the headphones can operate (active or passive), including any available setting (for example built-in volume level control). NOTE The values of 94 dBA – 75 mV correspond with 85dBA – 27 mV and 100 dBA – 150 mV. 		N/A

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	 Zx.4.2 Wired listening devices with digital input With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output LAeq,T of the listening device shall be ≤ 100 dBA. This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.). 		N/A
	NOTE An example of a wired listening device with digital input is a USB headphone.		
	 Zx.4.3 Wireless listening devices In wireless mode: with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and respecting the wireless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the abovementioned programme simulation noise, the acoustic output LAeq,T of the listening device is a Bluetooth headphone. 		N/A
	Zx.5 Measurement methodsMeasurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s.NOTE Test method for wireless equipment provided without listening device should be defined.		N/A

Page 8 of 19

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
Clause 2.7.1	Requirement + TestReplace the subclause as follows:Basic requirementsTo protect against excessive current, short-circuitsand earth faults in PRIMARY CIRCUITS,protective devices shall be included either asintegral parts of the equipment or as parts of thebuilding installation, subject to the following, a), b)and c):a) except as detailed in b) and c), protectivedevices necessary to comply with therequirements of 5.3 shall be included as parts ofthe equipment;b) for components in series with the mains input tothe equipment such as the supply cord, appliancecoupler, r.f.i. filter and switch, short-circuit andparts fault protection may be provided by	Result - Remark	Verdict N/A
	 c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet. 		N/A
2.7.2	This subclause has been declared 'void'.		N/A
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		N/A
3.2.5.1	Replace"60245 IEC 53" by "H05 RR-F"; "60227 IEC 52" by "H03 VV-F or H03 VVH2-F"; "60227 IEC 53" by "H05 VV-F or H05 VVH2-F2".In Table 3B, replace the first four lines by the following:Up to and including 6 0,75 a) Over 6 up to and including 10 (0,75) b)1,0 Over 10 up to and including 16 (1,0) c)1,5 In the conditions applicable to Table 3B delete the words "in some countries" in condition a).In NOTE 1, applicable to Table 3B, delete the second sentence.		N/A

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

I	EC 60950-1, GROUP DIFFERENCES (CENELEC c	ommon modifications EN)	
Clause	Requirement + Test	Result - Remark	Verdict
3.2.5.1 (A2:2013)	NOTE Z1 The harmonised code designations corresponding to the IEC cord types are given in Annex ZD		N/A
3.3.4	In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following: Over 10 up to and including 16 1,5 to 2,5 1,5 to 4 Delete the fifth line: conductor sizes for 13 to 16 A		N/A
4.3.13.6 (A1:2010)	Replace the existing NOTE by the following: NOTE Z1 Attention is drawn to: 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and 2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artifical optical radiation).		N/A
	Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.		N/A
Annex H	Replace the last paragraph of this annex by: At any point 10 cm from the surface of the OPERATOR ACCESS AREA, the dose rate shall not exceed 1 μ Sv/h (0,1 mR/h) (see NOTE). Account is taken of the background level. Replace the notes as follows: NOTE These values appear in Directive 96/29/Euratom. Delete NOTE 2.		N/A
Bibliography	Additional EN standards.		

ZA	NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH	
	THEIR CORRESPONDING EUROPEAN PUBLICATIONS	

ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict
1.2.4.1	In Denmark , certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N/A
1.2.13.14 (A11:2009)	In Norway and Sweden , for requirements see 1.7.2.1 and 7.3 of this annex.		N/A



IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

	ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)				
Clause	Requirement + Test	Result - Remark	Verdict		
1.5.7.1 (A11:2009)	In Finland , Norway and Sweden , resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N/A		
1.5.8	In Norway , due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N/A		
1.5.9.4	In Finland , Norway and Sweden , the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N/A		



IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

	ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict	
1.7.2.1	In Finland , Norway and Sweden , CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows: In Finland : "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In Norway : "Apparatet må tilkoples jordet stikkontakt" In Sweden : "Apparaten skall anslutas till jordat uttag"		N/A	
1.7.2.1 (A11:2009)	In Norway and Sweden , the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system. It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: "Equipment connected to the protective earthing of the building installation through the mains connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)."			

IEC60950_1F - ATTACHMENT

Clause

Requirement + Test

Result - Remark

Verdict

ZB ANNEX (normative)			
	SPECIAL NATIONAL CONDITIC	NS (EN)	
Clause	Requirement + Test	Result - Remark	Verdict
	NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min. Translation to Norwegian (the Swedish text will		N/A
	also be accepted in Norway):		
	nettplugg og/eller via annet jordtilkoplet		
	utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel- TV nettet."		
	Translation to Swedish:		
	jordat vägguttag och/eller via annan		
	utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medfőra risk főr		
	brand. Főr att undvika detta skall vid anslutning av utrustningen till kabel-TV nät		
	galvanisk isolator finnas mellan utrustningen och kabel-TV nätet."		
1.7.2.1 (A2:2013)	In Denmark , CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet.		N/A
	The marking text in Denmark shall be as follows: In Denmark : "Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord."		
1.7.5	In Denmark , socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1- 1b or DK 1-5a.		N/A
1.7.5 (A11:2009)	For CLASS II EQUIPMENT the socket outlet shall be in accordance with Standard Sheet DKA 1-4a.		

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)				
Clause	Requirement + Test	Result - Remark	Verdict	
1.7.5 (A2:2013)	In Denmark , socket-outlets for providing power to other equipment shall be in accordance with the DS 60884-2-D1:2011.		N/A	
	For class I equipment the following Standard Sheets are applicable: DK 1-3a, DK 1-1c, DK 1-1d, DK 1-5a or DK 1-7a, with the exception for STATIONARY EQUIPMENT where the socket-outlets shall be in accordance with Standard Sheet DK 1-1b, DK 1-1c, DK 1-1d or DK 1-5a.			
	Socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance with DS 60884-2-D1 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with by DS 60884-2-D1 Standard Sheet DKA 1-3a or DKA 1-3b.			
	Justification the Heavy Current Regulations, 6c			
2.2.4	In Norway , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A	
2.3.2	In Finland , Norway and Sweden there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N/A	
2.3.4	In Norway , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A	
2.6.3.3	In the United Kingdom , the current rating of the circuit shall be taken as 13 A, not 16 A.		N/A	
2.7.1	In the United Kingdom , to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N/A	
2.10.5.13	In Finland , Norway and Sweden , there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N/A	

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

	ZB ANNEX (normative)		
Clause	Bequirement + Test	Besult - Bemark	Verdict
3.2.1.1	In Switzerland , supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets: SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A		N/A
	 SEV 6533-2.1991 Plug Type 11 L+N 250 V, 10 A SEV 6534-2.1991 Plug Type 12 L+N+PE 250 V, 10 A In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16 A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998: SEV 5932-2.1998: Plug Type 25, 3L+N+PE 230/400 V, 16 A SEV 5934-2.1998: Plug Type 23, L+N+PE 250 V, 16 A 		
3.2.1.1	In Denmark , supply cords of single-phase equipment having a rated current not exceeding13 A shall be provided with a plug according to the Heavy Current Regulations, Section 107-2-D1. CLASS I EQUIPMENT provided with socket- outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If poly-phase equipment and single-phase equipment having a RATED CURRENT exceeding 13 A is provided with a supply cord with a plug, this plug shall be in accordance with the Heavy Current Regulations, Section 107-2-D1 or EN 60309-2.		N/A

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

ZB ANNEX (normative)			
	SPECIAL NATIONAL CONDITIO	ONS (EN)	1
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1 (A2:2013)	 In Denmark, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. 		N/A
	If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2.		
	Justification the Heavy Current Regulations, 6c		
3.2.1.1	In Spain , supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994.		N/A
	Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993.		
	CLASS I EQUIPMENT provided with socket- outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994.		
	If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.		
3.2.1.1	In the United Kingdom , apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations. NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		N/A

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

ZB ANNEX (normative)					
	SPECIAL NATIONAL CONDITIONS (EN)				
Clause	Requirement + Test	Result - Remark	Verdict		
3.2.1.1	In Ireland , apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.		N/A		
3.2.4	In Switzerland , for requirements see 3.2.1.1 of this annex.		N/A		
3.2.5.1	In the United Kingdom , a power supply cord with conductor of 1,25 mm2 is allowed for equipment with a rated current over 10 A and up to and including 13 A.		N/A		
3.3.4	In the United Kingdom , the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is: • 1,25 mm ² to 1,5 mm ² nominal cross-sectional area.		N/A		
4.3.6	In the United Kingdom , the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N/A		
4.3.6	In Ireland , DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.		N/A		

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

	ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict	
5.1.7.1	In Finland, Norway and Sweden TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment: • STATIONARY PLUGGABLE EQUIPMENT TYPE A that is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and is provided with instructions for the installation of that conductor by a SERVICE PERSON; • STATIONARY PLUGGABLE EQUIPMENT TYPE B; • STATIONARY PERMANENTLY CONNECTED EQUIPMENT.		N/A	
6.1.2.1 (A1:2010)	In Finland, Norway and Sweden, add the following text between the first and second paragraph of the compliance clause: If this insulation is solid, including insulation forming part of a component, it shall at least consist of either - two layers of thin sheet material, each of which shall pass the electric strength test below, or - one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below. Alternatively for components, there is no distance through insulation requirements for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition - passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and - is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.		N/A	

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

ZB ANNEX (normative)					
	SPECIAL NATIONAL CONDITIONS (EN)				
Clause	Requirement + Test	Result - Remark	Verdict		
	It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b).		N/A		
	It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2.				
	A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:				
	- the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1;				
	- the additional testing shall be performed on all the test specimens as described in EN 60384-14:				
	- the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.				
6.1.2.2	In Finland , Norway and Sweden , the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.		N/A		
7.2	In Finland , Norway and Sweden , for requirements see 6.1.2.1 and 6.1.2.2 of this annex.		N/A		
	6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.				
7.3 (A11:2009)	In Norway and Sweden , for requirements see 1.2.13.14 and 1.7.2.1 of this annex.		N/A		

IEC60950_1F - ATTACHMENT				
Clause	Requirement + Test		Result - Remark	Verdict

Annex ZD (informative)

IEC and CENELEC code designations for flexible cords

Type of flexible cord	Code desig	nations
	IEC	CENELEC
PVC insulated cords		
Flat twin tinsel cord	60227 IEC 41	H03VH-Y
Light polyvinyl chloride sheathed flexible cord	60227 IEC 52	H03VV-F H03VVH2-F
Ordinary polyvinyl chloride sheathed flexible cord	60277 IEC 53	H05VV-F H05VVH2-F
Rubber insulated cords		
Braided cord	60245 IEC 51	H03RT-F
Ordinary tough rubber sheathed flexible cord	60245 IEC 53	H05RR-F
Ordinary polychloroprene sheathed flexible cord	60245 IEC 57	H05RN-F
Heavy polychloroprene sheathed flexible cord	60245 IEC 66	H07RN-F
Cords having high flexibility		
Rubber insulated and sheathed cord	60245 IEC 86	H03RR-H
Rubber insulated, crosslinked PVC sheathed cord	60245 IEC 87	H03RV4-H
Crosslinked PVC insulated and sheathed cord	60245 IEC 88	H03V4V4-H



Attachment 2

Record Photographs

Issue 2 / 01-10





RECORD PHOTOGRAPH

External view



External Side and Front View (Fast Find 220)



External Side and Rear View (Fast Find 220)



Page 3 of 6 Report reference No.: 071-75942209-000

RECORD PHOTOGRAPH

External view



Top View (Fast Find 220)



Bottom View (Fast Find 220)





RECORD PHOTOGRAPH

External view



External Side View (Fast Find 220)



External Front view (Solo)

Page 5 of 6 Report reference No.: 071-75942209-000



RECORD PHOTOGRAPH

External view



External Front view (Solo)

Internal view



PCB Top View

Page 6 of 6 Report reference No.: 071-75942209-000



RECORD PHOTOGRAPH

Internal view



PCB Bottom View



Battery Pack