


# FCC RADIO TEST REPORT

FCC ID : 2AG0Z-CM5X  
Equipment : Media Receiver  
Brand Name : facebook  
Model Name : LW94NS  
Applicant : Facebook Technologies LLC  
1 Hacker Way Menlo Park CA 94025  
Standard : FCC Part 15 Subpart C §15.247

The product was received on Apr. 08, 2019 and testing was started from Apr. 08, 2019 and completed on Jun. 26, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Jones Tsai

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description.....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT .....	5
1.3 Testing Location .....	5
1.4 Applicable Standards.....	6
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1 Carrier Frequency Channel .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 Test Result.....</b>	<b>11</b>
3.1 6dB and 99% Bandwidth Measurement .....	11
3.2 Output Power Measurement.....	18
3.3 Power Spectral Density Measurement .....	19
3.4 Conducted Band Edges and Spurious Emission Measurement .....	26
3.5 Radiated Band Edges and Spurious Emission Measurement .....	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
<b>4 List of Measuring Equipment .....</b>	<b>42</b>
<b>5 Uncertainty of Evaluation.....</b>	<b>43</b>
<b>Appendix A. Conducted Test Results</b>	
<b>Appendix B. AC Conducted Emission Test Result</b>	
<b>Appendix C. Radiated Spurious Emission</b>	
<b>Appendix D. Radiated Spurious Emission Plots</b>	
<b>Appendix E. Duty Cycle Plots</b>	
<b>Appendix F. Setup Photographs</b>	



## History of this test report

Report No.	Version	Description	Issued Date
FR932216-01B	01	Initial issue of report	Jul. 04, 2019
FR932216-01B	02	1. Adding description of worst case in section 2.2 2. Revising the Connection Diagram of Test System in section 2.3	Jul. 21, 2019
FR932216-01B	03	Revising brand name	Jul. 31, 2019

## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 8.85 dB at 2310.42 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 11.23 dB at 0.683 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Dara Chiu**

# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac.

Product Specification subjective to this standard	
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No. 58, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	03CH011-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007



## 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in two setup, without all accessories, with all accessories. The worst cases (without all accessories) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
<b>Conducted Test Cases</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>Radiated Test Cases</b>	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
<b>AC Conducted Emission</b>	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + Adapter + MPEG4 + HDMI
<b>Remark:</b> For Radiated Test Cases, the tests were performed with Adapter and Notebook.	




## 2.3 Connection Diagram of Test System

### <Bluetooth LE Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	LCD Monitor	DELL	P2715Qt	FCC DoC	Shielded, 1.6m	Unshielded, 1.8m

## 2.5 EUT Operation Test Setup

The RF test items, utility "QRCT v3.0-00271" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 14.8 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 14.8 + 10 = 24.8 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<1Mbps>

#### 6 dB Bandwidth Plot on Channel 00




Date: 30.APR.2019 23:53:18

#### 6 dB Bandwidth Plot on Channel 19




Date: 30.APR.2019 23:58:33


### 6 dB Bandwidth Plot on Channel 39




**<2Mbps>**

### 6 dB Bandwidth Plot on Channel 00



**6 dB Bandwidth Plot on Channel 19**

Date: 1.MAY.2019 00:14:47

**6 dB Bandwidth Plot on Channel 39**

Date: 1.MAY.2019 00:09:32




### 3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<1Mbps>

#### 99% Bandwidth Plot on Channel 00





Date: 30.APR.2019 23:55:50



#### 99% Occupied Bandwidth Plot on Channel 19



Date: 1.MAY.2019 00:00:32

**99% Occupied Bandwidth Plot on Channel 39****<2Mbps>****99% Bandwidth Plot on Channel 00**



**99% Occupied Bandwidth Plot on Channel 19**

**99% Occupied Bandwidth Plot on Channel 39**


Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1Mbps>

#### PSD 100kHz Plot on Channel 00



Date: 30.APR.2019 23:53:42


#### PSD 100kHz Plot on Channel 19



Date: 30.APR.2019 23:59:28




PSD 100kHz Plot on Channel 39





Date: 1.MAY.2019 00:02:41

<2Mbps>

PSD 100kHz Plot on Channel 00



Date: 1.MAY.2019 00:19:35


**PSD 100kHz Plot on Channel 19****PSD 100kHz Plot on Channel 39**




### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

<1Mbps>

PSD 3kHz Plot on Channel 00




PSD 3kHz Plot on Channel 19






PSD 3kHz Plot on Channel 39



Date: 1.MAY.2019 00:02:12

<2Mbps>

PSD 3kHz Plot on Channel 00




Date: 1.MAY.2019 00:19:22






PSD 3kHz Plot on Channel 19



Date: 1.MAY.2019 00:15:06

PSD 3kHz Plot on Channel 39



Date: 1.MAY.2019 00:09:53

### 3.4 Conducted Band Edges and Spurious Emission Measurement

#### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.4.4 Test Setup






### 3.4.5 Test Result of Conducted Band Edges Plots


&lt;1Mbps&gt;

#### Low Band Edge Plot on Channel 00



Date: 26 JUN 2019 20:49:04


#### High Band Edge Plot on Channel 39




Date: 26 JUN 2019 20:54:47



&lt;2Mbps&gt;

**Low Band Edge Plot on Channel 00**

Date: 26 JUN 2019 21:04:48

**High Band Edge Plot on Channel 39**

Date: 26 JUN 2019 21:27:05




### 3.4.6 Test Result of Conducted Spurious Emission Plots

&lt;1Mbps&gt;

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00




Date: 26 JUN 2019 21:33:26

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00





Date: 26 JUN 2019 21:33:54

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps****GFSK Channel 19**

Date: 26 JUN 2019 20:52:50

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps****GFSK Channel 19**


Date: 26 JUN 2019 20:53:27

**Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39****Conducted Spurious Emission Plot on Bluetooth LE 1Mbps  
GFSK Channel 39**

<2Mbps>

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps**


**GFSK Channel 00**



Date: 26 JUN 2019 21:12:15


**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps**

**GFSK Channel 00**




Date: 26 JUN 2019 21:12:41




**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps****GFSK Channel 19**


Date: 26 JUN 2019 21:17:34

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps****GFSK Channel 19**

Date: 26 JUN 2019 21:24:23

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps****GFSK Channel 39**

Date: 26 JUN 2019 21:29:37

**Conducted Spurious Emission Plot on Bluetooth LE 2Mbps****GFSK Channel 39**

Date: 26 JUN 2019 21:30:38



### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments


See list of measuring equipment of this test report.

### 3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - $VBW = 10$  Hz, when duty cycle is no less than 98 percent.
    - $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

### 3.5.7 Duty Cycle

Please refer to Appendix E.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.





## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Sensor	DARE	RPR3006W	13I00030S NO32	9kHz~6GHz	Dec. 03, 2018	Apr. 16, 2019 ~ Jun. 26, 2019	Dec. 02, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz~40GHz	Nov. 21, 2018	Apr. 16, 2019 ~ Jun. 26, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Apr. 16, 2019 ~ Jun. 26, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW107090 3	N/A	Dec 19 2018	Apr. 16, 2019 ~ Jun. 26, 2019	Dec. 18, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 21, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	May 21, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	May 21, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	May 21, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	May 21, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	May 21, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	May 21, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz,VS WR : 2.5:1 max	Jul. 16, 2018	Apr. 08, 2019~ Apr. 25, 2019	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 04, 2018	Apr. 08, 2019~ Apr. 25, 2019	Dec. 03, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT- N0602	30MHz~1GHz	Oct. 13, 2018	Apr. 08, 2019~ Apr. 25, 2019	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 6	1GHz ~ 18GHz	Oct. 30, 2018	Apr. 08, 2019~ Apr. 25, 2019	Oct. 29, 2019	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Apr. 08, 2019~ Apr. 25, 2019	Jan. 06, 2020	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 14, 2018	Apr. 08, 2019~ Apr. 25, 2019	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2018	Apr. 08, 2019~ Apr. 25, 2019	Oct. 18, 2019	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Apr. 08, 2019~ Apr. 25, 2019	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Apr. 08, 2019~ Apr. 25, 2019	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	171000180 0054001	1GHz~18GHz	Apr. 16, 2018	Apr. 08, 2019~ Apr. 13, 2019	Apr. 15, 2019	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303	171000180 0055007	1GHz~18GHz	Apr. 01, 2019	Apr. 22, 2019~ Apr. 25, 2019	Mar. 31, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Apr. 08, 2019~ Apr. 25, 2019	Dec. 04, 2019	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY554201 70	N/A	Mar. 08, 2019	Apr. 08, 2019~ Apr. 25, 2019	Mar. 07, 2020	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-00104 2	N/A	N/A	Apr. 08, 2019~ Apr. 25, 2019	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 13, 2019	Apr. 08, 2019~ Apr. 25, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Apr. 08, 2019~ Apr. 25, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	30M-18G	Mar. 13, 2019	Apr. 08, 2019~ Apr. 25, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Apr. 08, 2019~ Apr. 25, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-153 0-8000-40SS	SN11	1G Low Pass	Sep. 16, 2018	Apr. 08, 2019~ Apr. 25, 2019	Sep. 17, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700- 3000-18000-60	SN3	2.7G High Pass	Sep. 16, 2018	Apr. 08, 2019~ Apr. 25, 2019	Sep. 17, 2019	Radiation (03CH11-HY)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.2 dB
---	--------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2 dB
---	--------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.5 dB
---	--------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2 dB
---	--------

**Appendix A. Test Result of Conducted Test Items**

Test Engineer:	Nick Yu / Kai Liao	Temperature:	21~25	°C
Test Date:	2019/4/30~2019/6/26	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.025	0.669	0.50	Pass
BLE	1Mbps	1	19	2440	1.025	0.669	0.50	Pass
BLE	1Mbps	1	39	2480	1.025	0.667	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.10	30.00	1.36	6.46	36.00	Pass
BLE	1Mbps	1	19	2440	4.50	30.00	1.36	5.86	36.00	Pass
BLE	1Mbps	1	39	2480	5.00	30.00	1.36	6.36	36.00	Pass

**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.35	-8.17	1.36	8.00	Pass
BLE	1Mbps	1	19	2440	5.78	-8.74	1.36	8.00	Pass
BLE	1Mbps	1	39	2480	6.10	-8.44	1.36	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Test Engineer:	Nick Yu / Kai Liao	Temperature:	21~25	°C
Test Date:	2019/4/30~2019/6/26	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.026	1.143	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.030	1.147	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.034	1.151	0.50	Pass

**TEST RESULTS DATA**  
**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	5.00	30.00	1.36	6.36	36.00	Pass
BLE5.0	2Mbps	1	19	2440	4.40	30.00	1.36	5.76	36.00	Pass
BLE5.0	2Mbps	1	39	2480	4.90	30.00	1.36	6.26	36.00	Pass


**TEST RESULTS DATA**  
**Peak Power Density**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	6.34	-11.81	1.36	8.00	Pass
BLE5.0	2Mbps	1	19	2440	5.76	-12.35	1.36	8.00	Pass
BLE5.0	2Mbps	1	39	2480	6.08	-12.13	1.36	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

## Appendix B. AC Conducted Emission Test Results


Test Engineer :	Eric Jeng	Temperature :	22~25°C
		Relative Humidity :	52~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line



### Final Result :

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
0.152250	---	37.06	55.88	18.82	L1	OFF	19.5
0.152250	43.10	---	65.88	22.78	L1	OFF	19.5
0.159000	---	40.65	55.52	14.87	L1	OFF	19.5
0.159000	44.33	---	65.52	21.19	L1	OFF	19.5
0.183750	---	38.46	54.31	15.85	L1	OFF	19.5
0.183750	41.87	---	64.31	22.44	L1	OFF	19.5
0.442500	---	34.88	47.02	12.14	L1	OFF	19.5
0.442500	40.37	---	57.02	16.65	L1	OFF	19.5
0.687750	---	33.08	46.00	12.92	L1	OFF	19.6
0.687750	35.05	---	56.00	20.95	L1	OFF	19.6
4.382250	---	24.57	46.00	21.43	L1	OFF	19.7
4.382250	25.53	---	56.00	30.47	L1	OFF	19.7

<b>Test Engineer :</b>	Eric Jeng	<b>Temperature :</b>	22~25°C
		<b>Relative Humidity :</b>	52~55%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral


**Final Result :**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	38.19	55.88	17.69	N	OFF	19.5
0.152250	43.38	---	65.88	22.50	N	OFF	19.5
0.159000	---	40.62	55.52	14.90	N	OFF	19.5
0.159000	44.86	---	65.52	20.66	N	OFF	19.5
0.174750	---	37.05	54.73	17.68	N	OFF	19.5
0.174750	41.82	---	64.73	22.91	N	OFF	19.5
0.186000	---	38.71	54.21	15.50	N	OFF	19.5
0.186000	42.16	---	64.21	22.05	N	OFF	19.5
0.208500	---	35.61	53.27	17.66	N	OFF	19.5
0.208500	39.14	---	63.27	24.13	N	OFF	19.5
0.377250	---	26.87	48.34	21.47	N	OFF	19.5
0.377250	29.99	---	58.34	28.35	N	OFF	19.5
0.442500	---	32.92	47.02	14.10	N	OFF	19.5
0.442500	37.54	---	57.02	19.48	N	OFF	19.5
0.683250	---	34.77	46.00	11.23	N	OFF	19.6
0.683250	36.44	---	56.00	19.56	N	OFF	19.6



## Appendix C. Radiated Spurious Emission

Test Engineer :	Hao Xu, Ken Wu, Fu Chen	Temperature :	20~25°C
		Relative Humidity :	50~54%

## 2.4GHz 2400~2483.5MHz

## BLE\_1Mbps (Band Edge @ 3m)

BLE	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BLE CH 00 2402MHz		2343.18	53.25	-20.75	74	42.69	27.63	16.58	33.65	100	242	P	H
		2326.065	43.37	-10.63	54	32.76	27.7	16.56	33.65	100	242	A	H
	*	2402	102.11	-	-	91.69	27.4	16.65	33.63	100	242	P	H
	*	2402	101.52	-	-	91.1	27.4	16.65	33.63	100	242	A	H
		2365.44	53.43	-20.57	74	42.92	27.54	16.61	33.64	102	94	P	V
		2360.82	43.46	-10.54	54	32.94	27.56	16.6	33.64	102	94	A	V
	*	2402	102.82	-	-	92.4	27.4	16.65	33.63	102	94	P	V
	*	2402	102.13	-	-	91.71	27.4	16.65	33.63	102	94	A	V
BLE CH 19 2440MHz		2325.36	52.8	-21.2	74	42.19	27.7	16.56	33.65	100	241	P	H
		2326.16	43.5	-10.5	54	32.88	27.7	16.57	33.65	100	241	A	H
	*	2440	101.53	-	-	91.13	27.32	16.69	33.61	100	241	P	H
	*	2440	100.94	-	-	90.54	27.32	16.69	33.61	100	241	A	H
		2488.08	52.46	-21.54	74	42.01	27.3	16.74	33.59	100	241	P	H
		2489.2	43.14	-10.86	54	32.69	27.3	16.74	33.59	100	241	A	H
		2329.68	53.09	-20.91	74	42.49	27.68	16.57	33.65	341	63	P	V
		2314.64	43.48	-10.52	54	32.85	27.74	16.55	33.66	341	63	A	V
	*	2440	102.6	-	-	92.2	27.32	16.69	33.61	341	63	P	V
	*	2440	102	-	-	91.6	27.32	16.69	33.61	341	63	A	V
		2498.08	52.47	-21.53	74	42.01	27.3	16.75	33.59	341	63	P	V
		2498.72	43.45	-10.55	54	32.99	27.3	16.75	33.59	341	63	A	V





<b>BLE CH 39 2480MHz</b>	*	2480	103.08	-	-	92.65	27.3	16.73	33.6	356	209	P	H
	*	2480	102.28	-	-	91.85	27.3	16.73	33.6	356	209	A	H
		2497.64	52.92	-21.08	74	42.46	27.3	16.75	33.59	356	209	P	H
		2483.84	43.68	-10.32	54	33.24	27.3	16.74	33.6	356	209	A	H
	*	2480	101.93	-	-	91.5	27.3	16.73	33.6	330	63	P	V
	*	2480	101.19	-	-	90.76	27.3	16.73	33.6	330	63	A	V
		2494.12	52.66	-21.34	74	42.2	27.3	16.75	33.59	330	63	P	V
		2499.24	43.55	-10.45	54	33.09	27.3	16.75	33.59	330	63	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**BLE\_1Mbps (Harmonic @ 3m)**

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
<b>BLE CH 00 2402MHz</b>		4804	36.7	-37.3	74	53.76	31.1	11	59.16	100	0	P	H
		4804	37.31	-36.69	74	54.37	31.1	11	59.16	100	0	P	V
<b>BLE CH 19 2440MHz</b>		4880	38.1	-35.9	74	55.18	31.04	11.06	59.18	100	0	P	H
		7320	41.22	-32.78	74	50.2	36.54	13.65	59.17	100	0	P	H
		4880	37.53	-36.47	74	54.61	31.04	11.06	59.18	100	0	P	V
		7320	41.45	-32.55	74	50.43	36.54	13.65	59.17	100	0	P	V
<b>BLE CH 39 2480MHz</b>		4960	37.68	-36.32	74	54.44	31.32	11.11	59.19	100	0	P	H
		7440	42.2	-31.8	74	51.22	36.48	13.62	59.12	100	0	P	H
		4960	38.33	-35.67	74	55.09	31.32	11.11	59.19	100	0	P	V
		7440	41.05	-32.95	74	50.07	36.48	13.62	59.12	100	0	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**2.4GHz 2400~2483.5MHz****BLE\_2Mbps (Band Edge @ 3m)**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
<b>BLE CH 00 2402MHz</b>		2311.575	53.29	-20.71	74	42.65	27.75	16.55	33.66	100	251	P	H
		2383.5	44.79	-9.21	54	34.32	27.47	16.63	33.63	100	251	A	H
	*	2402	102.25	-	-	91.83	27.4	16.65	33.63	100	251	P	H
	*	2402	100.89	-	-	90.47	27.4	16.65	33.63	100	251	A	H
		2323.755	53.2	-20.8	74	42.59	27.7	16.56	33.65	102	94	P	V
		2310.42	45.15	-8.85	54	34.5	27.76	16.55	33.66	102	94	A	V
	*	2402	102.85	-	-	92.43	27.4	16.65	33.63	102	94	P	V
	*	2402	101.6	-	-	91.18	27.4	16.65	33.63	102	94	A	V
<b>BLE CH 19 2440MHz</b>		2326.24	52.63	-21.37	74	42.01	27.7	16.57	33.65	173	206	P	H
		2364.46	44.81	-9.19	54	34.3	27.54	16.61	33.64	173	206	A	H
	*	2440	102.16	-	-	91.76	27.32	16.69	33.61	173	206	P	H
	*	2440	100.68	-	-	90.28	27.32	16.69	33.61	173	206	A	H
		2493.14	52.41	-21.59	74	41.95	27.3	16.75	33.59	173	206	P	H
		2494.33	44.88	-9.12	54	34.42	27.3	16.75	33.59	173	206	A	H
		2365.16	52.84	-21.16	74	42.33	27.54	16.61	33.64	341	63	P	V
		2330.3	44.98	-9.02	54	34.38	27.68	16.57	33.65	341	63	A	V
	*	2440	102.66	-	-	92.26	27.32	16.69	33.61	341	63	P	V
	*	2440	101.16	-	-	90.76	27.32	16.69	33.61	341	63	A	V
		2496.99	52.57	-21.43	74	42.11	27.3	16.75	33.59	341	63	P	V
		2489.92	44.76	-9.24	54	34.31	27.3	16.74	33.59	341	63	A	V



<b>BLE CH 39 2480MHz</b>	*	2480	103.08	-	-	92.65	27.3	16.73	33.6	357	207	P	H
	*	2480	101.72	-	-	91.29	27.3	16.73	33.6	357	207	A	H
		2483.56	55.46	-18.54	74	45.02	27.3	16.74	33.6	357	207	P	H
		2486.72	44.91	-9.09	54	34.46	27.3	16.74	33.59	357	207	A	H
	*	2480	102.14	-	-	91.71	27.3	16.73	33.6	328	64	P	V
	*	2480	100.76	-	-	90.33	27.3	16.73	33.6	328	64	A	V
		2483.52	55.93	-18.07	74	45.49	27.3	16.74	33.6	328	64	P	V
		2484.28	44.66	-9.34	54	34.22	27.3	16.74	33.6	328	64	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**BLE\_2Mbps (Harmonic @ 3m)**

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		4804	37.75	-36.25	74	54.81	31.1	11	59.16	100	0	P	H
		4804	38.1	-35.9	74	55.16	31.1	11	59.16	100	0	P	V
BLE CH 19 2440MHz		4880	37.84	-36.16	74	54.92	31.04	11.06	59.18	100	0	P	H
		7320	42.89	-31.11	74	51.87	36.54	13.65	59.17	100	0	P	H
		4880	38.11	-35.89	74	55.19	31.04	11.06	59.18	100	0	P	V
		7320	41.86	-32.14	74	50.84	36.54	13.65	59.17	100	0	P	V
BLE CH 39 2480MHz		4960	38.07	-35.93	74	54.83	31.32	11.11	59.19	100	0	P	H
		7440	42.51	-31.49	74	51.53	36.48	13.62	59.12	100	0	P	H
		4960	38.86	-35.14	74	55.62	31.32	11.11	59.19	100	0	P	V
		7440	42.76	-31.24	74	51.78	36.48	13.62	59.12	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Emission below 1GHz**
**2.4GHz BLE (LF)**

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
<b>2.4GHz BLE LF</b>		30.97	21.02	-18.98	40	29.03	23.58	0.78	32.37	-	-	P	H
		71.71	23.82	-16.18	40	42.83	12.19	1.15	32.35	-	-	P	H
		127	25.86	-17.64	43.5	39.32	17.34	1.5	32.3	-	-	P	H
		268.62	27.68	-18.32	46	38.69	18.95	2.24	32.2	-	-	P	H
		624.61	34.09	-11.91	46	36.95	25.91	3.42	32.19	100	0	P	H
		947.62	33.25	-12.75	46	29.42	30.43	4.31	30.91	-	-	P	H
		36.79	28.74	-11.26	40	39.48	20.81	0.82	32.37	-	-	P	V
		50.37	28.88	-11.12	40	46.37	13.94	0.94	32.37	100	0	P	V
		131.85	27.59	-15.91	43.5	41.09	17.26	1.53	32.29	-	-	P	V
		268.62	24.94	-21.06	46	35.95	18.95	2.24	32.2	-	-	P	V
		666.32	30.95	-15.05	46	33.16	26.4	3.55	32.16	-	-	P	V
		954.41	33.62	-12.38	46	29.38	30.77	4.32	30.85	-	-	P	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical

A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**









## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Hao Xu, Ken Wu, Fu Chen	Temperature :	20~25°C
		Relative Humidity :	50~54%





### Note symbol





-L	Low channel location
-R	High channel location

**2.4GHz 2400~2483.5MHz**
**BLE\_1Mbps (Band Edge @ 3m)**



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
Peak	 <p>           Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>
Avg.	 <p>           Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p></div>	<div><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p></div>
Avg	<div><p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p></div>	<div><p>Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p></div>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p>
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p>	 <p>Site : 03CH11-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p>







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
Peak	<div><p>Site : 03CH11-I-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p></div>	
Avg.	<div><p>Site : 03CH11-I-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p></div>	





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>
Avg.	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Project : Peak            : 932216         </p>	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Project : Peak            : 932216         </p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>Site : 03CH11-I-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p>	
Avg.	 <p>Site : 03CH11-I-HY Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p>	

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-JF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-JF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 932216</p>
Avg.	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-JF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p>	 <p>Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-JF HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : 932216</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : 932216         </p>	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : 932216         </p>
Avg.	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Project : 932216         </p>	 <p>           Date: 2019-04-23            Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto            Project : 932216         </p>

**2.4GHz 2400~2483.5MHz**  
**BLE\_1Mbps (Harmonic @ 3m)**

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
<b>Peak</b>  <b>Avg.</b>	 <p> Site : 03CHI1-HY  Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL  Detector : Peak  Project : 932216 </p>	 <p> Site : 03CHI1-HY  Condition : PEAK_74 3m HORN 9120D-HF VERTICAL  Detector : Peak  Project : 932216 </p>











BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<div><p>Level (dBuV/m) Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 932216</p></div>	<div><p>Level (dBuV/m) Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 932216</p></div>









BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<div><p>Level (dBuV/m) 140.0 130.0 120.0 110.0 100.0 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20.0 10.0 0</p><p>Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 932216</p></div>	<div><p>Level (dBuV/m) 140.0 130.0 120.0 110.0 100.0 90.0 80.0 70.0 60.0 50.0 40.0 30.0 20.0 10.0 0</p><p>Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 932216</p></div>

**2.4GHz 2400~2483.5MHz**  
**BLE\_2Mbps (Band Edge @ 3m)**





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Fundamental
<b>Peak</b>	 <p>           Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>
<b>Avg.</b>	 <p>           Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL            RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Detector : Peak            Project : 932216         </p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH00 2402MHz	
	Vertical	Fundamental
Peak	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>
Avg	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : Avg            : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : Avg            : 932216         </p>

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Horizontal	Fundamental
Peak	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : 932216         </p>
Avg.	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_54 3m HORN 91200-HF HORIZONTAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : 932216         </p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Horizontal	Fundamental
<b>Peak</b>	 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 932216</p>	
<b>Avg.</b>	 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 932216</p>	







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - L	
	Vertical	Fundamental
Peak	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Project : Peak            : 932216         </p>
Avg.	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : Avg.            : 932216         </p>	 <p>           Date: 2019-04-22            Site : 03CH11-HY            Condition : AVG_54 3m HORN 9120D-HF VERTICAL            Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto            Project : Avg.            : 932216         </p>

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH19 2440MHz - R	
	Vertical	Fundamental
Peak	 <p>           Site : 03CH11-HY            Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL            Detector : Peak            Project : 932216         </p>	
Avg.	 <p>           Site : 03CH11-HY            Condition : AVG_BE_54 3m HORN 91200-HF VERTICAL            Detector : Peak            Project : 932216         </p>	





BLE		2.4GHz 2400~2483.5MHz Band Edge @ 3m	
		BLE CH39 2480MHz	
		Horizontal	Fundamental
Peak		 <p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p>	 <p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p>
Avg.		 <p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 932216</p>	 <p>Site : 03CH11-HY Condition : AVG_54 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 932216</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Vertical	Fundamental
Peak	<div><p>Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p></div>	<div><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 932216</p></div>
Avg.	<div><p>Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 932216</p></div>	<div><p>Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 932216</p></div>

**2.4GHz 2400~2483.5MHz**
**BLE\_2Mbps (Harmonic @ 3m)**

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
<b>Peak</b>  <b>Avg.</b>	 <p>           Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CH11-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            Detector : Peak            Project : 932216         </p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	<div><p>Level (dBuV/m) Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 932216</p></div>	<div><p>Level (dBuV/m) Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 932216</p></div>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
Peak	<div><p>Level (dBuV/m)</p><p>Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 932216</p></div>	<div><p>Level (dBuV/m)</p><p>Date: 2019-04-23</p><p>Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 932216</p></div>

**Emission below 1GHz**
**2.4GHz BLE (LF)**


BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
<b>QP / Peak</b>	 <p>           Site : 03CHI1-HY            Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL            Detector : Peak            Project : 932216         </p>	 <p>           Site : 03CHI1-HY            Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL            Detector : Peak            Project : 932216         </p>



## Appendix E. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting	Duty Factor (dB)
Bluetooth LE_1Mbps	62.18	388.00	2.58	3kHz	2.06
Bluetooth LE_2Mbps	32.48	204.00	4.90	10kHz	4.88

### Bluetooth LE v4.0



Date: 16.APR.2019 22:08:26

### Bluetooth LE v5.0



Date: 16.APR.2019 22:10:53