

# Test Report

<b>Product</b>	FIDO2 Security Key
<b>Name and address of the applicant</b>	Pone Biometrics AS Universitetsgata 2 0164 Oslo, Norway
<b>Name and address of the manufacturer</b>	Pone Biometrics AS Universitetsgata 2 0164 Oslo, Norway
<b>Model</b>	OFFPAD+
<b>Rating</b>	Secondary Battery (3.7V, USB-C Charging)
<b>Trademark</b>	PONE
<b>Additional information</b>	Bluetooth LE
<b>Tested according to</b>	<b>FCC Part 15.247</b> Frequency Hopping Transmitters / Digital Transmission Systems <b>Industry Canada RSS-247, Issue 3</b> Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
<b>Order number</b>	PRJ0058629
<b>Tested in period</b>	2024-11-18 to 2024-11-19
<b>Issue date</b>	2025-02-28
<b>Name and address of the testing laboratory</b>	<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="text-align: center;">   Nemko Scandinavia AS  Instituttveien 6  2007 Kjeller, Norway  www.nemko.com </div> <div style="text-align: center;"> CAB Number:  FCC: NO0001  ISED: NO0470  ISED No: 2040D-1 </div> <div style="text-align: center;">    </div> </div> <p style="text-align: center; color: red; font-weight: bold;">An accredited technical test executed under the Norwegian accreditation scheme</p>
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">   Prepared by [Frode Sveinsen] </div> <div style="text-align: center;">   Approved by [Jan G Eriksen] </div> </div>	
This report was originally distributed electronically with digital signatures. For more information, please contact Nemko Scandinavia AS.	

## Revision history

Revision	Date	Comment	Sign
A	2025-02-28	First edition	FS

## GENERAL REMARKS

This report applies only to the sample(s) tested. It is the manufacturer's responsibility to ensure the additional production units of this product are manufactured with identical electrical and mechanical components. The manufacturer is solely responsible for any modifications to the product that could result in non-compliance with the relevant regulations.

This report shall not be reproduced, except in full, without the written approval of Nemko.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damage suffered by any third party because of decisions made or actions based on this report.

Opinions expressed within this report regarding general assessments and qualifications for PASS or FAIL to the standards limits and requirements, are not part of the current accreditation. Neither are opinions expressed regarding model variants covered by the testing of this report.

## CALIBRATION

All instruments used in the tests given in this test report are calibrated and traceable to national or international standards. Between calibrations all test set-ups are controlled and verified on a regular basis by periodic checks to ensure, with 95% confidence, that the instruments remain within the calibrated levels.

## MEASUREMENT UNCERTAINTY

Measurement uncertainties are calculated or considered for all instruments and instrument set-ups used during these tests. Uncertainty figures are found in a separate clause in this report.

## CONTENTS

<b>1</b>	<b>INFORMATION .....</b>	<b>4</b>
1.1	Test Item .....	4
1.2	Normal test condition .....	4
1.3	Test Engineers .....	4
1.4	Antenna Requirement .....	5
1.5	EUT Operating Modes .....	5
1.6	Comments .....	5
<b>2</b>	<b>TEST REPORT SUMMARY .....</b>	<b>6</b>
2.1	General .....	6
2.2	Test Summary .....	6
<b>3</b>	<b>TEST RESULTS .....</b>	<b>7</b>
3.1	Occupied Bandwidth (99% BW) .....	7
3.2	DTS Bandwidth .....	9
3.3	Peak Power Output .....	11
3.4	Conducted Emissions at Antenna Connector .....	13
3.5	Restricted Bands of operation .....	16
3.6	Radiated Emissions, Band Edge .....	17
3.7	Radiated Emissions, 30 – 1000 MHz .....	19
3.8	Radiated Emissions, 1 – 26 GHz .....	21
3.9	Power Spectral Density (PSD) .....	25
<b>4</b>	<b>Measurement Uncertainty .....</b>	<b>27</b>
<b>5</b>	<b>LIST OF TEST EQUIPMENT .....</b>	<b>28</b>
<b>6</b>	<b>BLOCK DIAGRAM .....</b>	<b>29</b>
6.1	Power Line Conducted Emission .....	29
6.2	Conducted Tests .....	29
6.3	Test Site Radiated Emission .....	30

# 1 INFORMATION

## 1.1 Test Item

Product	FIDO2 Security Key
Manufacturer	Pone Biometrics
Model	OFFPAD+
FCC ID	2BLGV-0202
ISED ID	33121-0202
Serial number	-
Hardware version	-
Software version	-
Frequency Range	2402 – 2480 MHz
Number of Channels	40
Operating Modes	Bluetooth Low Energy <input checked="" type="checkbox"/> 1Mb <input type="checkbox"/> 2Mb
Type of Modulation	GFSK
Conducted Output Power	2.9 mW
Antenna Connector	None
Number of Antennas	1
Diversity or Smart Antennas	No
Power Supply	Secondary Battery (3.7V Li-Ion)
Connectors	USB-C for Charging

### Description of Test Item

FIDO2 Security Key.

## 1.2 Normal test condition

Temperature:	20 - 24 °C
Relative humidity:	20 - 50 %
Normal test voltage:	3.7 V DC

All measurements were performed with the EUT powered from a fully charged battery.

The values are the limit registered during the test period.

## 1.3 Test Engineers

Frode Sveinsen

## 1.4 Antenna Requirement

Does the EUT have detachable antenna(s)?	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO
If detachable, is the antenna connector(s) non-standard?	<input type="checkbox"/> YES	<input type="checkbox"/> NO
The tested equipment has only integral antennas. Conducted tests were performed with a temporary antenna connector.		

Requirement: FCC 15.203, 15.204

## 1.5 EUT Operating Modes

Description of operating modes	The EUT was transmitting a modulated signal at maximum output power.
Additional information	All tests were performed with the EUT charging from a power bank.

## 1.6 Comments

/

## 2 TEST REPORT SUMMARY

### 2.1 General

The tests were conducted on a sample of the equipment for demonstrating compliance with one or more of the following standards.

Standard	Description
FCC CFR 47 Part 15.247	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz
ISED RSS-247, Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
ISED RSS-GEN Issue 5	General Requirements for Compliance of Radio Apparatus

The following standards and documents were used for one or more measurements:

Standard	Description
ANSI C63.4-2014	Unintentional Radiators
ANSI C63.10-2013	Intentional Radiators
FCC KDB 558074 D01	15.247 Measurement Guidance for DTS and Frequency Hopping Systems
FCC KDB 412172 D01	Determining ERP and EIRP

All measurements are traceable to national standards.

A description of the test facility is on file with FCC and ISED Canada.

<input checked="" type="checkbox"/> New Submission	<input checked="" type="checkbox"/> Production Unit
<input type="checkbox"/> Class II Permissive Change	<input type="checkbox"/> Pre-production Unit
DTS Equipment Class	<input type="checkbox"/> Family Listing

### 2.2 Test Summary

Name of test	FCC Part 15 reference	RSS-247 Issue 3, RSS-GEN Issue 5 reference	ANSI C63.10-2013 Reference	Result
Supply Voltage Variations	15.31(e)	6.11 (RSS-GEN)	5.13	N/A
Antenna Requirement	15.203	6.8 (RSS-GEN)	5.8	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	7.2 / 8.8 (RSS-GEN)	6.2	N/A
Occupied Bandwidth (99% BW)	N/A	6.7 (RSS-GEN)	6.9.3	Complies
DTS Bandwidth	15.247(a)(2)	5.2 (1) (RSS-247)	11.8 Option 2	Complies
Peak Power Output	15.247(b)	5.4 (RSS-247)	11.9.1.1	Complies
Power Spectral Density	15.247(d)	5.2 (2) (RSS-247)	11.10.2 PKPSD (DTS)	Complies
Spurious Emissions (Antenna Conducted)	15.247(c)	5.5 (RSS-247)	6.7 11.11 (DTS)	Complies
Spurious Emissions (Radiated)	15.247(c) 15.109(a) 15.209(a)	3.3 (RSS-247) 7.3 (RSS-GEN) 8.9 (RSS-GEN)	6.3, 6.5, 6.6, 6.10 11.12, 11.13 (DTS)	Complies

### 3 TEST RESULTS

#### 3.1 Occupied Bandwidth (99% BW)

ISED Canada RSS-GEN Issue 5, Clause 6.7

Measurement procedure: ANSI C63.10-2013 Clause 6.9.2

Test Results: Complies


Measurement Data:

Carrier Frequency, Data Rate	Occupied Bandwidth (99% BW)
2402 MHz, 1Mb	0.950 MHz
2440 MHz, 1Mb	1.002 MHz
2480 MHz, 1Mb	1.004 MHz

See attached plots.

#### Requirements:


No requirement for 99% BW, reported for information only.



99% Occupied BW, 2402 MHz, 1Mb



99% Occupied BW, 2440 MHz, 1Mb



99% Occupied BW, 2480 MHz, 1Mb



## 3.2 DTS Bandwidth

FCC Part 15.247 (a)(2)

ISED Canada RSS-247 Issue 3, Clause 5.2 (a)

Measurement procedure: ANSI C63.10-2013 Clause 11.8


Test Results: Complies

### Measurement Data:


Modulation type and bitrate	Measured DTS Bandwidth (kHz)		
	2402 MHz	2440 MHz	2480 MHz
GFSK 1 Mbps	658	665	665

Power supply variation within 85 % to 115% of nominal value has no influence on measured value.


Frequency Band	Requirement for systems using Digital Modulation
902-928 MHz	The minimum 6 dB bandwidth shall be at least 500 kHz.
2400-2483.5 MHz	
5725-5850 MHz	



DTS BW, 2402 MHz, 1M



DTS BW, 2440 MHz, 1M



DTS BW, 2480 MHz, 1M

### 3.3 Peak Power Output

FCC Part 15.247 (b)

ISED Canada RSS-247 Issue 3, Clause 5.4

Measurement procedure: ANSI C63.10-2013 Clause 11.9.1.2

Test Results: Complies

#### Measurement Data:

Carrier Frequency	Peak Conducted Power, dBm		Peak EIRP, dBm		Antenna Gain, dBi	
	GFSK 1Mb	GFSK 2Mb	GFSK 1Mb	GFSK 2Mb	GFSK 1Mb	GFSK 2Mb
2402 MHz	4.64	N/A	1.36	N/A	-3.3	N/A
2440 MHz	4.57	N/A	-6.68	N/A	-11.2	N/A
2480 MHz	4.43	N/A	-2.47	N/A	-6.9	N/A


Output Power reported is Maximum Peak Power.

Radiated Power was calculated from measured Field Strength using the method described in FCC KDB 412172 D01 and in ANSI C63.10-2013 Annex G.


Antenna Gain is less than 6 dBi.

See attached plots.

Requirements for Digital Modulation systems
For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
As an alternative to a peak power measurement, compliance with the 1 Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the <i>maximum conducted output power</i> is the highest total transmit power occurring in any mode.
Maximum allowed Antenna Gain
If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced below the stated value above by the amount in dB that the directional gain of the antenna exceeds 6 dBi.




Peak Power, 2402 MHz, 1Mb




Date: 18.NOV.2024 09:50:19

Peak EIRP, 2402 MHz, 1Mb




Peak Power, 2440 MHz, 1Mb




Date: 18.NOV.2024 12:47:43

Peak EIRP, 2440 MHz, 1Mb



Peak Power, 2480 MHz, 1Mb



Date: 18.NOV.2024 09:40:31

Peak EIRP, 2480 MHz, 1Mb

### 3.4 Conducted Emissions at Antenna Connector

FCC Part 15.247 (d)

ISED Canada RSS-247 Issue 3, Clause 5.5

Measurement procedure: ANSI C63.10-2013 Clause 11.11

Test Results: Complies


Measurement Data:

Carrier Frequency	Highest Value (dBc)	Margin (dB)	Verdict
2402 MHz	> 50	> 30	Pass
2440 MHz	> 50	> 30	Pass
2480 MHz	> 50	> 30	Pass


Measured with Peak Detector

RF conducted power to 25 GHz: see attached plots.


Requirements for all systems	
Peak measurement	RMS averaging (alternative measurement)
20 dB or more below carrier measured in 100 kHz bandwidth	30 dB or more below carrier measured in 100 kHz bandwidth
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.</p> <p>Attenuation below the general limits specified in § 15.209(a) is not required.</p>	




Conducted Emissions 10-2350 MHz, 2402 MHz, 1Mb




Conducted Emissions 2.55-10 GHz, 2402 MHz, 1Mb




Conducted Emissions 2350-2550 MHz, 2402 MHz, 1Mb




Conducted Emissions 10-26 GHz, 2402 MHz, 1Mb




Conducted Emissions 10-2350 MHz, 2440 MHz, 1Mb




Conducted Emissions 2.55-10 GHz, 2440 MHz, 1Mb




Conducted Emissions 2350-2550 MHz, 2440 MHz, 1Mb




Conducted Emissions 10-26 GHz, 2440 MHz, 1Mb




Conducted Emissions 10-2350 MHz, 2480 MHz, 1Mb



Conducted Emissions 2.55-10 GHz, 2480 MHz, 1Mb



Conducted Emissions 2350-2550 MHz, 2480 MHz, 1Mb



Conducted Emissions 10-26 GHz, 2480 MHz, 1Mb

### 3.5 Restricted Bands of operation

Restricted Bands of operation for FCC and ISSED are defined in FCC Part 15.205 and ISSED RSS-GEN, Issue 5 clause 8.10.

Generally, no fundamentals are allowed in the restricted bands and all emissions must comply with the limits in FCC 15.209 or RSS-GEN, Issue 5, clause 8.9.

FCC (MHz)	ISSED (MHz)	FCC (GHz)	ISSED (GHz)
0.090-0.110		<b>0.96-1.24</b> <b>1.3-1.427</b>	<b>0.96-1.427</b>
0.495-0.505		1.435-1.6265	
2.1735-2.1905		1.6455-1.6465	
	<b>3.020-3.026</b>	1.660-1.710	
4.125-4.128		1.7188-1.7222	
4.17725-4.17775		2.2-2.3	
4.20725-4.20775		2.31-2.39	
	<b>5.677-5.683</b>	2.4835-2.5	
6.215-6.218		<b>2.69-2.9</b>	<b>2.655-2.9</b>
6.26775-6.26825		3.26-3.267	
6.31175-6.31225		3.332-3.339	
8.291-8.294		3.3458-3.358	
8.362-8.366		<b>3.6-4.4</b>	<b>3.5-4.4</b>
8.37625-8.38675		4.5-5.15	
8.41425-8.41475		5.35-5.46	
12.29-12.293		7.25-7.75	
12.51975-12.52025		8.025-8.5	
12.57675-12.57725		9.0-9.2	
13.36-13.41		9.3-9.5	
16.42-16.423		10.6-12.7	
16.69475-16.69525		13.25-13.4	
16.80425-16.80475		14.47-14.5	
25.5-25.67		15.35-16.2	
37.5-38.25		17.7-21.4	
73-74.6		22.01-23.12	
74.8-75.2		23.6-24.0	
<b>108-121.94</b> <b>123-138</b>	<b>108-138</b>	31.2-31.8	
149.9-150.05		36.43-36.5	
156.52475-156.52525		Above 38.6	
156.7-156.9			
162.0125-167.17			
167.72-173.2			
240-285			
322-335.4			
399.9-410			
608-614			

Frequencies in **Bold** text are specific for FCC or ISSED, all other frequencies are common.



### 3.6 Radiated Emissions, Band Edge

FCC Part 15.209 (a)

ISED Canada RSS-GEN Issue 5, Clause 7.3 / 8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Test Results: Complies


#### Measurement Data:

Peak Detector					
Modulation and Bitrate	Measured field strength (dB $\mu$ V/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	dB	dB	
GFSK, 1Mb	43.0	52.1	74	31.0	21.9

Average Detector					
Modulation and Bitrate	Measured field strength (dB $\mu$ V/m)		Limit	Margin	
	2390 MHz	2483.5 MHz	dB	dB	
GFSK, 1Mb	/	/	54	/	/


Peak values are below Average Limit.

See attached plots.




Date: 18.NOV.2024 09:52:11

### Lower Band Edge, 2402 MHz, 1Mb, Peak



Date: 18.NOV.2024 09:41:19

### Upper Band Edge, 2480 MHz, 1Mb, Peak



Date: 18.NOV.2024 12:41:41

Duty Cycle = 86.6%

### 3.7 Radiated Emissions, 30 – 1000 MHz.

FCC Part 15.209 (a)

ISED Canada RSS-GEN Issue 5, Clause 7.3/8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Test Results: Complies

#### Measurement Data:

Detector: Peak

Measuring distance 3 m

Tested in test mode with EUT transmitting on 2440 MHz



Measured Frequency (MHz)	Carrier Frequency (MHz)	Modulation	Measured Emission (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30 – 88	2440	GFSK	< 34	40.0	> 6
88 – 216	2440	GFSK	< 30	43.5	> 13.5
216 – 960	2440	GFSK	< 40	46.0	> 6
960 – 1000	2440	GFSK	< 40	54.0	> 14

No emissions were detected.

See attached plots.

#### Requirements/Limit

FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, Clause 8.9 @ frequencies defined in clause 8.10	
Frequency	Radiated emission limit @3 meters	
30 – 88 MHz	100 µV/m	40.0 dBµV/m
88 – 216 MHz	150 µV/m	43.5 dBµV/m
216 – 960 MHz	200 µV/m	46.0 dBµV/m
960 – 1000 MHz	500 µV/m	54.0 dBµV/m
	Limits above are with Quasi Peak Detector	



### 3.8 Radiated Emissions, 1 – 26 GHz

FCC Part 15.209 (a)

ISED Canada RSS-GEN Issue 5, Clause 7.3/8.9

Measurement procedure: ANSI C63.10-2013 Clause 11.12

Test Results: Complies

Measurement Data:

Measuring distance: 3m (1 – 18 GHz)  
1m (18 – 26 GHz)

A pre-scan was performed above 18 GHz and no spurious emissions were detected.

RBW=1 MHz

Carrier Frequency (MHz)	Measured Frequency (GHz)	Mode	Measured Emissions (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
			Peak	Average	Pk	Av	Pk	Av
2402	7206	GFSK	58.5	53.3	74	54	15.5	0.7
2440	7320	GFSK	57.9	52.3	74	54	16.1	1.7
2480	7440	GFSK	56.6	50.7	74	54	17.4	3.3

A Band Reject Filter was used for measurements from 1 GHz to 18 GHz

Antenna factor, amplifier gain and cable loss are included in spectrum analyzer "Transducer factor".


See plots.

Duty Cycle Correction Factor:  $-20 \times \log(0.866)$  dB = 1.3 dB


DC Correction Factor is added to measured Average Values

#### Requirements/Limit


FCC	Part 15.209 @ frequencies defined in §15.205	
ISED	RSS-GEN Issue 5, clause 8.9 @ frequencies defined in clause 8.10	
	Radiated emission limit @3 meters	
Frequency	Average Detector	Peak Detector
1 – 26 GHz	54.0 dBμV/m	74.0 dBμV/m




Radiated Emissions 1 - 18 GHz, 2402 MHz, HP




Radiated Emissions 1 - 18 GHz, 2402 MHz, VP




Radiated Emissions 1 - 18 GHz, 2440 MHz, HP




Radiated Emissions 1 - 18 GHz, 2440 MHz, VP



Radiated Emissions 1 - 18 GHz, 2480 MHz, HP




Radiated Emissions 1 - 18 GHz, 2480 MHz, VP




Date: 11.FEB.2025 10:07:56

Radiated Emissions 18 - 26 GHz, 2440 MHz, HP, @1m




Date: 11.FEB.2025 10:06:37


Radiated Emissions 18 - 26 GHz, 2440 MHz, VP, @1m




Radiated Emissions 7206 MHz, 2402 MHz, Max: HP, Pk




Av




Radiated Emissions 7320 MHz, 2440 MHz, Max: HP, Pk



Av



Radiated Emissions 7440 MHz, 2480 MHz, Max: HP, Pk



Av



### 3.9 Power Spectral Density (PSD)

FCC part 15.247(d)

ISED Canada RSS-247 Issue 3, Clause 5.2 (2)

Measurement procedure: ANSI C63.10-2013 Clause 11.10

Test Results: Complies

#### Measurement Data:


The measurement procedure PKPSD described in ANSI C63.10-2013 was used.

Modulation Type and Bitrate	Measured Power Spectral Density (dBm/3kHz)		
	2402 MHz	2440 MHz	2480 MHz
GFSK 1Mb	-10.5	-10.1	-10.0


#### Requirement for systems using Digital Modulation

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


No requirements for Frequency Hopping Systems.



PSD, 2402 MHz, 1Mb



PSD, 2440 MHz, 1Mb



PSD, 2480 MHz, 1Mb

## 4 Measurement Uncertainty

Measurement Uncertainty Values		
Test Item		Uncertainty
Output Power		±0.5 dB
Power Spectral Density		±0.5 dB
Out of Band Emissions, Conducted	< 3.6 GHz	±0.6 dB
	> 3.6 GHz	±0.9 dB
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB
	> 1 GHz	±2.2 dB
Emission Bandwidth		±4 %
Power Line Conducted Emissions		+2.9 / -4.1 dB
Spectrum Mask Measurements	Frequency	±5 %
	Amplitude	±1.0 dB
Frequency Error		±0.6 ppm
Temperature Uncertainty		±1 °C

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2

## 5 LIST OF TEST EQUIPMENT

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the testhouse.


No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSW43	Spectrum Analyzer	Rohde & Schwarz	LR 1690	2024-01 2025-02	2025-01 2026-02
2	ESU40	Measuring Receiver	Rohde & Schwarz	LR 1639	2024-01 2025-02	2025-01 2026-02
3	6810.17B	Attenuator	Suhner	LR 1669	COU	
4	NO324415	Band Reject Filter	Microwave Circuits	LR 1760	COU	
5	JB3	BiLog Antenna	Sunol	N-4525	2023-04	2026-04
6	310	Preamplifier	Sonoma Inst.	LR 1686	2024-09	2025-09
7	3117-PA	Horn Antenna +PreAmp	EMCO	LR 1717	2024-09	2025-09
8	3115	Horn Antenna	EMCO	LR 1330		
9	8449A	Pre-amplifier	Hewlett Packard	LR 1322	2024-09	2025-09
10	WLK5-1100-1485-7000-40SS	Low Pass Filter	Wainwright Inst.	LR 1761	COU	
11	638	Antenna Horn	Narda	LR 1480	N/A	
12	ST18/SMA/N/36	RF Cable	Suhner	LR 1627	COU	

The software listed below has been used for one or more tests.


No.	Manufacturer	Name	Version	Comment
1	Rohde & Schwarz	EMC32	10.50.40	EMC test software
2	Rohde & Schwarz	GPIShot	2.7	Screenshots from R&S Spectrum Analyzers

## 6 BLOCK DIAGRAM

### 6.1 Power Line Conducted Emission




### 6.2 Conducted Tests



This test set-up is used for all Conducted tests.  
For Frequency Stability test the EUT was placed in a climatic chamber.

## 6.3 Test Site Radiated Emission



This test setup is used for all radiated emissions tests. For frequencies below 30 MHz the measuring distance is 10m, for all other frequencies it is 3m or 1m. Emissions above 1 GHz are measured with a Spectrum Analyzer and Horn Antenna. For measurements above 18 GHz the test receiver is moved inside the anechoic chamber and located next to the antenna to minimize the cable loss. All measurements at 1GHz and above were performed with turntable height 1.5m and with the ground plane covered by absorbers. A pre-amplifier is used for all measurements above 30 MHz, and High-Pass or Band-Pass filter is used for all harmonics.