

PAGE NO. 9 of 47. AMENDED September 29, 2000

NAME OF TEST: R. F. Power Output (Radiated)

SPECIFICATION: 47 CFR 2.1046(a)

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE (RADIATED)

1. The EUT was placed on an open-field site and its radiated field strength at a known distance was measured by means of a spectrum analyzer. Equivalent loading was calculated from the equation $P_t = ((E \times R)^2 / 49.2)$ watts, where $R = 3m$.
2. Measurement accuracy is ± 1.5 dB.

MEASUREMENT RESULTS

g0040006: 2000-Apr-05 Wed 13:29:00

STATE: 2:High Power

AMPS MODE:

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV/m	CF, dB	ERP, dBm	ERP, Watts
470.050000	470.048000	110.51	23.74	36.7	4.58
480.050000	480.048000	110.15	23.75	36.3	4.26
489.950000	489.948000	108.52	23.71	34.5	2.82

Sample Calculation:

$$\begin{aligned}
 E &= \text{Log}_{10}^{-1} \frac{110.51 + 23.74}{20} \\
 &= 5.01 \text{ Volts} \\
 P_t &= \frac{(5.01 \times 3)^2}{49.2} \\
 &= 4.58 \text{ W. ERP} \\
 &= 36.7 \text{ dbm ERP}
 \end{aligned}$$