

APPENDIX E: SAR SYSTEM VALIDATION

FCC ID: BCGA2117	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Head Mounted Device		APPENDIX: E Page 1 of 2

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-1
SAR System Validation Summary – 1g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM9	2450	02/28/2023	7427	2450	Head	1.870	39.800	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM9	5250	02/28/2023	7427	5250	Head	4.686	34.916	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5600	02/28/2023	7427	5600	Head	5.094	34.229	PASS	PASS	PASS	OFDM	N/A	PASS
AM9	5750	02/28/2023	7427	5750	Head	5.283	33.936	PASS	PASS	PASS	OFDM	N/A	PASS

Table E-2
SAR System Validation Summary – 10g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
AM11	2450	12/22/2022	3949	2450	Head	1.845	40.817	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
AM11	5250	03/06/2023	7308	5250	Head	4.780	34.753	PASS	PASS	PASS	OFDM	N/A	PASS
AM11	5600	03/06/2023	7308	5600	Head	5.165	34.039	PASS	PASS	PASS	OFDM	N/A	PASS
AM11	5750	03/06/2023	7308	5750	Head	5.334	33.750	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: Probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: BCGA2117	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Head Mounted Device		APPENDIX: E Page 2 of 2