

8

7

6

5

4

3

2

1

REVISIONS

ZONE	REV	DESCRIPTION	DATE	APPROVED
	A	New version release	2023.07.19	

Ground
Terre

Traveler
Pendentif

Neutral
Neutre

Tighten terminal screws to 12lbf-in
Serrer les vis de borne à 14Kgf-cm

Line/Load
Secteur/Charge

Strip length 5/8in.
Longueur de bande 16mm

Line/Load
Secteur/Charge

Actual size
Taille actuelle

Do not wrap around screw terminals
Ne pas enrouler autour des bornes à vis

JASCO
PRO

SERIES
ZWN4015

Date Code:2332

UL

Intertek
5023165

Appliance Controls
Contrôles
de l'appareil

For indoor use only

CU

MA

Pour utilisation intérieure uniquement

CU

MA

125VAC/125VCA 60HZ
Resistive load 15A
Charge résistive 15A
incandescent load 1250W
Charge 1250W
(incandescent)
Motor load 1/2HP
Charge de moteur 1/2HP
Resistive load 1875W
Charge résistive 1875W
104°F maximum
40°C maximale

In-Wall Smart Switch
Montage Mural
Interrupteur Intelligent
MODEL: ZWN4015
FCC ID: QOBZWN4015
IC: 6924A-ZWN4015

Jasco Products Company
Oklahoma City, OK
www.bjjasco.com
Made in Vietnam/
Fabriqué en Vietnam

2WAVE
PLUS LR

JASCO
PRO

CAUTION/
ADVERTENCIA

HIGH VOLTAGE.
DISCONNECT POWER
SUPPLY BEFORE
SERVICING/ALTO
VOLTAJE.
DESCONECTE
LA POTENCIA ANTES
DE REPARAR

NOAH

TOLERANCE UNLESS ESPECIALLY EXPLAIN X. '0.2 X.XX '0.05 X.X '0.1 aX~ '0.5~			MODEL NO:	4015	PART NAME:	
DRAW.BY:	曾清华	MAT'L:		P/N NO.		
CHECKED.BY:		COLOR:		FINISH:	镭雕	
REVIEWED BY:		SCALE:	N/A	QTY:	1	TOOL NO:
APPROVED BY:		SIZE:	A4	UNIT:	MM	SHEET:
						IOFI
						REV:
						A

8

7

6

5

4

3

2

1