



WiFi next-to-mouth Low CH1.....	2
WiFi next-to-mouth Middle CH6	3
WiFi next-to-mouth High CH11.....	4
WiFi wrist worn Low CH1.....	5
WiFi wrist worn Middle CH6	6
WiFi wrist worn High CH11.....	7

Test Laboratory: Compliance Certification Services Inc.

Date: 6/4/2018

WiFi next-to-mouth Low CH1**DUT: TicWatch Pro Smartwatch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2412 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2412$ MHz; $\sigma = 1.735$ S/m; $\epsilon_r = 37.815$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.4, 7.4, 7.4); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/Low CH1/Area Scan (10x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.297 W/kg


WiFi/Low CH1/Zoom Scan (7x7x5)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.55 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.390 W/kg

SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.135 W/kg

Maximum value of SAR (measured) = 0.315 W/kg



0 dB = 0.315 W/kg = -5.02 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 6/4/2018

WiFi next-to-mouth Middle CH6**DUT: TicWatch Pro Smartwatch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2437 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2437$ MHz; $\sigma = 1.764$ S/m; $\epsilon_r = 37.769$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.4, 7.4, 7.4); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/Middle CH6/Area Scan (10x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.361 W/kg


WiFi/Middle CH6/Zoom Scan (7x7x5)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.92 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.466 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.159 W/kg

Maximum value of SAR (measured) = 0.372 W/kg



0 dB = 0.372 W/kg = -4.29 dBW/kg

Test Laboratory: Compliance Certification Services Inc.

Date: 5/8/2018

WiFi next-to-mouth High CH11**DUT: Smart watch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2462 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.773 \text{ S/m}$; $\epsilon_r = 40.484$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/High CH11/Area Scan (10x10x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.453 W/kg


WiFi/High CH11/Zoom Scan (7x7x5)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.24 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.612 W/kg

SAR(1 g) = 0.363 W/kg; SAR(10 g) = 0.200 W/kg

Maximum value of SAR (measured) = 0.469 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 6/4/2018

WiFi wrist worn Low CH1**DUT: TicWatch Pro Smartwatch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2412 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2412$ MHz; $\sigma = 1.944$ S/m; $\epsilon_r = 51.974$; $\rho = 1000$ kg/m³

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/Low CH1/Area Scan (10x10x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.277 W/kg


WiFi/Low CH1/Zoom Scan (7x7x5)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.581 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.373 W/kg

SAR(1 g) = 0.198 W/kg; SAR(10 g) = 0.093 W/kg

Maximum value of SAR (measured) = 0.282 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 6/4/2018

WiFi wrist worn Middle CH6**DUT: TicWatch Pro Smartwatch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2437 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.965 \text{ S/m}$; $\epsilon_r = 52.18$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASYS 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/Middle CH6/Area Scan (10x10x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.247 W/kg


WiFi/Middle CH6/Zoom Scan (7x7x5)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.234 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.338 W/kg

SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.084 W/kg

Maximum value of SAR (measured) = 0.252 W/kg



Test Laboratory: Compliance Certification Services Inc.

Date: 5/9/2018

WiFi wrist worn High CH11**DUT: Smart watch; Type: WF12096; Serial: N/A**Communication System: UID 0, IEEE 820.11g (0); Communication System Band: ISM 2.4 GHz Band;
Frequency: 2462 MHz; Duty Cycle: 1:1Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 1.966 \text{ S/m}$; $\epsilon_r = 51.784$; $\rho = 1000 \text{ kg/m}^3$

Room Ambient Temperature: 22°C; Liquid Temperature: 21.5°C

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3798; ConvF(7.32, 7.32, 7.32); Calibrated: 7/26/2017;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1245; Calibrated: 7/20/2017
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: TP:xxxx
- DASY52 52.8.8(1222);
- SEMCAD X Version 14.6.10 (7331)

WiFi/High CH11/Area Scan (10x10x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Maximum value of SAR (measured) = 0.344 W/kg


WiFi/High CH11/Zoom Scan (7x7x5)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.678 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.462 W/kg

SAR(1 g) = 0.243 W/kg; SAR(10 g) = 0.114 W/kg

Maximum value of SAR (measured) = 0.336 W/kg



0 dB = 0.336 W/kg = -4.74 dBW/kg