



TEST REPORT

**KCTL Eurofins KCTL Co.Ltd.**

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-70-5008-1021
FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR24-SRF0141
Page (1) of (72)

**1. Client**

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2024-09-02

2. Use of Report : Certification**3. Name of Product / Model** : Wi-Fi/BLE combo module / ACAU711R**4. Manufacturer / Country of Origin** : Samsung Electronics Co., Ltd. / Korea**5. FCC ID** : A3LACAU711R**6. IC Certificate No.** : 649E-ACAU711R**7. Date of Test** : 2024-09-09 to 2024-10-23**8. Location of Test** : ☒ Permanent Testing Lab ☐ On Site Testing
(Address: 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)**9. Test method used** : FCC Part 15 Subpart C, 15.247
RSS-247 Issue 3 August 2023
RSS-Gen Issue 5 February 2021**10. Test Result** : Refer to the test result in the test report

This laboratory is not accredited for the test results marked. *

Affirmation	Tested by	Technical Manager
	Name : Minki Kim (Signature)	Name : Heesu Ahn (Signature)

The above testing certificate is the accredited test result by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

2024-10-25

Accredited by KOLAS, Republic of KOREA

Eurofins KCTL Co.,Ltd.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

 eurofins KCTL Co.Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-70-5008-1021 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR24-SRF0141 Page (2) of (72)	 
--	--	---

REPORT REVISION HISTORY

Date	Revision	Page No
2024-10-25	Originally issued	-

This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is certified according to KS Q ISO/IEC 17025 and KOLAS recognition.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Frequency/channel operations.....	5
2.2.	RF power setting in TEST SW	6
3.	Antenna requirement	7
4.	Summary of tests	8
5.	Measurement uncertainty	9
6.	Measurement results explanation example	10
7.	Test results	11
7.1.	Maximum peak output power	11
7.2.	Carrier frequency separation	13
7.3.	20 dB channel bandwidth & 99% bandwidth	17
7.4.	Number of hopping channels	23
7.5.	Time of occupancy(Dwell time).....	25
7.6.	Radiated spurious emissions & band edge.....	32
7.7.	Conducted Spurious Emission.....	65
7.8.	AC Conducted emission	70
8.	Measurement equipment	72

1. General information

Client : Samsung Electronics Co., Ltd.
 Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
 Manufacturer : Samsung Electronics Co., Ltd.
 Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
 Factory : Chengdu Xuguang Technology Co., Ltd
 Address : No.86 2nd Section, Park Road, Longquanyi District, Chengdu City, Sichuan Province, P.R. China
 Laboratory : Eurofins KCTL Co., Ltd.
 Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
 Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
 VCCI Registration No. : R-20080, G-20078, C-20059, T-20056
 CAB Identifier: KR0040
 ISED Number: 8035A
 KOLAS No.: KT231

2. Device information

Equipment under test : Wi-Fi/BLE combo module
 Model : ACAU711R
 Modulation technique : Bluetooth(BDR/EDR)_GFSK, $\pi/4$ DQPSK, 8DPSK
 Bluetooth(BLE)_GFSK
 WLAN(802.11b/g/n/ac/ax_HT20/VHT20/HE20)_DSSS, OFDM, OFDMA
 Number of channels : BT/LE : Bluetooth(BDR/EDR)_79 ch, Bluetooth(BLE)_40 ch
 2.400 GHz band : 802.11b/g/n/ac/ax_HT20/HE20_13 ch (20 MHz)
 UNII-1 : 802.11a/n/ac/ax_HT20/VHT20/HE20_4 ch (20 MHz)
 UNII-2A : 802.11a/n/ac/ax_HT20/VHT20/HE20_4 ch (20 MHz)
 UNII-2C : 802.11a/n/ac/ax_HT20/VHT20/HE20_12 ch (20 MHz)
 UNII-3 : 802.11a/n/ac/ax_HT20/VHT20/HE20_5 ch (20 MHz)
 Power source : DC 5 V, DC 12 V
 Antenna type : PCB Chip antenna
 Antenna gain : 2.400 GHz band : -0.10 dBi
 UNII-1 : 0.90 dBi
 UNII-2A : 0.20 dBi
 UNII-2C : -0.40 dBi
 UNII-3 : -0.70 dBi
 Frequency range : 2.400 GHz band : 2 402 MHz ~ 2 480 MHz (Bluetooth/BLE)
 2 412 MHz ~ 2 472 MHz (802.11b/g/n/ac/ax_HT20/HE20)
 UNII-1 : 5 180 MHz ~ 5 240 MHz (802.11a/n/ac/ax_HT20/VHT20/HE20)
 UNII-2A : 5 260 MHz ~ 5 320 MHz (802.11a/n/ac/ax_HT20/VHT20/HE20)
 UNII-2C : 5 500 MHz ~ 5 720 MHz (802.11a/n/ac/ax_HT20/VHT20/HE20)
 UNII-3 : 5 745 MHz ~ 5 825 MHz (802.11a/n/ac/ax_HT20/VHT20/HE20)
 Software version : v1.0
 Hardware version : v1.0
 Test device serial No. : Conducted: 9C443D587B34
 Radiated: 9C443D587B24
 Operation temperature : -20 °C ~ 85 °C

2.1. Frequency/channel operations

This device contains the following capabilities:

WLAN 2.4 GHz_802.11b/g/n(HT20)/ax(HE20), Bluetooth(BDR, EDR),
Bluetooth Low Energy(1 Mbps, 2 Mbps, 125 kbps, 500 kbps),
WLAN 5 GHz_802.11a/n(HT20)/ac(VHT20)/ax(HE20)

Ch.	Frequency (MHz)
00	2 402
39	2 441
78	2 480

Table 2.1.1. Bluetooth(BDR/EDR)

15.247 Requirements for Bluetooth transmitter:

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
 - 1) This system is hopping pseudo-randomly.
 - 2) Each frequency is used equally on the average by each transmitter.
 - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
 - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

2.2. RF power setting in TEST SW**[DC 5 V]**

Test Condition	Test Program	Test mode	Power Setting
Bluetooth	RtlBluetoothMP.dll v5.5.0.1 RTLBTAPP v5.2.4.12	DH1	15(0x4a) (DUT mode)
		DH3	
		DH5	
		2DH1	17(0x4e) (DUT mode)
		2DH3	
		2DH5	
		3DH1	17(0x4e) (DUT mode)
		3DH3	
		3DH5	

[DC 12 V]

Test Condition	Test Program	Test mode	Power Setting
Bluetooth	RtlBluetoothMP.dll v5.5.0.1 RTLBTAPP v5.2.4.12	DH1	15(0x4a) (DUT mode)
		DH3	
		DH5	
		2DH1	17(0x4e) (DUT mode)
		2DH3	
		2DH5	
		3DH1	17(0x4e) (DUT mode)
		3DH3	
		3DH5	

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Requirement of RSS-Gen Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

- The transmitter has permanently attached PCB Chip Antenna (Internal antenna) on board.
- The EUT Complies with the requirement of §15.203, §15.247.

4. Summary of tests

FCC Part section(s)	IC Rule reference	Parameter	Test Condition	Test results
15.247(b)(1),(4)	RSS-247, (5.4)(b)	Maximum peak output power	Conducted	Pass
15.247(a)(1)	RSS-247, (5.1)(b)	Carrier frequency separation		Pass
15.247(a)(1)	RSS-247, (5.1)(b)	20 dB channel bandwidth		Pass
-	RSS-Gen(6.7)	Occupied bandwidth		Pass
15.247(a)(iii) 15.247(b)(1)	RSS-247, (5.1)(d)	Number of hopping channel		Pass
15.247(a)(iii)	RSS-247, (5.1)(d)	Time of occupancy(dwel time)		Pass
15.207(a)	RSS-Gen(8.8)	AC Conducted Emissions		Pass
15.247(d)	RSS-247(5.5)	Conducted Spurious Emissions		Pass
15.205(a), 15.209(a)	RSS-Gen (8.9), (8.10)	Spurious emission	Radiated	Pass
		Band-edge, restricted band		Pass

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- EUT was investigated in three orthogonal orientations X, Y and Z. it was determined that **X** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **X** orientation.
- The worst-case data rate were: BDR Packet type DH-1
EDR Packet type 3DH-1
- The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2013
 - KDB 558074 D01 v05r02

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ($\pm$)	
Maximum Peak Output Power	0.9 dB	
Peak Power Spectral Density	1.0 dB	
6 dB Channel Bandwidth	0.1 %	
Occupied Bandwidth	0.1 %	
Conducted spurious emission	1.9 dB	
Radiated spurious Emissions (Bandedge, restricted band)	Below 30 MHz	2.3 dB
	30 MHz to 1 000 MHz	2.5 dB
	1 000 MHz to 18 000 MHz	4.7 dB
	Above 18 000 MHz	4.8 dB
Conducted Emissions	150 kHz to 30 MHz	2.8 dB

6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	16.05	9 000	19.25
50	16.15	10 000	19.34
100	16.25	11 000	19.44
200	16.36	12 000	19.25
300	16.54	13 000	19.64
400	16.25	14 000	19.74
500	16.65	15 000	19.84
600	16.65	16 000	19.94
700	16.88	17 000	20.25
800	16.89	18 000	20.29
900	17.01	19 000	20.64
1 000	17.12	20 000	20.74
2 000	17.12	21 000	20.83
3 000	17.16	22 000	21.15
4 000	17.54	23 000	21.35
5 000	17.68	24 000	21.68
6 000	17.84	25 000	21.69
7 000	17.99	26 000	21.87
8 000	18.84	26 500	22.05


Notes:

Offset(dB) = RF cable loss(dB) + Attenuator(dB) + Power Divider(dB)

7 Test results

7.1. Maximum peak output power

Test setup



Limit FCC

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to §15.247(b)(1), for frequency hopping systems operating in the 2 400-2 483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725-5 850 MHz band: 1 watt. For all other frequency hopping systems in the 2 400-2 483.5 MHz band: 0.125 watts.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

IC

According to RSS-247(5.4)(b), for FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels.

The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

Test procedure

ANSI C63.10-2013 - Section 7.8.5

Test settings

The test follows ANSI C63.10-2013 – Section 7.8.5. Using the power sensor instead of a spectrum analyzer.

Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

Test results**[DC 5 V]**

Frequency(MHz)	Data rate (Mbps)	Measured output power(dBm)						
		Conducted output power (dBm)		Limit (dBm)	Ant Gain (dBi)	Max. e.i.r.p. (dBm)		Max e.i.r.p. Limit (dBm)
		Peak	Average			Peak	Average	
2 402	1	6.19	5.82	20.97	-0.10	6.09	5.72	36.02
2 441	1	6.75	6.36			6.65	6.26	
2 480	1	5.87	5.51			5.77	5.41	
2 402	2	8.87	6.51			8.77	6.41	
2 441	2	8.96	6.56			8.86	6.46	
2 480	2	8.16	5.84			8.06	5.74	
2 402	3	9.52	6.52			9.42	6.42	
2 441	3	9.59	6.58			9.49	6.48	
2 480	3	8.83	5.89			8.73	5.79	

Notes:

1. e.i.r.p. Calculation: e.i.r.p. (dB m) = Conducted output power (dB m) + Antenna gain (dB i)

[DC 12 V]


Frequency(MHz)	Data rate (Mbps)	Measured output power(dBm)						
		Conducted output power (dBm)		Limit (dBm)	Ant Gain (dBi)	Max. e.i.r.p. (dBm)		Max e.i.r.p. Limit (dBm)
		Peak	Average			Peak	Average	
2 402	1	6.19	5.81	20.97	-0.10	6.09	5.71	36.02
2 441	1	6.75	6.39			6.65	6.29	
2 480	1	5.83	5.47			5.73	5.37	
2 402	2	8.86	6.49			8.76	6.39	
2 441	2	8.92	6.56			8.82	6.46	
2 480	2	8.16	5.83			8.06	5.73	
2 402	3	9.51	6.51			9.41	6.41	
2 441	3	9.59	6.56			9.49	6.46	
2 480	3	8.78	5.87			8.68	5.77	

Notes:

1. e.i.r.p. Calculation: e.i.r.p. (dB m) = Conducted output power (dB m) + Antenna gain (dB i)

7.2. Carrier frequency separation

Test setup



Limit

According to §15.247(a)(1) and RSS-247(5.1)(b), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test procedure

ANSI C63.10-2013 - Section 7.8.2

Test settings

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- Video (or average) bandwidth (VBW) $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

Test results**[DC 5 V]**


Frequency(MHz)	Data rate(Mbps)	Carrier frequency separation(MHz)	Limit(MHz)
2 402	1	0.996	0.651
2 441	1	0.990	0.685
2 480	1	0.993	0.683
2 402	3	1.032	0.901
2 441	3	1.329	0.901
2 480	3	1.005	0.901

[DC 12 V]


Frequency(MHz)	Data rate(Mbps)	Carrier frequency separation(MHz)	Limit(MHz)
2 402	1	0.972	0.687
2 441	1	0.783	0.653
2 480	1	0.787	0.687
2 402	3	1.338	0.899
2 441	3	0.993	0.901
2 480	3	1.017	0.901

[DC 5 V]

GFSK / Low ch.




8DPSK / Low ch.



GFSK / Mid ch.




8DPSK / Mid ch.



GFSK / High ch.




8DPSK / High ch.




[DC 12 V]

GFSK / Low ch.




8DPSK / Low ch.




GFSK / Mid ch.




8DPSK / Mid ch.



GFSK / High ch.




8DPSK / High ch.



7.3. 20 dB channel bandwidth & 99% bandwidth

Test setup



Limit

According to §15.247(a)(1) and RSS-247(5.1)(b), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2 400-2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test procedure

ANSI C63.10-2013 - Section 6.9.2

Test settings

20 dB channel bandwidth and Occupied bandwidth

The occupied bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are -6 dB, -20 dB, and -26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by “-xx dB.” The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the “-xx dB” bandwidth; other requirements might specify that the “-xx dB” bandwidth be entirely contained within the authorized or designated frequency band.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
- Span: Two times and five times the OBW.
- RBW = 1 % to 5 % of the OBW and VBW $\geq 3 \times$ RBW
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- Detector: peak
- Trace mode: max hold.
- Allow the trace to stabilize.
- Determine the “-xx dB down amplitude” using ((reference value) - xx). Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

- k) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

Test results

[DC 5 V]

Frequency(MHz)	Data rate (Mbps)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
2 402	1	0.977	0.911
2 441	1	1.028	0.911
2 480	1	1.025	0.911
2 402	3	1.352	1.199
2 441	3	1.352	1.199
2 480	3	1.352	1.199


[DC 12 V]

Frequency(MHz)	Data rate (Mbps)	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
2 402	1	1.031	0.908
2 441	1	0.980	0.911
2 480	1	1.031	0.911
2 402	3	1.349	1.199
2 441	3	1.352	1.199
2 480	3	1.352	1.199


20 dB bandwidth

[DC 5 V]


GFSK / Low ch.




8DPSK / Low ch.




GFSK / Mid ch.




8DPSK / Mid ch.



GFSK / High ch.




8DPSK / High ch.




[DC 12 V]


GFSK / Low ch.




8DPSK / Low ch.




GFSK / Mid ch.




8DPSK / Mid ch.



GFSK / High ch.



8DPSK / High ch.



99% bandwidth

[DC 5 V]

GFSK / Low ch.



8DPSK / Low ch.



GFSK / Mid ch.



8DPSK / Mid ch.



GFSK / High ch.



8DPSK / High ch.



[DC 12 V]

GFSK / Low ch.



8DPSK / Low ch.



GFSK / Mid ch.



8DPSK / Mid ch.



GFSK / High ch.




8DPSK / High ch.



7.4. Number of hopping channels

Test setup



Limit

According to §15.247(a)(1)(iii) and RSS-247(5.1)(d), frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels.

Test procedure

ANSI C63.10-2013 - Section 7.8.3

Test settings

- Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- RBW: To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- VBW $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Test results

[DC 5 V]

Mode	Number of hopping channel	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

[DC 12 V]


Mode	Number of hopping channel	Limit
GFSK	79	≥ 15
$\pi/4$ DQPSK	79	≥ 15
8DPSK	79	≥ 15

Notes:

In case of AFH mode, minimum number of hopping channels is 20.


DC 5 V

GFSK




DC 12 V


GFSK




$\pi/4$ DQPSK




$\pi/4$ DQPSK



8DPSK




8DPSK



7.5. Time of occupancy(Dwell time)

Test setup



Limit

According to §15.247(a)(1)(iii) and RSS-247(5.1)(d), frequency hopping systems in the 2 400-2 483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test procedure

ANSI C63.10-2013 - Section 7.8.4

Test settings

- Span: Zero span, centered on a hopping channel.
- $RBW \leq \text{channel spacing}$ and $\gg 1 / T$, where T is the expected dwell time per channel.
- Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- Detector function: Peak.
- Trace: Max hold.
- Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Test results**[DC 5 V]**

Non-AFH						
Modulation	Frequency (MHz)	Pulse Width (ms)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	800.000	79	0.122	0.400
DH3		1.638	400.000		0.262	
DH5		2.884	266.667		0.308	
2-DH1		0.391	800.000		0.125	
2-DH3		1.642	400.000		0.263	
2-DH5		2.888	266.667		0.308	
3-DH1		0.390	800.000		0.125	
3-DH3		1.640	400.000		0.262	
3-DH5		2.891	266.667		0.308	

AFH						
Modulation	Frequency (MHz)	Pulse Width (mss)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	400.000	20	0.061	0.400
DH3		1.638	200.000		0.131	
DH5		2.884	133.333		0.154	
2-DH1		0.391	400.000		0.062	
2-DH3		1.642	200.000		0.131	
2-DH5		2.888	133.333		0.154	
3-DH1		0.390	400.000		0.062	
3-DH3		1.640	200.000		0.131	
3-DH5		2.891	133.333		0.154	

Notes:

1. Non-AFH

- Period Time: 0.4 sec x 79 channels = 31.6 sec

- Result (s)= (Hopping rate (hop/s/slot) / 79 channels) x 31.6 sec x Pulse width (ms)

2. AFH

- Period Time: 0.4 sec x 20 channels = 8 sec

- Result (s)= (Hopping rate (hop/s/slot) / 20 channels) x 8 sec x Pulse width (ms)

[DC 12 V]

Non-AFH						
Modulation	Frequency (MHz)	Pulse Width (ms)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	800.000	79	0.122	0.400
DH3		1.638	400.000		0.262	
DH5		2.884	266.667		0.308	
2-DH1		0.391	800.000		0.125	
2-DH3		1.642	400.000		0.263	
2-DH5		2.888	266.667		0.308	
3-DH1		0.390	800.000		0.125	
3-DH3		1.640	400.000		0.262	
3-DH5		2.891	266.667		0.308	

AFH						
Modulation	Frequency (MHz)	Pulse Width (ms)	Hopping rate (hop/s)	Number of Channels	Result (s)	Limit (s)
DH1	2 441	0.382	400.000	20	0.061	0.400
DH3		1.638	200.000		0.131	
DH5		2.884	133.333		0.154	
2-DH1		0.391	400.000		0.062	
2-DH3		1.642	200.000		0.131	
2-DH5		2.888	133.333		0.154	
3-DH1		0.390	400.000		0.062	
3-DH3		1.640	200.000		0.131	
3-DH5		2.891	133.333		0.154	

Notes:

1. Non-AFH

- Period Time: 0.4 sec x 79 channels = 31.6 sec

- Result (s)= (Hopping rate (hop/s/slot) / 79 channels) x 31.6 sec x Pulse width (ms)



2. AFH

- Period Time: 0.4 sec x 20 channels = 8 sec



- Result (s)= (Hopping rate (hop/s/slot) / 20 channels) x 8 sec x Pulse width (ms)

[DC 5 V]



GFSK / DH1

 π /4DQPSK / 2-DH1


GFSK / DH3

 π /4DQPSK / 2-DH3


GFSK / DH5

 π /4DQPSK / 2-DH5


8DPSK / 3-DH1



8DPSK / 3-DH3





8DPSK / 3-DH5





Blank

[DC 12 V]



GFSK / DH1

 π /4DQPSK / 2-DH1


GFSK / DH3

 π /4DQPSK / 2-DH3


GFSK / DH5

 π /4DQPSK / 2-DH5


8DPSK / 3-DH1



8DPSK / 3-DH3



8DPSK / 3-DH5




Blank


7.6. Radiated spurious emissions & band edge

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



**Limit
FCC**

According to section 15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

IC

According to RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen(8.9), Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5- General field strength limits at frequencies above 30 MHz

Frequency(MHz)	Field strength ($\mu\text{V}/\text{m}$ at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Table 6- General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ($\mu\text{A}/\text{m}$)	Measurement distance(m)
9 – 490 kHz ¹⁾	6.37/F (F in kHz)	300
490 – 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

According to RSS-Gen(8.10), Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

- The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD).
- Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
- Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

Table 7- Restricted frequency bands*

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Test procedure

ANSI C63.10-2013

Test settings**Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW $\geq (3 \times \text{RBW})$
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

Table. RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

Average field strength measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW = $1/T \geq 1$ Hz
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times(1/duty cycle) traces

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 kHz ($\geq 1/T$) for Average detection (AV) at frequency above 1 GHz.

According to ANSI C63.10-2013, for average measurement during radiation test, Reduced VBW shall be greater than $[1/(\text{minimum transmitter on time})]$ and no less than 1 Hz.

2. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$

Where:

F_d = Distance factor in dB

D_m = Measurement distance in meters

D_s = Specification distance in meters


3. Factors(dB) = Antenna factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
4. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
5. Average test would be performed if the peak result were greater than the average limit.
6. ¹⁾ means restricted band.

7. Above 1 GHz the worst results between two antenna polarizations (H and V) were documented in the test report.
8. Below 30 MHz frequency range, In order to search for the worst result, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported. when the emission level was higher than 20 dB of the limit, then the following statement shall be made: "No spurious emissions were detected within 20 dB of the limit."
9. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dB μ V/m, which is equivalent to $Y - 51.5 = Z$ dB μ A/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.




[DC 5 V]

Test mode	Period (ms)	T _{On} time (ms)	Reduced VBW (Hz)
GFSK	1.225 0	0.379 0	2 638.522 4
8DPSK	1.234 0	0.386 5	2 587.322 1




[DC 12 V]

Test mode	Period (ms)	T _{On} time (ms)	Reduced VBW (Hz)
GFSK	1.225 0	0.379 0	2 638.522 4
8DPSK	1.234 0	0.386 5	2 587.322 1




[DC 5 V]**Test results (Below 30 MHz) – Worst case: 8DPSK 2 441 MHz**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical


Test results (Below 1 000 MHz) – Worst case: 8DPSK 2 441 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
37.28	V	37.50	20.91	-31.25	-	27.16	40.00	12.84
59.95	V	39.30	12.09	-30.89	-	20.50	40.00	19.50
119.97 ¹⁾	V	36.30	17.70	-30.05	-	23.95	43.50	19.55
240.01 ¹⁾	H	47.30	17.10	-28.80	-	35.60	46.00	10.40
332.76 ¹⁾	V	38.20	19.50	-27.97	-	29.73	46.00	16.27
479.72	V	32.40	22.70	-26.91	-	28.19	46.00	17.81
720.03	V	29.10	24.50	-25.41	-	28.19	46.00	17.81
960.11 ¹⁾	H	32.40	26.40	-23.05	-	35.75	54.00	18.25


Horizontal/Vertical

Test results (Above 1 000 MHz)**GFSK_Low Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.28 ¹⁾	H	33.72	32.09	-17.87	-	47.94	74.00	26.06
3 988.17 ¹⁾	V	71.80	33.29	-56.85	-	48.24	74.00	25.76
4 810.32 ¹⁾	H	64.08	34.02	-55.70	-	42.40	74.00	31.60
7 189.77	V	61.21	35.80	-52.05	-	44.96	74.00	29.04
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz





Horizontal/Vertical for 3.5 GHz ~ 18 GHz




GFSK_Mid Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
4 912.78 ¹⁾	V	64.26	34.07	-55.71	-	42.62	74.00	31.38
7 336.22 ¹⁾	V	62.25	35.80	-52.20	-	45.85	74.00	28.15
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**

GFSK_High Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 484.02 ¹	H	36.16	32.18	-17.81	-	50.53	74.00	23.47
4 970.30 ¹	V	63.68	34.09	-55.59	-	42.18	74.00	31.82
7 452.70 ¹	H	61.56	35.80	-52.32	-	45.04	74.00	28.96
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz




Horizontal/Vertical for 3.5 GHz ~ 18 GHz




8DPSK_Low Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 389.90 ¹⁾	H	35.07	32.09	-17.87	-	49.29	74.00	24.71
4 805.97 ¹⁾	H	63.87	34.02	-55.70	-	42.19	74.00	31.81
7 191.70	H	62.17	35.80	-52.05	-	45.92	74.00	28.08
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz





Horizontal/Vertical for 3.5 GHz ~ 18 GHz




8DPSK_Mid Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
4 862.03 ¹⁾	V	63.97	34.04	-55.72	-	42.29	74.00	31.71
7 316.40 ¹⁾	H	62.01	35.80	-52.18	-	45.63	74.00	28.37
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


Horizontal/Vertical for 1 GHz ~ 3.5 GHz**Horizontal/Vertical for 3.5 GHz ~ 18 GHz**

8DPSK_High Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 485.42 ¹⁾	H	36.05	32.19	-17.80	-	50.44	74.00	23.56
3 743.60 ¹⁾	V	68.01	33.09	-57.05	-	44.05	74.00	29.95
4 941.30 ¹⁾	V	63.50	34.08	-55.65	-	41.93	74.00	32.07
7 416.45 ¹⁾	V	63.32	35.80	-52.29	-	46.83	74.00	27.17
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


Horizontal/Vertical for Band-edge

Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz




Test results (Above 18 GHz) – Worst case: GFSK 2 480 MHz**Horizontal/Vertical for 18 GHz ~ 26.5 GHz**

Note: The Worst case was based on the lowest margin condition considering Harmonic and Spurious Emission


[DC 12 V]**Test results (Below 30 MHz) – Worst case: 8DPSK 2 441 MHz**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical

Test results (Below 1 000 MHz) – Worst case: 8DPSK 2 441 MHz

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Quasi peak data								
37.28	V	37.70	20.91	-31.25	-	27.36	40.00	12.64
59.95	V	38.70	12.09	-30.89	-	19.90	40.00	20.10
119.97 ¹⁾	V	36.10	17.70	-30.05	-	23.75	43.50	19.75
165.92 ¹⁾	V	38.10	15.41	-29.52	-	23.99	43.50	19.51
240.01 ¹⁾	H	47.60	17.10	-28.80	-	35.90	46.00	10.10
332.28 ¹⁾	V	37.20	19.50	-27.96	-	28.74	46.00	17.26
480.08	V	35.20	22.70	-26.91	-	30.99	46.00	15.01
720.03	V	29.60	24.50	-25.41	-	28.69	46.00	17.31
960.11 ¹⁾	H	32.40	26.40	-23.05	-	35.75	54.00	18.25

Horizontal/Vertical

Test results (Above 1 000 MHz)**GFSK_Low Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 388.46 ¹⁾	H	43.78	32.09	-27.84	-	48.03	74.00	25.97
3 994.93 ¹⁾	V	68.10	33.30	-56.87	-	44.53	74.00	29.47
4 789.05 ¹⁾	V	64.72	34.02	-55.74	-	43.00	74.00	31.00
7 207.17	V	62.31	35.80	-52.07	-	46.04	74.00	27.96
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

Horizontal/Vertical for Band-edge