

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Mobile Phone

ISSUED TO
vivo Mobile Communication Co., Ltd.

No.168 Jinghai East Rd., Chang'an, Dongguan, Guangdong, China



Tested by: Ye Hongji
Ye Hongji

Date: Aug. 25, 2021

Approved by: Liao Jianming
Liao Jianming
(Technical Director)

Date: Aug. 25, 2021

Report No.: BL-SZ2180012-603
EUT Name: Mobile Phone
Model Name: V2109
Brand Name: vivo
Test Standard: 47 CFR Part 15 Subpart C
(refer section 3.1)
FCC ID: 2AUCY-V2109

Test Conclusion: Pass
Test Date: Jul. 20, 2021 ~ Aug. 12, 2021
Date of Issue: Aug. 25, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Aug. 25, 2021</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION.....	6
2.1	Applicant Information.....	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Technical Information	7
2.6	Additional Instructions	9
3	SUMMARY OF TEST RESULTS.....	10
3.1	Test Standards	10
3.2	Verdict	10
4	GENERAL TEST CONFIGURATIONS.....	11
4.1	Test Environments	11
4.2	Test Equipment List.....	11
4.3	Measurement Uncertainty	11
4.4	Description of Test Setup	12
4.4.1	For Antenna Port Test	12
4.4.2	For AC Power Supply Port Test	12
4.4.3	For Radiated Test (Below 30 MHz)	13
4.4.4	For Radiated Test (30 MHz-1 GHz)	13
4.4.5	For Radiated Test (Above 1 GHz).....	14
4.5	Measurement Results Explanation Example.....	15

4.5.1	For conducted test items:	15
4.5.2	For radiated band edges and spurious emission test:.....	15
5	TEST ITEMS.....	16
5.1	Antenna Requirements.....	16
5.1.1	Relevant Standards.....	16
5.1.2	Antenna Anti-Replacement Construction	16
5.1.3	Antenna Gain	16
5.2	Output Power	17
5.2.1	Test Limit.....	17
5.2.2	Test Setup.....	17
5.2.3	Test Procedure	17
5.2.4	Test Result	18
5.3	6dB Bandwidth	19
5.3.1	Limit.....	19
5.3.2	Test Setup.....	19
5.3.3	Test Procedure	19
5.3.4	Test Result	19
5.4	Conducted Spurious Emission	20
5.4.1	Limit.....	20
5.4.2	Test Setup.....	20
5.4.3	Test Procedure	20
5.4.4	Test Result	21
5.5	Band Edge (Authorized-band band-edge).....	22
5.5.1	Limit.....	22
5.5.2	Test Setup.....	22
5.5.3	Test Procedure	22
5.5.4	Test Result	23
5.6	Conducted Emission	24
5.6.1	Limit.....	24
5.6.2	Test Setup.....	24
5.6.3	Test Procedure	24
5.6.4	Test Result	24

5.7	Radiated Spurious Emission	25
5.7.1	Limit.....	25
5.7.2	Test Setup	25
5.7.3	Test Procedure	25
5.7.4	Test Result	28
5.8	Band Edge (Restricted-band band-edge).....	29
5.8.1	Limit.....	29
5.8.2	Test Setup	29
5.8.3	Test Procedure	29
5.8.4	Test Result	29
5.9	Power Spectral density (PSD).....	30
5.9.1	Limit.....	30
5.9.2	Test Setup	30
5.9.3	Test Procedure	30
5.9.4	Test Result	30
ANNEX A	TEST RESULT	31
A.1	Output Power	31
A.2	Bandwidth.....	33
A.3	Conducted Spurious Emissions	40
A.4	Band Edge (Authorized-band band-edge).....	52
A.5	Conducted Emissions.....	57
A.6	Radiated Emission	59
A.7	Band Edge (Restricted-band band-edge).....	76
A.8	Power Spectral Density (PSD)	88
ANNEX B	TEST SETUP PHOTOS	92
ANNEX C	EUT EXTERNAL PHOTOS	92
ANNEX D	EUT INTERNAL PHOTOS	92

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v6.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	vivo Mobile Communication Co., Ltd.
Address	No.168 Jinghai East Rd., Chang'an, Dongguan, Guangdong, China

2.2 Manufacturer Information

Manufacturer	vivo Mobile Communication Co., Ltd.
Address	No.168 Jinghai East Rd., Chang'an, Dongguan, Guangdong, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	V2109
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	MP_0.1
Software Version	PD2147IF_EX_A_3.6.11
Dimensions (Approx.)	164.26*76.08*8.0mm
Weight (Approx.)	180g

2.5 Technical Information

Network and Wireless connectivity	WIFI 802.11b, 802.11g, 802.11n(HT20)
-----------------------------------	--------------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11.
Modulation Type	DSSS, OFDM
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PIFA Antenna
Antenna Gain	-3.0 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Output Power	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11
6dB Bandwidth	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11
Conducted Spurious Emission	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11
Conducted Emission	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11
Radiated Spurious Emission	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11
Band Edge	11b/11g/11n20	1/6/6.5 Mbps	1/2/10/11
Power spectral density (PSD)	11b/11g/11n20	1/6/6.5 Mbps	1/2/6/10/11

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.6 Additional Instructions


EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	SP_META		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Soft Set	
802.11 b	1	13.5	
	2	19.0	
	6	19.0	
	10	19.0	
	11	18.0	
802.11 g	1	13.5	
	2	17.0	
	6	17.0	
	10	17.0	
	11	16.0	
802.11 n20	1	13.5	
	2	16.0	
	6	16.0	
	10	16.0	
	11	15.0	

Run software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
3	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	Pass ^{Note 1}
2	Output Power	15.247 (b)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247 (a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247 (d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247 (d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247 (d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247 (d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247 (e)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	N/A	N/A ^{Note 2}

Note ¹: Please refer to section 5.1.

Note ²: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

Note ³: The only difference between the EUT (test samples in this report) and testing sample of report BL-SZ2170620-603, which was issued by Shenzhen BALUN Technology Co., Ltd. on Aug. 16, 2021 shown as below:

1. With different model name.
2. Change the LCD from HD to FHD.
3. Change the front camera from 8M to 16M.
4. Add the Gyroscope.

And others hardware circuit and software were all the same. So all of the test data originate from the report BL-SZ2170620-603, which was issued by Shenzhen BALUN Technology Co., Ltd. on Aug. 16, 2021.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.87 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2021.04.01	2022.03.31
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2021.06.01	2022.05.31
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.06.01	2022.05.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.06.01	2022.05.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.01	2022.05.31
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2022.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±2.8%
RF output power, conducted	±1.28 dB
Power Spectral Density, conducted	±1.30 dB
Unwanted Emissions, conducted	±1.84 dB
All emissions, radiated	±5.36 dB
Temperature	±0.82°C
Humidity	±4.1%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203; RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (d)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.36dB Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.7; RSS-247, 5.2 (a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)

c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).

d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).

e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

f) Compare the resultant electric field strength level to the applicable limit.

g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 1.

b) VBW $\geq 3 \times$ RBW.

c) Detector = Peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle
802.11b	8.368	8.425	99.32%
802.11g	1.385	1.433	96.65%
802.11n-20 MHz	1.301	1.346	96.66%

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	16.36	43.25	30	1000	Pass
2	21.52	141.91			Pass
6	21.88	154.17			Pass
10	21.66	146.55			Pass
11	20.69	117.22			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	21.65	146.22	30	1000	Pass
2	24.66	292.42			Pass
6	25.03	318.42			Pass
10	24.80	302.00			Pass
11	23.84	242.10			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	21.50	141.25	30	1000	Pass
2	23.67	232.81			Pass
6	23.93	247.17			Pass
10	23.70	234.42			Pass
11	22.74	187.93			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	13.36	21.68	30	1000	Pass
2	19.35	86.10			Pass
6	19.30	85.11			Pass
10	19.20	83.18			Pass
11	18.16	65.46			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	13.92	24.66	30	1000	Pass
2	16.86	48.53			Pass
6	17.33	54.08			Pass
10	17.27	53.33			Pass
11	16.24	42.07			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	13.78	23.88	30	1000	Pass
2	16.08	40.55			Pass
6	16.26	42.27			Pass
10	16.14	41.11			Pass
11	15.06	32.06			Pass

A.2 Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
1	8.200000	12.705000	≥ 500
2	9.100000	12.622000	≥ 500
6	8.600000	13.485000	≥ 500
10	8.600000	13.771000	≥ 500
11	8.600000	13.533000	≥ 500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
1	15.100000	17.002000	≥ 500
2	15.200000	17.272000	≥ 500
6	15.200000	17.382000	≥ 500
10	15.800000	17.396000	≥ 500
11	15.800000	17.351000	≥ 500

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
1	15.200000	17.958000	≥ 500
2	15.150000	18.114000	≥ 500
6	15.800000	18.235000	≥ 500
10	16.050000	18.198000	≥ 500
11	16.150000	18.200000	≥ 500


Test plots

6 dB Bandwidth

802.11b CHANNEL 1



802.11b CHANNEL 2



802.11b CHANNEL 6



802.11g CHANNEL 10



802.11b CHANNEL 11



802.11g CHANNEL 1



802.11g CHANNEL 2



802.11g CHANNEL 6



802.11g CHANNEL 10



802.11g CHANNEL 11



802.11n-20 MHz CHANNEL 1



802.11 n-20 MHz CHANNEL 2





99% Bandwidth

802.11b CHANNEL 1




802.11b CHANNEL 2



802.11b CHANNEL 6



802.11g CHANNEL 10



802.11b CHANNEL 11



802.11g CHANNEL 1



802.11g CHANNEL 2



802.11g CHANNEL 6



802.11g CHANNEL 10



802.11g CHANNEL 11



802.11n-20 MHz CHANNEL 1



802.11 n-20 MHz CHANNEL 2



802.11n-20 MHz CHANNEL 6



802.11n-20 MHz CHANNEL 10



802.11n-40 MHz CHANNEL 11



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-47.49	5.56	-14.44	Pass
2	-43.30	10.51	-9.49	Pass
6	-39.84	11.04	-8.96	Pass
10	-42.08	10.45	-9.55	Pass
11	-41.29	9.70	-10.30	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-47.88	3.71	-16.29	Pass
2	-47.23	6.65	-13.35	Pass
6	-47.35	7.12	-12.89	Pass
10	-47.98	6.39	-13.61	Pass
11	-47.44	5.38	-14.62	Pass

802.11n-20MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-47.66	3.72	-16.28	Pass
2	-47.62	5.78	-14.22	Pass
6	-48.46	5.47	-14.53	Pass
10	-47.25	5.30	-14.70	Pass
11	-48.09	4.49	-15.51	Pass

Test Plots

802.11b CHANNEL 1 CARRIER LEVEL




802.11b CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz




802.11b CHANNEL 2 CARRIER LEVEL



802.11b CHANNEL 2, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 2, SPURIOUS 2 GHz ~ 25 GHz




802.11b CHANNEL 6 CARRIER LEVEL



802.11b CHANNEL 6, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 6, SPURIOUS 2 GHz ~ 25 GHz



802.11b CHANNEL 10 CARRIER LEVEL



802.11b CHANNEL 10, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 10, SPURIOUS 2 GHz ~ 25 GHz




802.11b CHANNEL 11 CARRIER LEVEL




802.11b CHANNEL 11, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 11, SPURIOUS 2 GHz ~ 25 GHz




802.11g CHANNEL 1 CARRIER LEVEL




802.11g CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz




802.11g CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz



802.11g CHANNEL 2 CARRIER LEVEL




802.11g CHANNEL 2, SPURIOUS 30 MHz ~ 3 GHz




802.11g CHANNEL 2, SPURIOUS 2 GHz ~ 25 GHz



802.11g CHANNEL 6 CARRIER LEVEL



802.11g CHANNEL 6, SPURIOUS 30 MHz ~ 3 GHz




802.11g CHANNEL 6, SPURIOUS 2 GHz ~ 25 GHz



802.11g CHANNEL 10 CARRIER LEVEL




802.11g CHANNEL 10, SPURIOUS 30 MHz ~ 3 GHz




802.11g CHANNEL 10, SPURIOUS 2 GHz ~ 25 GHz



802.11g CHANNEL 11 CARRIER LEVEL




802.11g CHANNEL 11, SPURIOUS 30 MHz ~ 3 GHz



802.11g CHANNEL 11, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 CHANNEL 1 CARRIER LEVEL




802.11n-20 CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz

802.11n-20 CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 CHANNEL 2 CARRIER LEVEL




802.11n-20 CHANNEL 2, SPURIOUS 30 MHz ~ 3 GHz


802.11n-20 CHANNEL 2, SPURIOUS 2 GHz ~ 25 GHz



802.11n-20 CHANNEL 6 CARRIER LEVEL



802.11n-20 CHANNEL 6, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 CHANNEL 6, SPURIOUS 2 GHz ~ 25 GHz





802.11n-20 CHANNEL 10 CARRIER LEVEL



802.11n-20 CHANNEL 10, SPURIOUS
30 MHz ~ 3 GHz

802.11n-20 CHANNEL 10, SPURIOUS
2 GHz ~ 25 GHz


802.11n-20 CHANNEL 11 CARRIER LEVEL



802.11n-20 CHANNEL 11, SPURIOUS
30 MHz ~ 3 GHz

802.11n-20 CHANNEL 11, SPURIOUS
2 GHz ~ 25 GHz


A.4 Band Edge (Authorized-band band-edge)

Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-49.46	5.56	-14.44	Pass
2	-46.37	10.51	-9.49	Pass
10	-50.39	10.45	-9.55	Pass
11	-54.28	9.70	-10.30	Pass

802.11g Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-33.97	3.71	-16.29	Pass
2	-30.83	6.65	-13.35	Pass
10	-50.54	6.39	-13.61	Pass
11	-46.84	5.38	-14.62	Pass

802.11n-20 MHz Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-34.08	3.72	-16.28	Pass
2	-32.78	5.78	-14.22	Pass
10	-52.46	5.30	-14.70	Pass
11	-46.89	4.49	-15.51	Pass

Test Plots

802.11b CHANNEL 1, Carrier level




802.11b CHANNEL 1, Reference level




802.11b CHANNEL 2, Carrier level




802.11b CHANNEL 2, Reference level




802.11b CHANNEL 10, Carrier level




802.11b CHANNEL 10, Reference level



802.11b CHANNEL 11, Carrier level




802.11b CHANNEL 11, Reference level




802.11g CHANNEL 1, Carrier level




802.11g CHANNEL 1, Reference level




802.11g CHANNEL 2, Carrier level




802.11g CHANNEL 2, Reference level




802.11g CHANNEL 10, Carrier level




802.11g CHANNEL 10, Reference level




802.11g CHANNEL 11, Carrier level




802.11g CHANNEL 11, Reference level




802.11n-20 MHz CHANNEL 1, Carrier level




802.11n-20 MHz CHANNEL 1, Reference level




802.11n-20 MHz CHANNEL 2, Carrier level




802.11n-20 MHz CHANNEL 2, Reference level




802.11n-20 MHz CHANNEL 10, Carrier level




802.11n-20 MHz CHANNEL 10, Reference level



802.11n-20 MHz CHANNEL 11, Carrier level



802.11n-20 MHz CHANNEL 11, Reference level



A.5 Conducted Emissions


Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	43.46	10.41	66.00	-22.54	Peak	L	Pass
1**	0.150	31.59	10.41	56.00	-24.41	AV	L	Pass
2	0.380	41.95	10.30	58.28	-16.33	Peak	L	Pass
2**	0.380	31.22	10.30	48.28	-17.06	AV	L	Pass
3	0.520	42.54	10.30	56.00	-13.46	Peak	L	Pass
3**	0.520	31.41	10.30	46.00	-14.59	AV	L	Pass
4	0.892	40.65	10.25	56.00	-15.35	Peak	L	Pass
4**	0.892	26.22	10.25	46.00	-19.78	AV	L	Pass
5	1.374	40.79	10.25	56.00	-15.21	Peak	L	Pass
5**	1.374	26.60	10.25	46.00	-19.40	AV	L	Pass
6	17.636	49.07	10.48	60.00	-10.93	Peak	L	Pass
6**	17.636	34.21	10.48	50.00	-15.79	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.156	44.25	10.41	65.67	-21.42	Peak	N	Pass
1**	0.156	31.06	10.41	55.67	-24.61	AV	N	Pass
2	0.452	41.55	10.30	56.84	-15.29	Peak	N	Pass
2**	0.452	26.93	10.30	46.84	-19.91	AV	N	Pass
3	1.418	43.76	10.25	56.00	-12.24	Peak	N	Pass
3**	1.418	29.59	10.25	46.00	-16.41	AV	N	Pass
4	1.862	43.70	10.24	56.00	-12.30	Peak	N	Pass
4**	1.862	29.77	10.24	46.00	-16.23	AV	N	Pass
5	16.444	46.69	10.44	60.00	-13.31	Peak	N	Pass
5**	16.444	40.75	10.44	50.00	-9.25	AV	N	Pass
6	18.172	50.55	10.49	60.00	-9.45	Peak	N	Pass
6**	18.172	37.05	10.49	50.00	-12.95	AV	N	Pass

A.6 Radiated Emission

Note¹: The symbol of “--” in the table which means not application.


Note²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Test Data and Plots


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.285	14.46	-22.58	40.0	-25.54	Peak	161.90	100	Horizontal	Pass
2	79.276	17.31	-28.41	40.0	-22.69	Peak	331.80	200	Horizontal	Pass
3	96.348	18.92	-24.77	43.5	-24.58	Peak	280.40	200	Horizontal	Pass
4	143.830	22.49	-27.72	43.5	-21.01	Peak	13.00	200	Horizontal	Pass
5	312.998	31.26	-21.30	46.0	-14.74	Peak	115.40	100	Horizontal	Pass
6	816.767	28.11	-10.87	46.0	-17.89	Peak	322.90	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	52.698	24.85	-23.05	40.0	-15.15	Peak	246.90	100	Vertical	Pass
2	73.553	23.45	-28.49	40.0	-16.55	Peak	188.50	100	Vertical	Pass
3	95.281	24.95	-24.92	43.5	-18.55	Peak	56.00	100	Vertical	Pass
4	140.725	18.46	-27.57	43.5	-25.04	Peak	280.90	100	Vertical	Pass
5	202.369	23.44	-23.76	43.5	-20.06	Peak	72.90	100	Vertical	Pass
6	312.901	24.25	-21.32	46.0	-21.75	Peak	68.50	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

1 GHz to 18 GHz, ANT H 802.11b CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1992.100	39.61	-14.44	74.0	-34.39	Peak	184.00	150	Horizontal	Pass
1**	1992.100	26.58	-14.44	54.0	-27.42	AV	184.00	150	Horizontal	Pass
2	2411.100	100.93	-11.49	74.0	26.93	Peak	19.00	150	Horizontal	N/A
2**	2411.100	98.68	-11.49	54.0	44.68	AV	19.00	150	Horizontal	N/A
3	3710.250	47.13	-4.02	74.0	-26.87	Peak	252.00	150	Horizontal	Pass
3**	3710.250	37.91	-4.02	54.0	-16.09	AV	252.00	150	Horizontal	Pass
4	4769.250	51.47	0.69	74.0	-22.53	Peak	360.00	150	Horizontal	Pass
4**	4769.250	41.78	0.69	54.0	-12.22	AV	360.00	150	Horizontal	Pass
5	7397.250	55.38	3.63	74.0	-18.62	Peak	151.00	150	Horizontal	Pass
5**	7397.250	44.62	3.63	54.0	-9.38	AV	151.00	150	Horizontal	Pass
6	13812.500	55.91	6.94	74.0	-18.09	Peak	287.00	150	Horizontal	Pass
6**	13812.500	46.72	6.94	54.0	-7.28	AV	287.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1623.300	38.25	-16.42	74.0	-35.75	Peak	310.00	150	Vertical	Pass
1**	1623.300	24.80	-16.42	54.0	-29.20	AV	310.00	150	Vertical	Pass
2	2411.100	88.57	-11.49	74.0	14.57	Peak	159.00	150	Vertical	N/A
2**	2411.100	85.92	-11.49	54.0	31.92	AV	159.00	150	Vertical	N/A
3	3020.750	45.47	-5.89	74.0	-28.53	Peak	302.00	150	Vertical	Pass
3**	3020.750	35.14	-5.89	54.0	-18.86	AV	302.00	150	Vertical	Pass
4	5561.250	52.69	1.21	74.0	-21.31	Peak	155.00	150	Vertical	Pass
4**	5561.250	43.79	1.21	54.0	-10.21	AV	155.00	150	Vertical	Pass
5	10062.500	53.18	3.48	74.0	-20.82	Peak	347.00	150	Vertical	Pass
5**	10062.500	44.53	3.48	54.0	-9.47	AV	347.00	150	Vertical	Pass
6	13821.500	55.77	6.82	74.0	-18.23	Peak	248.00	150	Vertical	Pass
6**	13821.500	46.68	6.82	54.0	-7.32	AV	248.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2119.800	41.21	-12.90	74.0	-32.79	Peak	82.00	150	Horizontal	Pass
1**	2119.800	28.07	-12.90	54.0	-25.93	AV	82.00	150	Horizontal	Pass
2	2419.800	101.99	-11.51	74.0	27.99	Peak	227.00	150	Horizontal	N/A
2**	2419.800	99.24	-11.51	54.0	45.24	AV	227.00	150	Horizontal	N/A
3	3059.750	45.36	-5.52	74.0	-28.64	Peak	189.00	150	Horizontal	Pass
3**	3059.750	34.16	-5.52	54.0	-19.84	AV	189.00	150	Horizontal	Pass
4	5162.000	51.97	0.29	74.0	-22.03	Peak	307.00	150	Horizontal	Pass
4**	5162.000	42.94	0.29	54.0	-11.06	AV	307.00	150	Horizontal	Pass
5	7837.250	55.70	3.54	74.0	-18.30	Peak	213.00	150	Horizontal	Pass
5**	7837.250	47.01	3.54	54.0	-6.99	AV	213.00	150	Horizontal	Pass
6	11950.500	54.80	3.89	74.0	-19.20	Peak	47.00	150	Horizontal	Pass
6**	11950.500	45.95	3.89	54.0	-8.05	AV	47.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1467.200	37.85	-16.34	74.0	-36.15	Peak	319.00	150	Vertical	Pass
1**	1467.200	24.70	-16.34	54.0	-29.30	AV	319.00	150	Vertical	Pass
2	2416.100	91.94	-11.52	74.0	17.94	Peak	159.00	150	Vertical	N/A
2**	2416.100	89.94	-11.52	54.0	35.94	AV	159.00	150	Vertical	N/A
3	3139.750	46.39	-5.54	74.0	-27.61	Peak	232.00	150	Vertical	Pass
3**	3139.750	35.88	-5.54	54.0	-18.12	AV	232.00	150	Vertical	Pass
4	4205.500	48.76	-0.80	74.0	-25.24	Peak	132.00	150	Vertical	Pass
4**	4205.500	39.65	-0.80	54.0	-14.35	AV	132.00	150	Vertical	Pass
5	7712.250	55.40	4.25	74.0	-18.60	Peak	217.00	150	Vertical	Pass
5**	7712.250	46.36	4.25	54.0	-7.64	AV	217.00	150	Vertical	Pass
6	13379.000	56.74	6.32	74.0	-17.26	Peak	7.00	150	Vertical	Pass
6**	13379.000	46.59	6.32	54.0	-7.41	AV	7.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1461.400	37.17	-16.17	74.0	-36.83	Peak	299.00	150	Horizontal	Pass
1**	1461.400	24.10	-16.17	54.0	-29.90	AV	299.00	100	Horizontal	Pass
2	2437.900	102.08	-11.18	74.0	28.08	Peak	12.00	100	Horizontal	N/A
2**	2437.900	99.83	-11.18	54.0	45.83	AV	12.00	100	Horizontal	N/A
3	3269.250	45.29	-6.04	74.0	-28.71	Peak	152.00	100	Horizontal	Pass
3**	3269.250	35.56	-6.04	54.0	-18.44	AV	152.00	100	Horizontal	Pass
4	5562.000	52.59	1.27	74.0	-21.41	Peak	129.00	100	Horizontal	Pass
4**	5562.000	43.89	1.27	54.0	-10.11	AV	129.00	100	Horizontal	Pass
5	10779.500	53.49	2.73	74.0	-20.51	Peak	298.00	100	Horizontal	Pass
5**	10779.500	44.71	2.73	54.0	-9.29	AV	298.00	100	Horizontal	Pass
6	14036.000	55.18	6.08	74.0	-18.82	Peak	200.00	100	Horizontal	Pass
6**	14036.000	46.06	6.08	54.0	-7.94	AV	200.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2174.200	42.10	-12.27	74.0	-31.90	Peak	358.00	150	Vertical	Pass
1**	2174.200	29.34	-12.27	54.0	-24.66	AV	358.00	150	Vertical	Pass
2	2437.900	90.69	-11.18	74.0	16.69	Peak	280.00	150	Vertical	N/A
2**	2437.900	88.25	-11.18	54.0	34.25	AV	280.00	150	Vertical	N/A
3	3624.500	47.85	-3.69	74.0	-26.15	Peak	45.00	150	Vertical	Pass
3**	3624.500	36.45	-3.69	54.0	-17.55	AV	45.00	150	Vertical	Pass
4	5740.000	52.74	1.34	74.0	-21.26	Peak	76.00	150	Vertical	Pass
4**	5740.000	43.39	1.34	54.0	-10.61	AV	76.00	150	Vertical	Pass
5	7791.250	55.60	4.37	74.0	-18.40	Peak	356.00	150	Vertical	Pass
5**	7791.250	45.77	4.37	54.0	-8.23	AV	356.00	150	Vertical	Pass
6	14317.500	55.79	6.00	74.0	-18.21	Peak	7.00	150	Vertical	Pass
6**	14317.500	45.95	6.00	54.0	-8.05	AV	7.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1323.100	37.32	-16.35	74.0	-36.68	Peak	165.00	150	Horizontal	Pass
1**	1323.100	24.05	-16.35	54.0	-29.95	AV	165.00	150	Horizontal	Pass
2	2124.200	40.79	-12.82	74.0	-33.21	Peak	162.00	150	Horizontal	Pass
2**	2124.200	27.84	-12.82	54.0	-26.16	AV	162.00	150	Horizontal	Pass
3	2456.200	101.33	-11.42	74.0	27.33	Peak	238.00	150	Horizontal	N/A
3**	2456.200	99.19	-11.42	54.0	45.19	AV	238.00	150	Horizontal	N/A
4	3210.000	45.06	-6.07	74.0	-28.94	Peak	301.00	150	Horizontal	Pass
4**	3210.000	35.26	-6.07	54.0	-18.74	AV	301.00	150	Horizontal	Pass
5	4914.250	53.28	0.77	74.0	-20.72	Peak	76.00	150	Horizontal	Pass
5**	4914.250	49.18	0.77	54.0	-4.82	AV	76.00	150	Horizontal	Pass
6	11937.500	53.63	2.55	74.0	-20.37	Peak	18.00	150	Horizontal	Pass
6**	11937.500	44.28	2.55	54.0	-9.72	AV	18.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1286.100	37.84	-16.45	74.0	-36.16	Peak	94.00	150	Vertical	Pass
1**	1286.100	24.00	-16.45	54.0	-30.00	AV	94.00	150	Vertical	Pass
2	1748.300	39.15	-16.05	74.0	-34.85	Peak	296.00	150	Vertical	Pass
2**	1748.300	26.12	-16.05	54.0	-27.88	AV	296.00	150	Vertical	Pass
3	2456.100	93.55	-11.43	74.0	19.55	Peak	163.00	150	Vertical	N/A
3**	2456.100	91.56	-11.43	54.0	37.56	AV	163.00	150	Vertical	N/A
4	3631.250	46.86	-4.27	74.0	-27.14	Peak	128.00	150	Vertical	Pass
4**	3631.250	38.97	-4.27	54.0	-15.03	AV	128.00	150	Vertical	Pass
5	5590.000	53.03	0.74	74.0	-20.97	Peak	229.00	150	Vertical	Pass
5**	5590.000	42.66	0.74	54.0	-11.34	AV	229.00	150	Vertical	Pass
6	9978.000	51.80	0.96	74.0	-22.20	Peak	277.00	150	Vertical	Pass
6**	9978.000	42.61	0.96	54.0	-11.39	AV	277.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1168.200	38.06	-17.19	74.0	-35.94	Peak	178.00	150	Horizontal	Pass
1**	1168.200	23.16	-17.19	54.0	-30.84	AV	178.00	150	Horizontal	Pass
2	1870.400	39.03	-15.19	74.0	-34.97	Peak	139.00	150	Horizontal	Pass
2**	1870.400	25.50	-15.19	54.0	-28.50	AV	139.00	150	Horizontal	Pass
3	2464.800	102.00	-11.41	74.0	28.00	Peak	229.00	150	Horizontal	N/A
3**	2464.800	99.12	-11.41	54.0	45.12	AV	229.00	150	Horizontal	N/A
4	3107.250	45.57	-5.63	74.0	-28.43	Peak	261.00	150	Horizontal	Pass
4**	3107.250	35.76	-5.63	54.0	-18.24	AV	261.00	150	Horizontal	Pass
5	6676.500	54.59	2.18	74.0	-19.41	Peak	51.00	150	Horizontal	Pass
5**	6676.500	45.18	2.18	54.0	-8.82	AV	51.00	150	Horizontal	Pass
6	9325.000	53.11	3.37	74.0	-20.89	Peak	201.00	150	Horizontal	Pass
6**	9325.000	44.58	3.37	54.0	-9.42	AV	201.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1305.100	37.94	-16.49	74.0	-36.06	Peak	237.00	150	Vertical	Pass
1**	1305.100	24.35	-16.49	54.0	-29.65	AV	237.00	150	Vertical	Pass
2	2269.700	42.96	-11.25	74.0	-31.04	Peak	284.00	150	Vertical	Pass
2**	2269.700	30.57	-11.25	54.0	-23.43	AV	284.00	150	Vertical	Pass
3	2462.900	89.80	-11.36	74.0	15.80	Peak	125.00	150	Vertical	N/A
3**	2462.900	87.52	-11.36	54.0	33.52	AV	125.00	150	Vertical	N/A
4	3685.000	47.06	-3.93	74.0	-26.94	Peak	325.00	150	Vertical	Pass
4**	3685.000	37.45	-3.93	54.0	-16.55	AV	325.00	150	Vertical	Pass
5	6873.000	54.43	2.63	74.0	-19.57	Peak	224.00	150	Vertical	Pass
5**	6873.000	45.77	2.63	54.0	-8.23	AV	224.00	150	Vertical	Pass
6	11308.000	54.52	3.40	74.0	-19.48	Peak	29.00	150	Vertical	Pass
6**	11308.000	45.26	3.40	54.0	-8.74	AV	29.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1660.600	38.14	-16.31	74.0	-35.86	Peak	187.00	150	Horizontal	Pass
1**	1660.600	24.88	-16.31	54.0	-29.12	AV	187.00	150	Horizontal	Pass
2	2414.400	102.36	-11.55	74.0	28.36	Peak	234.00	150	Horizontal	N/A
2**	2414.400	94.84	-11.55	54.0	40.84	AV	234.00	150	Horizontal	N/A
3	4141.750	48.89	-2.85	74.0	-25.11	Peak	321.00	150	Horizontal	Pass
3**	4141.750	38.67	-2.85	54.0	-15.33	AV	321.00	150	Horizontal	Pass
4	5595.750	52.52	0.74	74.0	-21.48	Peak	360.00	150	Horizontal	Pass
4**	5595.750	42.49	0.74	54.0	-11.51	AV	360.00	150	Horizontal	Pass
5	9097.000	52.64	1.57	74.0	-21.36	Peak	352.00	150	Horizontal	Pass
5**	9097.000	43.66	1.57	54.0	-10.34	AV	352.00	150	Horizontal	Pass
6	11903.000	53.92	3.56	74.0	-20.08	Peak	308.00	150	Horizontal	Pass
6**	11903.000	45.08	3.56	54.0	-8.92	AV	308.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2196.100	42.04	-11.54	74.0	-31.96	Peak	225.00	150	Vertical	Pass
1**	2196.100	30.14	-11.54	54.0	-23.86	AV	225.00	150	Vertical	Pass
2	2407.100	90.19	-11.30	74.0	16.19	Peak	173.00	150	Vertical	N/A
2**	2407.100	82.22	-11.30	54.0	28.22	AV	173.00	150	Vertical	N/A
3	3017.750	45.92	-5.86	74.0	-28.08	Peak	361.00	150	Vertical	Pass
3**	3017.750	37.09	-5.86	54.0	-16.91	AV	361.00	150	Vertical	Pass
4	4779.250	52.18	1.04	74.0	-21.82	Peak	54.00	150	Vertical	Pass
4**	4779.250	41.66	1.04	54.0	-12.34	AV	54.00	150	Vertical	Pass
5	9333.500	53.90	3.36	74.0	-20.10	Peak	272.00	150	Vertical	Pass
5**	9333.500	45.60	3.36	54.0	-8.40	AV	272.00	150	Vertical	Pass
6	13141.000	55.02	5.43	74.0	-18.98	Peak	272.00	150	Vertical	Pass
6**	13141.000	45.96	5.43	54.0	-8.04	AV	272.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1920.100	39.99	-14.67	74.0	-34.01	Peak	133.00	150	Horizontal	Pass
1**	1920.100	26.77	-14.67	54.0	-27.23	AV	133.00	150	Horizontal	Pass
2	2409.700	103.86	-11.47	74.0	29.86	Peak	223.00	150	Horizontal	N/A
2**	2409.700	96.61	-11.47	54.0	42.61	AV	223.00	150	Horizontal	N/A
3	3612.500	46.67	-3.72	74.0	-27.33	Peak	189.00	150	Horizontal	Pass
3**	3612.500	38.10	-3.72	54.0	-15.90	AV	189.00	150	Horizontal	Pass
4	5071.000	51.05	0.86	74.0	-22.95	Peak	205.00	150	Horizontal	Pass
4**	5071.000	42.63	0.86	54.0	-11.37	AV	205.00	150	Horizontal	Pass
5	7250.500	54.82	3.39	74.0	-19.18	Peak	166.00	150	Horizontal	Pass
5**	7250.500	46.34	3.39	54.0	-7.66	AV	166.00	150	Horizontal	Pass
6	13540.000	55.69	5.80	74.0	-18.31	Peak	360.00	150	Horizontal	Pass
6**	13540.000	46.24	5.80	54.0	-7.76	AV	360.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1341.800	37.95	-16.42	74.0	-36.05	Peak	261.00	150	Vertical	Pass
1**	1341.800	26.45	-16.42	54.0	-27.55	AV	261.00	150	Vertical	Pass
2	2109.700	40.99	-13.18	74.0	-33.01	Peak	211.00	150	Vertical	Pass
2**	2109.700	28.48	-13.18	54.0	-25.52	AV	211.00	150	Vertical	Pass
3	2410.200	91.95	-11.49	74.0	17.95	Peak	198.00	150	Vertical	N/A
3**	2410.200	84.63	-11.49	54.0	30.63	AV	198.00	150	Vertical	N/A
4	3743.250	46.69	-2.15	74.0	-27.31	Peak	301.00	150	Vertical	Pass
4**	3743.250	38.15	-2.15	54.0	-15.85	AV	301.00	150	Vertical	Pass
5	7765.750	55.94	3.91	74.0	-18.06	Peak	0.00	150	Vertical	Pass
5**	7765.750	46.02	3.91	54.0	-7.98	AV	0.00	150	Vertical	Pass
6	12421.000	55.07	3.64	74.0	-18.93	Peak	72.00	150	Vertical	Pass
6**	12421.000	44.39	3.64	54.0	-9.61	AV	72.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1646.500	38.10	-16.54	74.0	-35.90	Peak	350.00	150	Horizontal	Pass
1**	1646.500	24.48	-16.54	54.0	-29.52	AV	350.00	150	Horizontal	Pass
2	2207.900	41.67	-11.19	74.0	-32.33	Peak	115.00	150	Horizontal	Pass
2**	2207.900	29.38	-11.19	54.0	-24.62	AV	115.00	150	Horizontal	Pass
3	2411.000	103.72	-11.49	74.0	29.72	Peak	8.00	150	Horizontal	N/A
3**	2411.000	96.61	-11.49	54.0	42.61	AV	8.00	150	Horizontal	N/A
4	4558.500	50.27	-1.37	74.0	-23.73	Peak	176.00	150	Horizontal	Pass
4**	4558.500	41.38	-1.37	54.0	-12.62	AV	176.00	150	Horizontal	Pass
5	7730.500	55.36	3.36	74.0	-18.64	Peak	137.00	150	Horizontal	Pass
5**	7730.500	46.73	3.36	54.0	-7.27	AV	137.00	150	Horizontal	Pass
6	12012.500	54.43	3.51	74.0	-19.57	Peak	90.00	150	Horizontal	Pass
6**	12012.500	45.96	3.51	54.0	-8.04	AV	90.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1901.700	39.67	-14.90	74.0	-34.33	Peak	195.00	150	Vertical	Pass
1**	1901.700	26.35	-14.90	54.0	-27.65	AV	195.00	150	Vertical	Pass
2	2058.300	41.04	-13.49	74.0	-32.96	Peak	179.00	150	Vertical	Pass
2**	2058.300	28.18	-13.49	54.0	-25.82	AV	179.00	150	Vertical	Pass
3	2407.300	92.55	-11.26	74.0	18.55	Peak	161.00	150	Vertical	N/A
3**	2407.300	84.70	-11.26	54.0	30.70	AV	161.00	150	Vertical	N/A
4	4049.000	48.09	-2.28	74.0	-25.91	Peak	170.00	150	Vertical	Pass
4**	4049.000	38.40	-2.28	54.0	-15.60	AV	170.00	150	Vertical	Pass
5	6297.750	52.92	2.35	74.0	-21.08	Peak	357.00	150	Vertical	Pass
5**	6297.750	43.71	2.35	54.0	-10.29	AV	357.00	150	Vertical	Pass
6	12011.000	54.73	3.55	74.0	-19.27	Peak	314.00	150	Vertical	Pass
6**	12011.000	46.33	3.55	54.0	-7.67	AV	314.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1914.200	39.56	-14.97	74.0	-34.44	Peak	342.00	150	Horizontal	Pass
1**	1914.200	27.50	-14.97	54.0	-26.50	AV	342.00	150	Horizontal	Pass
2	2454.900	103.42	-11.56	74.0	29.42	Peak	234.00	150	Horizontal	N/A
2**	2454.900	96.16	-11.56	54.0	42.16	AV	234.00	150	Horizontal	N/A
3	4130.750	48.80	-2.35	74.0	-25.20	Peak	184.00	150	Horizontal	Pass
3**	4130.750	39.16	-2.35	54.0	-14.84	AV	184.00	150	Horizontal	Pass
4	6014.500	53.47	3.43	74.0	-20.53	Peak	107.00	150	Horizontal	Pass
4**	6014.500	44.85	3.43	54.0	-9.15	AV	107.00	150	Horizontal	Pass
5	10060.000	52.59	2.35	74.0	-21.41	Peak	117.00	150	Horizontal	Pass
5**	10060.000	43.74	2.35	54.0	-10.26	AV	117.00	150	Horizontal	Pass
6	13616.500	54.36	4.85	74.0	-19.64	Peak	272.00	150	Horizontal	Pass
6**	13616.500	45.82	4.85	54.0	-8.18	AV	272.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1264.700	37.54	-16.55	74.0	-36.46	Peak	332.00	150	Vertical	Pass
1**	1264.700	24.29	-16.55	54.0	-29.71	AV	332.00	150	Vertical	Pass
2	2191.400	42.25	-11.88	74.0	-31.75	Peak	337.00	150	Vertical	Pass
2**	2191.400	29.09	-11.88	54.0	-24.91	AV	337.00	150	Vertical	Pass
3	2454.700	93.82	-11.58	74.0	19.82	Peak	90.00	150	Vertical	N/A
3**	2454.700	86.58	-11.58	54.0	32.58	AV	90.00	150	Vertical	N/A
4	3776.250	47.32	-3.53	74.0	-26.68	Peak	360.00	150	Vertical	Pass
4**	3776.250	38.06	-3.53	54.0	-15.94	AV	360.00	150	Vertical	Pass
5	6318.500	54.58	2.19	74.0	-19.42	Peak	59.00	150	Vertical	Pass
5**	6318.500	43.89	2.19	54.0	-10.11	AV	59.00	150	Vertical	Pass
6	10791.999	52.03	1.94	74.0	-21.97	Peak	0.00	150	Vertical	Pass
6**	10791.999	45.12	1.94	54.0	-8.88	AV	0.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1462.400	38.22	-16.17	74.0	-35.78	Peak	252.00	150	Horizontal	Pass
1**	1462.400	25.68	-16.17	54.0	-28.32	AV	252.00	150	Horizontal	Pass
2	2413.200	103.70	-11.53	74.0	29.70	Peak	21.00	150	Horizontal	N/A
2**	2413.200	96.90	-11.53	54.0	42.90	AV	21.00	150	Horizontal	N/A
3	3057.000	45.10	-5.19	74.0	-28.90	Peak	144.00	150	Horizontal	Pass
3**	3057.000	35.80	-5.19	54.0	-18.20	AV	144.00	150	Horizontal	Pass
4	4953.750	52.05	1.28	74.0	-21.95	Peak	252.00	150	Horizontal	Pass
4**	4953.750	41.80	1.28	54.0	-12.20	AV	252.00	150	Horizontal	Pass
5	6757.250	54.55	2.10	74.0	-19.45	Peak	244.00	150	Horizontal	Pass
5**	6757.250	44.38	2.10	54.0	-9.62	AV	244.00	150	Horizontal	Pass
6	8692.500	52.69	2.17	74.0	-21.31	Peak	68.00	150	Horizontal	Pass
6**	8692.500	43.39	2.17	54.0	-10.61	AV	68.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1496.300	38.30	-16.39	74.0	-35.70	Peak	105.00	150	Vertical	Pass
1**	1496.300	24.59	-16.39	54.0	-29.41	AV	105.00	150	Vertical	Pass
2	2259.300	42.19	-11.42	74.0	-31.81	Peak	253.00	150	Vertical	Pass
2**	2259.300	29.17	-11.42	54.0	-24.83	AV	253.00	150	Vertical	Pass
3	2413.700	91.79	-11.55	74.0	17.79	Peak	278.00	150	Vertical	N/A
3**	2413.700	84.36	-11.55	54.0	30.36	AV	278.00	150	Vertical	N/A
4	3747.750	47.63	-2.22	74.0	-26.37	Peak	278.00	150	Vertical	Pass
4**	3747.750	38.72	-2.22	54.0	-15.28	AV	278.00	150	Vertical	Pass
5	7078.250	55.26	3.03	74.0	-18.74	Peak	162.00	150	Vertical	Pass
5**	7078.250	44.42	3.03	54.0	-9.58	AV	162.00	150	Vertical	Pass
6	12892.000	55.08	4.86	74.0	-18.92	Peak	250.00	150	Vertical	Pass
6**	12892.000	45.74	4.86	54.0	-8.26	AV	250.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1980.400	40.53	-14.25	74.0	-33.47	Peak	360.00	150	Horizontal	Pass
1**	1980.400	27.08	-14.25	54.0	-26.92	AV	360.00	150	Horizontal	Pass
2	2410.700	101.83	-11.49	74.0	27.83	Peak	16.00	150	Horizontal	N/A
2**	2410.700	94.61	-11.49	54.0	40.61	AV	16.00	150	Horizontal	N/A
3	4352.750	48.65	-1.64	74.0	-25.35	Peak	-1.00	150	Horizontal	Pass
3**	4352.750	35.95	-1.64	54.0	-18.05	AV	-1.00	150	Horizontal	Pass
4	5078.500	51.01	0.90	74.0	-22.99	Peak	-1.00	150	Horizontal	Pass
4**	5078.500	41.48	0.90	54.0	-12.52	AV	-1.00	150	Horizontal	Pass
5	9461.000	53.03	2.80	74.0	-20.97	Peak	17.00	150	Horizontal	Pass
5**	9461.000	44.39	2.80	54.0	-9.61	AV	17.00	150	Horizontal	Pass
6	15239.500	55.55	4.65	74.0	-18.45	Peak	292.00	150	Horizontal	Pass
6**	15239.500	45.37	4.65	54.0	-8.63	AV	292.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 CHANNEL 1

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1377.800	37.63	-16.35	74.0	-36.37	Peak	158.00	150	Vertical	Pass
1**	1377.800	24.48	-16.35	54.0	-29.52	AV	158.00	100	Vertical	Pass
2	2409.900	90.02	-11.48	74.0	16.02	Peak	154.00	100	Vertical	N/A
2**	2409.900	82.93	-11.48	54.0	28.93	AV	154.00	100	Vertical	N/A
3	3850.750	48.50	-3.43	74.0	-25.50	Peak	353.00	100	Vertical	Pass
3**	3850.750	39.00	-3.43	54.0	-15.00	AV	353.00	100	Vertical	Pass
4	6470.500	53.83	2.05	74.0	-20.17	Peak	191.00	100	Vertical	Pass
4**	6470.500	43.64	2.05	54.0	-10.36	AV	191.00	100	Vertical	Pass
5	11889.500	54.66	3.46	74.0	-19.34	Peak	309.00	100	Vertical	Pass
5**	11889.500	45.33	3.46	54.0	-8.67	AV	309.00	100	Vertical	Pass
6	14301.500	55.56	6.38	74.0	-18.44	Peak	157.00	100	Vertical	Pass
6**	14301.500	46.68	6.38	54.0	-7.32	AV	157.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1884.500	39.42	-15.21	74.0	-34.58	Peak	337.00	150	Horizontal	Pass
1**	1884.500	25.34	-15.21	54.0	-28.66	AV	337.00	150	Horizontal	Pass
2	2206.200	42.17	-11.21	74.0	-31.83	Peak	176.00	150	Horizontal	Pass
2**	2206.200	28.75	-11.21	54.0	-25.25	AV	176.00	150	Horizontal	Pass
3	2413.200	102.39	-11.53	74.0	28.39	Peak	19.00	150	Horizontal	N/A
3**	2413.200	94.58	-11.53	54.0	40.58	AV	19.00	150	Horizontal	N/A
4	4508.000	49.26	-0.41	74.0	-24.74	Peak	217.00	150	Horizontal	Pass
4**	4508.000	39.68	-0.41	54.0	-14.32	AV	217.00	150	Horizontal	Pass
5	7931.500	55.40	4.49	74.0	-18.60	Peak	256.00	150	Horizontal	Pass
5**	7931.500	46.07	4.49	54.0	-7.93	AV	256.00	150	Horizontal	Pass
6	13365.500	56.31	6.40	74.0	-17.69	Peak	62.00	150	Horizontal	Pass
6**	13365.500	46.65	6.40	54.0	-7.35	AV	62.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 CHANNEL 2

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2264.100	43.07	-11.19	74.0	-30.93	Peak	224.00	150	Vertical	Pass
1**	2264.100	29.76	-11.19	54.0	-24.24	AV	224.00	150	Vertical	Pass
2	2416.000	90.20	-11.53	74.0	16.20	Peak	156.00	150	Vertical	N/A
2**	2416.000	83.37	-11.53	54.0	29.37	AV	156.00	150	Vertical	N/A
3	3734.250	47.25	-3.45	74.0	-26.75	Peak	308.00	150	Vertical	Pass
3**	3734.250	37.48	-3.45	54.0	-16.52	AV	308.00	150	Vertical	Pass
4	6665.500	53.52	2.27	74.0	-20.48	Peak	199.00	150	Vertical	Pass
4**	6665.500	45.09	2.27	54.0	-8.91	AV	199.00	150	Vertical	Pass
5	7786.750	55.11	4.62	74.0	-18.89	Peak	74.00	150	Vertical	Pass
5**	7786.750	46.45	4.62	54.0	-7.55	AV	74.00	150	Vertical	Pass
6	12538.500	54.78	3.62	74.0	-19.22	Peak	200.00	150	Vertical	Pass
6**	12538.500	45.48	3.62	54.0	-8.52	AV	200.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1708.500	38.52	-16.21	74.0	-35.48	Peak	333.00	150	Horizontal	Pass
1**	1708.500	24.42	-16.21	54.0	-29.58	AV	333.00	150	Horizontal	Pass
2	2438.100	103.99	-11.18	74.0	29.99	Peak	316.00	150	Horizontal	N/A
2**	2438.100	97.47	-11.18	54.0	43.47	AV	316.00	150	Horizontal	N/A
3	4163.000	48.42	-2.83	74.0	-25.58	Peak	9.00	150	Horizontal	Pass
3**	4163.000	38.47	-2.83	54.0	-15.53	AV	9.00	150	Horizontal	Pass
4	7793.250	56.16	4.33	74.0	-17.84	Peak	256.00	150	Horizontal	Pass
4**	7793.250	46.38	4.33	54.0	-7.62	AV	256.00	150	Horizontal	Pass
5	11289.500	54.29	3.50	74.0	-19.71	Peak	161.00	150	Horizontal	Pass
5**	11289.500	45.34	3.50	54.0	-8.66	AV	161.00	150	Horizontal	Pass
6	13810.500	56.38	6.96	74.0	-17.62	Peak	293.00	150	Horizontal	Pass
6**	13810.500	46.81	6.96	54.0	-7.19	AV	293.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 CHANNEL 6

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1320.700	37.90	-16.32	74.0	-36.10	Peak	294.00	150	Vertical	Pass
1**	1320.700	24.22	-16.32	54.0	-29.78	AV	294.00	150	Vertical	Pass
2	2200.100	41.45	-11.35	74.0	-32.55	Peak	156.00	150	Vertical	Pass
2**	2200.100	29.66	-11.35	54.0	-24.34	AV	156.00	150	Vertical	Pass
3	2437.900	90.26	-11.18	74.0	16.26	Peak	277.00	150	Vertical	N/A
3**	2437.900	83.44	-11.18	54.0	29.44	AV	277.00	150	Vertical	N/A
4	3621.500	47.36	-3.45	74.0	-26.64	Peak	120.00	150	Vertical	Pass
4**	3621.500	36.44	-3.45	54.0	-17.56	AV	120.00	150	Vertical	Pass
5	5122.000	52.00	0.80	74.0	-22.00	Peak	298.00	150	Vertical	Pass
5**	5122.000	42.25	0.80	54.0	-11.75	AV	298.00	150	Vertical	Pass
6	14517.500	55.86	5.75	74.0	-18.14	Peak	143.00	150	Vertical	Pass
6**	14517.500	46.62	5.75	54.0	-7.38	AV	143.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1725.900	38.18	-16.27	74.0	-35.82	Peak	332.00	150	Horizontal	Pass
1**	1725.900	25.24	-16.27	54.0	-28.76	AV	332.00	150	Horizontal	Pass
2	2178.300	41.35	-12.26	74.0	-32.65	Peak	151.00	150	Horizontal	Pass
2**	2178.300	28.30	-12.26	54.0	-25.70	AV	151.00	150	Horizontal	Pass
3	2455.600	102.11	-11.48	74.0	28.11	Peak	227.00	150	Horizontal	N/A
3**	2455.600	95.10	-11.48	54.0	41.10	AV	227.00	150	Horizontal	N/A
4	4776.500	51.24	1.13	74.0	-22.76	Peak	341.00	150	Horizontal	Pass
4**	4776.500	42.13	1.13	54.0	-11.87	AV	341.00	150	Horizontal	Pass
5	6308.750	53.67	2.34	74.0	-20.33	Peak	361.00	150	Horizontal	Pass
5**	6308.750	43.59	2.34	54.0	-10.41	AV	361.00	150	Horizontal	Pass
6	12472.500	53.83	2.92	74.0	-20.17	Peak	196.00	150	Horizontal	Pass
6**	12472.500	44.88	2.92	54.0	-9.12	AV	196.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 CHANNEL 10

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1343.800	37.80	-16.55	74.0	-36.20	Peak	273.00	150	Vertical	Pass
1**	1343.800	24.49	-16.55	54.0	-29.51	AV	273.00	150	Vertical	Pass
2	1915.700	39.78	-14.99	74.0	-34.22	Peak	355.00	150	Vertical	Pass
2**	1915.700	25.79	-14.99	54.0	-28.21	AV	355.00	150	Vertical	Pass
3	2454.900	92.67	-11.56	74.0	18.67	Peak	86.00	150	Vertical	N/A
3**	2454.900	84.84	-11.56	54.0	30.84	AV	86.00	150	Vertical	N/A
4	4486.750	49.31	-1.00	74.0	-24.69	Peak	315.00	150	Vertical	Pass
4**	4486.750	39.67	-1.00	54.0	-14.33	AV	315.00	150	Vertical	Pass
5	7979.250	55.79	2.74	74.0	-18.21	Peak	323.00	150	Vertical	Pass
5**	7979.250	46.79	2.74	54.0	-7.21	AV	323.00	150	Vertical	Pass
6	14042.500	54.90	5.11	74.0	-19.10	Peak	121.00	150	Vertical	Pass
6**	14042.500	45.66	5.11	54.0	-8.34	AV	121.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1269.700	38.03	-16.58	74.0	-35.97	Peak	261.00	150	Horizontal	Pass
1**	1269.700	24.05	-16.58	54.0	-29.95	AV	261.00	150	Horizontal	Pass
2	2195.400	41.48	-11.62	74.0	-32.52	Peak	193.00	150	Horizontal	Pass
2**	2195.400	30.00	-11.62	54.0	-24.00	AV	193.00	150	Horizontal	Pass
3	2413.100	102.36	-11.53	74.0	28.36	Peak	13.00	150	Horizontal	N/A
3**	2413.100	95.51	-11.53	54.0	41.51	AV	13.00	150	Horizontal	N/A
4	4785.750	51.59	0.92	74.0	-22.41	Peak	115.00	150	Horizontal	Pass
4**	4785.750	42.44	0.92	54.0	-11.56	AV	115.00	150	Horizontal	Pass
5	7783.750	55.28	4.60	74.0	-18.72	Peak	216.00	150	Horizontal	Pass
5**	7783.750	46.71	4.60	54.0	-7.29	AV	216.00	150	Horizontal	Pass
6	13796.500	55.78	6.94	74.0	-18.22	Peak	348.00	150	Horizontal	Pass
6**	13796.500	46.30	6.94	54.0	-7.70	AV	348.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 CHANNEL 11

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1451.000	37.64	-16.49	74.0	-36.36	Peak	167.00	150	Vertical	Pass
1**	1451.000	24.36	-16.49	54.0	-29.64	AV	167.00	150	Vertical	Pass
2	1978.400	40.17	-14.45	74.0	-33.83	Peak	85.00	150	Vertical	Pass
2**	1978.400	26.96	-14.45	54.0	-27.04	AV	85.00	150	Vertical	Pass
3	2408.200	103.00	-11.26	74.0	29.00	Peak	21.00	150	Vertical	N/A
3**	2408.200	95.30	-11.26	54.0	41.30	AV	21.00	150	Vertical	N/A
4	4207.750	49.32	-0.64	74.0	-24.68	Peak	293.00	150	Vertical	Pass
4**	4207.750	38.89	-0.64	54.0	-15.11	AV	293.00	150	Vertical	Pass
5	6189.750	53.98	1.26	74.0	-20.02	Peak	136.00	150	Vertical	Pass
5**	6189.750	44.40	1.26	54.0	-9.60	AV	136.00	150	Vertical	Pass
6	12499.000	54.36	4.46	74.0	-19.64	Peak	287.00	150	Vertical	Pass
6**	12499.000	46.09	4.46	54.0	-7.91	AV	287.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Data and Plots


802.11b Mode:

CHANNEL 1




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	57.88	31.17	74.0	-16.12	Peak	15.00	150	Horizontal	Pass
1**	2390.000	48.05	31.17	54.0	-5.95	AV	15.00	150	Horizontal	Pass
2	2355.500	60.14	31.25	74.0	-13.86	Peak	8.00	150	Horizontal	Pass
2**	2355.500	47.67	31.25	54.0	-6.33	AV	8.00	150	Horizontal	Pass

CHANNEL 2




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	52.96	32.63	74.0	-21.04	Peak	14.00	100	Horizontal	Pass
1**	2390.000	35.40	32.63	54.0	-18.60	AV	14.00	100	Horizontal	Pass
2	2389.167	55.06	32.67	74.0	-18.94	Peak	8.00	100	Horizontal	Pass
2**	2389.167	35.57	32.67	54.0	-18.43	AV	8.00	100	Horizontal	Pass

CHANNEL 10



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.12	32.80	74.0	-19.88	Peak	15.00	150	Horizontal	Pass
1**	2483.500	34.95	32.80	54.0	-19.05	AV	15.00	150	Horizontal	Pass
2	2488.000	55.70	32.69	74.0	-18.30	Peak	8.00	150	Horizontal	Pass
2**	2488.000	34.58	32.69	54.0	-19.42	AV	8.00	150	Horizontal	Pass


CHANNEL 11



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	58.72	31.26	74.0	-15.28	Peak	11.00	150	Horizontal	Pass
1**	2483.500	49.32	31.26	54.0	-4.68	AV	11.00	150	Horizontal	Pass
2	2485.000	59.90	31.25	74.0	-14.10	Peak	14.00	150	Horizontal	Pass
2**	2485.000	48.50	31.25	54.0	-5.50	AV	14.00	150	Horizontal	Pass


802.11g Mode:

CHANNEL 1




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	66.42	-1.85	74.0	-7.58	Peak	10.00	150	Horizontal	Pass
1**	2390.000	50.11	-1.85	54.0	-3.89	AV	10.00	150	Horizontal	Pass
2	2389.500	64.93	-1.83	74.0	-9.07	Peak	9.00	150	Horizontal	Pass
2**	2389.500	49.03	-1.83	54.0	-4.97	AV	9.00	150	Horizontal	Pass

CHANNEL 2




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	64.89	-1.85	74.0	-9.11	Peak	13.00	150	Horizontal	Pass
1**	2390.000	49.72	-1.85	54.0	-4.28	AV	13.00	150	Horizontal	Pass
2	2387.333	65.64	-1.66	74.0	-8.36	Peak	13.00	150	Horizontal	Pass
2**	2387.333	47.80	-1.66	54.0	-6.20	AV	13.00	150	Horizontal	Pass

CHANNEL 10



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	60.67	31.26	74.0	-13.33	Peak	14.00	150	Horizontal	Pass
1**	2483.500	49.05	31.26	54.0	-4.95	AV	14.00	150	Horizontal	Pass
2	2483.650	62.53	31.26	74.0	-11.47	Peak	0.00	150	Horizontal	Pass
2**	2483.650	49.11	31.26	54.0	-4.89	AV	0.00	150	Horizontal	Pass


CHANNEL 11



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	64.69	-1.28	74.0	-9.31	Peak	2.00	150	Horizontal	Pass
1**	2483.500	49.85	-1.28	54.0	-4.15	AV	2.00	150	Horizontal	Pass
2	2483.800	66.67	-1.28	74.0	-7.33	Peak	8.00	150	Horizontal	Pass
2**	2483.800	49.09	-1.28	54.0	-4.91	AV	8.00	150	Horizontal	Pass


802.11n-20 MHz Mode:

CHANNEL 1




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	67.05	-1.85	74.0	-6.95	Peak	3.00	150	Horizontal	Pass
1**	2390.000	50.40	-1.85	54.0	-3.60	AV	3.00	150	Horizontal	Pass
2	2388.667	67.60	-1.79	74.0	-6.40	Peak	2.00	150	Horizontal	Pass
2**	2388.667	48.45	-1.79	54.0	-5.55	AV	2.00	150	Horizontal	Pass

CHANNEL 2



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	65.78	31.17	74.0	-8.22	Peak	14.00	150	Horizontal	Pass
1**	2390.000	50.98	31.17	54.0	-3.02	AV	14.00	150	Horizontal	Pass

CHANNEL 10



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	52.00	32.80	74.0	-22.00	Peak	1.00	150	Horizontal	Pass
1**	2483.500	34.96	32.80	54.0	-19.04	AV	1.00	150	Horizontal	Pass
2	2490.100	56.24	32.65	74.0	-17.76	Peak	12.00	150	Horizontal	Pass
2**	2490.100	34.53	32.65	54.0	-19.47	AV	12.00	150	Horizontal	Pass

CHANNEL 11



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	67.92	-1.28	74.0	-6.08	Peak	7.00	150	Horizontal	Pass
1**	2483.500	50.80	-1.28	54.0	-3.20	AV	7.00	150	Horizontal	Pass
2	2483.850	69.47	-1.28	74.0	-4.53	Peak	4.00	150	Horizontal	Pass
2**	2483.850	50.61	-1.28	54.0	-3.39	AV	4.00	150	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
1	-18.18	8
2	-13.39	8
6	-13.15	8
10	-13.46	8
11	-14.16	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
1	-20.50	8
2	-17.55	8
6	-17.15	8
10	-17.36	8
11	-18.56	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
1	-20.52	8
2	-18.52	8
6	-18.52	8
10	-18.80	8
11	-19.37	8

Test plots

802.11b CHANNEL 1



802.11b CHANNEL 2



802.11b CHANNEL 6



802.11g CHANNEL 10



802.11b CHANNEL 11



802.11g CHANNEL 1



802.11g CHANNEL 2



802.11g CHANNEL 6



802.11g CHANNEL 10



802.11g CHANNEL 11



802.11n-20 MHz CHANNEL 1



802.11 n-20 MHz CHANNEL 2



802.11n-20 MHz CHANNEL 6



802.11n-20 MHz CHANNEL 10



802.11n-40 MHz CHANNEL 11



ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ2180012-AR.pdf".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ2180012-AW.pdf".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ2180012-AI.pdf".

--END OF REPORT--