Subject: Manufacturer's Declaration for ⊠ - Modular Approval



Raspberry Pi LTD

194 Cambridge Science Park Milton Road Cambridge CB4 0AB United Kingdom raspberrypi.com

 \square - Split Modular Approval

Request for Modular/Limited Modular Approval

	□ - Limited Modular Approval □ - Limited Sp	lit Modular	Approval
Cont	Edentiality Request for: 2ABCB-PICO2W		
	8 Basic Requirements – FCC Part 15.212(a)(1)		
	For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F		
- 1	Modular Approval Requirement	Require	ment Met
1.	The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)
	Details: <example a="" all="" and="" board="" circlocated="" components="" contains="" covers="" metal="" module="" of="" on="" rf="" shield="" the="" top="" which="" –=""></example>	cuitry. The sl	nield is
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)
	Details: <example as="" buffered="" circuit="" data="" descapplication="" described="" in="" is="" modulation="" operational="" the="" to="" –=""></example>	cription provi	ded with the
3.	The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)
	Details: <example application="" contains="" its="" module="" own="" please="" power="" refer="" regulation.="" scheme="" supply="" the="" to="" –=""></example>	atic filed with	this
4.	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)
	Details: <example antenna="" board="" connects="" its="" module="" on="" only="" the="" to="" –=""></example>		
5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment	⊠ - YES	□ - NO(*)



194 Cambridge Science Park
Milton Road
Cambridge
CB4 0AB
United Kingdom
raspberrypi.com

	connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)		
	Details: <example application="" as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" test="" tested="" the="" this="" was="" with="" –=""></example>		
	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This	⊠ - YES	□ - NO(*)
	exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi) Details: <example a="" application.="" are="" as="" exhibit="" filed="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" the="" there="" this="" with="" –=""></example>	application.	Host specific
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" complies="" fcc="" filed="" g="" in="" installation="" instructions="" manual="" module="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	DEM installer	are provided
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example application.="" as="" exclusion="" exposure="" in="" info="" levels="" meets="" module="" portable="" rf="" shown="" the="" –=""></example>	ormation filed	d with this



194 Cambridge Science Park Milton Road Cambridge CB4 0AB United Kingdom raspberrypi.com

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>



194 Cambridge Science Park
Milton Road
Cambridge
CB4 0AB
United Kingdom
raspberrypi.com

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement		Requirement Met	
 For non-Software Defined Radio transmitter mode ensure compliance of the device, technical descrip such control is implemented to ensure prevention KDB Publication 594280. 	tion must be provided about how	□ - Provided in Separate Cover Letter	□ - N/A
Details: <example application.="" cover="" device="" filed="" firmware="" letter="" of="" the="" this="" with="" –=""></example>	can not be modified or adjusted by	the end user as described in	a separate
 For <u>Software Defined Radio (SDR)</u> devices, trans provide a software security description; see KDB 	**	☐ - Provided in Separate Cover Letter	⊠ - N/A
Details: <example a="" –n=""></example>			

Split Modular Requirements				
Requirement	Provided in Manual			
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	⊠ - N/A		
Details: <example a="" n="" –=""></example>				



194 Cambridge Science Park Milton Road Cambridge CB4 0AB United Kingdom raspberrypi.com

OEM Integration Manual Guidance – KDB 996369 D03 Section 2

		ing the Conditions, Limitations, and Proce integrate the module into a host device.	dures		
Requirement					
Is this module intended for sale to third parties?	· ⊠ - YES	☐ - No, If No, and LMA applies, the applicant can optionally choose to not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the information below must still be included in the operational description. If the applicant wishes to keep this info confidential, this will require a separate statement cover letter explaining the module is not for sale to third parties and that integration instructions are internal confidential documents.			
Items required to be in the manual – See KDB 996369 D03, Section 2 As of May 1, 2019, the FCC requires ALL the following information to be in the installation manual. Modular transmitter applicants should include information in their instructions for all these items indicating clearly when they are not applicable. For example information on trace antenna design could indicate "Not Applicable". Also if a module is limited to only a grantees own products and not intended for sale to third parties, the user instructions may not need to be detailed and the following items can be placed in the operational description, but this should include a cover letter as cited above.					
	es. KDB 996369 D03, Section		del us circu usove.		
a. Only list rul	les related to the transmitter.				
a. Conditions point system 3. Limited Module Procedure a. Describe alt necessary li b. When RF et that complia	point systems, professional installation info ted Module Procedures. KDB 996369 D03, Section 2.4 a. Describe alternative means that the grantee uses to verify the host meets the necessary limiting conditions b. When RF exposure evaluation is necessary, state how control will be maintained such that compliance is ensured, such as Class II for new hosts, etc.				
for design v confidential provided in	race design, parts list, antenna, rerification, and production test l, the method used to keep conf the operational description.	connectors, isolation requirements, tests t procedures for ensuring compliance. If fidential must be identified and information	ectors, isolation requirements, tests redures for ensuring compliance. If ial must be identified and information Guide (or UM) for Full Modular Approval (MA) or LMA.		
module. To define cond	explicitly state conditions that wo types of instructions are nec	allow host manufacturers to use the cessary: first to the host manufacturer to m from body) and second additional text	☐ - An LMA applies and is approved ONLY for use by the grantee in their own products, and not intended for sale to		
6. Antennas. KDB 996369 D		•	3 rd parties as provided		
a. List of anter instructions (monopole,	nnas included in the application when applicable. The antenna PIFA, dipole, etc – note that "c	n and all applicable professional installer list shall also identify the antenna types omni-directional" is not considered a type)	in a separate cover letter. Therefore the information shown to		
		o provide a physical or e-label stating	the left is found in the theory of operation.		
8. Information on test modes a. Test modes clarification	and additional testing requirementates that should be taken into consi	nents. KDB 996369 D03, Section 2.9 ideration by host integrators including d simultaneous configurations.			

DocuSigned by:

James Adams

9. Additional testing, Part 15 Subpart B disclaimer. KDB 996369 D03, Section 2.10

08 October 2024 | 14:13 BST

CTO (Hardware)