

LABEL LOCATION

FCC ID: F7SF9K1010V2



1		2		3		4		5		6																																																																																																																																																																																																																			
A									Remark	Description	Editor	Date																																																																																																																																																																																																																	
B	1. 以下由供应商印刷																																																																																																																																																																																																																												
	0 -0.2 20.5 mm 0 -0.2 40.5 mm belkin Wireless N300 Router Model: F9K1010v2 RoHS FCC ID: K7SF9K1010V2 INPUT: 12V 0.5A Ver.2000																																																																																																																																																																																																																												
C	2. 以下在1基础上由 工厂打印																																																																																																																																																																																																																												
	belkin Wireless N300 Router Model: F9K1010v2 RoHS FCC ID: K7SF9K1010V2 INPUT: 12V 0.5A Ver.2000 Network Name (SSID): belkin,XXX Password: XXXXXXXX PIN code: XXXXXXXX Security Type: WPA/WPA2 8830-22350 Rev.A00 Made in China 位数和内容见生产信息发布流程, 字体Arial,Regular,4.7pt XXX与WLAN MAC 后三位一致 由装配软件算号器生成 由装配软件算号器生成 Network Name (SSID): belkin,XXX Password: XXXXXXXX PIN code: XXXXXXXX Security Type: WPA/WPA2 打印字体为: Arial, 大小5.2pt																																																																																																																																																																																																																												
D	来料方式: 卷装																																																																																																																																																																																																																												
	PANTONE 429C																																																																																																																																																																																																																												
NOTES (技术要求):																																																																																																																																																																																																																													
1. 彩色印刷, 无边框, R1.5 (colour printing, no frame,R1.5)																																																																																																																																																																																																																													
2.材料: 50# 亮白PET, 加打印膜(哑膜), 背胶 (Material:50# bright white PET,with matte film,adhesive)																																																																																																																																																																																																																													
3.原材料及后处理工艺均能满足我司《环保技术标准》要求 (Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards.)																																																																																																																																																																																																																													
<table><tr><td colspan="2">DIM</td><td colspan="2">TOL±</td><td colspan="2">△</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">CUSTOMER: BELKIN</td><td colspan="4">T&W 同维 SHENZHEN GONGJIN ELECTRONICS CO., LTD.</td></tr><tr><td colspan="2">RANGE</td><td>C1</td><td>C2</td><td>C3</td><td>C4</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">TITLE: PRINTING Bottom label 1</td><td colspan="2">MODEL: N300</td><td colspan="4">PART NO: 611000004922</td></tr><tr><td colspan="2">0~6</td><td>0.1</td><td>0.1</td><td>0.15</td><td>0.2</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td>UNIT'S</td><td>mm</td><td>VER</td><td>A0</td><td>DRAW</td><td>饶鸿</td><td>DATE: 20150207</td></tr><tr><td colspan="2">6~30</td><td>0.2</td><td>0.3</td><td>0.4</td><td>0.5</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td>MAT'L</td><td>XXXX</td><td>SCALE</td><td>1:1</td><td>CHECK</td><td>李浩铭</td><td></td></tr><tr><td colspan="2">30~80</td><td>0.25</td><td>0.5</td><td>0.9</td><td>1.2</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">80~180</td><td>0.3</td><td>0.8</td><td>1.2</td><td>1.5</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">180~315</td><td>0.5</td><td>1.3</td><td>1.8</td><td>3</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">315~500</td><td>0.7</td><td>1.5</td><td>2.5</td><td>4</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">500~800</td><td>0.9</td><td>1.8</td><td>3</td><td>5</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">ANG.TOL±</td><td colspan="2">0°~30°/0.1°</td><td colspan="2">30°~60°/0.3°</td><td colspan="2">60°~90°/0.5°</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td>FINISH</td><td>N/A</td><td>SHEET</td><td>1 / 1</td><td>PDE</td><td colspan="2">N/A</td></tr></table>												DIM		TOL±		△										CUSTOMER: BELKIN		T&W 同维 SHENZHEN GONGJIN ELECTRONICS CO., LTD.				RANGE		C1	C2	C3	C4									TITLE: PRINTING Bottom label 1		MODEL: N300		PART NO: 611000004922				0~6		0.1	0.1	0.15	0.2									UNIT'S	mm	VER	A0	DRAW	饶鸿	DATE: 20150207	6~30		0.2	0.3	0.4	0.5									MAT'L	XXXX	SCALE	1:1	CHECK	李浩铭		30~80		0.25	0.5	0.9	1.2																80~180		0.3	0.8	1.2	1.5																180~315		0.5	1.3	1.8	3																315~500		0.7	1.5	2.5	4																500~800		0.9	1.8	3	5																ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°								FINISH	N/A	SHEET	1 / 1	PDE	N/A	
DIM		TOL±		△										CUSTOMER: BELKIN		T&W 同维 SHENZHEN GONGJIN ELECTRONICS CO., LTD.																																																																																																																																																																																																													
RANGE		C1	C2	C3	C4									TITLE: PRINTING Bottom label 1		MODEL: N300		PART NO: 611000004922																																																																																																																																																																																																											
0~6		0.1	0.1	0.15	0.2									UNIT'S	mm	VER	A0	DRAW	饶鸿	DATE: 20150207																																																																																																																																																																																																									
6~30		0.2	0.3	0.4	0.5									MAT'L	XXXX	SCALE	1:1	CHECK	李浩铭																																																																																																																																																																																																										
30~80		0.25	0.5	0.9	1.2																																																																																																																																																																																																																								
80~180		0.3	0.8	1.2	1.5																																																																																																																																																																																																																								
180~315		0.5	1.3	1.8	3																																																																																																																																																																																																																								
315~500		0.7	1.5	2.5	4																																																																																																																																																																																																																								
500~800		0.9	1.8	3	5																																																																																																																																																																																																																								
ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°								FINISH	N/A	SHEET	1 / 1	PDE	N/A																																																																																																																																																																																																										
1		2		3		4		5		6																																																																																																																																																																																																																			