

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	8.59	7.23	8.5±1	9.5	8.91	<5	2.76834	3.00	YES
	2.437	9.01	7.96	8.5±1	9.5	8.91	<5	2.78264	3.00	YES
	2.462	8.24	6.67	8.5±1	9.5	8.91	<5	2.79688	3.00	YES
802.11g	2.412	8.51	7.10	8±1	9	7.94	<5	2.46728	3.00	YES
	2.437	8.6	7.24	8±1	9	7.94	<5	2.48003	3.00	YES
	2.462	7.88	6.14	8±1	9	7.94	<5	2.49272	3.00	YES
802.11n H20	2.412	8.92	7.80	8±1	9	7.94	<5	2.46728	3.00	YES
	2.437	8.82	7.62	8±1	9	7.94	<5	2.48003	3.00	YES
	2.462	8.12	6.49	8±1	9	7.94	<5	2.49272	3.00	YES

Conclusion:

For the max result : $2.79688 \leq 3.0$ for 1g SAR, SAR is not required.

Signature:



Date: 2025-03-12

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.