



# TEST REPORT

Applicant Name : Shenzhen Jiteng Network Technology Co., Ltd  
Address : No.1202, Bitian Pavilion, Bizhong Garden, No.10 Bibo First Street,  
Bibo Community, Huangbei Street, Luohu District, Shenzhen City,  
China  
Report Number : SZNS1211111-58026E-00B  
FCC ID: 2AY4C-GM

**Test Standard (s)**  
FCC PART 15.247

## Sample Description

Product: Mini PC  
Trademark: GEEKOM  
Tested Model: GM08i5T  
Multiple Model: GM08i5S, GMXXiXT, GMXXiXS, GMXXiXSS, GMXXiXTS,  
(X substitutes 0, 1, 3, 5, 7, 8)  
Date Received: 2021-11-11  
Date of Test: 2021-11-16 to 2021-11-24  
Report Date: 2021-12-13

|              |       |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

\* In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Fan Yang  
EMC Engineer

**Approved By:**

Candy Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "\*\*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**Shenzhen Accurate Technology Co., Ltd.**

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

|                                                                              |           |
|------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION</b>                                                   | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)                           | 4         |
| OBJECTIVE                                                                    | 4         |
| TEST METHODOLOGY                                                             | 4         |
| MEASUREMENT UNCERTAINTY                                                      | 5         |
| <b>SYSTEM TEST CONFIGURATION</b>                                             | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION                                            | 6         |
| EQUIPMENT MODIFICATIONS                                                      | 6         |
| EUT EXERCISE SOFTWARE                                                        | 6         |
| DUTY CYCLE                                                                   | 6         |
| SUPPORT EQUIPMENT LIST AND DETAILS                                           | 7         |
| EXTERNAL I/O CABLE                                                           | 8         |
| BLOCK DIAGRAM OF TEST SETUP                                                  | 9         |
| <b>SUMMARY OF TEST RESULTS</b>                                               | <b>11</b> |
| <b>TEST EQUIPMENT LIST</b>                                                   | <b>12</b> |
| <b>FCC §1.1310 &amp; §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b>         | <b>13</b> |
| <b>FCC §15.203 - ANTENNA REQUIREMENT</b>                                     | <b>15</b> |
| APPLICABLE STANDARD                                                          | 15        |
| ANTENNA CONNECTOR CONSTRUCTION                                               | 15        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS</b>                         | <b>16</b> |
| APPLICABLE STANDARD                                                          | 16        |
| EUT SETUP                                                                    | 16        |
| EMI TEST RECEIVER SETUP                                                      | 16        |
| TEST PROCEDURE                                                               | 16        |
| TRANSD FACTOR & MARGIN CALCULATION                                           | 17        |
| TEST DATA                                                                    | 17        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS</b>            | <b>26</b> |
| APPLICABLE STANDARD                                                          | 26        |
| EUT SETUP                                                                    | 26        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP                                  | 27        |
| TEST PROCEDURE                                                               | 27        |
| FACTOR & MARGIN CALCULATION                                                  | 27        |
| TEST DATA                                                                    | 27        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH &amp; OCCUPIED BANDWIDTH</b> | <b>36</b> |
| APPLICABLE STANDARD                                                          | 36        |
| TEST PROCEDURE                                                               | 36        |
| TEST DATA                                                                    | 36        |
| <b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER</b>                   | <b>37</b> |
| APPLICABLE STANDARD                                                          | 37        |
| TEST PROCEDURE                                                               | 37        |
| TEST DATA                                                                    | 37        |
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE</b>             | <b>38</b> |
| APPLICABLE STANDARD                                                          | 38        |

|                                                          |           |
|----------------------------------------------------------|-----------|
| TEST PROCEDURE .....                                     | 38        |
| TEST DATA .....                                          | 38        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>     | <b>39</b> |
| APPLICABLE STANDARD .....                                | 39        |
| TEST PROCEDURE .....                                     | 39        |
| TEST DATA .....                                          | 39        |
| <b>APPENDIX Wi-Fi.....</b>                               | <b>40</b> |
| APPENDIX A: 6dB EMISSION BANDWIDTH.....                  | 40        |
| APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....             | 53        |
| APPENDIX C: MAXIMUM CONDUCTED OUTPUT AVERAGE POWER ..... | 66        |
| APPENDIX D: POWER SPECTRAL DENSITY .....                 | 67        |
| APPENDIX E: BAND EDGE MEASUREMENTS.....                  | 80        |
| APPENDIX F: DUTY CYCLE .....                             | 88        |

**GENERAL INFORMATION****Product Description for Equipment under Test (EUT)**

|                                     |                                                                                                             |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Product                             | Mini PC                                                                                                     |
| Tested Model                        | GM08i5T                                                                                                     |
| Multiple Model                      | GM08i5S, GMXXiXT, GMXXiXS, GMXXiXSS, GMXXiXTS,<br>(X substitutes 0, 1, 3, 5, 7, 8)                          |
| Model Difference                    | Please refer to the DoS letter                                                                              |
| Frequency Range                     | Wi-Fi: 2412-2462MHz                                                                                         |
| Maximum Conducted Peak Output Power | Wi-Fi: 19.10dBm(802.11b), 18.91dBm(802.11g), 18.95dBm(802.11n20), 19.01dBm(802.11n40)                       |
| Modulation Technique                | Wi-Fi: DSSS, OFDM                                                                                           |
| Antenna Specification*              | Internal Antenna:<br>Ant 0: 1.89dBi(provided by the applicant)<br>Ant 1: 2.68dBi(provided by the applicant) |
| Voltage Range                       | DC 19V from Adapter                                                                                         |
| Sample number                       | SZNS1211111-58026E-RF-S1 (Assigned by ATC)                                                                  |
| Sample/EUT Status                   | Good condition                                                                                              |
| Adapter 1 information               | Model: HKA09019047-6U<br>Input: AC 100-240V, 50/60Hz, 1.5A<br>Output: DC 19V, 4.74A                         |
| Adapter 2 information               | Model: HKA06519034-6J<br>Input: AC 100-240V, 50/60Hz, 1.5A<br>Output: DC 19V, 3.42A                         |
| Adapter 3 information               | Model: ADS-110CL-19-3 190090E<br>Input: AC 100-240V, 50/60Hz, 1.5A<br>Output: DC 19V, 4.74A                 |
| Adapter 4 information               | Model: ADS-65HI-19A-3 19065E<br>Input: AC 100-240V, 50/60Hz, 1.5A<br>Output: DC 19V, 3.42A                  |

**Objective**

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

**Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Parameter                          |                 | Uncertainty |
|------------------------------------|-----------------|-------------|
| Occupied Channel Bandwidth         |                 | 5%          |
| RF output power, conducted         |                 | 0.73dB      |
| Unwanted Emission, conducted       |                 | 1.6dB       |
| AC Power Lines Conducted Emissions |                 | 2.72dB      |
| Emissions,<br>Radiated             | 30MHz - 1GHz    | 4.28dB      |
|                                    | 1GHz - 18GHz    | 4.98dB      |
|                                    | 18GHz - 26.5GHz | 5.06dB      |
| Temperature                        |                 | 1°C         |
| Humidity                           |                 | 6%          |
| Supply voltages                    |                 | 0.4%        |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $K$  with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

**Test Facility**

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 mode, total 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 7       | 2442            |
| 2       | 2417            | 8       | 2447            |
| 3       | 2422            | 9       | 2452            |
| 4       | 2427            | 10      | 2457            |
| 5       | 2432            | 11      | 2462            |
| 6       | 2437            | /       | /               |

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT40 mode was tested with Channel 3, 6 and 9.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

“DRTU”\* software was used to test and power level as below:

Ant 0:

| Mode         | Data rate | Power Level* |                |              |
|--------------|-----------|--------------|----------------|--------------|
|              |           | Low Channel  | Middle Channel | High Channel |
| 802.11b      | 1 Mbps    | 11           | 11             | 11           |
| 802.11g      | 6 Mbps    | 11           | 11             | 11           |
| 802.11n-HT20 | MCS0      | 11           | 11             | 11           |
| 802.11n-HT40 | MCS0      | 11           | 11             | 11           |

Ant 1:

| Mode         | Data rate | Power Level* |                |              |
|--------------|-----------|--------------|----------------|--------------|
|              |           | Low Channel  | Middle Channel | High Channel |
| 802.11b      | 1 Mbps    | 11           | 11             | 11           |
| 802.11g      | 6 Mbps    | 11           | 11             | 11           |
| 802.11n-HT20 | MCS0      | 11           | 11             | 11           |
| 802.11n-HT40 | MCS0      | 11           | 11             | 11           |

The worst-case data rates are determined to be as above for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths and modulations. The device supports SISO and MIMO 2T2R in all modes. Per pretest, 2TX mode was the worst mode and recorded in this report.

### Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

**Support Equipment List and Details**

| Manufacturer | Description    | Model         | Serial Number      |
|--------------|----------------|---------------|--------------------|
| DELL         | Keyboard       | KB216d1       | Unknown            |
| DELL         | Mouse          | MS116c        | Unknown            |
| PHILIPS      | Monitor        | 275M7C        | UK02141059255272   |
| XIAOMI       | TV             | L43M5-ES      | 25131/114100057334 |
| DELL         | laptop         | LatitudeE5570 | 6DCCRC2            |
| Kingston     | U-DISK         | DTSE9 16GB    | Unknown            |
| SanDisk      | SD Card        | Ultra 32GB    | Unknown            |
| HUAWEI       | Mobile Phone 1 | HUAWEI Mate30 | FEC0220506013544   |
| XIAOMI       | Mobile Phone 2 | MI 10         | 957921bb           |
| HUAWEI       | Earphone       | Unknown       | Unknown            |


**External I/O Cable**

| Cable Description                     | Length (m) | From Port | To            |
|---------------------------------------|------------|-----------|---------------|
| Unshielded Detachable AC output Cable | 1.0        | Adapter   | LISN          |
| Unshielded Detachable DC power Cable  | 1.5        | EUT       | Adapter 1     |
| Unshielded Detachable DC power Cable  | 1.2        | EUT       | Adapter 2     |
| Unshielded Detachable DC power Cable  | 1.2        | EUT       | Adapter 3     |
| Unshielded Detachable DC power Cable  | 1.5        | EUT       | Adapter 4     |
| Unshielded Detachable HDMI Cable      | 1.05       | EUT       | TV            |
| Unshielded Detachable DP Cable        | 0.95       | EUT       | Monitor       |
| Unshielded Detachable USB Cable       | 1.5        | EUT       | Mouse         |
| Unshielded Detachable USB Cable       | 1.5        | EUT       | Keyboard      |
| Unshielded Detachable RJ45 Cable      | 3          | EUT       | Notebook      |
| Unshielded Detachable earphone Cable  | 0.75       | EUT       | Earphone      |
| Unshielded Detachable USB Cable       | 1.15       | EUT       | Mobile phone1 |
| Unshielded Detachable USB Cable       | 0.95       | EUT       | Mobile phone2 |


## Block Diagram of Test Setup

For conducted emission:


AC Mains:



For Radiated emission:  
Below 1GHz:



Above 1GHz:



**SUMMARY OF TEST RESULTS**

| FCC Rules                      | Description of Test                          | Result    |
|--------------------------------|----------------------------------------------|-----------|
| §15.247 (I), §1.1310 & §2.1091 | Maximum Permissible Exposure (MPE)           | Compliant |
| §15.203                        | Antenna Requirement                          | Compliant |
| §15.207 (a)                    | AC Line Conducted Emissions                  | Compliant |
| §15.205, §15.209, §15.247(d)   | Spurious Emissions                           | Compliant |
| §15.247 (a)(2)                 | 6 dB Emission Bandwidth & Occupied Bandwidth | Compliant |
| §15.247(b)(3)                  | Maximum Conducted Output Power               | Compliant |
| §15.247(d)                     | 100 kHz Bandwidth of Frequency Band Edge     | Compliant |
| §15.247(e)                     | Power Spectral Density                       | Compliant |

Note: Per pre-test with models of GM08i5T and GM08i5S, and the worst case about maximum emission is model of GM08i5T, which was recorded in this report.

**TEST EQUIPMENT LIST**

| Manufacturer                                    | Description                     | Model                | Serial Number      | Calibration Date | Calibration Due Date |
|-------------------------------------------------|---------------------------------|----------------------|--------------------|------------------|----------------------|
| Conducted Emissions Test                        |                                 |                      |                    |                  |                      |
| Rohde& Schwarz                                  | EMI Test Receiver               | ESCI                 | 100784             | 2021/02/03       | 2022/02/02           |
| R & S                                           | L.I.S.N.                        | ENV216               | 101314             | 2020/12/25       | 2021/12/24           |
| Anritsu Corp                                    | 50Ω Coaxial Switch              | MP59B                | 6200506474         | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable                | N-2m                 | No.2               | 2020/12/25       | 2021/12/24           |
| Conducted Emission Test Software: e3 19821b(V9) |                                 |                      |                    |                  |                      |
| Radiated Emissions Test                         |                                 |                      |                    |                  |                      |
| Rohde& Schwarz                                  | Test Receiver                   | ESR                  | 102725             | 2020/12/25       | 2021/12/24           |
| Rohde&Schwarz                                   | Spectrum Analyzer               | FSV40                | 101949             | 2021/5/18        | 2022/5/17            |
| A.H. Systems, inc.                              | Preamplifier                    | PAM-0118P            | 531                | 2021/11/9        | 2022/11/8            |
| Quinstar                                        | Amplifier                       | QLW-184055<br>36-J0  | 15964001002        | 2020/11/28       | 2021/11/27           |
| SONOMA<br>INSTRUMENT                            | Amplifier                       | 310 N                | 186131             | 2020/12/25       | 2021/12/24           |
| Anritsu Corp                                    | 50 Coaxial Switch               | MP59B                | 6100237248         | 2020/12/25       | 2021/12/24           |
| Schwarzbeck                                     | Bilog Antenna                   | VULB9163             | 9163-323           | 2020/01/05       | 2023/01/04           |
| Schwarzbeck                                     | Horn Antenna                    | BBHA9120D            | 9120D-1067         | 2020/01/05       | 2023/01/04           |
| Schwarzbeck                                     | HORN ANTENNA                    | BBHA9170             | 9170-359           | 2020/01/05       | 2023/01/04           |
| Unknown                                         | RF Coaxial Cable                | N-5m                 | No.3               | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable                | N-1m                 | No.5               | 2020/12/25       | 2021/12/24           |
| Unknown                                         | RF Coaxial Cable                | N-10m                | No.7               | 2021/11/09       | 2022/11/08           |
| Unknown                                         | RF Coaxial Cable                | N-2m                 | No.8               | 2021/11/09       | 2022/11/08           |
| Wainwright                                      | High Pass Filter                | WHKX3.6/18<br>G-10SS | 5                  | 2020/12/25       | 2021/12/24           |
| Radiated Emission Test Software: e3 19821b(V9)  |                                 |                      |                    |                  |                      |
| RF Conducted Test                               |                                 |                      |                    |                  |                      |
| Rohde&Schwarz                                   | Spectrum Analyzer               | FSV40                | 101949             | 2021/5/18        | 2022/5/17            |
| Rohde & Schwarz                                 | Open Switch and<br>Control Unit | OSP120 +OSP<br>-B157 | 101244 +<br>100866 | 2020/12/24       | 2021/12/23           |

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3-1.34                                                | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30                                                 | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500                                                | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000                                            | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

For worst case:

| Mode            | Frequency Range (MHz) | Antenna Gain |           | Tune-up Output Power |       | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|-----------------|-----------------------|--------------|-----------|----------------------|-------|--------------------------|-------------------------------------|---------------------------------|
|                 |                       | (dBi)        | (numeric) | (dBm)                | (mW)  |                          |                                     |                                 |
| BT              | 2402-2480             | 1.89         | 1.55      | 7.00                 | 5.01  | 20                       | 0.0015                              | 1.0                             |
| 2.4G Wi-Fi      | 2412-2462             | 2.68         | 1.85      | 19.50                | 89.13 | 20                       | 0.0329                              | 1.0                             |
| 5G Wi-Fi Band 1 | 5150-5250             | 3.47         | 2.22      | 17.00                | 50.12 | 20                       | 0.0222                              | 1.0                             |
| 5G Wi-Fi Band 4 | 5725-5850             | 4.31         | 2.70      | 17.00                | 50.12 | 20                       | 0.0269                              | 1.0                             |

Note: 1. The BT function can transmit at the same time with the Wi-Fi function.

2. The 2.4G Wi-Fi function can transmit at the same time with the 5G Wi-Fi function.

Simultaneous transmitting consideration:

The ratio=  $MPE_{BT}/limit + MPE_{2.4G\ Wi-Fi}/limit + MPE_{5G\ Wi-Fi}/limit = 0.0015/1 + 0.0329/1 + 0.0269/1 = 0.0613 < 1.0$

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

---

**FCC §15.203 - ANTENNA REQUIREMENT**

---

**Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

**Antenna Connector Construction**

The EUT has two internal antennas used arrangement for Wi-Fi, which was permanently attached and the antenna gain is 1.89dBi (Ant0) and 2.68dBi (Ant1), fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

---

**Transd Factor & Margin Calculation**

---

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25 °C     |
| <b>Relative Humidity:</b> | 64 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Bin Duan on 2021-11-23.*


*EUT operation mode: 2.4G Wi-Fi Transmitting (Worst case as below)*

**Adapter 1:**  
**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI Transmitting


|    | Freq   | Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|--------|--------|------------|-------|------------|------------|---------|
|    | MHz    | dB     | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.163  | 9.87   | 36.46      | 46.33 | 55.28      | -8.95      | Average |
| 2  | 0.163  | 9.87   | 41.70      | 51.57 | 65.28      | -13.71     | QP      |
| 3  | 0.210  | 9.80   | 28.09      | 37.89 | 53.22      | -15.33     | Average |
| 4  | 0.210  | 9.80   | 34.16      | 43.96 | 63.22      | -19.26     | QP      |
| 5  | 0.442  | 9.80   | 10.78      | 20.58 | 47.02      | -26.44     | Average |
| 6  | 0.442  | 9.80   | 19.87      | 29.67 | 57.02      | -27.35     | QP      |
| 7  | 0.915  | 9.81   | 10.13      | 19.94 | 46.00      | -26.06     | Average |
| 8  | 0.915  | 9.81   | 13.64      | 23.45 | 56.00      | -32.55     | QP      |
| 9  | 2.898  | 9.93   | 10.70      | 20.63 | 46.00      | -25.37     | Average |
| 10 | 2.898  | 9.93   | 12.96      | 22.89 | 56.00      | -33.11     | QP      |
| 11 | 29.216 | 10.48  | 10.47      | 20.95 | 50.00      | -29.05     | Average |
| 12 | 29.216 | 10.48  | 14.91      | 25.39 | 60.00      | -34.61     | QP      |

**AC 120V/60 Hz, Neutral**

Site : Shielding Room  
Condition: Neutral  
Mode : 2.4G WIFI Transmitting


|    | Freq   | Factor | Read<br>Level | Level | Limit<br>Line | Over<br>Limit | Remark  |
|----|--------|--------|---------------|-------|---------------|---------------|---------|
|    | MHz    | dB     | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | 0.169  | 9.94   | 36.40         | 46.34 | 55.00         | -8.66         | Average |
| 2  | 0.169  | 9.94   | 40.94         | 50.88 | 65.00         | -14.12        | QP      |
| 3  | 0.230  | 9.98   | 25.46         | 35.44 | 52.45         | -17.01        | Average |
| 4  | 0.230  | 9.98   | 33.52         | 43.50 | 62.45         | -18.95        | QP      |
| 5  | 0.469  | 9.91   | 11.55         | 21.46 | 46.53         | -25.07        | Average |
| 6  | 0.469  | 9.91   | 16.76         | 26.67 | 56.53         | -29.86        | QP      |
| 7  | 0.520  | 9.91   | 12.48         | 22.39 | 46.00         | -23.61        | Average |
| 8  | 0.520  | 9.91   | 16.73         | 26.64 | 56.00         | -29.36        | QP      |
| 9  | 2.892  | 9.98   | 7.59          | 17.57 | 46.00         | -28.43        | Average |
| 10 | 2.892  | 9.98   | 9.88          | 19.86 | 56.00         | -36.14        | QP      |
| 11 | 29.081 | 10.38  | 8.37          | 18.75 | 50.00         | -31.25        | Average |
| 12 | 29.081 | 10.38  | 13.57         | 23.95 | 60.00         | -36.05        | QP      |

**Adapter 2:**  
**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI Transmitting


|    | Freq  | Factor | Read Level | Level | Limit | Over Limit | Remark  |
|----|-------|--------|------------|-------|-------|------------|---------|
|    | MHz   | dB     | dBuV       | dBuV  | dBuV  | dB         |         |
| 1  | 0.161 | 9.88   | 28.78      | 38.66 | 55.43 | -16.77     | Average |
| 2  | 0.161 | 9.88   | 37.12      | 47.00 | 65.43 | -18.43     | QP      |
| 3  | 0.203 | 9.80   | 21.13      | 30.93 | 53.48 | -22.55     | Average |
| 4  | 0.203 | 9.80   | 32.27      | 42.07 | 63.48 | -21.41     | QP      |
| 5  | 0.350 | 9.80   | 28.16      | 37.96 | 48.95 | -10.99     | Average |
| 6  | 0.350 | 9.80   | 31.85      | 41.65 | 58.95 | -17.30     | QP      |
| 7  | 0.701 | 9.81   | 20.98      | 30.79 | 46.00 | -15.21     | Average |
| 8  | 0.701 | 9.81   | 27.88      | 37.69 | 56.00 | -18.31     | QP      |
| 9  | 2.512 | 9.93   | 24.40      | 34.33 | 46.00 | -11.67     | Average |
| 10 | 2.512 | 9.93   | 29.28      | 39.21 | 56.00 | -16.79     | QP      |
| 11 | 7.718 | 10.08  | 20.94      | 31.02 | 50.00 | -18.98     | Average |
| 12 | 7.718 | 10.08  | 24.80      | 34.88 | 60.00 | -25.12     | QP      |

**AC 120V/60 Hz, Neutral**

Site : Shielding Room  
 Condition: Neutral  
 Mode : 2.4G WIFI Transmitting


|    | Freq   | Factor | Read Level | Level | Limit Line | Over Limit | Remark  |
|----|--------|--------|------------|-------|------------|------------|---------|
|    | MHz    | dB     | dBuV       | dBuV  | dBuV       | dB         |         |
| 1  | 0.180  | 9.96   | 34.24      | 44.20 | 54.48      | -10.28     | Average |
| 2  | 0.180  | 9.96   | 38.49      | 48.45 | 64.48      | -16.03     | QP      |
| 3  | 0.211  | 9.99   | 23.43      | 33.42 | 53.15      | -19.73     | Average |
| 4  | 0.211  | 9.99   | 31.14      | 41.13 | 63.15      | -22.02     | QP      |
| 5  | 0.361  | 9.94   | 27.37      | 37.31 | 48.71      | -11.40     | Average |
| 6  | 0.361  | 9.94   | 30.56      | 40.50 | 58.71      | -18.21     | QP      |
| 7  | 0.507  | 9.90   | 23.50      | 33.40 | 46.00      | -12.60     | Average |
| 8  | 0.507  | 9.90   | 29.00      | 38.90 | 56.00      | -17.10     | QP      |
| 9  | 2.736  | 9.98   | 24.13      | 34.11 | 46.00      | -11.89     | Average |
| 10 | 2.736  | 9.98   | 29.05      | 39.03 | 56.00      | -16.97     | QP      |
| 11 | 10.152 | 10.10  | 21.57      | 31.67 | 50.00      | -18.33     | Average |
| 12 | 10.152 | 10.10  | 25.46      | 35.56 | 60.00      | -24.44     | QP      |

**Adapter 3:**  
**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI Transmitting


|    | Freq   | Factor | Read<br>Level | Level | Limit<br>Line | Over<br>Limit | Remark  |
|----|--------|--------|---------------|-------|---------------|---------------|---------|
|    | MHz    | dB     | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | 0.162  | 9.87   | 23.78         | 33.65 | 55.35         | -21.70        | Average |
| 2  | 0.162  | 9.87   | 35.75         | 45.62 | 65.35         | -19.73        | QP      |
| 3  | 0.263  | 9.80   | 22.36         | 32.16 | 51.33         | -19.17        | Average |
| 4  | 0.263  | 9.80   | 28.32         | 38.12 | 61.33         | -23.21        | QP      |
| 5  | 0.403  | 9.80   | 23.41         | 33.21 | 47.80         | -14.59        | Average |
| 6  | 0.403  | 9.80   | 25.95         | 35.75 | 57.80         | -22.05        | QP      |
| 7  | 0.568  | 9.81   | 19.47         | 29.28 | 46.00         | -16.72        | Average |
| 8  | 0.568  | 9.81   | 21.02         | 30.83 | 56.00         | -25.17        | QP      |
| 9  | 2.081  | 9.92   | 11.02         | 20.94 | 46.00         | -25.06        | Average |
| 10 | 2.081  | 9.92   | 14.63         | 24.55 | 56.00         | -31.45        | QP      |
| 11 | 27.362 | 10.42  | 18.19         | 28.61 | 50.00         | -21.39        | Average |
| 12 | 27.362 | 10.42  | 21.89         | 32.31 | 60.00         | -27.69        | QP      |

**AC 120V/60 Hz, Neutral**

Site : Shielding Room  
Condition: Neutral  
Mode : 2.4G WIFI Transmitting


|    | Freq   | Factor | Read<br>Level | Level | Limit<br>Line | Over<br>Limit | Remark  |
|----|--------|--------|---------------|-------|---------------|---------------|---------|
|    | MHz    | dB     | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | 0.162  | 9.93   | 28.21         | 38.14 | 55.37         | -17.23        | Average |
| 2  | 0.162  | 9.93   | 36.67         | 46.60 | 65.37         | -18.77        | QP      |
| 3  | 0.265  | 9.97   | 23.94         | 33.91 | 51.29         | -17.38        | Average |
| 4  | 0.265  | 9.97   | 28.56         | 38.53 | 61.29         | -22.76        | QP      |
| 5  | 0.441  | 9.91   | 15.93         | 25.84 | 47.05         | -21.21        | Average |
| 6  | 0.441  | 9.91   | 20.37         | 30.28 | 57.05         | -26.77        | QP      |
| 7  | 0.506  | 9.90   | 12.62         | 22.52 | 46.00         | -23.48        | Average |
| 8  | 0.506  | 9.90   | 19.58         | 29.48 | 56.00         | -26.52        | QP      |
| 9  | 4.734  | 10.05  | 5.32          | 15.37 | 46.00         | -30.63        | Average |
| 10 | 4.734  | 10.05  | 10.62         | 20.67 | 56.00         | -35.33        | QP      |
| 11 | 29.293 | 10.38  | 18.54         | 28.92 | 50.00         | -21.08        | Average |
| 12 | 29.293 | 10.38  | 22.84         | 33.22 | 60.00         | -26.78        | QP      |

**Adapter 4:**  
**AC 120V/60 Hz, Line**



Site : Shielding Room  
 Condition: Line  
 Mode : 2.4G WIFI Transmitting

|    | Freq   | Factor | Read<br>Level | Level | Limit<br>Line | Over<br>Limit | Remark  |
|----|--------|--------|---------------|-------|---------------|---------------|---------|
|    | MHz    | dB     | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | 0.155  | 9.89   | 26.37         | 36.26 | 55.73         | -19.47        | Average |
| 2  | 0.155  | 9.89   | 36.33         | 46.22 | 65.73         | -19.51        | QP      |
| 3  | 0.274  | 9.80   | 21.33         | 31.13 | 50.99         | -19.86        | Average |
| 4  | 0.274  | 9.80   | 28.47         | 38.27 | 60.99         | -22.72        | QP      |
| 5  | 0.405  | 9.80   | 23.97         | 33.77 | 47.74         | -13.97        | Average |
| 6  | 0.405  | 9.80   | 26.59         | 36.39 | 57.74         | -21.35        | QP      |
| 7  | 0.557  | 9.81   | 21.01         | 30.82 | 46.00         | -15.18        | Average |
| 8  | 0.557  | 9.81   | 22.70         | 32.51 | 56.00         | -23.49        | QP      |
| 9  | 4.338  | 9.95   | 6.13          | 16.08 | 46.00         | -29.92        | Average |
| 10 | 4.338  | 9.95   | 11.28         | 21.23 | 56.00         | -34.77        | QP      |
| 11 | 29.488 | 10.48  | 17.90         | 28.38 | 50.00         | -21.62        | Average |
| 12 | 29.488 | 10.48  | 21.75         | 32.23 | 60.00         | -27.77        | QP      |

**AC 120V/60 Hz, Neutral**

Site : Shielding Room  
 Condition: Neutral  
 Mode : 2.4G WIFI Transmitting

|    | Freq   | Factor | Read<br>Level | Level | Limit<br>Line | Over<br>Limit | Remark  |
|----|--------|--------|---------------|-------|---------------|---------------|---------|
|    | MHz    | dB     | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | 0.163  | 9.93   | 27.16         | 37.09 | 55.28         | -18.19        | Average |
| 2  | 0.163  | 9.93   | 35.86         | 45.79 | 65.28         | -19.49        | QP      |
| 3  | 0.273  | 9.97   | 25.14         | 35.11 | 51.02         | -15.91        | Average |
| 4  | 0.273  | 9.97   | 28.47         | 38.44 | 61.02         | -22.58        | QP      |
| 5  | 0.416  | 9.92   | 28.88         | 38.80 | 47.53         | -8.73         | Average |
| 6  | 0.416  | 9.92   | 30.49         | 40.41 | 57.53         | -17.12        | QP      |
| 7  | 0.651  | 9.91   | 24.27         | 34.18 | 46.00         | -11.82        | Average |
| 8  | 0.651  | 9.91   | 26.21         | 36.12 | 56.00         | -19.88        | QP      |
| 9  | 3.196  | 10.00  | 8.60          | 18.60 | 46.00         | -27.40        | Average |
| 10 | 3.196  | 10.00  | 12.45         | 22.45 | 56.00         | -33.55        | QP      |
| 11 | 27.966 | 10.36  | 19.41         | 29.77 | 50.00         | -20.23        | Average |
| 12 | 27.966 | 10.36  | 23.49         | 33.85 | 60.00         | -26.15        | QP      |


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W               | IF B/W  | Measurement |
|-------------------|---------|-------------------------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz                 | 120 kHz | QP          |
| Above 1 GHz       | 1MHz    | 3 MHz                   | /       | PK          |
|                   | 1MHz    | 10 Hz <sup>Note 1</sup> | /       | Average     |
|                   | 1MHz    | > 1/T <sup>Note 2</sup> | /       | Average     |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## Test Data


### Environmental Conditions

|                    |                 |
|--------------------|-----------------|
| Temperature:       | 25 °C           |
| Relative Humidity: | 50-64 %         |
| ATM Pressure:      | 101.0-103.0 kPa |

The testing was performed by Chao Mo on 2021-11-16 for below 1GHz and 2021-11-20 for above 1GHz.


EUT operation mode: Transmitting

(Scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes, the worst case as below)

**30MHz-1GHz: (Worst case for 802.11 N20, middle channel)****Adapter 1:****Horizontal:**


Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 31.06  | -20.32 | 39.47      | 19.15  | 40.00      | -20.85     | QP     |
| 2 | 94.51  | -20.30 | 42.41      | 22.11  | 43.50      | -21.39     | QP     |
| 3 | 146.63 | -21.71 | 53.59      | 31.88  | 43.50      | -11.62     | QP     |
| 4 | 393.30 | -15.78 | 44.93      | 29.15  | 46.00      | -16.85     | QP     |
| 5 | 445.05 | -14.30 | 44.50      | 30.20  | 46.00      | -15.80     | QP     |
| 6 | 950.43 | -8.05  | 37.20      | 29.15  | 46.00      | -16.85     | QP     |

**Vertical**


Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 33.23  | -19.04 | 49.85      | 30.81  | 40.00      | -9.99      | QP     |
| 2 | 90.74  | -21.10 | 45.92      | 24.82  | 43.50      | -18.68     | QP     |
| 3 | 157.08 | -21.72 | 46.60      | 24.88  | 43.50      | -18.62     | QP     |
| 4 | 327.03 | -16.73 | 52.80      | 36.07  | 46.00      | -9.93      | QP     |
| 5 | 445.05 | -14.30 | 45.82      | 31.52  | 46.00      | -14.48     | QP     |
| 6 | 854.40 | -9.46  | 40.35      | 30.89  | 46.00      | -15.11     | QP     |

**Adapter 2:****Horizontal:**


Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 30.77  | -20.38 | 35.95         | 15.57  | 40.00         | -24.43        | QP     |
| 2 | 67.97  | -20.94 | 47.63         | 26.69  | 40.00         | -13.31        | QP     |
| 3 | 151.33 | -21.61 | 53.85         | 32.24  | 43.50         | -11.26        | QP     |
| 4 | 309.32 | -16.66 | 50.95         | 34.29  | 46.00         | -11.71        | QP     |
| 5 | 445.05 | -14.30 | 43.90         | 29.60  | 46.00         | -16.40        | QP     |
| 6 | 890.34 | -8.52  | 39.80         | 31.28  | 46.00         | -14.72        | QP     |

**Vertical**


Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 30.92  | -20.35 | 49.77         | 29.42  | 40.00         | -10.58        | QP     |
| 2 | 87.34  | -21.78 | 48.91         | 27.13  | 40.00         | -12.87        | QP     |
| 3 | 141.33 | -21.90 | 53.25         | 31.35  | 43.50         | -12.15        | QP     |
| 4 | 325.74 | -16.74 | 49.69         | 32.95  | 46.00         | -13.05        | QP     |
| 5 | 435.59 | -14.34 | 44.92         | 30.58  | 46.00         | -15.42        | QP     |
| 6 | 890.34 | -8.52  | 40.69         | 32.17  | 46.00         | -13.83        | QP     |

**Adapter 3:****Horizontal:**

Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 45.28  | -9.95  | 26.97         | 17.02  | 40.00         | -22.98        | QP     |
| 2 | 95.97  | -12.31 | 36.18         | 23.87  | 43.50         | -19.63        | QP     |
| 3 | 212.83 | -11.75 | 43.76         | 32.01  | 43.50         | -11.49        | QP     |
| 4 | 285.48 | -9.43  | 45.48         | 36.05  | 46.00         | -9.95         | QP     |
| 5 | 589.42 | -2.77  | 41.37         | 38.60  | 46.00         | -7.40         | QP     |
| 6 | 840.65 | 0.28   | 38.47         | 38.75  | 46.00         | -7.25         | QP     |


**Vertical**

Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 32.65  | -12.07 | 46.00         | 34.53  | 40.00         | -5.47         | QP     |
| 2 | 57.90  | -9.92  | 39.07         | 29.95  | 40.00         | -10.05        | QP     |
| 3 | 117.67 | -13.09 | 42.06         | 28.97  | 43.50         | -14.53        | QP     |
| 4 | 326.02 | -8.21  | 40.71         | 32.50  | 46.00         | -13.50        | QP     |
| 5 | 539.00 | -4.01  | 39.93         | 35.92  | 46.00         | -10.08        | QP     |
| 6 | 852.90 | 0.34   | 35.23         | 35.57  | 46.00         | -10.43        | QP     |

Adapter 4:


Horizontal:



Site : chamber  
Condition: 3m HORIZONTAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 47.81  | -10.00 | 30.76      | 20.76  | 40.00      | -19.24     | QP     |
| 2 | 95.43  | -12.40 | 35.38      | 22.98  | 43.50      | -20.52     | QP     |
| 3 | 148.31 | -15.36 | 40.12      | 24.76  | 43.50      | -18.74     | QP     |
| 4 | 266.84 | -10.37 | 45.35      | 34.98  | 46.00      | -11.02     | QP     |
| 5 | 699.00 | -1.61  | 36.66      | 35.05  | 46.00      | -10.95     | QP     |
| 6 | 831.86 | 0.09   | 39.97      | 40.06  | 46.00      | -5.94      | QP     |

Vertical



Site : chamber  
Condition: 3m VERTICAL  
Job No. : SZNS1211111-58026E-RF  
Test Mode: 2.4G WIFI Transmitting

|   | Freq   | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|--------|--------|------------|--------|------------|------------|--------|
|   | MHz    | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 40.84  | -10.20 | 41.03      | 30.83  | 40.00      | -9.17      | QP     |
| 2 | 56.54  | -10.11 | 43.60      | 33.49  | 40.00      | -6.51      | QP     |
| 3 | 133.09 | -14.98 | 40.36      | 25.38  | 43.50      | -18.12     | QP     |
| 4 | 332.08 | -7.83  | 39.64      | 31.81  | 46.00      | -14.19     | QP     |
| 5 | 593.57 | -2.71  | 39.61      | 36.90  | 46.00      | -9.10      | QP     |
| 6 | 890.34 | 0.94   | 37.02      | 37.96  | 46.00      | -8.04      | QP     |

**2TX Mode (Worst case)****1-25 GHz:**

| Frequency<br>(MHz)        | Receiver          |           | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|-----------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| 802.11B, Low Channel      |                   |           |                     |               |                |                               |                                    |                   |                |
| 2310                      | 52.55             | PK        | 341                 | 1.4           | H              | -7.23                         | 45.32                              | 74                | -28.68         |
| 2310                      | 53.12             | PK        | 285                 | 1.8           | V              | -7.23                         | 45.89                              | 74                | -28.11         |
| 2390                      | 53.06             | PK        | 153                 | 1.3           | H              | -7.21                         | 45.85                              | 74                | -28.15         |
| 2390                      | 57.97             | PK        | 89                  | 1.3           | V              | -7.21                         | 50.76                              | 74                | -23.24         |
| 4824                      | 46.18             | PK        | 217                 | 1.2           | H              | -3.53                         | 42.65                              | 74                | -31.35         |
| 4824                      | 47.51             | PK        | 299                 | 1.4           | V              | -3.53                         | 43.98                              | 74                | -30.02         |
| 802.11B, Middle Channel   |                   |           |                     |               |                |                               |                                    |                   |                |
| 4874                      | 44.91             | PK        | 261                 | 1.6           | H              | -3.42                         | 41.49                              | 74                | -32.51         |
| 4874                      | 46.63             | PK        | 295                 | 2.2           | V              | -3.42                         | 43.21                              | 74                | -30.79         |
| 11B, High Channel         |                   |           |                     |               |                |                               |                                    |                   |                |
| 2483.5                    | 52.44             | PK        | 350                 | 2             | H              | -7.2                          | 45.24                              | 74                | -28.76         |
| 2483.5                    | 50.44             | PK        | 80                  | 2.4           | V              | -7.2                          | 43.24                              | 74                | -30.76         |
| 2500                      | 53.38             | PK        | 49                  | 1.4           | H              | -7.18                         | 46.2                               | 74                | -27.8          |
| 2500                      | 55.45             | PK        | 3                   | 1.1           | V              | -7.18                         | 48.27                              | 74                | -25.73         |
| 4924                      | 45.38             | PK        | 122                 | 1.9           | H              | -3.16                         | 42.22                              | 74                | -31.78         |
| 4924                      | 45.94             | PK        | 138                 | 1.7           | V              | -3.16                         | 42.78                              | 74                | -31.22         |
| 802.11G, Low Channel      |                   |           |                     |               |                |                               |                                    |                   |                |
| 2310                      | 51.53             | PK        | 270                 | 2.2           | H              | -7.23                         | 44.3                               | 74                | -29.7          |
| 2310                      | 53.81             | PK        | 241                 | 1.2           | V              | -7.23                         | 46.58                              | 74                | -27.42         |
| 2390                      | 52.25             | PK        | 165                 | 2             | H              | -7.21                         | 45.04                              | 74                | -28.96         |
| 2390                      | 54.81             | PK        | 295                 | 2.1           | V              | -7.21                         | 47.6                               | 74                | -26.4          |
| 4824                      | 47                | PK        | 75                  | 1.2           | H              | -3.53                         | 43.47                              | 74                | -30.53         |
| 4824                      | 45.67             | PK        | 186                 | 1             | V              | -3.53                         | 42.14                              | 74                | -31.86         |
| 802.11G, Middle Channel   |                   |           |                     |               |                |                               |                                    |                   |                |
| 4874                      | 46.7              | PK        | 131                 | 1.1           | H              | -3.42                         | 43.28                              | 74                | -30.72         |
| 4874                      | 47.58             | PK        | 337                 | 1.4           | V              | -3.42                         | 44.16                              | 74                | -29.84         |
| 802.11G, High Channel     |                   |           |                     |               |                |                               |                                    |                   |                |
| 2483.5                    | 51.75             | PK        | 145                 | 1.9           | H              | -7.2                          | 44.55                              | 74                | -29.45         |
| 2483.5                    | 50.28             | PK        | 263                 | 2.3           | V              | -7.2                          | 43.08                              | 74                | -30.92         |
| 2500                      | 48.6              | PK        | 259                 | 2             | H              | -7.18                         | 41.42                              | 74                | -32.58         |
| 2500                      | 45.92             | PK        | 6                   | 1.5           | V              | -7.18                         | 38.74                              | 74                | -35.26         |
| 4924                      | 45.33             | PK        | 141                 | 1.1           | H              | -3.16                         | 42.17                              | 74                | -31.83         |
| 4924                      | 47.05             | PK        | 336                 | 1.5           | V              | -3.16                         | 43.89                              | 74                | -30.11         |
| 802.11N20, Low Channel    |                   |           |                     |               |                |                               |                                    |                   |                |
| 2310                      | 53.59             | PK        | 244                 | 1.9           | H              | -7.23                         | 46.36                              | 74                | -27.64         |
| 2310                      | 55.1              | PK        | 133                 | 1             | V              | -7.23                         | 47.87                              | 74                | -26.13         |
| 2390                      | 52.89             | PK        | 40                  | 1.2           | H              | -7.21                         | 45.68                              | 74                | -28.32         |
| 2390                      | 55.82             | PK        | 323                 | 1             | V              | -7.21                         | 48.61                              | 74                | -25.39         |
| 4824                      | 45.01             | PK        | 176                 | 1.5           | H              | -3.53                         | 41.48                              | 74                | -32.52         |
| 4824                      | 44.92             | PK        | 322                 | 1.8           | V              | -3.53                         | 41.39                              | 74                | -32.61         |
| 802.11N20, Middle Channel |                   |           |                     |               |                |                               |                                    |                   |                |
| 4874                      | 49.05             | PK        | 65                  | 1.6           | H              | -3.42                         | 45.63                              | 74                | -28.37         |
| 4874                      | 48.7              | PK        | 134                 | 1.5           | V              | -3.42                         | 45.28                              | 74                | -28.72         |
| 802.11N20, High Channel   |                   |           |                     |               |                |                               |                                    |                   |                |
| 2483.5                    | 55.79             | PK        | 264                 | 1.1           | H              | -7.2                          | 48.59                              | 74                | -25.41         |

|                           |       |    |     |     |   |       |       |    |        |
|---------------------------|-------|----|-----|-----|---|-------|-------|----|--------|
| 2483.5                    | 61.08 | PK | 36  | 2.2 | V | -7.2  | 53.88 | 74 | -20.12 |
| 2500                      | 54.29 | PK | 344 | 1.9 | H | -7.18 | 47.11 | 74 | -26.89 |
| 2500                      | 56.1  | PK | 107 | 1.4 | V | -7.18 | 48.92 | 74 | -25.08 |
| 4924                      | 46.63 | PK | 309 | 2.1 | H | -3.16 | 43.47 | 74 | -30.53 |
| 4924                      | 46.3  | PK | 12  | 2.5 | V | -3.16 | 43.14 | 74 | -30.86 |
| 802.11N40, Low Channel    |       |    |     |     |   |       |       |    |        |
| 2310                      | 54.41 | PK | 129 | 1.4 | H | -7.23 | 47.18 | 74 | -26.82 |
| 2310                      | 53.77 | PK | 237 | 2.5 | V | -7.23 | 46.54 | 74 | -27.46 |
| 2390                      | 53.07 | PK | 173 | 2.5 | H | -7.21 | 45.86 | 74 | -28.14 |
| 2390                      | 60.87 | PK | 12  | 1.1 | V | -7.21 | 53.66 | 74 | -20.34 |
| 4844                      | 44.11 | PK | 322 | 2.5 | H | -3.53 | 40.58 | 74 | -33.42 |
| 4844                      | 47.1  | PK | 287 | 1.6 | V | -3.53 | 43.57 | 74 | -30.43 |
| 802.11N40, Middle Channel |       |    |     |     |   |       |       |    |        |
| 4874                      | 47.3  | PK | 18  | 1.8 | H | -3.42 | 43.88 | 74 | -30.12 |
| 4874                      | 46.67 | PK | 332 | 2.3 | V | -3.42 | 43.25 | 74 | -30.75 |
| 802.11N40, High Channel   |       |    |     |     |   |       |       |    |        |
| 2483.5                    | 56.82 | PK | 1   | 1.2 | H | -7.2  | 49.62 | 74 | -24.38 |
| 2483.5                    | 61.35 | PK | 255 | 1.7 | V | -7.2  | 54.15 | 74 | -19.85 |
| 2483.5                    | 50.89 | AV | 199 | 1.5 | V | -7.2  | 43.69 | 54 | -10.31 |
| 2500                      | 56.07 | PK | 228 | 1.3 | H | -7.18 | 48.89 | 74 | -25.11 |
| 2500                      | 56.33 | PK | 173 | 2.5 | V | -7.18 | 49.15 | 74 | -24.85 |
| 4904                      | 45.63 | PK | 235 | 2.1 | H | -3.16 | 42.47 | 74 | -31.53 |
| 4904                      | 46.79 | PK | 177 | 1.8 | V | -3.16 | 43.63 | 74 | -30.37 |

**Bluetooth & 2.4G Wi-Fi (802.11b mode, 2437MHz) & 5G Wi-Fi (802.11ac20 mode, 5180MHz) Simultaneously Transmission:**

| Frequency (MHz) | Receiver       |            | Turntable Degree | Rx Antenna |             | Corrected Factor (dB/m) | Corrected Amplitude (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|------------|------------------|------------|-------------|-------------------------|------------------------------|----------------|-------------|
|                 | Reading (dBμV) | PK/QP/Ave. |                  | Height (m) | Polar (H/V) |                         |                              |                |             |
| 146.63          | 53.05          | QP         | 193              | 1.6        | H           | -21.71                  | 31.34                        | 43.5           | -12.16      |
| 325.45          | 48.66          | QP         | 321              | 2.2        | V           | -16.77                  | 31.89                        | 46             | -14.11      |
| 2571.06         | 51.92          | PK         | 273              | 1.3        | H           | -6.9                    | 45.02                        | 74             | -28.98      |
| 2716.74         | 50.36          | PK         | 259              | 2.4        | V           | -6.6                    | 43.76                        | 74             | -30.24      |

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected Amplitude- Limit


The other spurious emission which is 20dB below to the limit was not recorded.

The test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


1-18 GHz:

Pre-scan plots:

802.11 N20 Middle Channel  
Horizontal




Vertical




18 -25GHz:

Pre-scan plots:

802.11 N20 Middle Channel  
Horizontal



Vertical




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 48 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Fan Yang from 2021-11-23 to 2021-11-24*

*EUT operation mode: Transmitting*


Test Result: Compliant. Please refer to the Appendix Wi-Fi.

**FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER****Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

**Test Procedure**

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24 °C     |
| <b>Relative Humidity:</b> | 48 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Fan Yang on from 2021-11-23 to 2021-11-24*

*EUT operation mode: Transmitting*


Test Result: Compliant. Please refer to the Appendix Wi-Fi.

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24 °C     |
| <b>Relative Humidity:</b> | 48 %      |
| <b>ATM Pressure:</b>      | 101.0 kPa |

*The testing was performed by Fan Yang on from 2021-11-23 to 2021-11-24*

*EUT operation mode: Transmitting*

Test Result: Compliant.

**Conducted Band Edge Result:**


Please refer to the Appendix Wi-Fi.

**FCC §15.247(e) - POWER SPECTRAL DENSITY****Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

**Test Procedure**

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 48 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Fan Yang on from 2021-11-23 to 2021-11-24*

*EUT operation mode: Transmitting*

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

## APPENDIX Wi-Fi


### Appendix A: 6dB Emission Bandwidth


#### Test Result


| TestMode | Antenna | Channel [MHz] | DTS BW [MHz] | Limit[MHz] | Verdict |
|----------|---------|---------------|--------------|------------|---------|
| 11B      | Ant0    | 2412          | 10.160       | 0.5        | PASS    |
|          |         | 2437          | 10.160       | 0.5        | PASS    |
|          |         | 2462          | 10.160       | 0.5        | PASS    |
| 11G      | Ant0    | 2412          | 16.480       | 0.5        | PASS    |
|          |         | 2437          | 16.480       | 0.5        | PASS    |
|          |         | 2462          | 16.520       | 0.5        | PASS    |
| 11N20    | Ant0    | 2412          | 17.680       | 0.5        | PASS    |
|          |         | 2437          | 17.680       | 0.5        | PASS    |
|          |         | 2462          | 17.640       | 0.5        | PASS    |
| 11N40    | Ant0    | 2422          | 36.480       | 0.5        | PASS    |
|          |         | 2437          | 36.480       | 0.5        | PASS    |
|          |         | 2452          | 36.480       | 0.5        | PASS    |


| TestMode | Antenna | Channel [MHz] | DTS BW [MHz] | Limit[MHz] | Verdict |
|----------|---------|---------------|--------------|------------|---------|
| 11B      | Ant1    | 2412          | 10.120       | 0.5        | PASS    |
|          |         | 2437          | 10.160       | 0.5        | PASS    |
|          |         | 2462          | 10.160       | 0.5        | PASS    |
| 11G      | Ant1    | 2412          | 16.400       | 0.5        | PASS    |
|          |         | 2437          | 16.440       | 0.5        | PASS    |
|          |         | 2462          | 16.400       | 0.5        | PASS    |
| 11N20    | Ant1    | 2412          | 17.680       | 0.5        | PASS    |
|          |         | 2437          | 17.640       | 0.5        | PASS    |
|          |         | 2462          | 17.680       | 0.5        | PASS    |
| 11N40    | Ant1    | 2422          | 36.480       | 0.5        | PASS    |
|          |         | 2437          | 36.480       | 0.5        | PASS    |
|          |         | 2452          | 36.480       | 0.5        | PASS    |


## Test Graphs


































**Appendix B: Occupied Channel Bandwidth****Test Result**


| TestMode | Antenna | Channel[MHz] | OCB [MHz] | Limit[MHz] | Verdict |
|----------|---------|--------------|-----------|------------|---------|
| 11B      | Ant0    | 2412         | 15.025    | ---        | PASS    |
|          |         | 2437         | 15.025    | ---        | PASS    |
|          |         | 2462         | 15.025    | ---        | PASS    |
| 11G      | Ant0    | 2412         | 17.223    | ---        | PASS    |
|          |         | 2437         | 17.223    | ---        | PASS    |
|          |         | 2462         | 17.223    | ---        | PASS    |
| 11N20    | Ant0    | 2412         | 18.661    | ---        | PASS    |
|          |         | 2437         | 18.661    | ---        | PASS    |
|          |         | 2462         | 18.661    | ---        | PASS    |
| 11N40    | Ant0    | 2422         | 36.843    | ---        | PASS    |
|          |         | 2437         | 36.843    | ---        | PASS    |
|          |         | 2452         | 36.923    | ---        | PASS    |


| TestMode | Antenna | Channel[MHz] | OCB [MHz] | Limit[MHz] | Verdict |
|----------|---------|--------------|-----------|------------|---------|
| 11B      | Ant1    | 2412         | 15.065    | ---        | PASS    |
|          |         | 2437         | 15.025    | ---        | PASS    |
|          |         | 2462         | 15.025    | ---        | PASS    |
| 11G      | Ant1    | 2412         | 17.702    | ---        | PASS    |
|          |         | 2437         | 17.662    | ---        | PASS    |
|          |         | 2462         | 17.742    | ---        | PASS    |
| 11N20    | Ant1    | 2412         | 18.621    | ---        | PASS    |
|          |         | 2437         | 18.621    | ---        | PASS    |
|          |         | 2462         | 18.621    | ---        | PASS    |
| 11N40    | Ant1    | 2422         | 36.843    | ---        | PASS    |
|          |         | 2437         | 36.843    | ---        | PASS    |
|          |         | 2452         | 36.923    | ---        | PASS    |


## Test Graphs
































**Test Graphs****Appendix C: Maximum Conducted Output Peak Power****Test Result**

| Test Mode | Channel [MHz] | Power Result [dBm] |       |       | Limit [dBm] | Verdict |
|-----------|---------------|--------------------|-------|-------|-------------|---------|
|           |               | Ant 0              | Ant 1 | Total |             |         |
| 11B       | 2412          | 16.65              | 15.44 | 19.10 | <=30        | PASS    |
|           | 2437          | 16.25              | 15.32 | 18.82 | <=30        | PASS    |
|           | 2462          | 16.69              | 15.12 | 18.99 | <=30        | PASS    |
| 11G       | 2412          | 16.50              | 15.21 | 18.91 | <=30        | PASS    |
|           | 2437          | 15.93              | 15.21 | 18.59 | <=30        | PASS    |
|           | 2462          | 16.24              | 15.42 | 18.86 | <=30        | PASS    |
| 11N20     | 2412          | 16.21              | 15.20 | 18.74 | <=30        | PASS    |
|           | 2437          | 16.49              | 15.30 | 18.95 | <=30        | PASS    |
|           | 2462          | 16.08              | 15.14 | 18.65 | <=30        | PASS    |
| 11N40     | 2422          | 16.52              | 15.42 | 19.01 | <=30        | PASS    |
|           | 2437          | 16.23              | 15.42 | 18.85 | <=30        | PASS    |
|           | 2452          | 15.84              | 15.20 | 18.54 | <=30        | PASS    |

Note 1: The maximum antenna gain is 2.68dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0dB (i.e., no array gain) For  $N_{ANT} \leq 4$ ;

So: Directional gain=2.68dBi <6dBi

**Appendix D: Power spectral density****Test Result**


| TestMode | Channel[MHz] | Result[dBm/3kHz] |        |        | Limit[dBm/3kHz] | Verdict |
|----------|--------------|------------------|--------|--------|-----------------|---------|
|          |              | Ant 0            | Ant 1  | Total  |                 |         |
| 11B      | 2412         | -12.7            | -14.83 | -10.63 | <=8             | PASS    |
|          | 2437         | -12.59           | -14.64 | -10.48 | <=8             | PASS    |
|          | 2462         | -12.7            | -14.51 | -10.5  | <=8             | PASS    |
| 11G      | 2412         | -14.82           | -16.11 | -12.41 | <=8             | PASS    |
|          | 2437         | -13.87           | -15.85 | -11.74 | <=8             | PASS    |
|          | 2462         | -14.19           | -16.08 | -12.02 | <=8             | PASS    |
| 11N20    | 2412         | -14.52           | -16.26 | -12.29 | <=8             | PASS    |
|          | 2437         | -14.61           | -16.75 | -12.54 | <=8             | PASS    |
|          | 2462         | -14.33           | -16.15 | -12.14 | <=8             | PASS    |
| 11N40    | 2422         | -17.37           | -18.66 | -14.96 | <=8             | PASS    |
|          | 2437         | -17.78           | -18.55 | -15.14 | <=8             | PASS    |
|          | 2452         | -16.39           | -19.65 | -14.71 | <=8             | PASS    |


Note 1: The maximum antenna gain is 2.68 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices


$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{ss}})\text{dB}$$


So: Directional gain =  $G_{\text{ANT}} + \text{Array Gain} = 2.68 + 10 * \log(2/1) = 5.69\text{dBi} < 6\text{dBi}$


## Test Graphs




































## Appendix E: Band edge measurements


### Test Graphs






















**Appendix F: Duty Cycle****Test Result**


| TestMode | Antenna | Channel [MHz] | Transmission Duration [ms] | Transmission Period [ms] | Duty Cycle [%] |
|----------|---------|---------------|----------------------------|--------------------------|----------------|
| 11B      | Ant0    | 2412          | 12.18                      | 12.72                    | 95.75          |
|          |         | 2437          | 12.37                      | 12.75                    | 97.02          |
|          |         | 2462          | 12.35                      | 12.81                    | 96.41          |
| 11G      | Ant0    | 2412          | 1.02                       | 1.23                     | 82.93          |
|          |         | 2437          | 1.02                       | 1.23                     | 82.93          |
|          |         | 2462          | 1.02                       | 1.23                     | 82.93          |
| 11N20    | Ant0    | 2412          | 1.89                       | 2.26                     | 83.63          |
|          |         | 2437          | 1.89                       | 2.25                     | 84.00          |
|          |         | 2462          | 1.89                       | 2.26                     | 83.63          |
| 11N40    | Ant0    | 2422          | 0.92                       | 1.11                     | 82.88          |
|          |         | 2437          | 0.92                       | 1.11                     | 82.88          |
|          |         | 2452          | 0.92                       | 1.11                     | 82.88          |


| TestMode | Antenna | Channel [MHz] | Transmission Duration [ms] | Transmission Period [ms] | Duty Cycle [%] |
|----------|---------|---------------|----------------------------|--------------------------|----------------|
| 11B      | Ant1    | 2412          | 12.16                      | 12.72                    | 95.60          |
|          |         | 2437          | 12.16                      | 12.72                    | 95.60          |
|          |         | 2462          | 12.16                      | 12.72                    | 95.60          |
| 11G      | Ant1    | 2412          | 2.03                       | 2.42                     | 83.88          |
|          |         | 2437          | 2.03                       | 2.42                     | 83.88          |
|          |         | 2462          | 2.03                       | 2.42                     | 83.88          |
| 11N20    | Ant1    | 2412          | 1.89                       | 2.25                     | 84.00          |
|          |         | 2437          | 1.89                       | 2.26                     | 83.63          |
|          |         | 2462          | 1.89                       | 2.25                     | 84.00          |
| 11N40    | Ant1    | 2422          | 0.92                       | 1.11                     | 82.88          |
|          |         | 2437          | 0.92                       | 1.11                     | 82.88          |
|          |         | 2452          | 0.92                       | 1.11                     | 82.88          |


## Test Graphs
































\*\*\*\*\* END OF REPORT \*\*\*\*\*