

# FCC RF EXPOSURE REPORT

FCC ID: 2AG7C-SNAP8S

**Project No.** : 2005H045

**Equipment**: BATTERY CAMERA

Brand Name : N/A Test Model : Snap 8S

Series Model : Snap 8T, GO1, GO1T, GO1S

**Applicant**: Hangzhou Meari Technology Co., Ltd.

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

Manufacturer : Hangzhou Meari Technology Co., Ltd.?

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

**Factory**: Hangzhou Meari Technology Co., Ltd.?

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

Date of Receipt : May 29, 2020

**Date of Test** : Jun. 01, 2020 ~ Jul. 07, 2020

**Issued Date** : Jul. 20, 2020

Report Version : R00

**Test Sample** : Engineering Sample No.: SH20200527414, SH20200527413,

SH20200527413-3

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by: Allen Wei

Approved by: Ryan Wang

IAC-MRA ACCREDITED

Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666 Web: www.newbtl.com



# **REPORT ISSUED HISTORY**

Report Version	Description	Issued Date	
R00	Original Issue	Jul. 20, 2020	





## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRF}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

#### Table for Filed Antenna

Ant.	Brand	Model Name Antenna		Connector	Gain(dBi)	
1	N/A	N/A	PCB	N/A	3	



# 2. TEST RESULTS

### For 2.4GHz:

Directional gain (dBi)	Directional gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
3	1.9953	23.40	218.7762	0.08689	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

**End of Test Report**