



Model Difference Declaration

We, Powercore Technology Co., Ltd. declare:

DC Electric Vehicle Charging Station: LDC001ABCD-E

A may be C1 or NACS, denotes to one of the output connector interface type, C1:CCS1

B may be 120, 150, 175, 180, denotes to one of the output rating, 120:120kW, 150:150kW, 175:175kW, 180:180kW

C may be C1 or NACS, denotes to the other of the output connector interface type, C1:CCS1

D may be 120, 150, 175, 180, denotes to the other of the output rating, 120:120kW, 150:150kW, 175:175kW, 180:180kW

E may be NC or LC, denotes to the type of the cooling, NC: Natural Cooling, LC: Liquid Cooling

LDC001C1120C1120-LC, LDC001C1120NACS120-LC, LDC001NACS120NACS120-LC,
LDC001C1150C1120-LC, LDC001C1150NACS120-LC, LDC001NACS150NACS120-LC,
LDC001C1150C1150-LC, LDC001C1150NACS150-LC, LDC001NACS150NACS150-LC,
LDC001C1180C1150-LC, LDC001C1180NACS150-LC, LDC001NACS180NACS150-LC,
LDC001C1175C1175-LC, LDC001C1175NACS175-LC, LDC001NACS175NACS175-LC,
LDC001C1180C1180-LC, LDC001C1180NACS180-LC, LDC001NACS180NACS180-LC,
LDC001C1120C1120-NC, LDC001C1120NACS120-NC, LDC001NACS120NACS120-NC,
LDC001C1150C1120-NC, LDC001C1150NACS120-NC, LDC001NACS150NACS120-NC,
LDC001C1150C1150-NC, LDC001C1150NACS150-NC, LDC001NACS150NACS150-NC,
LDC001C1180C1150-NC, LDC001C1180NACS150-NC, LDC001NACS180NACS150-NC,
LDC001C1175C1175-NC, LDC001C1175NACS175-NC, LDC001NACS175NACS175-NC,
LDC001C1180C1180-NC, LDC001C1180NACS180-NC, LDC001NACS180NACS180-NC

The products above are electric identical except the charging gun, cooling type and rated power.

LDC001A120C120-LC: Input: 480VAC±10%, 50/60Hz, 304A Max
Output: 150-1000VDC, 500A Max, 240kW Max

LDC001A150C120-LC: Input: 480VAC±10%, 50/60Hz, 342A Max
Output: 150-1000VDC, 500A Max, 270kW Max

LDC001A150C150-LC: Input: 480VAC±10%, 50/60Hz, 380A Max
Output: 150-1000VDC, 500A Max, 300kW Max

LDC001A180C150-LC: Input: 480VAC±10%, 50/60Hz, 418A Max
Output: 150-1000VDC, 500A Max, 330kW Max

LDC001A175C175-LC: Input: 480VAC±10%, 50/60Hz, 443A Max
Output: 150-1000VDC, 500A Max, 350kW Max

LDC001A180C180-LC: Input: 480VAC±10%, 50/60Hz, 456A Max
Output: 150-1000VDC, 500A Max, 360kW Max

LDC001A120C120-NC: Input: 480VAC±10%, 50/60Hz, 304A Max
Output: 150-1000VDC, 300A Max, 240kW Max

LDC001A150C120-NC: Input: 480VAC±10%, 50/60Hz, 342A Max
Output: 150-1000VDC, 300A Max, 270kW Max

LDC001A150C150-NC: Input: 480VAC±10%, 50/60Hz, 380A Max



Output: 150-1000VDC, 300A Max, 300kW Max
LDC001A180C150-NC: Input: 480VAC $\pm$ 10%, 50/60Hz, 418A Max
Output: 150-1000VDC, 300A Max, 330kW Max
LDC001A175C175-NC: Input: 480VAC $\pm$ 10%, 50/60Hz, 443A Max
Output: 150-1000VDC, 300A Max, 350kW Max
LDC001A180C180-NC: Input: 480VAC $\pm$ 10%, 50/60Hz, 456A Max
Output: 150-1000VDC, 300A Max, 360kW Max

A handwritten signature in black ink that reads 'Cheri Ma'. The signature is written in a cursive style and is positioned above a horizontal line.

Cheri Ma

Powercore Technology Co., Ltd.

Email: mayj@cnchargepoint.com

Date: July 19, 2023