

# TEST REPORT

EMI Test for FCC Certification / ISED of LG L322DL

APPLICANT  
LG Electronics USA, Inc.

REPORT NO.  
HCT-EM-1905-FI004

DATE OF ISSUE  
May 24, 2019

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

# TEST REPORT

EMI Test for  
FCC Certification  
/ISED

**REPORT NO.**

HCT-EM-1905-FI004

**DATE OF ISSUE**

May 24, 2019

**FCC ID / IC**

ZNFL322DL / 2703C-X320WM

**Applicant** LG Electronics USA, Inc.  
1000 Sylvan Avenue, Englewood Cliffs NJ 07632 United States

**Product Name** Multi-band CDMA/GSM/EDGE/WCDMA/LTE Phone with WLAN and Bluetooth  
**Model Name** LG L322DL  
**Series Model Name** Refer to the clause 1.1 Description of EUT

**Travel Adaptor Information** Model name: MCS-V01WA  
Manufacturer: AOHA1

**Date of Test** May 13, 2019 to May 16, 2019

**Test Standard Used** FCC CFR 47 PART 15 Subpart B Class B / ICES-003 Issue 6 Class B  
ANSI C63.4-2014

**Test Results** Refer to the present document

**Manufacturer** LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

**Tested by**  
Na-Eun Song

(signature)

**Technical Manager**  
Jeong-Hyun Choi

(signature)

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	May 24, 2019	Initial Release

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

## CONTENTS

1. GENERAL INFORMATION	05
1.1 Description of EUT	05
1.2 Tested System Details	06
1.3 Cable Description	06
1.4 Noise Suppression Parts on Cable. (I/O Cable)	06
1.5 Test Facility	07
1.6 Calibration of Measuring Instrument	07
1.7 Measurement Uncertainty	07
2. DESCRIPTION OF TEST	08
2.1 Measurement of Conducted Emission	08
2.2 Measurement of Radiated Emission	09
2.3 Configuration of Tested System	10
3. PRELIMINARY TEST	11
3.1 Conducted Emission	11
3.2 Radiated Emission	11
4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY	12
4.1 Conducted Emission	12
4.2 Radiated Emission Below 1 GHz	19
4.3 Radiated Emission Above 1 GHz	21
5. CONCLUSION	23
6. APPENDIX A. TEST SETUP PHOTOGRAPHS	24

## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFL322DL
IC	2703C-X320WM
Model	LG L322DL
Series Model Name	LGL322DL, L322DL, LM-X320WM, LMX320WM, X320WM, LM-X320QMG, LMX320QMG, X320QMG, LM-X320QML, LMX320QML, X320QML, LM-X320QM6, LMX320QM6, X320QM6
EUT Type	Multi-band CDMA/GSM/EDGE/WCDMA/LTE Phone with WLAN and Bluetooth
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 704 MHz to 716 MHz (LTE B17) 1 710 MHz to 1 780 MHz (LTE B66) 663 MHz to 698 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 1 932.4 MHz to 1 987.6 MHz (WCDMA B2) 2 112.4 MHz to 2 152.6 MHz (WCDMA B4) 871.40 MHz to 891.60 MHz (WCDMA B5) 1 930 MHz to 1 990 MHz (LTE B2)

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

	2 110 MHz to 2 155 MHz (LTE B4) 869 MHz to 894 MHz (LTE B5) 729 MHz to 746 MHz (LTE B12) 746 MHz to 756 MHz (LTE B13) 734 MHz to 746 MHz (LTE B17) 2 110 MHz to 2 200 MHz (LTE B66) 617 MHz to 652 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
--	---

## 1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	LG L322DL	-	LG
Data Cable	EAD62377921	-	LEAGTECH
Earphone	EAB64468444	-	CRESYN
TA	MCS-V01WA	-	AOHAI
Micro SD card	Extreme Micro SDHC UHS-1 CLASS 10 (32 GB)	-	SanDisk

## 1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	N/A	(P)1.0
	Earphone	N/A	N	(D)1.2

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

## 1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## 1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Designation No.
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	

## 1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

## 1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Conducted Emission (0.15 MHz to 30 MHz)	1.82 dB
Radiated Emissions (30 MHz to 1 GHz)	5.20 dB
Radiated Emissions (1 GHz to 18 GHz)	5.24 dB
Radiated Emissions (18 GHz to 40 GHz)	5.40 dB

## 2. DESCRIPTION OF TEST

### 2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### Conducted Emission Limits

Frequency (MHz)	Resolution Bandwidth (kHz)	Class A		Class B	
		Quasi-Peak (dBμV)	Average (dBμV)	Quasi-Peak (dBμV)	Average (dBμV)
0.15 to 0.5	9	79	66	66 to 56*	56 to 46*
0.5 to 5	9	73	60	56	46
5 to 30	9	73	60	60	50

NOTE. Decreases with the logarithm of the frequency.



## 2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.  
(1 GHz to 40 GHz)

### Radiated Emission Limits


Frequency (MHz)	Class A			Class B		
	Antenna Distance (m)	Field Strength ( $\mu\text{V/m}$ )	Quasi-Peak (dB $\mu\text{V/m}$ )	Antenna Distance (m)	Field Strength ( $\mu\text{V/m}$ )	Quasi-Peak (dB $\mu\text{V/m}$ )
30 to 88	10	90	39.0	3	100	40.0
88 to 216	10	150	43.5	3	150	43.5
216 to 960	10	210	46.4	3	200	46.0
Above 960	10	300	49.5	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Class A		Class B		
		Peak (dB $\mu\text{V/m}$ )	Average (dB $\mu\text{V/m}$ )	Peak (dB $\mu\text{V/m}$ )	Average (dB $\mu\text{V/m}$ )	
Above 1 000	3	80	60	74	54	

### 2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 GHz, whichever is lower
Below 1.705	30

### 2.3 Configuration of Tested System



### 3. PRELIMINARY TEST

#### 3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Modes:** FRONT CAMERA & MP3 mode

REAR CAMERA & FM RADIO mode

IDLE mode

NOTE. The worst-case emissions are reported.

#### 3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Modes:** FRONT CAMERA & MP3 mode

REAR CAMERA & FM RADIO mode

IDLE mode

NOTE. The worst-case emissions are reported.

## 4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

### 4.1 Conducted Emission

#### 4.1.1 Measuring instruments

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/> EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.25.2018
<input checked="" type="checkbox"/> LISN	Rohde & Schwarz	ENV216	102245	1 year	12.12.2018
<input checked="" type="checkbox"/> Software	Rohde & Schwarz	EMC32 VER8.54.0	-	-	-


#### 4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:

Test Standard Used	FCC CFR 47 PART 15 Subpart B Class B ICES-003 Issue 6 Class B ANSI C63.4-2014
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operating Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	Shielded Room
Temperature	22.7 °C
Relative Humidity	43.3 %
Test Date	May 13, 2019

### 4.1.3 Measuring Data

Figure 1: Conducted Emission, AC Main Port, Line (L1)



### QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	39.4	9.000	L1	9.7	26.5	65.9
0.156000	39.6	9.000	L1	9.7	26.1	65.7
0.178000	37.6	9.000	L1	9.7	27.0	64.6
0.182000	37.9	9.000	L1	9.7	26.5	64.4
0.200000	36.5	9.000	L1	9.8	27.2	63.6
0.204000	36.2	9.000	L1	9.7	27.2	63.4
1.148000	35.6	9.000	L1	9.8	20.4	56.0
1.198000	36.7	9.000	L1	9.8	19.3	56.0
1.296000	37.4	9.000	L1	9.9	18.6	56.0
1.300000	37.7	9.000	L1	9.9	18.3	56.0
1.312000	36.7	9.000	L1	9.9	19.3	56.0
1.348000	36.9	9.000	L1	9.9	19.1	56.0
5.222000	26.6	9.000	L1	10.0	33.4	60.0
5.356000	25.8	9.000	L1	10.0	34.2	60.0
5.438000	25.7	9.000	L1	10.0	34.3	60.0
14.048000	25.3	9.000	L1	10.4	34.7	60.0
14.114000	25.7	9.000	L1	10.4	34.3	60.0
14.416000	24.8	9.000	L1	10.4	35.2	60.0


### Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

## CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	26.7	9.000	L1	9.7	29.2	55.9
0.156000	24.8	9.000	L1	9.7	30.9	55.7
0.178000	22.7	9.000	L1	9.7	31.9	54.6
0.186000	22.8	9.000	L1	9.7	31.4	54.2
0.212000	19.5	9.000	L1	9.7	33.7	53.1
0.222000	20.4	9.000	L1	9.7	32.4	52.7
1.148000	25.2	9.000	L1	9.8	20.8	46.0
1.296000	24.2	9.000	L1	9.9	21.8	46.0
1.300000	24.5	9.000	L1	9.9	21.5	46.0
1.348000	24.3	9.000	L1	9.9	21.7	46.0
1.396000	23.6	9.000	L1	9.9	22.4	46.0
1.400000	23.7	9.000	L1	9.9	22.3	46.0
5.312000	16.3	9.000	L1	10.0	33.7	50.0
5.356000	15.7	9.000	L1	10.0	34.3	50.0
5.438000	15.6	9.000	L1	10.0	34.4	50.0
14.048000	14.9	9.000	L1	10.4	35.1	50.0
14.114000	15.5	9.000	L1	10.4	34.5	50.0
14.416000	14.5	9.000	L1	10.4	35.5	50.0

Figure 2: Conducted Emission, AC Main Port, Line (N)





## QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	44.1	9.000	N	9.8	21.8	65.9
0.156000	43.1	9.000	N	9.8	22.6	65.7
0.162000	38.5	9.000	N	9.8	26.9	65.4
0.170000	36.3	9.000	N	9.8	28.6	65.0
0.178000	40.6	9.000	N	9.8	24.0	64.6
0.188000	39.1	9.000	N	9.8	25.0	64.1
1.060000	35.5	9.000	N	10.0	20.5	56.0
1.112000	34.9	9.000	N	10.0	21.1	56.0
1.166000	36.0	9.000	N	10.0	20.0	56.0
1.218000	36.8	9.000	N	10.0	19.2	56.0
1.272000	37.9	9.000	N	10.0	18.1	56.0
1.322000	37.8	9.000	N	10.0	18.2	56.0
16.140000	31.6	9.000	N	10.7	28.4	60.0
16.196000	32.2	9.000	N	10.7	27.8	60.0
16.368000	31.0	9.000	N	10.7	29.0	60.0
16.416000	30.4	9.000	N	10.7	29.6	60.0
16.456000	30.4	9.000	N	10.7	29.6	60.0
16.614000	29.2	9.000	N	10.7	30.8	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152000	28.5	9.000	N	9.8	27.4	55.9
0.156000	27.0	9.000	N	9.8	28.7	55.7
0.160000	25.7	9.000	N	9.8	29.7	55.5
0.164000	24.7	9.000	N	9.8	30.6	55.3
0.178000	24.5	9.000	N	9.8	30.0	54.6
0.190000	22.9	9.000	N	9.8	31.1	54.0
1.094000	24.5	9.000	N	10.0	21.5	46.0
1.110000	24.1	9.000	N	10.0	21.9	46.0
1.168000	24.2	9.000	N	10.0	21.8	46.0
1.272000	23.9	9.000	N	10.0	22.1	46.0
1.324000	23.7	9.000	N	10.1	22.3	46.0
1.328000	23.5	9.000	N	10.1	22.5	46.0
16.140000	18.9	9.000	N	10.7	31.1	50.0
16.368000	18.7	9.000	N	10.7	31.3	50.0
16.386000	18.9	9.000	N	10.7	31.1	50.0
16.416000	18.3	9.000	N	10.7	31.7	50.0
16.456000	18.5	9.000	N	10.7	31.5	50.0
16.614000	17.4	9.000	N	10.7	32.6	50.0

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## 4.2 Radiated Emission Below 1 GHz

### 4.2.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/>	EMI test receiver	Rohde & Schwarz	ESi40	831564103	1 year	10.31.2018
<input checked="" type="checkbox"/>	Trilog antenna	Schwarzbeck	VULB 9168	255	2 year	03.26.2019
<input checked="" type="checkbox"/>	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	INNCO Systems	CO 3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/>	Turn Table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/>	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-

### 4.2.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ICES-003 Issue 6 Class B ANSI C63.4-2014
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operating Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.0 / 23.8 °C
Relative Humidity	42.2 / 45.2 %
Test Date	May 15 / May 16, 2019

### 4.2.3 Measuring Data

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.785571	18.4	125.2	V	288.0	18.3	21.6	40.0
46.715431	18.2	100.0	V	88.0	19.5	21.8	40.0
125.308617	23.9	100.0	H	254.0	17.8	19.6	43.5
150.342685	24.1	174.9	V	17.0	19.4	19.4	43.5
699.156313	27.4	100.0	V	31.0	28.6	18.6	46.0
906.330662	30.6	225.0	V	219.0	31.4	15.4	46.0

#### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

### 4.3 Radiated Emission Above 1 GHz

#### 4.3.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
<input checked="" type="checkbox"/>	EMI test receiver	Rohde & Schwarz	ES140	831564103	1 year	10.31.2018
<input checked="" type="checkbox"/>	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
<input checked="" type="checkbox"/>	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
<input checked="" type="checkbox"/>	Turn table	INNCO Systems	1060	-	N/A	-
<input checked="" type="checkbox"/>	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
<input checked="" type="checkbox"/>	Horn antenna	Schwarzbeck	BBHA 9120D	01836	2 year	07.20.2018
<input checked="" type="checkbox"/>	Low Noise amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.04.2019
<input checked="" type="checkbox"/>	Software	Rohde & Schwarz	EMC32 VER8.40.0	-	-	-

#### 4.3.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ICES-003 Issue 6 Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	2 480 MHz
Tested Frequency Range	1 GHz to 18 GHz
Operation Mode	FRONT CAMERA & MP3 mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.1 °C
Relative Humidity	41.9 %
Test Date	May 14, 2019

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

### 4.3.3 Measuring Data

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
4037.625250	35.7	100.0	V	50.0	-19.6	38.3	74.0
5506.362725	39.2	100.0	V	78.0	-15.4	34.8	74.0
7334.519038	45.0	350.1	V	29.0	-9.9	29.0	74.0
9565.581162	48.7	100.0	V	121.0	-5.4	25.3	74.0
10934.519038	49.5	100.0	V	94.0	-2.8	24.5	74.0
14813.777555	49.8	112.4	H	212.0	0.9	24.2	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
4037.625250	23.3	100.0	V	50.0	-19.6	30.7	54.0
5506.362725	26.4	100.0	V	78.0	-15.4	27.6	54.0
7334.519038	32.2	350.1	V	29.0	-9.9	21.8	54.0
9565.581162	36.0	100.0	V	121.0	-5.4	18.0	54.0
10934.519038	36.4	100.0	V	94.0	-2.8	17.6	54.0
14813.777555	37.0	112.4	H	212.0	0.9	17.0	54.0

#### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

## 5. CONCLUSION

The data collected shows that the **EUT Type: Multi-band CDMA/GSM/EDGE/WCDMA/LTE Phone with WLAN and Bluetooth, Model: LG L322DL** complies with §15.107 and §15.109 of the FCC rules and ICES-003 Issue 6 of the IC rules.

## 6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A

File No.	Date of Issue	Description
HCT-EM-1905-FI004-P	May 24, 2019	Initial Release

End of report