

# FCC TEST REPORT

## (Part 15, Subpart C)

Applicant:	KYOCERA Corporation
Address:	Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan

Manufacturer or Supplier:	KYOCERA Corporation
Address:	Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi, Kanagawa, Japan
Product:	Mobile Phone
Brand Name:	KYOCERA
Model Name:	EB1217
FCC ID:	JOYEB1217
Date of tests:	Oct. 21, 2024~Dec. 05, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2020**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
	
Date: Dec. 05, 2024	Date: Dec. 05, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/>, and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or Characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

# TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	5
1. SUMMARY OF TEST RESULTS .....	6
1.1 MEASUREMENT UNCERTAINTY .....	7
2. GENERAL INFORMATION .....	8
2.2 GENERAL DESCRIPTION OF EUT .....	8
2.3 DESCRIPTION OF TEST MODES .....	11
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	12
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	12
2.4 DUTY CYCLE OF TEST SIGNAL .....	16
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	16
2.6 DESCRIPTION OF SUPPORT UNITS .....	17
3. TEST TYPES AND RESULTS .....	18
3.1 CONDUCTED EMISSION MEASUREMENT .....	18
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	18
3.1.2 TEST INSTRUMENTS .....	19
3.1.3 TEST PROCEDURES .....	20
3.1.4 DEVIATION FROM TEST STANDARD .....	20
3.1.5 TEST SETUP .....	21
3.1.6 EUT OPERATING CONDITIONS .....	21
3.1.7 TEST RESULTS .....	22
3.2 RADIATED EMISSION MEASUREMENT .....	24
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	24
3.2.2 TEST INSTRUMENTS .....	25
3.2.3 TEST PROCEDURES .....	26
3.2.4 DEVIATION FROM TEST STANDARD .....	26
3.2.5 TEST SETUP .....	27
3.2.6 EUT OPERATING CONDITIONS .....	28
3.2.7 TEST RESULTS .....	29
3.3 6 DB BANDWIDTH MEASUREMENT .....	113
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT .....	113
3.3.2 TEST INSTRUMENTS .....	113
3.3.3 TEST PROCEDURE .....	114
3.3.4 DEVIATION FROM TEST STANDARD .....	115
3.3.5 TEST SETUP .....	115
3.3.6 EUT OPERATING CONDITIONS .....	115
3.3.7 TEST RESULTS .....	115
3.4 CONDUCTED OUTPUT POWER .....	116

3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	116
3.4.2	TEST SETUP .....	116
3.4.3	TEST INSTRUMENTS.....	116
3.4.4	TEST PROCEDURES .....	116
3.4.5	DEVIATION FROM TEST STANDARD .....	116
3.4.6	EUT OPERATING CONDITIONS .....	116
3.4.7	TEST RESULTS .....	117
3.4.7.1	MAXIMUM PEAK OUTPUT POWER .....	117
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	118
3.5	POWER SPECTRAL DENSITY MEASUREMENT .....	119
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	119
3.5.2	TEST SETUP .....	119
3.5.3	TEST INSTRUMENTS.....	119
3.5.4	TEST PROCEDURE.....	119
3.5.5	DEVIATION FROM TEST STANDARD .....	119
3.5.6	EUT OPERATING CONDITION .....	119
3.5.7	TEST RESULTS .....	120
3.6	OUT OF BAND EMISSION MEASUREMENT .....	121
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	121
3.6.2	TEST SETUP .....	121
3.6.3	TEST INSTRUMENTS.....	121
3.6.4	TEST PROCEDURE.....	121
3.6.5	DEVIATION FROM TEST STANDARD .....	122
3.6.6	EUT OPERATING CONDITION .....	122
3.6.7	TEST RESULTS .....	122
3.7	ANTENNA REQUIREMENTS .....	123
3.7.1	STANDARD APPLICABLE .....	123
3.7.2	ANTENNA CONNECTED CONSTRUCTION .....	123
3.7.3	ANTENNA GAIN .....	123
4	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	124
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	125
6	APPENDIX A:2.4GWIFI .....	126
	DTS BANDWIDTH .....	126
	TEST RESULT .....	126
	TEST GRAPHS.....	127
	OBW BANDWIDTH.....	133
	TEST RESULT .....	133

TEST GRAPHS .....	134
MAXIMUM CONDUCTED OUTPUT POWER .....	140
TEST RESULT .....	140
MAXIMUM POWER SPECTRAL DENSITY .....	142
TEST RESULT .....	142
TEST GRAPHS .....	143
BAND EDGE MEASUREMENTS .....	150
TEST RESULT .....	150
TEST GRAPHS .....	151
CONDUCTED SPURIOUS EMISSION .....	155
TEST RESULT .....	155
TEST GRAPHS .....	156
DUTY CYCLE .....	162
TEST RESULT .....	162
TEST GRAPHS .....	163
7 APPENDIX B:BLE .....	165
DTS BANDWIDTH .....	165
TEST RESULT .....	165
TEST GRAPHS .....	166
OCCUPIED CHANNEL BANDWIDTH .....	172
TEST RESULT .....	172
TEST GRAPHS .....	173
MAXIMUM CONDUCTED OUTPUT POWER .....	179
TEST RESULT .....	179
MAXIMUM POWER SPECTRAL DENSITY .....	180
TEST RESULT .....	180
TEST GRAPHS .....	181
BAND EDGE MEASUREMENTS .....	187
TEST RESULT .....	187
TEST GRAPHS .....	188
CONDUCTED SPURIOUS EMISSION .....	192
TEST RESULT .....	192
TEST GRAPHS .....	193
DUTY CYCLE .....	199
TEST RESULT .....	199
TEST GRAPHS .....	200

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QBJ2409140110RF06	Original release	Dec. 05, 2024



## 1. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	Compliance	A
15.247(a)(2)	6dB bandwidth	Compliance	A
15.247(b)	Conducted Output power	Compliance	A
15.247(e)	Power Spectral Density	Compliance	A
15.203	Antenna Requirement	Compliance	A

Note : Except RSE and AC Power Conducted Emission, other data please refer to Appendix B.

### \*Test Lab Information Reference

#### Lab A:

Huarui 7Layers High TeCHnology (Suzhou) Co., Ltd.

#### Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-teCH District, Suzhou City, Anhui Province

**Accredited Test Lab Cert 6613.01**

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



## 2 GENERAL INFORMATION

### 2.2 GENERAL DESCRIPTION OF EUT

<b>PRODUCT*</b>	Mobile Phone	
<b>BRAND NAME*</b>	KYOCERA	
<b>MODEL NAME*</b>	EB1217	
<b>NOMINAL VOLTAGE*</b>	3.91Vdc (Battery)	
<b>MODULATION *</b>	BLE	GFSK
	2.4G WIFI	DSSS,OFDM
<b>TRANSMISSION RATE*</b>	BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps	
	802.11b: 11/5.5/2.0/1.0 Mbps	
	802.11g: 54/48/36/24/18/9/6 Mbps	
	802.11n(HT20): up to 72.2 Mbps	
	802.11n(HT40): up to 150 Mbps	
<b>OPERATING FREQUENCY</b>	2402-2480MHz for BT-LE	
	2412-2462MHz for 11b/g/n(HT20/40)	
<b>MAX. OUTPUT POWER</b>	BT-LE: 3.97mW (Maximum)	
	WLAN: 297.85mW (Maximum)	
<b>ANTENNA GAIN*</b>	BLE	-2.5dBi
	2.4G WIFI	-2.5dBi
<b>ANTENNA TYPE*</b>	BLE	IFA Antenna
	2.4G WIFI	IFA Antenna
<b>HW VERSION*</b>	DVT2	
<b>SW VERSION*</b>	0.330SR	
<b>I/O PORTS*</b>	Refer to user's manual	
<b>CABLE SUPPLIED*</b>	N/A	

**NOTE:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



3. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n(HT20)	1TX/1RX
802.11n(HT40)	1TX/1RX
BT_LE(1MHz)	1TX/1RX
BT_LE(2MHz)	1TX/1RX
BT_LE(S2)	1TX/1RX
BT_LE(S8)	1TX/1RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
5. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.
6. The detail differences from the Main manufacturer and Secondary manufacturer are as listed below:

Description	Main manufacturer	Secondary manufacturer
LCM	ShenZhen LIDE Communications Ltd.	Wannian Lianchuang Display Technology Co. , Ltd.
Audio jack FPC	Shenzhen Xinyu Tengyue Electronics Co.,Ltd.	Jiangxi Zhiboxin Technology Limited Company
MIC	AAC	Gettop
Memory	Samsung	Biwin
Radio frequency switch_DFN-6_0.4-4.2 GHz_SPDT_GPIO_patch	Innowave	Champhill

The above materials have only manufacturer differences, and the functions are the same. Other than these changes, other RF performance is the same and does not affect the RF results.

**7. List of Accessory:**

ACCESSORIES	BRAND	MODEL	SPECIFICATION
CPU	MTK	MT6835T	N/A
eMMC 1 (=ROM 1)	samsung	KM5P9001DM-B424	N/A



eMMC 2 (=ROM 2)	biwin	BW2A2KZC02-64G	N/A
RAM 1	samsun	KM5P9001DM-B424	N/A
RAM 2	biwin	BW2A2KZC02-64G	N/A
Battery	KYOCERA	5AAXB152	Capacity : 3.91Vdc, 4400mAh/17.3Wh

## 2.3 DESCRIPTION OF TEST MODES

11 Channels are provided for 802.11b, 802.11g and 802.11n20 (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.  
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

**RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: No need to concern of Conducted Emission due to the EUT is powered by battery.

### RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following Channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n20	1 to 11	6	OFDM	MCS0
BT-LE	0 to 39	19	GFSK	2.0



**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity arCHitecture).

☒ The following CHannel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

**POWER LINE CONDUCTED EMISSION TEST**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity arCHitecture).

☒ The following CHannel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n20	1 to 11	6	OFDM	MCS0

**BANDEDGE MEASUREMENT:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following CHannel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0



**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of eaCH mode, but only includes spectrum plot of worst value of eaCH mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity arCHitecture).
- ☒ The following CHannel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 5V By Adapter	Hanwen Xu
PLC	25deg. C, 52%RH	DC 5V By Adapter	Hanwen Xu
APCM	25deg. C, 60%RH	DC 5V By Adapter	Hanwen Xu

## 2.4 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix B Of this test report..

## 2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v05r02**

**ANSI C63.10-2020**

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



## 2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Adapter	N/A	N/A	N/A	N/A
2	Earphone	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Unshielded, Detachable, 1.0m;



### 3 TEST TYPES AND RESULTS

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.28,24	Mar.27,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,24	Apr.26,25
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,24	Apr.26,25

**NOTE:**

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.

### 3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were Checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

### 3.1.5 TEST SETUP



**Note:** 1.Support units were connected to second LISN.  
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



## 3.1.7 TEST RESULTS


## CONDUCTED WORST-CASE DATA

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Hanwen Xu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.411	38.23	57.63	19.40	23.15	47.63	24.47	11.76	L1	9.000
1	1.203	21.92	56.00	34.08	7.40	46.00	38.60	11.75	L1	9.000
1	2.796	16.91	56.00	39.09	3.90	46.00	42.10	11.77	L1	9.000
1	5.352	17.08	60.00	42.92	6.04	50.00	43.96	11.79	L1	9.000
1	13.556	23.38	60.00	36.62	4.60	50.00	45.40	11.84	L1	9.000
1	24.392	10.76	60.00	49.24	4.26	50.00	45.74	11.89	L1	9.000

## REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Hanwen Xu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.411	35.31	57.63	22.32	19.94	47.63	27.69	12.81	N	9.000
1	1.194	18.01	58.00	37.99	5.92	46.00	40.08	12.73	N	9.000
1	2.792	13.14	58.00	42.86	4.08	46.00	41.92	12.74	N	9.000
1	6.747	12.37	60.00	47.63	4.98	50.00	45.02	12.77	N	9.000
1	13.524	13.98	60.00	46.02	5.13	50.00	44.87	12.81	N	9.000
1	26.250	11.35	60.00	48.65	5.13	50.00	44.87	12.88	N	9.000

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



**3.2 RADIATED EMISSION MEASUREMENT****3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.





## 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,25

**NOTE:**

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.

### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter CHamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using fresh batteries. The turntable was rotated to maximize the emission level.

#### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results were added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.5 TEST SETUP


#### <Frequency Range 9KHz~30MHz >



#### < Frequency Range 30MHz~1GHz >



### <Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific CHannel frequency.
- The necessary accessories enable the EUT in full functions.



## 3.2.7 TEST RESULTS

## BELOW 1GHz WORST-CASE DATA

**NOTE:** The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

## 802.11n(20MHz)


CHANNEL	TX Channel 6	DETECTOR	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	

## ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	47.606	29.94	40.00	10.06	-3.58	H	1	1.00	120.000
1	73.893	21.37	40.00	18.63	-10.01	H	284.2	2.00	120.000
1	190.147	19.79	43.50	23.71	-6.15	H	284.2	2.00	120.000
1	311.979	22.29	46.00	23.71	-1.23	H	203.6	1.00	120.000
1	416.642	24.89	46.00	21.11	3.08	H	0.9	2.00	120.000
1	585.471	27.26	46.00	18.74	2.73	H	0.9	2.00	120.000

## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.






CHANNEL	TX Channel 6	DETECTOR	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	

## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	36.111	27.97	40.00	12.03	-7.85	V	359.1	1.00	120.000
1	47.072	29.11	40.00	10.89	-4.60	V	359	2.00	120.000
1	77.676	25.00	40.00	15.00	-11.44	V	359.1	1.00	120.000
1	117.397	23.54	43.50	19.96	-6.50	V	359	2.00	120.000
1	258.532	21.04	46.00	24.96	-3.12	V	151.5	2.00	120.000
1	476.443	25.38	46.00	20.62	2.46	V	4.9	1.00	120.000

## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.






ABOVE 1GHz WORST-CASE DATA

Note:

1. For radiated emissions testing, the full testing range of different modes have been scanned, only the worst case harmonic data is reported in the sheet.
2. All other emissions were greater than 20dB below the limit was not recorded





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,385.500	34.97	54.00	19.03	5.74	H	36.8	2.00
1	2,390.000	34.23	54.00	19.77	5.77	H	36.8	2.00
1	2,413.000	99.88			5.93	H	241.9	1.00








ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,356.000	46.20	74.00	27.80	5.60	V	0.9	2.00
1	2,390.000	44.43	74.00	29.57	5.77	V	279.5	2.00
1	2,413.500	93.62			5.93	V	279.5	2.00






## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,385.500	31.31	54.00	22.69	5.74	V	281.8	2.00
1	2,390.000	30.99	54.00	23.01	5.77	V	281.8	2.00
1	2,411.500	89.42			5.92	V	200.6	2.00



## REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.






**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	48.64	74.00	25.36	37.56	54.00	16.44	13.53	V	1	1.00
2	7,311.000	54.02	74.00	19.98	42.74	54.00	11.26	18.89	V	0.9	2.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2437MHz: Fundamental frequency.








ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	100.53			5.83	H	325.6	1.00
2	2,483.500	37.70	54.00	16.30	5.91	H	359.1	1.00
2	2,487.000	41.07	54.00	12.93	5.94	H	355.8	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	90.25			5.83	V	1	2.00
2	2,483.500	44.49	74.00	29.51	5.91	V	281.8	2.00
2	2,487.500	45.95	74.00	28.05	5.94	V	251.4	1.00





**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	86.10			5.83	V	1.1	2.00
2	2,483.500	30.79	54.00	23.21	5.91	V	281.8	2.00
2	2,488.000	31.67	54.00	22.33	5.94	V	355.8	2.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2462MHz: Fundamental frequency.






802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.000	69.45	74.00	4.55	5.76	H	359.1	1.00
1	2,390.000	69.36	74.00	4.64	5.77	H	359.1	1.00
1	2,409.000	104.13			5.90	H	352.2	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	44.62	54.00	9.38	5.77	H	359	1.00
1	2,390.000	45.65	54.00	8.35	5.77	H	359	1.00
1	2,407.000	92.04			5.89	H	359	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.000	58.09	74.00	15.91	5.76	V	87.7	1.00
1	2,390.000	56.95	74.00	17.05	5.77	V	87.7	1.00
1	2,417.000	92.72			5.96	V	178.6	1.00





## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	35.64	54.00	18.36	5.77	V	272.3	2.00
1	2,390.000	36.48	54.00	17.52	5.77	V	272.3	2.00
1	2,414.000	78.64			5.94	V	272.3	2.00



## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.








**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	50.08	74.00	23.92	37.76	54.00	16.24	13.53	V	359	1.00
2	7,311.000	53.96	74.00	20.04	42.61	54.00	11.39	18.89	V	0.9	2.00



**REMARKS:**


- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
- 2437MHz: Fundamental frequency.



<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.500	104.70			5.82	H	348.1	1.00
2	2,483.500	70.46	74.00	3.54	5.91	H	355.1	2.00
2	2,488.000	66.07	74.00	7.93	5.94	H	359.1	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	92.14			5.83	H	348	1.00
2	2,483.500	46.79	54.00	7.21	5.91	H	348	1.00
2	2,484.500	44.56	54.00	9.44	5.92	H	348	1.00








ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,464.000	91.39			5.81	V	4.9	1.00
2	2,483.500	58.52	74.00	15.48	5.91	V	175	1.00
2	2,484.000	59.04	74.00	14.96	5.92	V	175	1.00






**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	79.67			5.82	V	5	1.00
2	2,483.500	36.79	54.00	17.21	5.91	V	173.8	1.00
2	2,485.000	34.47	54.00	19.53	5.92	V	173.8	1.00



**REMARKS:**


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2462MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	44.30	54.00	9.70	5.77	H	1	2.00
1	2,390.000	45.09	54.00	8.91	5.77	H	7	2.00
1	2,413.500	90.59			5.93	H	253.9	1.00








ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	60.19	74.00	13.81	5.77	V	279.5	2.00
1	2,390.000	60.37	74.00	13.63	5.77	V	279.5	2.00
1	2,415.000	92.79			5.94	V	165.4	1.00






**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.500	35.13	54.00	18.87	5.76	V	278.3	2.00
1	2,390.000	37.09	54.00	16.91	5.77	V	278.3	2.00
1	2,406.000	78.51			5.88	V	278.3	2.00



**REMARKS:**


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.





## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	48.24	74.00	25.76	37.59	54.00	16.41	13.53	V	88.9	1.00
2	7,311.000	53.62	74.00	20.38	42.58	54.00	11.42	18.89	V	359	2.00



## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2437MHz: Fundamental frequency.








ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	90.46			5.83	H	339.4	1.00
2	2,483.500	44.58	54.00	9.42	5.91	H	339.4	1.00
2	2,484.000	43.78	54.00	10.22	5.92	H	339.4	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,464.000	90.92			5.81	V	20.6	2.00
2	2,483.500	56.30	74.00	17.70	5.91	V	20.6	2.00
2	2,484.000	52.19	74.00	21.81	5.92	V	253.8	1.00





## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.000	79.17			5.82	V	14.1	2.00
2	2,483.500	33.56	54.00	20.44	5.91	V	182.2	1.00
2	2,484.000	33.16	54.00	20.84	5.92	V	182.2	1.00



## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2462MHz: Fundamental frequency.








ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	47.18	54.00	6.82	5.77	H	1	2.00
3	2,390.000	47.53	54.00	6.47	5.77	H	17.8	2.00
3	2,424.000	87.96			5.95	H	1	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,388.500	57.72	74.00	16.28	5.76	V	83	1.00
3	2,389.500	58.01	74.00	15.99	5.77	V	83	1.00
3	2,420.500	89.72			5.95	V	170.2	1.00





**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.500	37.91	54.00	16.09	5.77	V	83	1.00
3	2,390.000	38.19	54.00	15.81	5.77	V	83	1.00
3	2,420.500	76.77			5.95	V	170.2	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.









**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	48.33	74.00	25.67	37.49	54.00	16.51	13.53	V	0.9	2.00
2	7,311.000	53.15	74.00	20.85	42.71	54.00	11.29	18.89	V	0.9	2.00



**REMARKS:**


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2437MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,449.000	88.75			5.90	H	359.1	1.00
4	2,483.500	46.52	54.00	7.48	5.91	H	346	1.00
4	2,485.000	45.83	54.00	8.17	5.92	H	359.1	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,438.000	86.17			5.92	V	262.2	1.00
4	2,483.500	59.20	74.00	14.80	5.91	V	173.8	1.00
4	2,485.000	56.88	74.00	17.12	5.92	V	173.8	1.00








**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,449.500	75.58			5.89	V	100.1	2.00
4	2,483.500	37.60	54.00	16.40	5.91	V	172.6	1.00
4	2,484.500	37.01	54.00	16.99	5.92	V	172.6	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2452MHz: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA


BT-LE_2M			
CHANNEL	TX Channel 19	ODETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	44.356	29.80	40.00	10.20	-3.82	H	359.1	1.00	120.000
1	97.609	23.61	43.50	19.89	-6.35	H	4.9	1.00	120.000
1	181.320	25.52	43.50	17.98	-7.51	H	156.3	2.00	120.000
1	295.198	21.80	46.00	24.20	-1.20	H	203.7	1.00	120.000
1	440.650	25.51	46.00	20.49	3.31	H	359.1	1.00	120.000
1	691.928	28.34	46.00	17.66	3.76	H	359	2.00	120.000

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level






CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	34.220	34.44	40.00	5.56	-8.35	V	359	1.00	120.000
1	49.837	28.56	40.00	11.44	-4.53	V	1	2.00	120.000
1	77.773	30.32	40.00	9.68	-11.43	V	359	1.00	120.000
1	225.067	20.31	46.00	25.69	-4.64	V	359	2.00	120.000
1	436.333	24.99	46.00	21.01	2.88	V	1	1.00	120.000
1	812.548	36.79	46.00	9.21	5.04	V	1	1.00	120.000

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level






### ABOVE 1GHz TEST DATA

#### Note:

- For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.
- All other emissions were greater than 20dB below the limit was not recorded





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,384.000	30.73	54.00	23.27	5.73	H	6.6	2.00
5	2,390.000	30.65	54.00	23.35	5.77	H	355.8	2.00
5	2,402.000	93.30			5.85	H	359	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,377.500	45.45	74.00	28.55	5.68	V	318.9	2.00
5	2,390.000	44.76	74.00	29.24	5.77	V	273.1	1.00
5	2,402.000	90.45			5.85	V	227.6	1.00





**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,382.500	30.58	54.00	23.42	5.72	V	6.2	2.00
5	2,390.000	30.42	54.00	23.58	5.77	V	0.9	2.00
5	2,402.000	83.25			5.85	V	272.3	2.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2402MHz: Fundamental frequency.








ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	49.12	74.00	24.88	37.66	54.00	16.34	13.54	V	1.6	2.00
2	7,320.000	53.10	74.00	20.90	42.71	54.00	11.29	18.90	V	1	2.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2440MHz: Fundamental frequency.








ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	92.87			5.89	H	359	1.00
6	2,483.500	31.74	54.00	22.26	5.91	H	359	1.00
6	2,492.000	31.46	54.00	22.54	5.97	H	359	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.500	87.82			5.89	V	218.5	2.00
6	2,483.500	45.32	74.00	28.68	5.91	V	292.6	2.00
6	2,490.000	58.09	74.00	15.91	5.96	V	292.6	2.00





**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.750	82.61			5.89	V	219.7	2.00
6	2,483.500	30.42	54.00	23.58	5.91	V	8.7	2.00
6	2,493.500	30.80	54.00	23.20	5.98	V	214.5	1.00



**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2480MHz: Fundamental frequency.