



# SAR TEST REPORT

**REPORT NO.:** SA920124H01

**MODEL NO.:** WB2500

**RECEIVED:** Feb. 19, 2003

**TESTED:** Feb. 20, 2003

**APPLICANT:** AboCom Systems, Inc.

**ADDRESS:** 1F, No.21, R&D Rd.II, SBIP, Hsin-Chu,  
Tawain R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 15 pages in total except Appendix. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



## Table of Contents

|     |                                                   |   |
|-----|---------------------------------------------------|---|
| 1.  | CERTIFICATION.....                                | 3 |
| 2.  | GENERAL INFORMATION .....                         | 4 |
| 2.1 | GENERAL DESCRIPTION OF EUT .....                  | 4 |
| 2.2 | GENERAL DESCRIPTION OF APPLIED STANDARDS .....    | 4 |
| 2.3 | GENERAL INFORMATION OF THE SAR SYSTEM .....       | 5 |
| 2.4 | GENERAL DESCRIPTION OF THE PROBE SCAN RULE .....  | 6 |
| 3.  | DESCRIPTION OF TEST MODES AND CONFIGURATIONS..... | 6 |
| 4.  | DESCRIPTION OF SUPPORT UNITS .....                | 6 |
| 5.  | TEST RESULTS.....                                 | 6 |
| 5.1 | TEST PROCEDURES .....                             | 6 |
| 5.2 | MEASURED SAR RESULT.....                          | 6 |
| 5.3 | SAR LIMITS.....                                   | 6 |
| 5.4 | EUT CONDUCTED POWER VARIATION .....               | 6 |
| 5.5 | TISSUE .....                                      | 6 |
| 5.6 | TEST EQUIPMENT FOR TISSUE PROPERTY .....          | 6 |
| 6.  | SYSTEM VALIDATION.....                            | 6 |
| 7.  | MEASUREMENT UNCERTAINTIES.....                    | 6 |
| 8.  | INFORMATION ON THE TESTING LABORATORIES.....      | 6 |

APPENDIX A: TEST CONFIGURATIONS AND TEST DATA  
 APPENDIX B: ADT SAR MEASUREMENT SYSTEM  
 APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION  
 APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION



## 1. CERTIFICATION

**PRODUCT :** 802.11b Wireless CardBus PC Card  
**MODEL NO. :** WB2500  
**BRAND NAME :** AboCom  
**APPLICANT :** AboCom Systems, Inc.  
**STANDARDS :** 47 CFR Part 2 (Section 2.1093), FCC OET Bulletin 65, Supplement C (01-01), RSS-102

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility on 20<sup>th</sup> Feb. 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate, and it was tested according to the standards listed above. This device was found to be in compliance with the Specific Absorption Rate (SAR) requirement specified in FCC part 2.1093 under General Population / Uncontrolled Exposure condition.

**CHECKED BY :** Bunny Yao **DATE :** Feb. 24, 2003  
Bunny Yao

**APPROVED BY :** Dr. Alan Lane **DATE :** Feb. 24, 2003  
Dr. Alan Lane, Manager

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                               |                                  |
|-------------------------------|----------------------------------|
| <b>PRODUCT</b>                | 802.11b Wireless CardBus PC Card |
| <b>MODEL NO.</b>              | WB2500                           |
| <b>POWER SUPPLY</b>           | 3.3VDC powered by host equipment |
| <b>CLASSIFICATION</b>         | Portable device, production unit |
| <b>MODULATION TYPE</b>        | BPSK, QPSK, CCK                  |
| <b>RADIO TECHNOLOGY</b>       | DSSS                             |
| <b>TRANSFER RATE</b>          | 1/2/5.5/11Mbps                   |
| <b>FREQUENCY RANGE</b>        | 2412MHz ~ 2462MHz                |
| <b>NUMBER OF CHANNEL</b>      | 11                               |
| <b>CONDUCTED OUTPUT POWER</b> | 43.85mW                          |
| <b>ANTENNA TYPE</b>           | Patch Antenna                    |
| <b>PEAK SAR</b>               | 0.612W/kg                        |
| <b>DATA CABLE</b>             | NA                               |
| <b>I/O PORTS</b>              | PCMCIA                           |
| <b>ASSOCIATED DEVICES</b>     | NA                               |

### 2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to the specifications of the manufacturer, this product must comply with the requirements of the following standards:

**FCC 47 CFR Part 2 (2.1093)**  
**FCC OET Bulletin 65, Supplement C (01- 01)**  
**RSS-102**

All tests have been performed and recorded as per the above standards.



## 2.3 GENERAL INFORMATION OF THE SAR SYSTEM

DASY3 (software 3.1d) consists of high precision robotics system, probe alignment sensor, phantom, robot controller, controlled PC and near-field probe. The robot includes six axis that can move to the precision position of the DASY3 software defined. The DASY3 software can define the area which is detected by the probe. The robot is connected to controlled box. Controlled PC is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement, surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

### ET3DV6 ISOTROPIC E-FIELD PROBE

|                                  |                                                                                                                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>              | Symmetrical design with triangular core.<br>Built-in optical fiber for surface detection system.<br>Built-in shielding against static charges.<br>PEEK enclosure material (resistant to organic solvents, e.g., glycoether). |
| <b>Calibration</b>               | Basic Broad Band Calibration in air: 10-2500 MHz<br>Conversion Factors (CF) for HSL 900 and HSL 1800<br>CF-Calibration for other liquids and frequencies upon request                                                        |
| <b>Frequency</b>                 | 10 MHz to 3 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)                                                                                                                                                                   |
| <b>Directivity</b>               | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.4$ dB in HSL (rotation normal to probe axis)                                                                                                                      |
| <b>Dynamic Range</b>             | 5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                                                                           |
| <b>Optical Surface Detection</b> | $\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces                                                                                                                                         |
| <b>Dimensions</b>                | Overall length: 330 mm (Tip Length: 16 mm)<br>Tip diameter: 6.8 mm (Body diameter: 12 mm)<br>Distance from probe tip to dipole centers: 2.7 mm                                                                               |
| <b>Application</b>               | General dosimetric measurements up to 3 GHz<br>Compliance tests of mobile phones<br>Fast automatic scanning in arbitrary phantoms (ET3DV6)                                                                                   |

## TWIN SAM V4.0

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot. |
| <b>Shell Thickness</b> | $2 \pm 0.2$ mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Filling Volume</b>  | Approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Dimensions</b>      | Height: 810 mm; Length: 1000 mm; Width: 500 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## SYSTEM VALIDATION KITS: D900V2 – D2450V2

|                         |                                                                                                                                                                                                                                       |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>     | Symmetrical dipole with 1/4 balun<br>Enables measurement of feedpoint impedance with NWA<br>Matched for use near flat phantoms filled with brain simulating solutions<br>Includes distance holder and tripod adaptor                  |
| <b>Calibration</b>      | Calibrated SAR value for specified position and input power at the flat phantom in brain simulating solutions                                                                                                                         |
| <b>Frequency</b>        | 900, 1800, 1900, 2450 MHz                                                                                                                                                                                                             |
| <b>Return Loss</b>      | > 20 dB at specified validation position                                                                                                                                                                                              |
| <b>Power Capability</b> | > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )                                                                                                                                                                           |
| <b>Options</b>          | Dipoles for other frequencies or solutions and other calibration conditions upon request                                                                                                                                              |
| <b>Dimensions</b>       | D900V2: dipole length: 149 mm; overall height: 83.3mm<br>D1800V2: dipole length: 72 mm; overall height: 41.2 mm<br>D1900V2: dipole length: 68 mm; overall height: 39.5 mm<br>D2450V2: dipole length: 51.5 mm; overall height: 30.6 mm |



## 2.4 GENERAL DESCRIPTION OF THE PROBE SCAN RULE

The maximum search is automatically performed after each coarse scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the coarse scan measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations.

The 1g peak evaluations are only available for the predefined cube 5x5x7 scans. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 32x32x30mm contains about 35g of tissue. The first procedure is an extrapolation (incl. boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid (35000 points). In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is then moved around until the highest averaged SAR is found. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

### 3. DESCRIPTION OF TEST MODES AND CONFIGURATIONS

|                                                                      |                                                                             |
|----------------------------------------------------------------------|-----------------------------------------------------------------------------|
| <b>CARRIER MODULATION UNDER TEST</b>                                 | DSSS                                                                        |
| <b>CREST FACTOR</b>                                                  | 1.0                                                                         |
| <b>CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER</b> | 43.85mW / Ch1: 2412MHz<br>42.75mW / Ch6: 2437MHz<br>41.49mW / Ch11: 2462MHz |
| <b>ANTENNA CONFIGURATION</b>                                         | Patch Antenna                                                               |
| <b>EUT POWER SOURCE</b>                                              | From Host Notebook                                                          |
| <b>HOST POWER SOURCE</b>                                             | Fully Charged Battery                                                       |

The following test configurations have been applied in this test report:

- Mode 1 EUT in the PCMCIA slot of the notebook, the bottom of the notebook contact the bottom of the flat phantom with 0 cm separation distance.
- Mode 2 EUT in the PCMCIA slot of the notebook, the keyboard face of the notebook is perpendicular to the bottom of the flat phantom and the left side (PCMCIA slot) of notebook is facing the phantom. The separation distance is 1.5 cm between the left side of the notebook and the bottom of the flat phantom.
- Mode 3 EUT in the PCMCIA slot of the notebook, the keyboard face of the notebook is perpendicular to the bottom of the flat phantom and the left side of notebook is facing the phantom. The separation distance is 0 cm between the left side (PCMCIA slot) of notebook and the bottom of the flat phantom.

**NOTE:** Please reference "APPENDIX A" for the photos of test configuration.



#### 4. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO.                 | FCC ID              |
|-----|---------|-------|-----------|----------------------------|---------------------|
| 1   | NB      | ACER  | 2009      | 9141Q01J0C1380052EK00<br>- | FCC DoC<br>APPROVED |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|-----------------------------------------------------|
| 1   | NA                                                  |

## 5. TEST RESULTS

### 5.1 TEST PROCEDURES

The SAR value was calculated via the 3D spline interpolation algorithm which has been implemented in the software of DASY3 SAR measurement system manufactured and calibrated by Schmid & Partner.

A coarse scan with 20mm x 20mm grid was performed for the highest spatial SAR location. A fine scan with 32mm x 32mm x 30mm volume was performed for SAR value averaged over 1g and 10g spatial volumes.

### 5.2 MEASURED SAR RESULT

| VIRONMENTAL<br>ONDITION |         | Temperature : 23.1°C, Humidity : 53%RH |                           |
|-------------------------|---------|----------------------------------------|---------------------------|
| TESTED BY               |         | Bunny Yao                              |                           |
| MODE                    | CHANNEL | FREQUENCY (MHz)                        | MEASURED 1g SAR<br>(W/kg) |
| 1                       | 1       | 2412                                   | 0.261                     |
|                         | 6       | 2437                                   | 0.265                     |
|                         | 11      | 2462                                   | 0.245                     |
| 2                       | 1       | 2412                                   | 0.107                     |
|                         | 6       | 2437                                   | 0.106                     |
|                         | 11      | 2462                                   | 0.099                     |
| 3                       | 1       | 2412                                   | 0.612                     |
|                         | 6       | 2437                                   | 0.573                     |
|                         | 11      | 2462                                   | 0.503                     |

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix for the photo of the test configuration and also the data.

### 5.3 SAR LIMITS

| HUMAN EXPOSURE                                             | SAR (W/kg)                                               |                                                  |
|------------------------------------------------------------|----------------------------------------------------------|--------------------------------------------------|
|                                                            | (General Population / Uncontrolled Exposure Environment) | (Occupational / controlled Exposure Environment) |
| Spatial Average (whole body)                               | 0.08                                                     | 0.4                                              |
| Spatial Peak (averaged over 1 g)                           | <b>1.6</b>                                               | 8.0                                              |
| Spatial Peak (hands/wrists/feet/ankles averaged over 10 g) | 4.0                                                      | 20.0                                             |

### 5.4 EUT CONDUCTED POWER VARIATION

The variation of the EUT conducted power measured before and after SAR testing should not over 5%. The test procedures for conducted power level is described in FCC rule part 2.1046.

The maximum variation in this testing is listed in the following table.

| Channel | Conducted Power (Before) | Conducted Power (After) | Variation (%) |
|---------|--------------------------|-------------------------|---------------|
| 1       | 43.85                    | 43.3                    | -1.25         |
| 6       | 42.75                    | 43.0                    | 0.58          |
| 11      | 41.49                    | 42.1                    | 0.93          |

## 5.5 TISSUE

| Tissue Components |        |        |
|-------------------|--------|--------|
| Ingredient        | Brain  | Muscle |
| Water             | 55.20% | 69.95% |
| Glycol Monobutyl  | 44.80% | 30.00% |
| Salt              | -      | 0.05%  |

The tissue of 2450MHz for brain and body was well prepared according to the standard procedures. The required and measured dielectric parameters are listed in this table.

|                               | Brain         |          | Muscle        |          |
|-------------------------------|---------------|----------|---------------|----------|
|                               | Required      | Measured | Required      | Measured |
| Permittivity ( $\epsilon_r$ ) | 39.2 $\pm$ 5% | NA       | 52.7 $\pm$ 5% | 52.4     |
| Conductivity (s)              | 1.8 $\pm$ 5%  | NA       | 1.95 $\pm$ 5% | 1.98     |

The measured parameters of the used tissue.

| Tissue Prepared and Measured on 20 <sup>th</sup> Feb. 2003 |       |             |        |            |
|------------------------------------------------------------|-------|-------------|--------|------------|
|                                                            | Brain |             | Muscle |            |
|                                                            | Value | Freq. (MHz) | Value  | Freq.(MHz) |
| Permittivity                                               | NA    | NA          | 52.8   | 2412       |
|                                                            | NA    | NA          | 52.6   | 2437       |
|                                                            | NA    | NA          | 52.4   | 2462       |
| Conductivity                                               | NA    | NA          | 1.93   | 2412       |
|                                                            | NA    | NA          | 1.97   | 2437       |
|                                                            | NA    | NA          | 2.01   | 2462       |

## 5.6 TEST EQUIPMENT FOR TISSUE PROPERTY

| Item | Name             | Provider | Type   | Series No. | Calibrated Until |
|------|------------------|----------|--------|------------|------------------|
| 1    | Network Analyzer | Agilent  | 8720ES | NA         | May 6, 2003      |
| 2    | Dielectric Probe | Agilent  | 85070C | NA         | NA               |

## 6. SYSTEM VALIDATION

The system validation was performed in the flat phantom with equipment listed in the following table. Since the SAR value is calculated from the measured electric field, dielectric constant and conductivity of the body tissue, and the SAR is proportional to the square of the electric field. So, the SAR value will be also proportional to the RF power input to the system validation dipole under the same test environment. In our system validation test, 50mW RF input power was used instead of 250mW used by Schmid & Partner, then the measured SAR will be linearly extrapolated to that of 250mW RF power.

### 6.1 TEST EQUIPMENT

| Item | Name              | Provider             | Type         | Series No. | Calibrated Until |
|------|-------------------|----------------------|--------------|------------|------------------|
| 1    | SAM Phantom       | S & P                | QD000 P40 CA | PT-1150    | NA               |
| 2    | Validation Dipole | S & P                | D2450V2      | 716        | Sept. 25, 2004   |
| 3    | Signal Generator  | R & S                | SMP04        | 10001      | May 5, 2003      |
| 4    | E-Field Probe     | S & P                | ET3DV6       | 1687       | Sept. 27, 2003   |
| 5    | DAE               | S & P                | DAE3 V1      | 510        | April 10, 2004   |
| 6    | Robot Positioner  | Staubli<br>Unimation | NA           | NA         | NA               |

### 6.2 VALIDATION RESULT

|                                               |                                        |               |                     |
|-----------------------------------------------|----------------------------------------|---------------|---------------------|
| ENVIRONMENTAL ONDICTION                       | Temperature : 23.1°C, Humidity : 53%RH |               |                     |
| TESTED BY                                     | Bunny Yao                              |               |                     |
| 2450MHz System Validation Test in Body Tissue |                                        |               |                     |
| Required                                      | Measured                               | Deviation (%) | Separation Distance |
| 14.30 (1g)                                    | 13.5                                   | -5.92         | 1.0cm               |
| 6.74 (10g)                                    | 6.3                                    | -6.98         | 1.0cm               |

**NOTE:** Please see Appendix for the photo of system validation test.

## 7. MEASUREMENT UNCERTAINTIES

|                                      | Uncertainty Value | Probability Distribution | Divisor    | C <sub>i</sub> | Standard Uncertainty |
|--------------------------------------|-------------------|--------------------------|------------|----------------|----------------------|
| <b>Test Sample Related</b>           |                   |                          |            |                |                      |
| Test Sample Positioning              | ±6%               | Normal                   | 1          | 1              | ±6%                  |
| Drift of Output Power                | ±5%               | Rectangular              | $\sqrt{3}$ | 1              | ±2.9%                |
| <b>Phantom and Setup</b>             |                   |                          |            |                |                      |
| Phantom Uncertainty                  | ±0%               | Rectangular              | $\sqrt{3}$ | 1              | ±0%                  |
| Liquid Conductivity(target)          | ±5%               | Rectangular              | $\sqrt{3}$ | 0.5            | ±1.4%                |
| Liquid Conductivity(meas)            | ±10%              | Rectangular              | $\sqrt{3}$ | 0.5            | ±2.9%                |
| Liquid Permittivity(target)          | ±5%               | Rectangular              | $\sqrt{3}$ | 0.5            | ±1.4%                |
| Liquid Permittivity(meas)            | ±5%               | Rectangular              | $\sqrt{3}$ | 0.5            | ±1.4%                |
| RF Ambient Conditions                | ±3%               | Rectangular              | $\sqrt{3}$ | 1              | ±1.7%                |
| <b>System Check</b>                  |                   |                          |            |                |                      |
| Calibration                          | ± 2.6 %           | normal                   | 1          | 1              | ± 2.6 %              |
| Axial isotropy                       | ± 2.3 %           | rectangular              | $\sqrt{3}$ | $(1-cp)^{1/2}$ | ± 0.9 %              |
| Hemispherical isotropy               | ± 9.6 %           | rectangular              | $\sqrt{3}$ | $\sqrt{cp}$    | ± 3.9 %              |
| Spatial resolution                   | ± 0.5 %           | rectangular              | $\sqrt{3}$ | 1              | ± 0.3 %              |
| Boundary effect                      | ± 4.0 %           | rectangular              | $\sqrt{3}$ | 1              | ± 6.4 %              |
| Linearity                            | ± 4.7 %           | rectangular              | $\sqrt{3}$ | 1              | ± 2.7 %              |
| Detection Limit                      | ± 2.0 %           | rectangular              | $\sqrt{3}$ | 1              | ± 1.2 %              |
| Readout Electronics                  | ± 1.0 %           | normal                   | 1          | 1              | ± 1.0 %              |
| Mechanical Constrains of Robot       | ± 0.4 %           | normal                   | 1          | 1              | ± 0.4 %              |
| Probe positioning                    | ± 5.0 %           | rectangular              | $\sqrt{3}$ | 1              | ± 2.9 %              |
| Extrapolation/Integration            | ± 3.9 %           | rectangular              | $\sqrt{3}$ | 1              | ± 2.3 %              |
| Dipole/Liquid Distance               | ± 1.0 %           | rectangular              | $\sqrt{3}$ | 1              | ± 0.6 %              |
| Dipole Input Power                   | ± 4.7 %           |                          | 1          | 1              | ± 4.7 %              |
| Liquid conductivity (target)         | ± 5.0 %           | rectangular              | $\sqrt{3}$ | 0.6            | ± 1.7 %              |
| Liquid conductivity (meas.)          | ± 10 %            | rectangular              | $\sqrt{3}$ | 0.6            | ± 3.5 %              |
| Liquid permittivity (target)         | ± 5.0 %           | rectangular              | $\sqrt{3}$ | 0.6            | ± 1.7 %              |
| Liquid permittivity (meas.)          | ± 5.0 %           | rectangular              | $\sqrt{3}$ | 0.6            | ± 1.7 %              |
| RF Ambient condition                 | ± 3.0 %           | normal                   | 1          | 1              | ± 1.7 %              |
| <b>Combined Standard Uncertainty</b> |                   |                          |            |                | ±12.4 %              |
| <b>Expanded Uncertainty (K=2)</b>    |                   |                          |            |                | ±24.9 %              |



## 8. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

|                    |                 |
|--------------------|-----------------|
| <b>USA</b>         | FCC, NVLAP      |
| <b>Germany</b>     | TUV Rheinland   |
| <b>Japan</b>       | VCCI            |
| <b>New Zealand</b> | MoC             |
| <b>Norway</b>      | NEMKO           |
| <b>R.O.C.</b>      | BSMI, DGT, CNLA |

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.

## APPENDIX A: TEST CONFIGURATIONS AND TEST DATA

### A1: TEST CONFIGURATION

#### Mode 1






## Mode 2



## Mode 3



## EUT Photo




A2: TEST DATA

02/20/03

802.11b Wireless CardBus PC Card Mode 1

Separation distance : 0mm (Laptop PC to Phantom)  
Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade  
SAM Phantom; Flat Section; Position: (90°,90°);  
Antenna type : Internal Antenna  
Modulation type : DSSS  
Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0  
Test Frequency : 2412 MHz  
Liquid parameters : Body 2412 MHz  $\sigma = 1.93 \text{ mho/m}$   $\epsilon_r = 52.8$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse : Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7: SAR (1g): 0.261 mW/g, SAR (10g): 0.136 mW/g, (Worst-case extrapolation)  
Powerdrift: 0.03 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 1

Separation distance : 0mm (Laptop PC to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2437 MHz

Liquid parameters : Body 2437 MHz  $\sigma = 1.97$  mho/m  $\epsilon_r = 52.6$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse : Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.265 mW/g, SAR (10g): 0.134 mW/g, (Worst-case extrapolation)


Powerdrift: -0.12 dB



02/20/03

# 802.11b Wireless CardBus PC Card Mode 1

Separation distance : 0mm (Laptop PC to Phantom)  
Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade  
SAM Phantom; Flat Section; Position: (90°,90°);  
Antenna type : Internal Antenna  
Modulation type : DSSS  
Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0  
Test Frequency : 2462 MHz  
Liquid parameters : Body 2462 MHz  $\sigma = 2.01 \text{ mho/m}$   $\epsilon_r = 52.4$   $\rho = 1.00 \text{ g/cm}^3$   
Coarse : Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7: SAR (1g): 0.245 mW/g, SAR (10g): 0.125 mW/g, (Worst-case extrapolation)  
Powerdrift: 0.03 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 2

Separation distance : 15mm (EUT tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2412 MHz

Liquid parameters : Body 2412 MHz  $\sigma = 1.93$  mho/m  $\epsilon_r = 52.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.107 mW/g, SAR (10g): 0.0581 mW/g, (Worst-case extrapolation)

Powerdrift: -0.12 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 2

Separation distance : 15mm (EUT tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2437 MHz

Liquid parameters : Body 2437 MHz  $\sigma = 1.97$  mho/m  $\epsilon_r = 52.6$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.106 mW/g, SAR (10g): 0.0574 mW/g, (Worst-case extrapolation)

Powerdrift: -0.04 dB





02/20/03

## 802.11b Wireless CardBus PC Card Mode 2

Separation distance : 15mm (EUT tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2462 MHz

Liquid parameters : Body 2462 MHz  $\sigma = 2.01$  mho/m  $\epsilon_r = 52.4$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.0985 mW/g, SAR (10g): 0.0521 mW/g, (Worst-case extrapolation)

Powerdrift: -0.02 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 3

Separation distance : 0mm (EUT Tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2412 MHz

Liquid parameters : Body 2412 MHz  $\sigma = 1.93$  mho/m  $\epsilon_r = 52.8$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.612 mW/g, SAR (10g): 0.284 mW/g, (Worst-case extrapolation)

Powerdrift: -0.03 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 3

Separation distance : 0mm (EUT Tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2437 MHz

Liquid parameters : Body 2437 MHz  $\sigma = 1.97$  mho/m  $\epsilon_r = 52.6$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.573 mW/g, SAR (10g): 0.271 mW/g, (Worst-case extrapolation)

Powerdrift: 0.05 dB



02/20/03

## 802.11b Wireless CardBus PC Card Mode 3

Separation distance : 0mm (EUT Tip to Phantom)

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

SAM Phantom; Flat Section; Position: (90°,90°);

Antenna type : Internal Antenna

Modulation type : DSSS

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0


Test Frequency : 2462 MHz

Liquid parameters : Body 2462 MHz  $\sigma = 2.01$  mho/m  $\epsilon_r = 52.4$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 5x5x7: SAR (1g): 0.503 mW/g, SAR (10g): 0.246 mW/g, (Worst-case extrapolation)

Powerdrift: 0.05 dB



### A3: VALIDATION TEST DATA

02/20/03

#### Validation Dipole D2450V2 SN:716,d=10mm

SAM; Flat

Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade

Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0

Liquid parameters : Body 2450 MHz  $\sigma = 1.98$  mho/m  $\epsilon_r = 52.4$   $\rho = 1.00$  g/cm<sup>3</sup>


Modulation type : CW

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cubes (2): Peak: 5.41 mW/g  $\pm 0.02$  dB, SAR (1g): 2.70 mW/g  $\pm 0.03$  dB, SAR (10g): 1.26 mW/g  $\pm 0.06$  dB, (Worst-case extrapolation)

Penetration depth: 7.3 (7.0, 8.2) [mm]


Powerdrift: -0.01 dB



02/20/03

802.11b Wireless CardBus PC Card Mode 3


Separation distance : 0mm (EUT Tip to Phantom)  
Air temperature : 23.1 degrees centigrade ; Liquid temperature : 22.2 degrees centigrade  
SAM Phantom; Section; Position: ;  
Antenna type : Internal Antenna  
Modulation type : DSSS  
Probe: ET3DV6 - SN1687; ConvF(4.40,4.40,4.40); Crest factor: 1.0  
Test Frequency : 2412 MHz  
Liquid parameters : Body 2412 MHz  $\sigma = 1.93 \text{ mho/m}$   $\epsilon_r = 52.8$   $\rho = 1.00 \text{ g/cm}^3$   
Z-Axis: Dx = 0.0, Dy = 0.0, Dz = 2.0  
: , ()



## APPENDIX B: ADT SAR MEASUREMENT SYSTEM



## APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION





## APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION

### D1: SAM PHANTOM

#### Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

#### Certificate of conformity / First Article Inspection

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Item                  | SAM Twin Phantom V4.0                                                    |
| Type No               | QD 000 P40 CA                                                            |
| Series No             | TP-1150 and higher                                                       |
| Manufacturer / Origin | Untersee Composites<br>Hauptstr. 69<br>CH-8559 Fruthwilen<br>Switzerland |

#### Tests

The series production process used allows the limitation to test of first articles. Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

| Test                 | Requirement                                                                             | Details                                                              | Units tested                |
|----------------------|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------|-----------------------------|
| Shape                | Compliance with the geometry according to the CAD model.                                | IT'IS CAD File (*)                                                   | First article, Samples      |
| Material thickness   | Compliant with the requirements according to the standards                              | 2mm +/- 0.2mm in specific areas                                      | First article, Samples      |
| Material parameters  | Dielectric parameters for required frequencies                                          | 200 MHz – 3 GHz<br>Relative permittivity < 5<br>Loss tangent < 0.05. | Material sample<br>TP 104-5 |
| Material resistivity | The material has been tested to be compatible with the liquids defined in the standards | Liquid type HSL 1800 and others according to the standard.           | Pre-series, First article   |

#### Standards

- [1] CENELEC EN 50361
- [2] IEEE P1528-200x draft 6.5
- [3] IEC PT 62209 draft 0.9
- (\*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of [1] and [3].

#### Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date 28.02.2002

Signature / Stamp

*F. Bernhardt*

Schmid & Partner  
Engineering AG

Zeughausstrasse 43, CH-8004 Zurich  
Tel. +41 1 245 97 00, Fax +41 1 245 97 79

*Thomas Kofler*

## D2: 2450MHz SYSTEM VALIDATION DIPOLE

### Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

### Calibration Certificate

#### 2450 MHz System Validation Dipole

Type:

D2450V2

Serial Number:

716

Place of Calibration:

Zurich

Date of Calibration:

September 26, 2002

Calibration Interval:

24 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

D. Vella

Approved by:

Antonio Kaya

**Schmid & Partner  
Engineering AG**

**Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79**

---

**DASY**

**Dipole Validation Kit**

**Type: D2450V2**

**Serial: 716**

**Manufactured: September 10, 2002**  
**Calibrated: September 26, 2002**

## **1. Measurement Conditions**

The measurements were performed in the flat section of the new SAM twin phantom filled with head simulating solution of the following electrical parameters at 2450 MHz:

|                       |                   |            |
|-----------------------|-------------------|------------|
| Relative permittivity | <b>37.7</b>       | $\pm 5\%$  |
| Conductivity          | <b>1.88 mho/m</b> | $\pm 10\%$ |

The DASY System with a dosimetric E-field probe ET3DV6 (SN:1507, conversion factor 5.0 at 2450 MHz) was used for the measurements.

The dipole feedpoint was positioned below the center marking and oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.

### **2.1. SAR Measurement with DASY3 System**

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the worst-case extrapolation are:

|                                                    |                  |
|----------------------------------------------------|------------------|
| averaged over 1 cm <sup>3</sup> (1 g) of tissue:   | <b>57.2 mW/g</b> |
| averaged over 10 cm <sup>3</sup> (10 g) of tissue: | <b>26.4 mW/g</b> |

### **2.2 SAR Measurement with DASY4 System**

Standard SAR-measurements were performed according to the measurement conditions described in section 1. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the advanced extrapolation are:

|                                                    |                  |
|----------------------------------------------------|------------------|
| averaged over 1 cm <sup>3</sup> (1 g) of tissue:   | <b>54.0 mW/g</b> |
| averaged over 10 cm <sup>3</sup> (10 g) of tissue: | <b>25.2 mW/g</b> |

### **3. Dipole impedance and return loss**

The impedance was measured at the SMA-connector with a network analyzer and numerically transformed to the dipole feedpoint. The transformation parameters from the SMA-connector to the dipole feedpoint are:

|                      |                 |                                       |
|----------------------|-----------------|---------------------------------------|
| Electrical delay:    | <b>1.148 ns</b> | (one direction)                       |
| Transmission factor: | <b>0.982</b>    | (voltage transmission, one direction) |

The dipole was positioned at the flat phantom sections according to section 1 and the distance holder was in place during impedance measurements.

|                                  |                                |
|----------------------------------|--------------------------------|
| Feedpoint impedance at 2450 MHz: | $\text{Re}\{Z\} = 54.1 \Omega$ |
|                                  | $\text{Im}\{Z\} = 2.4 \Omega$  |
| Return Loss at 2450 MHz          | <b>- 26.8 dB</b>               |

### **4. Measurement Conditions**

The measurements were performed in the flat section of the new SAM twin phantom filled with body simulating solution of the following electrical parameters at 2450 MHz:

|                       |                   |            |
|-----------------------|-------------------|------------|
| Relative permittivity | <b>52.4</b>       | $\pm 5\%$  |
| Conductivity          | <b>1.99 mho/m</b> | $\pm 10\%$ |

The DASY System with a dosimetric E-field probe ET3DV6 (SN:1507, conversion factor 4.5 at 2450 MHz) was used for the measurements.

The dipole feedpoint was positioned below the center marking and oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10mm from dipole center to the solution surface. The included distance holder was used during measurements for accurate distance positioning.

The coarse grid with a grid spacing of 20mm was aligned with the dipole. The 5x5x7 fine cube was chosen for cube integration. Probe isotropy errors were cancelled by measuring the SAR with normal and 90° turned probe orientations and averaging.

The dipole input power (forward power) was 250mW  $\pm 3\%$ . The results are normalized to 1W input power.

### **5.1. SAR Measurement with DASY3 System**

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the worst-case extrapolation are:

|                                                    |                  |
|----------------------------------------------------|------------------|
| averaged over 1 cm <sup>3</sup> (1 g) of tissue:   | <b>57.2 mW/g</b> |
| averaged over 10 cm <sup>3</sup> (10 g) of tissue: | <b>27.0 mW/g</b> |

### **5.2 SAR Measurement with DASY4 System**

Standard SAR-measurements were performed according to the measurement conditions described in section 4. The results (see figure supplied) have been normalized to a dipole input power of 1W (forward power). The resulting averaged SAR-values measured with the dosimetric probe ET3DV6 SN:1507 and applying the advanced extrapolation are:

|                                                    |                  |
|----------------------------------------------------|------------------|
| averaged over 1 cm <sup>3</sup> (1 g) of tissue:   | <b>51.6 mW/g</b> |
| averaged over 10 cm <sup>3</sup> (10 g) of tissue: | <b>25.0 mW/g</b> |

### **6. Dipole impedance and return loss**

The dipole was positioned at the flat phantom sections according to section 4 (with body tissue inside the phantom) and the distance holder was in place during impedance measurements.

|                                  |                                         |
|----------------------------------|-----------------------------------------|
| Feedpoint impedance at 2450 MHz: | <b>Re{Z} = 49.6 <math>\Omega</math></b> |
|                                  | <b>Im {Z} = 4.2 <math>\Omega</math></b> |
| Return Loss at 2450 MHz          | <b>- 27.5 dB</b>                        |

25 Sep 2002 11:22:10

CH1 S11 1 U FS

1: 54.092  $\Omega$  2: 3984  $\Omega$  155.81  $\mu$ H

2 450.000 000 MHz

Del


PRm

Cor

Avg

16

↑




CH2 S11 LOG 5 dB/REF 0 dB 1: -26.816 dB 2 450.000 000 MHz

PRm

Cor

↑



START 2 250.000 000 MHz

STOP 2 650.000 000 MHz

## D3: DOSIMETRIC E-FILED PROBE

### Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

## Calibration Certificate

### Dosimetric E-Field Probe

Type:

ET3DV6

Serial Number:

1687

Place of Calibration:

Zurich

Date of Calibration:

June 5, 2002

Calibration Interval:

12 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

D. Vellen

Approved by:

Alain Kofler



**Probe ET3DV6**


**SN:1687**

|                   |              |
|-------------------|--------------|
| Manufactured:     | May 28, 2002 |
| Last calibration: | June 5, 2002 |


**Calibrated for System DASY3**

ET3DV6 SN:1687

June 5, 2002



### Isotropy Error ( $\Phi$ ), $\theta = 0^\circ$




ET3DV6 SN:1687



June 5, 2002

## Frequency Response of E-Field

(TEM – Cell:ifi110, Waveguide R22)



# Dynamic Range f (SAR<sub>brain</sub>) (Waveguide R22)



## Calibration Certificate

### Dosimetric E-Field Probe

Type:

**ET3DV6**

Serial Number:

**1687**

Place of Calibration:

**Zurich**

Date of Calibration:

**September 28, 2002**

Calibration Interval:

**12 months**

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

*D. Vekken*

Approved by:

*Alvaro Klotz*

**Probe ET3DV6**

**SN:1687**

**Additonal Conversion Factors**

**Calibrated: September 28, 2002**


**Calibrated for DASY Systems**

**(Note: non-compatible with DASY2 system!)**

ET3DV6 SN:1687

September 28, 2002

## Conversion Factor Assessment


**Head**
**2450 MHz**
 $\epsilon_r = 39.2 \pm 5\%$ 
 $\sigma = 1.80 \pm 5\% \text{ mho/m}$ 

 ConvF X      **4.9**  $\pm 8.9\%$  (k=2)

Boundary effect:

 ConvF Y      **4.9**  $\pm 8.9\%$  (k=2)

 Alpha      **1.00**

 ConvF Z      **4.9**  $\pm 8.9\%$  (k=2)

 Depth      **1.70**
**Body**
**2450 MHz**
 $\epsilon_r = 52.7 \pm 5\%$ 
 $\sigma = 1.95 \pm 5\% \text{ mho/m}$ 

 ConvF X      **4.4**  $\pm 8.9\%$  (k=2)

Boundary effect:

 ConvF Y      **4.4**  $\pm 8.9\%$  (k=2)

 Alpha      **1.00**

 ConvF Z      **4.4**  $\pm 8.9\%$  (k=2)

 Depth      **1.65**