

# Wireless test report – 392760-1TRFWL

Applicant:

**Silicon Laboratories Finland Oy**

Product type:

**Radio module**

Model:

**BGM13P32A**

FCC ID:

**QOQ-BGM13P**

ISED Registration number:

**5123A-BGM13P**

Specifications:

◆ **FCC 47 CFR Part 15 Subpart C, §15.247 – partial testing**

Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz

◆ **RSS-247, Issue 2, Feb 2017, Section 5 – partial testing**

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs)  
and Licence-Exempt Local Area Network (LE-LAN) Devices5) Standard specifications for frequency hopping systems and digital transmission systems operating in the  
bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz

Date of issue: April 22, 2020

**Yong Huang, Wireless/EMC Specialist**

Tested by



Signature

**Andrey Adelberg, Senior Wireless/EMC Specialist**

Reviewed by

Signature

---

**Test location(s)**

---

Company name	Nemko Canada Inc.
Site name	Montreal
Address	292 Labrosse Avenue
City	Pointe-Claire
Province	Quebec
Postal code	H9R 5L8
Country	Canada
Telephone	+1 514 694 2684
Facsimile	+1 514 694 3528
Toll free	+1 800 563 6336
Website	www.nemko.com
Site number (3 m SAC)	FCC: CA2041; IC: 2040G-5

---

**Limits of responsibility**

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

---

**Copyright notification**

---

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

## Table of contents

<b>Table of contents .....</b>	<b>3</b>
<b>Section 1. Report summary .....</b>	<b>4</b>
1.1 Applicant and manufacturer .....	4
1.2 Test specifications .....	4
1.3 Test methods.....	4
1.4 Statement of compliance .....	4
1.5 Exclusions.....	4
1.6 Test report revision history .....	4
<b>Section 2. Summary of test results.....</b>	<b>5</b>
2.1 FCC Part 15 Subpart C, general requirements test results.....	5
2.2 FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS) .....	5
2.3 ISSED RSS-Gen, Issue 5, test results.....	6
2.4 ISSED RSS-247, Issue 2, test results for digital transmission systems (DTS).....	6
<b>Section 3. Equipment under test (EUT) details .....</b>	<b>7</b>
3.1 Sample information.....	7
3.2 EUT information .....	7
3.3 Technical information .....	7
3.4 Product description and theory of operation .....	8
3.5 EUT exercise details.....	8
3.6 EUT setup diagram .....	9
3.7 EUT sub assemblies .....	9
<b>Section 4. Engineering considerations.....</b>	<b>10</b>
4.1 Modifications incorporated in the EUT.....	10
4.2 Technical judgment .....	10
4.3 Deviations from laboratory tests procedures .....	10
<b>Section 5. Test conditions .....</b>	<b>11</b>
5.1 Atmospheric conditions .....	11
5.2 Power supply range.....	11
<b>Section 6. Measurement uncertainty .....</b>	<b>12</b>
6.1 Uncertainty of measurement .....	12
<b>Section 7. Test equipment .....</b>	<b>13</b>
7.1 Test equipment list.....	13
<b>Section 8. Testing data .....</b>	<b>14</b>
8.1 FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies .....	14
8.2 FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement.....	16
8.3 FCC 15.247(b) and RSS-247 5.4(d) Transmitter output power and e.i.r.p. requirements for DTS in 2 GHz .....	17
8.4 FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions.....	22
<b>Section 9. Block diagrams of test set-ups .....</b>	<b>36</b>
9.1 Radiated emissions set-up for frequencies below 1 GHz.....	36
9.2 Radiated emissions set-up for frequencies above 1 GHz.....	36

## Section 1. Report summary

---

### 1.1 Applicant and manufacturer

---

Company name	Silicon Laboratories Finland Oy
Address	Bertel Jungin aukio 3 FI-02600 ESPOO FINLAND

### 1.2 Test specifications

---

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–585 MHz
RSS-247, Issue 2, Feb 2017, Section 5	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

### 1.3 Test methods

---

ANSI C63.10 v2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
558074 D01 15.247 Meas Guidance v05r02 (April 2, 2019)	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules.
RSS-Gen, Issue 5 Amendment 1, March 2019	General Requirements for Compliance of Radio Apparatus

### 1.4 Statement of compliance

---

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.5 below. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See “Summary of test results” for full details.

### 1.5 Exclusions

---

As per quotation Q102170758, the scope of this report is for verification or antenna change, only output power and radiated spurious emissions tests are evaluated, all other requirements are excluded.

### 1.6 Test report revision history

---

Revision #	Date of issue	Details of changes made to test report
TRF	April 22, 2020	Original report issued

## Section 2. Summary of test results

### 2.1 FCC Part 15 Subpart C, general requirements test results

**Table 2.1-1: FCC general requirements results**

Part	Test description	Verdict
§15.207(a)	Conducted limits	Not tested
§15.31(e)	Variation of power source	Not tested
§15.31(m)	Number of tested frequencies	Pass
§15.203	Antenna requirement	Pass

Notes: None

### 2.2 FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS)

**Table 2.2-1: FCC 15.247 results for DTS**

Part	Test description	Verdict
§15.247(a)(2)	Minimum 6 dB bandwidth	Not tested
§15.247(b)(3)	Maximum peak output power in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands	Pass
§15.247(c)(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Not applicable
§15.247(c)(2)	Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams	Not applicable
§15.247(d)	Spurious emissions	Pass
§15.247(e)	Power spectral density	Not tested
§15.247(f)	Time of occupancy for hybrid systems	Not applicable

## 2.3 ISED RSS-Gen, Issue 5, test results

**Table 2.3-1: RSS-Gen results**

Part	Test description	Verdict
7.3	Receiver radiated emission limits	Not applicable
7.4	Receiver conducted emission limits	Not applicable
6.9	Operating bands and selection of test frequencies	Pass
8.8	AC power-line conducted emissions limits	Not tested

Notes: <sup>1</sup> According to sections 5.2 and 5.3 of RSS-Gen, Issue 5 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.

## 2.4 ISED RSS-247, Issue 2, test results for digital transmission systems (DTS)

**Table 2.4-1: RSS-247 results for DTS**

Part	Test description	Verdict
5.2 (a)	Minimum 6 dB bandwidth	Not tested
5.2 (b)	Maximum power spectral density	Not tested
5.3	Hybrid Systems	
5.3 (a)	Digital modulation turned off	Not applicable
5.3 (b)	Frequency hopping turned off	Not applicable
5.4	Transmitter output power and e.i.r.p. requirements	
5.4 (d)	Systems employing digital modulation techniques	Pass
5.4 (e)	Point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band	Not applicable
5.4 (f)	Transmitters which operate in the 2400–2483.5 MHz band with multiple directional beams	Not applicable
5.5	Unwanted emissions	Pass

Notes: None

## Section 3. Equipment under test (EUT) details

### 3.1 Sample information

Receipt date	February 10, 2020
Nemko sample ID number	1,2,3,4

### 3.2 EUT information

Product type	Radio module
Model	BGM13P32A
Model variant	None
Serial number	None

### 3.3 Technical information

Applicant IC company number	5123A																									
IC UPN number	BGM13P																									
All used IC test site(s) Reg. number	2040G-5																									
RSS number and Issue number	RSS-247 Issue 2, Feb 2017																									
Frequency band	2400–2483.5 MHz																									
Frequency Min (MHz)	2402																									
Frequency Max (MHz)	2480																									
RF power Max (W), Conducted	0.0741 (18.7 dBm)																									
Field strength, dBμV/m @ 3 m	119.9																									
Measured BW (kHz), 99% OBW	N/A																									
Type of modulation	GFSK																									
Emission classification (F1D, G1D, D1D)	F1D																									
Transmitter spurious, dBμV/m @ 3 m	53.9, average at 2483.5 MHz																									
Power requirements	3.3 V <sub>DC</sub> via USB																									
Antenna information	External antennas with RSMA connectors																									
	<table><tr><th>#</th><th>Antenna type</th><th>Model number</th><th>Manufacturer</th><th>Peak gain (dBi)</th></tr><tr><td>1</td><td>1/2 wave dipole</td><td>ANT-DB1-RAF-RPS</td><td>Linx</td><td>2.5</td></tr><tr><td>2</td><td>1/4 wave Dipole</td><td>6602813031</td><td>Kinsun</td><td>2</td></tr><tr><td>3</td><td>1/4 wave Dipole</td><td>W1049B</td><td>Pulse</td><td>2</td></tr><tr><td>4</td><td>Patch</td><td>ANTX200P001B24003</td><td>Yageo</td><td>4.4</td></tr></table>	#	Antenna type	Model number	Manufacturer	Peak gain (dBi)	1	1/2 wave dipole	ANT-DB1-RAF-RPS	Linx	2.5	2	1/4 wave Dipole	6602813031	Kinsun	2	3	1/4 wave Dipole	W1049B	Pulse	2	4	Patch	ANTX200P001B24003	Yageo	4.4
	#	Antenna type	Model number	Manufacturer	Peak gain (dBi)																					
	1	1/2 wave dipole	ANT-DB1-RAF-RPS	Linx	2.5																					
	2	1/4 wave Dipole	6602813031	Kinsun	2																					
3	1/4 wave Dipole	W1049B	Pulse	2																						
4	Patch	ANTX200P001B24003	Yageo	4.4																						
Firmware and software version	Use BG Tool RF Regulatory test view																									

### 3.4 Product description and theory of operation

Silabs RF module BGM13P32A

### 3.5 EUT exercise details

During test EUT was set to continuous transmit mode with test software.

- 1 Use Silabs Bgtool
- 2 Silabs RF module setting


Modulation: GFSK

Duty cycle: 45% (firmware from Silabs)

Power level: 200

Chanel: 0–39

Duty cycle measured:





### 3.6 EUT setup diagram




Figure 3.6-1: Setup diagram

### 3.7 EUT sub assemblies

Table 3.7-1: EUT sub assemblies

Description	Brand name	Model/Part number
RF module	Silicon Labs	BGM13P32A
Antenna1	Linx	MN: ANT-DB1-RAF-RPS
Antenna2	Kinsun	MN: 6602813031
Antenna3	Pulse	MN: W1049B
Antenna4	Yageo	MN: ANT-X200P001B24003

## Section 4. Engineering considerations

---

### 4.1 Modifications incorporated in the EUT

---

There were no modifications performed to the EUT during this assessment.

### 4.2 Technical judgment

---

During tests, EUT was configured as per customer provided SW, tx continuously with constant duty cycle, which is declared to be the highest in product application (45% Duty cycle, Packet length setting:60), details in section 3.5.

### 4.3 Deviations from laboratory tests procedures

---

No deviations were made from laboratory procedures.

## Section 5. Test conditions

---

### 5.1 Atmospheric conditions

---

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

### 5.2 Power supply range

---

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages  $\pm 5\%$ , for which the equipment was designed.

## Section 6. Measurement uncertainty

---

### 6.1 Uncertainty of measurement

---

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of  $K = 2$  with 95% certainty.

**Table 6.1-1: Measurement uncertainty**

Test name	Measurement uncertainty, dB
All antenna port measurements	0.55
Conducted spurious emissions	1.13
Radiated spurious emissions	3.78
AC power line conducted emissions	3.55

## Section 7. Test equipment

### 7.1 Test equipment list

**Table 7.1-1: Equipment list**

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber (Emissions)	TDK	SAC-3	FA002532e	2 year	March 10, 2020
Flush mount turntable	Sunol	FM2022	FA002550	—	NCR
Controller	Sunol	SC104V	FA002551	—	NCR
Antenna mast	Sunol	TLT2	FA002552	—	NCR
Bilog antenna (20–2000 MHz)	Sun AR	JB1	FA003009	1 year	December 18, 2020
Receiver/spectrum analyzer	Rohde & Schwarz	ESU 40	FA002071	1 year	December 9, 2020
Horn antenna (1–18 GHz)	EMCO	3115	FA001451	1 year	April 12, 2020
Horn antenna (18–40 GHz)	EMCO	3116	FA002487	2 year	September 11, 2020
Pre-amplifier (0.5–18 GHz)	Com-Power	PAM-118A	FA002561	1 year	September 18, 2020
Pre-amplifier (18–40 GHz)	Com-Power	PAM-840	FA002508	1 year	September 20, 2020
2.4 GHz band Notch Filter	Microwave Circuits	N0324413	FA002693	—	VOU
50 Ω coax cable	C.C.A.	None	FA002603	1 year	February 5, 2021

Note: NCR - no calibration required, VOU - verify on use

## Section 8. Testing data

### 8.1 FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies

#### 8.1.1 Definitions and limits

**FCC:**

Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

**ISED:**

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

**Table 8.1-1: Frequency Range of Operation**

Frequency range over which the device operates (in each band)	Number of test frequencies required	Location of measurement frequency inside the operating frequency range
1 MHz or less	1	Center (middle of the band)
1–10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near center and 1 near low end

Note: "near" means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

#### 8.1.2 Test date

Start date February 10, 2020

#### 8.1.3 Observations, settings and special notes

Per ANSI C63.10 Subclause 5.6.2.1:

The number of channels tested can be reduced by measuring the center channel bandwidth first and then applying the following relaxations as appropriate:

- For each operating mode, if the measured channel bandwidth on the middle channel is at least 150% of the minimum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.
- For multiple-input multiple-output (MIMO) systems, if the measured channel bandwidth on testing the middle channel exceeds the minimum permitted bandwidth by more than 50% on one transmit chain, then it is not necessary to repeat testing on the other chains.
- If the measured channel bandwidth on the middle channel is less than 50% of the maximum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.

Per ANSI C63.10 Subclause 5.6.2.2:

For devices with multiple operating modes, measurements on the middle channel can be used to determine the worst-case mode(s). The worst-case modes are as follows:

- Band edge requirements—Measurements on the mode with the widest bandwidth can be used to cover the same channel (center frequency) on modes with narrower bandwidth that have the same or lower output power for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- Spurious emissions—Measure the mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- In-band PSD—Measurements on the mode with the narrowest bandwidth can be used to cover all modes within the same modulation family of an equal or lower output power provided the result is less than 50% of the limit.

## 8.1.4 Test data

Table 8.1-2: Test channels selection

Start of Frequency range, MHz	End of Frequency range, MHz	Frequency range bandwidth, MHz	Low channel, MHz	Mid channel, MHz	High channel, MHz
2400	2483.5	83.5	2402	2440	2480

## 8.2 FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement

---

### 8.2.1 Definitions and limits

---

**FCC:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

**ISED:**

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

### 8.2.2 Test date

---

Start date      February 10, 2020

### 8.2.3 Observations, settings and special notes

---

The antenna is connected to U.FL on PCB board of RF module.

### 8.2.4 Test data

---

Must the EUT be professionally installed?	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO
Does the EUT have detachable antenna(s)?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
If detachable, is the antenna connector(s) non-standard?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO <input type="checkbox"/> N/A



## 8.3 FCC 15.247(b) and RSS-247 5.4(d) Transmitter output power and e.i.r.p. requirements for DTS in 2 GHz

---

### 8.3.1 Definitions and limits

---

**FCC:**

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (3) For systems using digital modulation in the 2400–2483.5 MHz band: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
  - (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (c) Operation with directional antenna gains greater than 6 dBi.
- (1) Fixed point-to-point operation:
    - (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
    - (iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.
  - (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
    - (i) Different information must be transmitted to each receiver.
    - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
      - (A) The directional gain shall be calculated as the sum of  $10 \log$  (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
      - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
    - (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
    - (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

#### ISED:

d. For DTSs employing digital modulation techniques operating in the 2400–2483.5 MHz band, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

e. Fixed point-to-point systems in the 2400–2483.5 MHz band are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding an e.i.r.p. of 4 W.

f. Transmitters operating in the band 2400–2483.5 MHz, may employ antenna systems that emit multiple directional beams simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers, provided that the emissions comply with the following:

i Different information must be transmitted to each receiver.

ii If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit specified in sections 5.4(b) and 5.4(d). However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or staff having the highest gain.

iii If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the applicable power limit specified in sections 5.4(b) and 5.4(d). If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the applicable limit specified in sections 5.4(b) and 5.4(d). In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the applicable limit specified in sections 5.4(b) and 5.4(d) by more than 8 dB.

iv Transmitters that transmit a single directional beam shall operate under the provisions of sections 5.4(b), 5.4(d) and 5.4(e).

### 8.3.2 Test date

Start date	February 10, 2020
------------	-------------------

### 8.3.3 Observations, settings and special notes

The test was performed as per ANSI C63.10 subclause 11.9.1 (peak power)

The test was performed using method RBW≥DTS bandwidth (Maximum peak conducted output power). Radiated measurement has been performed with actual antenna configurations.

EUT's tx power level was set to max (200) during the tests, difference of calculated conducted power was based on declared antenna gains, and all results are below the limit of 1 W.

Spectrum analyser settings:

Resolution bandwidth	3 MHz
Video bandwidth	≥3 × RBW
Frequency span	10 MHz
Detector mode	Peak
Trace mode	Maxhold

### 8.3.4 Test data

**Table 8.3-1: Output power measurements results, antenna 1 configuration**

Frequency, MHz	Field Strength at 3 m, dBμV/m	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB	Conducted output power, dBm		Margin, dB
					Measured	Limit	
2402	117.1	21.9	36.0	14.1	18.7	30.0	11.3
2440	118.5	23.3	36.0	12.7	18.7	30.0	11.3
2480	118.4	23.2	36.0	12.8	18.6	30.0	11.4

**Table 8.3-2: Output power measurements results antenna 2 configuration**

Frequency, MHz	Field Strength at 3 m, dBμV/m	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB	Conducted output power, dBm		Margin, dB
					Measured	Limit	
2402	118.8	23.6	36.0	12.4	18.7	30.0	11.3
2440	119.3	24.1	36.0	11.9	18.7	30.0	11.3
2480	119.9	24.7	36.0	11.3	18.6	30.0	11.4

**Table 8.3-3: Output power measurements results antenna 3 configuration**

Frequency, MHz	Field Strength at 3 m, dBμV/m	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB	Conducted output power, dBm		Margin, dB
					Measured	Limit	
2402	119.4	24.2	36.0	11.8	18.7	30.0	11.3
2440	118.5	23.3	36.0	12.7	18.7	30.0	11.3
2480	118.1	22.9	36.0	13.1	18.6	30.0	11.4


**Table 8.3-4: Output power measurements results antenna 4 configuration**

Frequency, MHz	Field Strength at 3 m, dBμV/m	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB	Conducted output power, dBm		Margin, dB
					Measured	Limit	
2402	118.7	23.5	36.0	12.5	18.7	30.0	11.3
2440	116.8	21.6	36.0	14.4	18.7	30.0	11.3
2480	118.3	23.1	36.0	12.9	18.6	30.0	11.4

Note: Tests were performed by radiated measurement, calculation as below:


EIRP = Field Strength at 3 m – 95.2 dB

### 8.3.4 Test data, continued




Date: 11.FEB.2020 13:59:59

**Figure 8.3-1:** Field strength of Fundamental sample plot, low channel



Date: 11.FEB.2020 14:16:07


**Figure 8.3-2:** Field strength of Fundamental sample plot, mid channel



Date: 11.FEB.2020 14:09:51


**Figure 8.3-3:** Field strength of Fundamental sample plot, high channel

### 8.3.4 Test data, continued




Date: 12.FEB.2020 14:51:21

**Figure 8.3-4:** Conducted output power, low channel



Date: 12.FEB.2020 14:50:58

**Figure 8.3-5** Conducted output power, mid channel



Date: 12.FEB.2020 14:50:38

**Figure 8.3-6:** Conducted output power, high channel

## 8.4 FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions

### 8.4.1 Definitions and limits

#### FCC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### ISED:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

**Table 8.4-1: FCC §15.209 and RSS-Gen – Radiated emission limits**

Frequency, MHz	Field strength of emissions		Measurement distance, m
	μV/m	dBμV/m	
0.009–0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490–1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test

**Table 8.4-2: ISED restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	12.57675–12.57725	399.9–410	7.25–7.75
0.495–0.505	13.36–13.41	608–614	8.025–8.5
2.1735–2.1905	16.42–16.423	960–1427	9.0–9.2
3.020–3.026	16.69475–16.69525	1435–1626.5	9.3–9.5
4.125–4.128	16.80425–16.80475	1645.5–1646.5	10.6–12.7
4.17725–4.17775	25.5–25.67	1660–1710	13.25–13.4
4.20725–4.20775	37.5–38.25	1718.8–1722.2	14.47–14.5
5.677–5.683	73–74.6	2200–2300	15.35–16.2
6.215–6.218	74.8–75.2	2310–2390	17.7–21.4
6.26775–6.26825	108–138	2483.5–2500	22.01–23.12
6.31175–6.31225	149.9–150.05	2655–2900	23.6–24.0
8.291–8.294	156.52475–156.52525	3260–3267	31.2–31.8
8.362–8.366	156.7–156.9	3332–3339	36.43–36.5
8.37625–8.38675	162.0125–167.17	3345.8–3358	
8.41425–8.41475	167.72–173.2	3500–4400	
12.29–12.293	240–285	4500–5150	Above 38.6
12.51975–12.52025	322–335.4	5350–5460	

Note: Certain frequency bands listed in Table 8.4-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

**Table 8.4-3: FCC restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

#### 8.4.2 Test date

Start date February 10, 2020

#### 8.4.3 Observations, settings and special notes

The spectrum was searched from 30 MHz to the 10<sup>th</sup> harmonic. No emissions were detected within 6 dB below the limit above 18 GHz.

EUT was set to transmit with constant duty cycle.

Radiated measurements were performed at a distance of 3 m, the EUT was transmitting with actual antennas.

DTS emissions in non-restricted frequency bands test was found to be 20 dBc below the fundamental.

DTS emissions in restricted frequency bands test was performed as per ANSI C63.10 subclause 11.12.

DTS band-edge emission measurements test was performed as per ANSI C63.10 subclause 11.13.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:


Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for average radiated measurements within restricted bands above 1 GHz:


Resolution bandwidth:	1 MHz
Video bandwidth:	No less than 30 Hz*
Detector mode:	Peak
Trace mode:	Max Hold

Note: \*As per ANSI C63.10, section 4.1.4.2.3. the lowest VBW is calculated as  $[1 / (\text{minimum transmitter on time})]$  during a 0.1 second interval =  $1 / 0.045 = 22.2$  Hz


#### 8.4.4 Test data



**Figure 8.4-1:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 1, Low channel




**Figure 8.4-2:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 1, mid channel




**Figure 8.4-3:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 1, High channel




#### 8.4.4 Test data, continued



**Figure 8.4-4:** Radiated spurious emissions 1 to 18 GHz with antenna 1, Low channel



**Figure 8.4-5:** Radiated spurious emissions 1 to 18 GHz with antenna 1, mid channel



**Figure 8.4-6:** Radiated spurious emissions 1 to 18 GHz with antenna 1, High channel

Note: Spectrum was investigated from 30 MHz to 25 GHz. Above 18 GHz, no emission related to RF portion were detected within 6 dB below the limit.


#### 8.4.4 Test data, continued

**Table 8.4-4:** Radiated field strength measurement results within restricted band with antenna 1


Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	56.2	74.0	17.8	48.1	54.0	5.9
Low	4804.0	54.6	74.0	19.4	51.1	54.0	2.9
Mid	4880.0	54.5	74.0	19.5	46.8	54.0	7.2
High	2483.5	62.2	74.0	11.8	53.2	54.0	0.8
High	4960.0	54.5	74.0	19.5	49.2	54.0	4.8

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.


#### 8.4.5 Test data, continued



**Figure 8.4-7:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 2, Low channel




**Figure 8.4-8:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 2, mid channel




**Figure 8.4-9:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 2, High channel


#### 8.4.4 Test data, continued



**Figure 8.4-10:** Radiated spurious emissions 1 to 18 GHz with antenna 2, Low channel



**Figure 8.4-11:** Radiated spurious emissions 1 to 18 GHz with antenna 2, mid channel



**Figure 8.4-12:** Radiated spurious emissions 1 to 18 GHz with antenna 2, High channel

Note: Spectrum was investigated from 30 MHz to 25 GHz. Above 18 GHz, no emission related to RF portion were detected within 6 dB below the limit.


#### 8.4.4 Test data, continued

**Table 8.4-5:** Radiated field strength measurement results within restricted band with antenna 2


Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	56.2	74.0	17.8	48.3	54.0	5.7
Low	4804.0	55.2	74.0	18.8	52.8	54.0	1.2
Mid	4880.0	52.2	74.0	21.8	48.7	54.0	5.3
High	2483.5	62.2	74.0	11.8	53.9	54.0	0.1
High	4960.0	51.7	74.0	22.3	44.0	54.0	10.0

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.


#### 8.4.4 Test data, continued



**Figure 8.4-13:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 3, Low channel




**Figure 8.4-14:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 3, mid channel




**Figure 8.4-15:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 3, High channel


#### 8.4.4 Test data, continued



**Figure 8.4-16:** Radiated spurious emissions 1 to 18 GHz with antenna 3, Low channel



**Figure 8.4-17:** Radiated spurious emissions 1 to 18 GHz with antenna 3, mid channel



**Figure 8.4-18:** Radiated spurious emissions 1 to 18 GHz with antenna 3, High channel

Note: Spectrum was investigated from 30 MHz to 25 GHz. Above 18 GHz, no emission related to RF portion were detected within 6 dB below the limit.

#### 8.4.4 Test data, continued


**Table 8.4-6:** Radiated field strength measurement results within restricted band with antenna 3

Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	56.3	74.0	17.7	48.3	54.0	5.7
Low	4804.0	52.6	74.0	21.4	48.7	54.0	5.3
Mid	4880.0	50.1	74.0	23.9	45.5	54.0	8.5
High	2483.5	62.1	74.0	11.9	53.0	54.0	1.0
High	4960.0	51.7	74.0	22.3	44.0	54.0	10.0


Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.




#### 8.4.4 Test data, continued



**Figure 8.4-19:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 4, Low channel




**Figure 8.4-20:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 4, mid channel




**Figure 8.4-21:** Radiated spurious emissions 30 MHz to 1 GHz with antenna 4, High channel


#### 8.4.4 Test data, continued



**Figure 8.4-22:** Radiated spurious emissions 1 to 18 GHz with antenna 4, Low channel



**Figure 8.4-23:** Radiated spurious emissions 1 to 18 GHz with antenna 4, mid channel



**Figure 8.4-24:** Radiated spurious emissions 1 to 18 GHz with antenna 4, High channel

Note: Spectrum was investigated from 30 MHz to 25 GHz. Above 18 GHz, no emission related to RF portion were detected within 6 dB below the limit.

#### 8.4.4 Test data, continued


**Table 8.4-7:** Radiated field strength measurement results within restricted band with antenna 4

Channel	Frequency, MHz	Peak Field strength, dBμV/m		Margin, dB	Average Field strength, dBμV/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	56.1	74.0	17.9	47.5	54.0	6.5
Low	4804.0	49.5	74.0	24.5	45.4	54.0	8.6
Mid	4880.0	51.9	74.0	22.1	48.8	54.0	5.2
High	2483.5	58.2	74.0	15.8	51.2	54.0	2.8
High	4960.0	60.0	74.0	14.0	50.0	54.0	4.0


Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.

## Section 9. Block diagrams of test set-ups

### 9.1 Radiated emissions set-up for frequencies below 1 GHz



### 9.2 Radiated emissions set-up for frequencies above 1 GHz



(End of report)