


SAR Test exemption documentation according to CFR 47 §1.1307

Report identification number: 1-6290/23-01-03 Exemption / (FCC)


contains the module with the following certification numbers	
FCC ID	2AYVBD2S0009734958

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Labs



Michael Dorongovski
Lab Manager
Radio Labs

EUT technologies:

E.I.R.P. worst case:

Technologies:	Max. measured E.I.R.P. per BW=1MHz:		BW	Max. E.I.R.P. for Full BW: Max. E.I.R.P. _{@1MHz} × (BW/1MHz)	#
	(dBm)	(μW)	(MHz)		
UWB 3100 to 10600 MHz	-43.8	0.04169	736	0.04169 μW × 736 = 30.7 μW	A

Conducted power worst case:

Technologies:	Max. calculated conducted. per BW=1MHz:		BW	Max. conducted power for Full BW: Max.decl.E.I.R.P. _{@1MHz} × (BW/1MHz)	#
	(dBm)	(μW)	(MHz)		
UWB 3100 to 10600 MHz	-48.0	0.01585	736	0.01585 μW × 736 = 11.7 μW	B

Details and origins of the measurements shown in the table above:

#	Results from:	Additional information
A	1-6290/23-01-02 cetecom advanced GmbH	Bandwidth (Page 24), EIRP (Page 29)
B	Antenna datasheet	

Blanket test exemption according CFR 47 §1.1307:

§1.1307(b)(3)(i)(A) – A single RF source is exempt if the available maximum time-averaged power is **no more than 1 mW**, regardless of separation distance.

(Applicable from 100 kHz to 100 GHz)