



TEST REPORT NUMBER: (8522)244-0297-(B)

TEST REPORT

Applicant:	International Toy, Inc.	Fax:	---
		E-mail:	---
Address :	17682 Cowan 100,Irvine,California,United States 92614		
Test Date :	2022-09-07 to 2022-09-15		

Manufacturer or Supplier :	International Toy, Inc.
Address :	17682 Cowan 100,Irvine,California,United States 92614
Sample Description:	MVL QUANTUM CORE
Model number:	101Q123U221
Additional Model :	N/A
Rated Voltage:	DC6V (AA*4)
FCC ID :	2ACU8INT113
The submitted sample of the above equipment has been tested according to following standard(s)	
47 CFR Part 15, Subpart C 247	
CONCLUSION: The submitted sample was found to COMPLY with the test requirement	

Assistant Manager

Name: Nick Lung

Date: September 20, 2022



TEST REPORT NUMBER: (8522)244-0297-(B)

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 GENERAL DESCRIPTION OF BT	3
2.4 GENERAL DESCRIPTION OF BLE	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 <i>Standard Requirement</i>	5
3.1.2 <i>Limits</i>	5
3.1.3 <i>EUT RF Exposure</i>	7



TEST REPORT NUMBER: (8522)244-0297-(B)

2 General Information

2.1 Client Information

Applicant:	International Toy, Inc.
Address of Applicant:	17682 Cowan 100,Irvine,California,United States 92614
Manufacturer:	International Toy, Inc.
Address of Manufacturer:	17682 Cowan 100,Irvine,California,United States 92614

2.2 General Description of EUT

Product Name:	MVL QUANTUM CORE
Model No.:	101Q123U221
Test Model No.:	101Q123U221
Trade Mark:	N/A
Software Version:	BK6988V2.3P40F.8M-16M-BTS84-(Quantum Core)-LY-TF-USB-PWD-V1.1-20220531-CRC-(f831)
Hardware Version:	22071A-V3(20220818)
Power Supply:	DC6V (AA*4)

2.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	0dBi



TEST REPORT NUMBER: (8522)244-0297-(B)

2.4 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	0 dBi



TEST REPORT NUMBER: (8522)244-0297-(B)

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Standard Requirement

447498 D04 Interim General RF Exposure Guidance v01

3.2. SAR Test Reduction Guidance

SAR test reduction procedures [Glossary] allow using a particular set of test data as representative of other, similar, test conditions. This may be applied for data within different test positions (e.g. body, head, extremity), wireless modes (e.g. Wi-Fi, cellular), and frequency bands. This test reduction process provides for the use of test data for one specific channel, while referencing to those data for demonstrating compliance in other required channels for each test position of an exposure condition, within the operating mode of a frequency band. This is limited specifically to when the reported 1-g or 10-g SAR for the mid-band or highest output power channel meets any of the following conditions.

3.1.2 Limits

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).



BUREAU
VERITAS

TEST REPORT NUMBER: (8522)244-0297-(B)

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169



TEST REPORT NUMBER: (8522)244-0297-(B)

3.1.3 EUT RF Exposure

1) For BT

Measurement Data

Channel	EIRP(dBm)	Maximum tune-up Power (mW)	Exclusion threshold (mW)
Lowest (2402MHz)	0.97	1.25	3.0
Middle (2441MHz)	2.72	1.87	
Highest (2480MHz)	2.99	1.99	

Remark: The Max Conducted Peak Output Power data refer to Test Report Number: (8522)244-0297
Maximum tune-up Power=1.99mW<3.0mW

The maximum output power of this product is less than 3mW
So the SAR test is not required.

2) For BLE

Measurement Data

Channel	EIRP(dBm)	Maximum tune-up Power (mW)	Exclusion threshold (mW)
Lowest (2402MHz)	-0.74	0.84	3.0
Middle (2441MHz)	0.86	1.22	
Highest (2480MHz)	0.13	1.03	

Remark: The Max Conducted Peak Output Power data refer to Test Report Number: (8522)244-0297
Maximum tune-up Power=1.22 mW<3.0mW

The maximum output power of this product is less than 3mW
So the SAR test is not required.

***** END OF REPORT *****