

FCC RF Test Report

APPLICANT : Sony Mobile Communications Inc.
EQUIPMENT : Wireless Headset
BRAND NAME : Sony
FCC ID : PY7-13007N
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 06, 2017 and testing was completed on Nov. 09, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Descriptions of Test Mode.....	8
2.3 Test Mode.....	9
2.4 Connection Diagram of Test System.....	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	17
3.4 Conducted Band Edges and Spurious Emission Measurement	22
3.5 Radiated Band Edges and Spurious Emission Measurement	27
3.6 Antenna Requirements.....	31
4 LIST OF MEASURING EQUIPMENT.....	32
5 UNCERTAINTY OF EVALUATION.....	34
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7O0620-01B	Rev. 01	Initial issue of report	Dec. 28, 2017
FR7O0620-01B	Rev. 02	Add accessories in section 2.5.	Jan. 09, 2018
FR7O0620-01B	Rev. 03	Add test panels description in section 2.2	Jan. 10, 2018
FR7O0620-01B	Rev. 04	Remove accessories in section 2.5.	Jan. 12, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.78 dB at 2495.640 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not required	-
3.6	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-
Note: Not required means after assessing, test items are not necessary to carry out.					

1 General Description

1.1 Applicant

Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.2 Manufacturer

Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.3 Product Feature of Equipment Under Test.

Bluetooth

Product Specification subjective to this standard			
Antenna Type / Gain		PIFA Antenna with gain 1.6 dBi	
EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.0.26	N/A	RF conducted measurement Radiated Spurious Emission

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth – LE RF Output Peak Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	6.79 dBm
Ch19	2440MHz	7.24 dBm
Ch39	2480MHz	7.57 dBm

Channel	Frequency	Bluetooth – LE RF Output Average Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	6.31 dBm
Ch19	2440MHz	6.86 dBm
Ch39	2480MHz	7.21 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report


2.3 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps

2.4 Connection Diagram of Test System

<Bluetooth Tx Mode >





2.5 EUT Operation Test Setup

The RF test items, an engineering test program was provided and enabled to make EUT transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


6 dB Bandwidth Plot on Channel 00



Date: 7.NOV.2017 17:59:48




6 dB Bandwidth Plot on Channel 19



Date: 7.NOV.2017 18:09:39

6 dB Bandwidth Plot on Channel 39




Date: 7.NOV.2017 18:15:28

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


99% Bandwidth Plot on Channel 00



Date: 7.NOV.2017 18:07:02




99% Occupied Bandwidth Plot on Channel 19



Date: 7.NOV.2017 18:13:01

99% Occupied Bandwidth Plot on Channel 39



Date: 7.NOV.2017 18:23:04

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup






3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)


PSD 100kHz Plot on Channel 00



Date: 7.NOV.2017 18:03:45




PSD 100kHz Plot on Channel 19



Date: 7.NOV.2017 18:11:08

PSD 100kHz Plot on Channel 39




Date: 7.NOV.2017 18:16:56



3.3.7 Test Result of Power Spectral Density Plots (3kHz)


PSD 3kHz Plot on Channel 00



Date: 7.NOV.2017 18:02:15




PSD 3kHz Plot on Channel 19



Date: 7.NOV.2017 18:10:22

PSD 3kHz Plot on Channel 39



Date: 7.NOV.2017 18:16:08

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup




3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 7.NOV.2017 18:04:28

High Band Edge Plot on Channel 39




Date: 7.NOV.2017 18:17:29




3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 7.NOV.2017 18:05:20


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 7.NOV.2017 18:05:28




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19




Date: 7.NOV.2017 18:11:30

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19




Date: 7.NOV.2017 18:11:39

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.NOV.2017 18:17:52

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 7.NOV.2017 18:18:00

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 26, 2017	Nov. 02, 2017~ Nov. 07, 2017	Sep. 25, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GHz	Sep. 26, 2017	Nov. 02, 2017~ Nov. 07, 2017	Sep. 25, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz ~ 30GHz	Nov. 17, 2016	Nov. 02, 2017~ Nov. 07, 2017	Nov. 16, 2017	Conducted (TH05-HY)
Hygrometer	TECEPIL	DTM-303B	TP157151	N/A	Mar. 20, 2017	Nov. 02, 2017~ Nov. 07, 2017	Mar. 19, 2018	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21	1GHz~26GHz	Dec. 02, 2016	Nov. 02, 2017~ Nov. 07, 2017	Dec. 01, 2017	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Nov. 08, 2017~ Nov. 09, 2017	Oct. 19, 2018	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Jan. 07, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 06, 2018	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 23, 2017	Nov. 08, 2017~ Nov. 09, 2017	Aug. 22, 2018	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 576	18GHz ~ 40GHz	Apr. 27, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 26, 2018	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 16, 2018	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 12, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 11, 2018	Radiation (03CH07-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jul. 17, 2018	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 25, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 24, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Nov. 08, 2017~ Nov. 09, 2017	Mar. 13, 2018	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 30, 2017	Nov. 08, 2017~ Nov. 09, 2017	Oct. 29, 2018	Radiation (03CH07-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	HTC-2	1	N/A	Jun. 27, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jun. 26, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21	30MHz~1GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21+MY842 09521	1GHz~26GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21+MY842 09521	26GHz~40GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208 368	Control Ant Mast	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Test Software	Audix	E3	6.2009-8-2 4(sporton)	N/A	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Filter	Wainwright	WLKS1200-8S S	SN3	1.2G Low Pass	Nov. 22, 2016	Nov. 08, 2017~ Nov. 09, 2017	Nov. 21, 2017	Radiation (03CH07-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Nov. 22, 2016	Nov. 08, 2017~ Nov. 09, 2017	Nov. 21, 2017	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.70
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2017/11/2~2017/11/7	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.054	0.670	0.50	Pass
BLE	1Mbps	1	19	2440	1.056	0.672	0.50	Pass
BLE	1Mbps	1	39	2480	1.056	0.672	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.79	30.00	1.60	8.39	36.00	Pass
BLE	1Mbps	1	19	2440	7.24	30.00	1.60	8.84	36.00	Pass
BLE	1Mbps	1	39	2480	7.57	30.00	1.60	9.17	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	0.71	6.31
BLE	1Mbps	1	19	2440	0.71	6.86
BLE	1Mbps	1	39	2480	0.71	7.21

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.14	-9.71	1.60	8.00	Pass
BLE	1Mbps	1	19	2440	6.58	-9.41	1.60	8.00	Pass
BLE	1Mbps	1	39	2480	6.93	-8.94	1.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. Radiated Spurious Emission

Test Engineer :	Jesse Wang and James Chiu	Temperature :	21~23°C
		Relative Humidity :	52~56%



2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2323.86	57.51	-16.49	74	51.54	31.79	8.28	34.1	264	254	P	H
		2311.89	47.02	-6.98	54	41.07	31.74	8.28	34.07	264	254	A	H
	*	2402	92.95	-	-	86.95	31.95	8.24	34.19	264	254	P	H
	*	2402	92.24	-	-	86.24	31.95	8.24	34.19	264	254	A	H
													H
													H
		2342.76	57.2	-16.8	74	51.24	31.83	8.26	34.13	135	283	P	V
		2382.24	47.2	-6.8	54	41.21	31.91	8.24	34.16	135	283	A	V
	*	2402	99.39	-	-	93.39	31.95	8.24	34.19	135	283	P	V
	*	2402	98.62	-	-	92.62	31.95	8.24	34.19	135	283	A	V
													V
													V
BLE CH 19 2440MHz		2358.58	56.46	-17.54	74	50.46	31.87	8.26	34.13	286	256	P	H
		2383.08	47.01	-6.99	54	41.02	31.91	8.24	34.16	286	256	A	H
	*	2440	93.43	-	-	87.29	32.08	8.27	34.21	286	256	P	H
	*	2440	92.55	-	-	86.41	32.08	8.27	34.21	286	256	A	H
		2487.33	57.21	-16.79	74	51.02	32.16	8.3	34.27	286	256	P	H
		2485.93	47.08	-6.92	54	40.89	32.16	8.3	34.27	286	256	A	H
		2336.46	56.88	-17.12	74	50.87	31.83	8.28	34.1	244	289	P	V
		2352.42	47.08	-6.92	54	41.08	31.87	8.26	34.13	244	289	A	V
	*	2440	98.95	-	-	92.81	32.08	8.27	34.21	244	289	P	V
	*	2440	98.36	-	-	92.22	32.08	8.27	34.21	244	289	A	V
		2488.1	56.74	-17.26	74	50.51	32.2	8.3	34.27	244	289	P	V
		2486.28	47.06	-6.94	54	40.87	32.16	8.3	34.27	244	289	A	V



BLE CH 39 2480MHz	*	2480	93.77	-	-	87.58	32.16	8.3	34.27	252	256	P	H
	*	2480	93.13	-	-	86.94	32.16	8.3	34.27	252	256	A	H
		2492.4	56.96	-17.04	74	50.76	32.2	8.3	34.3	252	256	P	H
		2495.64	47.22	-6.78	54	41.02	32.2	8.3	34.3	252	256	A	H
													H
													H
	*	2480	101	-	-	94.81	32.16	8.3	34.27	270	285	P	V
	*	2480	100.4	-	-	94.21	32.16	8.3	34.27	270	285	A	V
		2492.6	56.88	-17.12	74	50.68	32.2	8.3	34.3	270	285	P	V
		2491.32	47.12	-6.88	54	40.89	32.2	8.3	34.27	270	285	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	42.09	-31.91	74	55.29	34.24	11.96	59.4	100	0	P	H
													H
													H
													H
		4804	42.32	-31.68	74	55.52	34.24	11.96	59.4	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	44.21	-29.79	74	57.38	34.22	11.9	59.29	100	0	P	H
		7320	43.36	-30.64	74	50.78	35.7	14.94	58.06	100	0	P	H
													H
													H
		4880	44.43	-29.57	74	57.6	34.22	11.9	59.29	100	0	P	V
		7320	46.64	-27.36	74	54.06	35.7	14.94	58.06	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	42.1	-31.9	74	55.21	34.21	11.84	59.16	100	0	P	H
		7440	43.76	-30.24	74	51.19	35.63	15.1	58.16	100	0	P	H
													H
													H
		4960	43.15	-30.85	74	56.26	34.21	11.84	59.16	100	0	P	V
		7440	47.05	-26.95	74	54.48	35.63	15.1	58.16	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30.27	25.94	-14.06	40	30.86	24.72	1.71	31.35	-	-	P	H
		139.35	29.21	-14.29	43.5	41.14	17.25	2.34	31.52	-	-	P	H
		261.66	22.64	-23.36	46	31.22	19.5	3.28	31.36	-	-	P	H
		563.2	28.72	-17.28	46	29.53	25.87	4.2	30.88	-	-	P	H
		768.3	32.29	-13.71	46	30	28.03	4.88	30.62	-	-	P	H
		957.3	35.63	-10.37	46	29.88	30.86	5.4	30.51	100	0	P	H
													H
													H
													H
													H
													H
													H
		30	27.12	-12.88	40	32.04	24.72	1.71	31.35	-	-	P	V
		120.72	19.55	-23.95	43.5	31.28	17.47	2.34	31.54	-	-	P	V
		285.69	21.38	-24.62	46	30.53	18.89	3.28	31.32	-	-	P	V
		561.8	28.68	-17.32	46	29.45	25.92	4.2	30.89	-	-	P	V
		792.1	32.11	-13.89	46	29.75	27.98	4.98	30.6	-	-	P	V
		951.7	34.48	-11.52	46	29.02	30.57	5.4	30.51	100	0	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Jesse Wang and James Chiu	Temperature :	21~23°C
		Relative Humidity :	52~56%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL</p>	 <p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL</p>
Avg.	 <p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 HORIZONTAL</p>	 <p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 HORIZONTAL</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL</p>	 <p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL</p>
Avg	 <p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 VERTICAL</p>	 <p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	<div><p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL</p></div>	<div><p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL</p></div>
Avg.	<div><p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 HORIZONTAL</p></div>	<div><p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 HORIZONTAL</p></div>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF ANT 0007596Z HORIZONTAL</p>	Left blank
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF ANT 0007596Z HORIZONTAL</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL</p>	<p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL</p>
Avg.	<p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 VERTICAL</p>	<p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH07-HY Condition : PEAK_BE_74 3m HF ANT: 0007596Z VERTICAL</p>	Left blank
Avg.	 <p>Site : 03CH07-HY Condition : AVG_BE_54 3m HF ANT: 0007596Z VERTICAL</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL</p>	<p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL</p>
Avg.	<p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 HORIZONTAL</p>	<p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 HORIZONTAL</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL</p>	<p>Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL</p>
Avg.	<p>Site : 03CH07-HY Condition : AVG BE 54 3m HF ANT 00075962 VERTICAL</p>	<p>Site : 03CH07-HY Condition : AVG 54 3m HF ANT 00075962 VERTICAL</p>





2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL</p>	 <p>Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH07-4FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL</p>	 <p>Site : 03CH07-4FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	<div><p>Level (dBuV/m)</p><p>Date: 2017-11-08</p><p>Frequency (MHz)</p><p>Site : 03CH07-4FY Condition : PEAK_74 3m SHF-EHF 131029 HORIZONTAL</p></div>	<div><p>Level (dBuV/m)</p><p>Date: 2017-11-08</p><p>Frequency (MHz)</p><p>Site : 03CH07-4FY Condition : PEAK_74 3m SHF-EHF 131029 VERTICAL</p></div>


Emission below 1GHz
2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak	 <p>Site : 03C407-11Y Condition : QP-3m LF-ANT-35419f6) HORIZONTAL</p>	 <p>Site : 03C407-11Y Condition : QP-3m LF-ANT-35419f6) VERTICAL</p>

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth -LE	84.92	2140	0.47	1kHz

Bluetooth - LE



Date: 2.NOV.2017 20:18:17