



EMI – TEST REPORT

- Human Exposure -

Type / Model Name : FFZ-radio module; eP 2.0 Master

Product Description : Truck anchor for distance measurements to a person tag

Applicant : Jungheinrich AG

Address : Friedrich-Ebert-Damm 129

22047 HAMBURG, GERMANY

Manufacturer : ACD Elektronik GmbH

Address : Engelberg 2

88480 ACHSTETTEN, GERMANY

Test Result according to the standards
listed in clause 1 test standards:

POSITIVE

Test Report No. : **T43580-02-01FX**

11. May 2022

Date of issue



Deutsche
Akkreditierungsstelle
D-PL-12030-01-01
D-PL-12030-01-02

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test results
without the written permission of the test laboratory.

FCC ID: 2AK6M-EP20FMMASTER

Contents

1	<u>TEST STANDARDS</u>	<u>3</u>
2	<u>EQUIPMENT UNDER TEST</u>	<u>4</u>
2.1	Photo documentation of the EUT – See ATTACHMENT A1 and A2	4
2.2	Equipment type, category	4
2.3	Short description of the equipment under test (EUT)	4
2.4	Variants of the EUT	4
2.5	Operation frequency and channel plan	4
2.6	Antennas	4
2.7	Power supply system utilised	4
3	<u>TEST RESULT SUMMARY</u>	<u>5</u>
3.1	Final assessment	5
4	<u>TEST ENVIRONMENT</u>	<u>6</u>
4.1	Address of the test laboratory	6
4.2	Environmental conditions	6
4.3	Statement of the measurement uncertainty	6
5	<u>HUMAN EXPOSURE</u>	<u>7</u>
5.1	Maximum peak conducted output power	7
5.2	Maximum permissible exposure (MPE)	8
5.3	Co-location and Co-transmission	10

ATTACHMENT A1 and A2 as separate supplement

FCC ID: 2AK6M-EP20FMMASTER

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 1, Subpart I - Procedures Implementing the National Environmental Policy Act of 1969

Part 1, Subpart I, Section 1.1310 Radiofrequency radiation exposure limits

Part 1, Subpart 2, Section 2.1091 Radiofrequency radiation exposure evaluation: **mobile devices**.

Part 1, Subpart 2, Section 2.1093 Radiofrequency radiation exposure evaluation: **portable devices**.

OET Bulletin 65, 65A, 65B Edition 97-01, August 1997 – Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.

KDB 447498 D01 v06 RF Exposure procedures and equipment authorisation policies for mobile and portable devices, October 23, 2015.

KDB 865664 D01 v01r04 SAR Measurement Requirements for 100 MHz to 6 GHz, August 7, 2015.

ANSI C95.1: 2005 IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz

ETSI TR 100 028 V1.3.1: 2001-03, Electromagnetic Compatibility and Radio Spectrum Matters (ERM);
Uncertainties in the Measurement of Mobile Radio Equipment
Characteristics—Part 1 and Part 2

FCC ID: 2AK6M-EP20FMMASTER

2 EQUIPMENT UNDER TEST

2.1 Photo documentation of the EUT – See ATTACHMENT A1 and A2

2.2 Equipment type, category

Part of mobile UWB, BLE, NFC Device (mounted on industrial truck)

2.3 Short description of the equipment under test (EUT)

The EUT is one of 4 anchors, mounted on a truck. These anchors are communicating with the truck via CAN-bus and with one person tag via UWB. The operator wears the person tag on the body. After an initial pairing process between the EUT and the person tag (by NFC or UWB), the 4 anchors can localize the position of the person tag related to a truck fixed coordinate system. If there are no obstacles, the truck follows the EUT (in driving direction).

Number of tested samples: 1
Serial number: 186800000221
Firmware version: V2.07
UWB driver version: V2.5.9

EUT configuration:

(The CDF filled by the applicant can be viewed at the test laboratory.)

2.4 Variants of the EUT

There are no variants.

2.5 Operation frequency and channel plan

UWB is working at 3993.6 MHz

BLE is working in the frequency range 2400 MHz to 2483.5 MHz

NFC is working at 13.56 MHz.

2.6 Antennas

UWB: The EUT uses an integrated antenna.

BLE: The EUT uses an integrated antenna.

NFC: The EUT uses an integrated dantenna.

2.7 Power supply system utilised

Power supply voltage, V_{nom} : 24 V DC

FCC ID: 2AK6M-EP20FMMASTER**3 TEST RESULT SUMMARY**

FCC Rule Part	Description	Result
KDB 447498, 7.1	MPE	passed
KDB 447498, 4.3.1	SAR exclusion consideration	not applicable
KDB 447498, 7.2	Co-location, Co-transmission	passed

3.1 Final assessment

The equipment under test fulfills the EMI requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 31 May 2019

Testing concluded on : 14 June 2019

Checked by:

Tested by:

Klaus Gegenfurtner
Teamleader Radio

Franz-Xaver Schrettenbrunner
Radio Team

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

**CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY**

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 °C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 / 11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. For all measurements shown in this report, the measurement uncertainty of the test laboratory, CSA Group Bayern GmbH, is below the measurement uncertainty as defined by CISPR. Therefore, no special measures must be taken into consideration with regard to the limits according to CISPR. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Measurement Type	Range	Confidence Level	Calculated Uncertainty
AC power line conducted emissions	0.15 MHz to 30 MHz	95%	± 3.29 dB
EBW and OBW	2400 MHz to 3000 MHz	95%	$\pm 2.5 \times 10^{-7}$
Maximum peak conducted output power	2400 MHz to 3000 MHz	95%	± 0.62 dB
Power spectral density	2400 MHz to 3000 MHz	95%	± 0.62 dB
Conducted Spurious Emissions	9 kHz to 10000 MHz	95%	± 2.15 dB
Conducted Spurious Emissions	10000 MHz to 40000 MHz	95%	± 3.47 dB
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	± 3.53 dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	± 3.71 dB
Radiated Spurious Emissions	1000 MHz to 10000 MHz	95%	± 2.34 dB
Field strength of the fundamental	100 kHz to 100 MHz	95%	± 3.53 dB

5 HUMAN EXPOSURE

5.1 Maximum peak conducted output power

5.1.1 Test result

UWB 1:

EIRP = rated output power + tune up tolerance + gain = -35 dBm/MHz + 2.77 dB + 3.62 dBi = **-28.61 dBm/MHz**

Bluetooth low energy:

The output power of the device is taken from the power measurement in the test report 276131-2 of the test laboratory SGS Fimko.

2402 MHz: EIRP = conducted power + tune up tolerance + gain = **6.79 mW = 8.32 dBm**

NFC:

Calculation of EIRP level

The calculation of the EIRP level of the fundamental frequency of the EuT is done according to KDB 412172 D01 subclause 1.3.1 forumula (1). The used field strength is taken from testreport T43580-01-00WP issued by CSA Group Bayern GmbH.

Values according to report subclause 1.1.2.2:

Fieldstrength: 51.4 dBμV/m at a test distance of 3 m

Used formula: $EIRP = (E \times d)^2 / 30$

where EIRP = equivalent isotropically radiated power in watts

E = electrical field strength in V/m

d = measurement distance in meters

calculation: $EIRP = (371.53 \times 10^{-6} \times 3)^2 / 30 \text{ W} = 41.41 \times 10^{-9} \text{ W}$

Result: EIRP = 0.0000414 mW = **-43.8 dBm**

Remarks: As worst case the power values are not averaged over time.

FCC ID: 2AK6M-EP20FMMASTER**5.2 Maximum permissible exposure (MPE)****5.2.1 Description of the test location**

Test location: NONE

5.2.2 Applicable standard

According to FCC Part 15, Section 15.247(i):

Systems operating under the provisions of this section shall be operated in a manner that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

The test methods used comply with ANSI/IEEE C95.1, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz".

This test report shows the compliance with the limits for Maximum Permissible Exposure (MPE) specified in FCC Part 1, Section 1.1310 and the criteria to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in FCC Part 1, Section 1.1307(b).

5.2.3 Description of Determination

The maximum rated output power conducted included the tune up tolerance is used to calculate the EIRP. Through the Friis transmission formula, the known maximum gain of the antenna and the maximum power, can be calculated the MPE in a defined distance away from the product.

Friis transmission formula:

$$P_d = \frac{P_{out} * G}{4 * \pi * r^2}$$

Where:

P_d = power density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna (linear scale)

r = distance between antenna and observation point (cm)

According to FCC Rules 47CFR 2.1093(b) the EUT is not a portable device. The EUT is designed to be used that radiating structures are 20 cm outside of the body of the user. ($r = 20$ cm)

FCC ID: 2AK6M-EP20FMMASTER

5.2.4 Determination of MPE according FCC

5.2.4.1 UWB

Rated output spectral density:		-35.00 dBm/MHz
Measured UWB EBW:		688 MHz
Rated output power:	0.22 mW	-6.62 dBm
Tune-up tolerance:	2.77 dB	
Maximum output power:	-3.85 dBm	0.41 mW
Antenna gain max:	3.62 dBi	
Maximum EIRP:	-0.2 dBm	0.95 mW

Calculation of power density:

$$S = 0.95 \text{ mW} / (4 \times \pi \times [20 \text{ cm}]^2) = 0.000189 \text{ mW/cm}^2$$

Limit: 1.0 mW /cm²

5.2.4.2 BLE

Calculation of power density:

$$S = 6.79 \text{ mW} / (4 \times \pi \times [20 \text{ cm}]^2) = 0.00135 \text{ mW/cm}^2$$

Limit: 1.0 mW /cm²

5.2.4.3 NFC

Calculation of power density:

$$S = 0.0000414 \text{ mW} / (4 \times \pi \times [20 \text{ cm}]^2) = 8.2 \times 10^{-9} \text{ mW/cm}^2$$

Limit: $180 / (13.56)^2 \text{ mW/cm}^2 = 0.98 \text{ mW /cm}^2$

Limits for maximum permissible exposure (MPE):

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/ f ²	30
30 - 300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100000	---	---	1.0	30

f = Frequency in MHz

The requirements are **FULFILLED**.

Remarks:

FCC ID: 2AK6M-EP20FMMASTER**5.3 Co-location and Co-transmission****Applicable standard:**

OET Bulletin 65, Edition 97-01, Section 2: Multiple-transmitter sites and Complex Environments

The FCC's MPE limits vary with frequency. Therefore, in mixed or broadband RF fields where several sources and frequencies are involved, the fraction of the recommended limit (in terms of power density or square of the electric or magnetic field strength) incurred within each frequency interval should be determined, and the sum of all fractional contributions should not exceed 1.0, or 100 % in terms of percentage.

- | | |
|----------------|---|
| 1. MPE of UWB: | $P_d = 0.000189 \text{ mW/cm}^2$
Limit: 1.0 mW/cm^2
Fraction: $< 0.2 \%$ |
| 2. MPE BLE: | $P_d = 0.00135 \text{ mW/cm}^2$
Limit: 1.0 mW/cm^2
Fraction: $< 0.2 \%$ |
| 3. MPE NFC | $P_d = 8.2 \times 10^{-9} \text{ mW/cm}^2$
Limit: 0.98 mW/cm^2
Fraction: $< 0.2 \%$ |

Calculation of the sum of MPE ratios

$$\begin{aligned} &\text{Transmitter 1} + \text{Transmitter 2} + \text{Transmitter 3} \leq 100 \% ; \\ &0.2 \% + 0.2 \% + 0.2 \% = \mathbf{0.6 \% \leq 100 \%}; \end{aligned}$$

The requirements are **FULFILLED**.**Remarks:**
