Exhibit I: Antenna Description

FCC ID: HN2SB555-2



APPROVED SUPPLIERS

Manufacturer	Address/Telephone	805-606	Manufacturer's Part No.
Mobile Mark, Incorporated	3900-B River Road Schiller Park, II 60176 (847) 671-6690	-001 -002 -003 -004	PSTG0-2400RSCI PSTG0-900/1900SCI PSTG0-925/1800SCI PSTG0-1900SCI

1.0 Scope: This specification describes the requirements for a family of dual band, stubby portable wide area network antennas with SMA plug mounting as follows:

Intermec P/N	Antenna Type	Nominal Frequency	Color Dot
-001	802.11b	2400 MHz	green
(-002)	(CDMA)	900/1900 MHz	red
-003	GSM/GPRS	925/1800 MHz	blue
(-004)	CDMA	(1900)(MHz)	(white)

- 2.0 Quality Assurance: Intermec Receiving Inspection reserves the right to use AQL sampling techniques when inspecting a lot.
- 3.0 Packaging: All antennas will be packaged in containers capable of protecting them from damage in common carrier shipping and handling.
- 4.0 Markings: Individual antennas will be color coded with a color dot per Paragraph 1.0 on the antenna end opposite the connector. Each container will be labeled or otherwise marked with the manufacturer's name or trademark, and the part number designation. Major shipping cartons will be marked with the Intermec part number.

REVISION HISTORY

Rev.	File No.	Description of Change	Date	Approved
Α	C3233	Release	4/22/02	DV
В	C3332	¶1.0 Blue was yellow; ¶5.2 Was TBS; ¶5.3 Was TBS; ¶5.4 Was TBS; ¶6.2 Was	6/10/02	JS
		fractional wave; ¶6.3 -30° to +60°C was TBS; ¶8.0 Blue was yellow; ¶9.0 Was TBS		
С	C3463	Add -004 part; Revise ¶1.0, ¶5.2, ¶5.3 & ¶6.2; ¶7.2 Was not specified; ¶8.0 Add	10/31/02	JS
		length & -004 status; ¶9.0 Redrawn, L was 2.23, add 0.34, add 0.19 & add 0.09 (typ)		
D	C3534	¶5.2 3dBi & 4dBi were TBS; ¶5.3 3.0:1 was TBS; ¶8.0 1.10 was .90, & add white	12/16/02	JS

REVISION LEVEL [5	D	С																						
SHEET NUMBER '	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
COMPONENT ENGR.		DAT	Έ	TITLE																					
J. McROBERTS		3/2	28/0	0	Intermec Technologies Corp. DUAL BAND ANTENNA, SMA MOUN							JNT	-												
COGNIZANT ENGR.		DAT	Έ		550 Second Street S.E.				S.E. DRAWING NO.																
S. HOFSTETTER	HOFSTETTER Cedar Rapids, IA 52401 805-606-0XX																								
APPROVED		DAT	Έ		Te	leph	one	No.	(31	9) 36	69-3 <i>°</i>	100													
K. VORHIES by DV 4/22/02		Fa	csim	nile N	lo.	(31	9) 36	69-3 ²	153									,	Shee	et 1	Of 3	3			

5.0 Antenna Specifications:

- 5.1 Frequency: See parts tabulation below
- 5.2 Antenna Gain: -001 P/N 1.3 dBi
 -002 P/N 3 dBi

-003 P/N - 3 dBi -004 P/N - 4 dBi

5.3 VSWR: -001 P/N - 2.0:1 upper band

(-002 P/N - 3.0:1 lower band/3.0:1 upper band) -003 P/N - 3.8:1 lower band/2.5:1 upper band

-004 P/N - 3.0:1 upper band

- 5.4 Power: 1 Watt
- 5.5 Radiation: Omnidirectional
- 5.6 Polarization: Linear
- 5.7 Nominal Impedance: 50 Ohms

6.0 Mechanical Ratings:

- **6.1** Mounting Means: SMA plug mount (mounts to SMA receptacle, per tabulation below)
- **6.2** Element Length: $-001 \text{ P/N} 1/2\lambda$

 $(-002 \text{ P/N} - 1/4\lambda)$

 $-003 \text{ P/N} - 1/4\lambda$

 $(-004 \text{ P/N} - 1/4\lambda)$

6.3 Ambient Operating Temperature: -30°C to +60°C

7.0 Materials:

- 7.1 Antenna Material: Not specified
- 7.2 Sheath Material: 50/50 blend of K-Resin and Santoprene 7311

8.0 Parts Tabulation:

Part Number	Lower Band Freq. (MHz)	Upper Band Freq. (MHz)	Interconnection	Length L (inch)	Color Dot
-001	none	2400 to 2483.5	rev. sex SMA plug	2.23	green
-002	(824 to 894)	1850 to 1990	std. sex SMA plug	2.23	red
-003	890 to 960	1700 to 1880	std. sex SMA plug	2.23	blue
(-004)	none	(1850 to 1990)	std. sex SMA plug	(1.10)	white

9.0 Outline Drawing (inches):

