Bluetooth

Frequency: 2480 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used: f = 2480 MHz; σ = 1.839 S/m; ϵ_r = 38.16; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(7.62, 7.62, 7.62) @ 2480 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/Bluetooth_Ch78/Area Scan (6x8x1): Measurement grid:

dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.673 W/kg

Tablet/Aux Ant/Edge 4/Bluetooth_Ch78/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.888 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 1.26 W/kg **SAR(1 g) = 0.381 W/kg; SAR(10 g) = 0.128 W/kg** Smallest distance from peaks to all points 3 dB below = 6.3 mm Ratio of SAR at M2 to SAR at M1 = 32.5% Maximum value of SAR (measured) = 0.867 W/kg



Bluetooth

Frequency: 2480 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used: f = 2480 MHz; σ = 1.839 S/m; ϵ_r = 38.16; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1
- Probe: EX3DV4 SN7369; ConvF(7.62, 7.62, 7.62) @ 2480 MHz; Calibrated: 2021/6/3
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/BLE_Ch39/Area Scan (6x8x1): Measurement grid:

dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.265 W/kg

Tablet/Aux Ant/Edge 4/BLE_Ch39/Zoom Scan (7x7x7)/Cube 0: Measurement

grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.721 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.694 W/kg **SAR(1 g) = 0.231 W/kg; SAR(10 g) = 0.079 W/kg** Smallest distance from peaks to all points 3 dB below = 6.1 mm Ratio of SAR at M2 to SAR at M1 = 35.9% Maximum value of SAR (measured) = 0.475 W/kg



WiFi-2.4GHz

Frequency: 2437 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 2437 MHz; σ = 1.792 S/m; ϵ_r = 38.326; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(7.62, 7.62, 7.62) @ 2437 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Main Ant/Edge 2/802.11b_Ch6/Area Scan (6x8x1): Measurement grid:

dx=12mm, dy=12mm Maximum value of SAR (measured) = 2.12 W/kg

Tablet/Main Ant/Edge 2/802.11b_Ch6/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 10.74 V/m; Power Drift = 0.13 dB Peak SAR (extrapolated) = 3.46 W/kg **SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.400 W/kg** Smallest distance from peaks to all points 3 dB below = 5.8 mm Ratio of SAR at M2 to SAR at M1 = 38.4% Maximum value of SAR (measured) = 2.42 W/kg



WiFi-2.4GHz

Frequency: 2462 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 2462 MHz; σ = 1.819 S/m; ϵ_r = 38.231; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(7.62, 7.62, 7.62) @ 2462 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/802.11b_Ch11/Area Scan (6x8x1): Measurement grid:

dx=12mm, dy=12mm Maximum value of SAR (measured) = 2.14 W/kg

Tablet/Aux Ant/Edge 4/802.11b_Ch11/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 9.214 V/m; Power Drift = -0.04 dB Peak SAR (extrapolated) = 3.87 W/kg **SAR(1 g) = 1.2 W/kg; SAR(10 g) = 0.412 W/kg** Smallest distance from peaks to all points 3 dB below = 6.3 mm Ratio of SAR at M2 to SAR at M1 = 32.8% Maximum value of SAR (measured) = 2.68 W/kg



WiFi-5GHz

Frequency: 5290 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5290 MHz; σ = 4.888 S/m; ϵ_r = 35.275; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(5, 5, 5) @ 5290 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Main Ant/Edge2/802.11ac80_Ch58/Area Scan (5x7x1): Measurement

grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 1.97 W/kg

Tablet/Main Ant/Edge2/802.11ac80_Ch58/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 0.3570 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 7.15 W/kg **SAR(1 g) = 1.24 W/kg; SAR(10 g) = 0.266 W/kg** Smallest distance from peaks to all points 3 dB below = 4.7 mm Ratio of SAR at M2 to SAR at M1 = 49.2% Maximum value of SAR (measured) = 3.87 W/kg



WiFi-5GHz

Frequency: 5210 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5210 MHz; σ = 4.79 S/m; ϵ_r = 35.482; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(5.15, 5.15, 5.15) @ 5210 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/802.11ac80_Ch42/Area Scan (5x7x1): Measurement grid:

dx=10mm, dy=10mm Maximum value of SAR (measured) = 3.18 W/kg

Tablet/Aux Ant/Edge 4/802.11ac80_Ch42/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 3.097 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 7.11 W/kg **SAR(1 g) = 1.24 W/kg; SAR(10 g) = 0.275 W/kg** Smallest distance from peaks to all points 3 dB below = 4.3 mm Ratio of SAR at M2 to SAR at M1 = 49.2% Maximum value of SAR (measured) = 3.38 W/kg



WiFi-5GHz

Frequency: 5610 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5610 MHz; σ = 5.277 S/m; ϵ_r = 34.47; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(4.66, 4.66, 4.66) @ 5610 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Main Ant/Edge2/802.11ac80_Ch122/Area Scan (5x7x1): Measurement

grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 2.22 W/kg

Tablet/Main Ant/Edge2/802.11ac80_Ch122/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 0 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 7.64 W/kg **SAR(1 g) = 1.18 W/kg; SAR(10 g) = 0.255 W/kg** Smallest distance from peaks to all points 3 dB below = 4.7 mm Ratio of SAR at M2 to SAR at M1 = 44.4% Maximum value of SAR (measured) = 3.90 W/kg



WiFi-5GHz

Frequency: 5530 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5530 MHz; σ = 5.18 S/m; ϵ_r = 34.669; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(4.66, 4.66, 4.66) @ 5530 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/802.11ac80_Ch106/Area Scan (5x7x1): Measurement

grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 3.26 W/kg

Tablet/Aux Ant/Edge 4/802.11ac80_Ch106/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 2.173 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 8.07 W/kg **SAR(1 g) = 1.35 W/kg; SAR(10 g) = 0.299 W/kg** Smallest distance from peaks to all points 3 dB below = 4.9 mm Ratio of SAR at M2 to SAR at M1 = 46.8% Maximum value of SAR (measured) = 3.96 W/kg



WiFi-5GHz

Frequency: 5775 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5775 MHz; σ = 5.473 S/m; ϵ_r = 34.061; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1

- Probe: EX3DV4 - SN7369; ConvF(4.61, 4.61, 4.61) @ 5775 MHz; Calibrated: 2021/6/3

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm (Mechanical Surface Detection)

- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Main Ant/Edge2/802.11ac80_Ch155/Area Scan (5x7x1): Measurement

grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 2.75 W/kg

Tablet/Main Ant/Edge2/802.11ac80_Ch155/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 0 V/m; Power Drift =0.00 dB Peak SAR (extrapolated) = 8.45 W/kg **SAR(1 g) = 1.29 W/kg; SAR(10 g) = 0.274 W/kg** Smallest distance from peaks to all points 3 dB below = 5.1 mm Ratio of SAR at M2 to SAR at M1 = 45% Maximum value of SAR (measured) = 4.20 W/kg



WiFi-5GHz

Frequency: 5775 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 23.0°C; Liquid Temperature: 22.0°C

Medium parameters used (interpolated): f = 5775 MHz; σ = 5.473 S/m; ϵ_r = 34.061; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1486; Calibrated: 2021/6/1
- Probe: EX3DV4 SN7369; ConvF(4.61, 4.61, 4.61) @ 5775 MHz; Calibrated: 2021/6/3
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI V5.0 (20deg probe tilt); Type: QD OVA 002 AA; Serial: 1240

Tablet/Aux Ant/Edge 4/802.11ac80_Ch155/Area Scan (5x7x1): Measurement

grid: dx=10mm, dy=10mm. Maximum value of SAR (measured) = 2.59 W/kg

Tablet/Aux Ant/Edge 4/802.11ac80_Ch155/Zoom Scan (7x7x12)/Cube 0:

Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 2.088 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 8.19 W/kg **SAR(1 g) = 1.25 W/kg; SAR(10 g) = 0.270 W/kg** Smallest distance from peaks to all points 3 dB below = 4.3 mm Ratio of SAR at M2 to SAR at M1 = 44.8% Maximum value of SAR (measured) = 3.75 W/kg

