REV	DESCRIPTION OF REVISION	ENG APPD	DATE
01	INITIAL RELEASE	RHU	16APR19

NOTE:

- 1. REFER TO NETGEAR SPEC. DOC-00093 FOR COLOR TOLERANCES.
- 2. INK COLOR IS SHOWN TO THE RIGHT.
- 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.
- 4. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.
- 5. See NTGR DOC-00112 for SN standard.

6. SN, MAC address,

to be encoded QR (2D) barcode.

A. EACH DATA ELÈMENT IS TO BE SEPARATED BY A SEMICOLON WITH NO SPACE, AND TO BE PRINTED IN

THIS EXACT ORDER.

ELEMENT: SN:SERIAL NUMBER; SK:NETGEAR SKU NAME; MAC:MAC ADDRESS;

EXAMPLE: 510789235724097;ORBI BASE STATION;8A:00:27:C5:84:B3

The definition and sequence of QR code

WIFI:S:SSID;T:WPA2;P:PASSWORD;SN:SERIAL NUMBER;SK:NETGEAR SKU NAME;MAC:MAC ADDRESS;

The information of string

[WIFI:S:SSID]->(WIFI:S:Orbi_setup)->fix character


[T:WPA2;P:]-> (T:WPA2;P:)->fix character


[SN:SERIAL NUMBER] --(SN:)->固定字元/ (SERIAL NUMBER)->依照產品輸入訊息(EX:@62NDYMSC00001@) [SK:NETGEAR SKU NAME] -> (SK:)->固定字元/ NETGEAR SKU NAME->依照工單&生產品名By work order and

7. INSURE COUNTRY OF ORIGIN IS CORRECT.

A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER AND INCLUDE COUNTRY OF ORIGIN ON LABEL.

B. IF COUNTRY OF ORIGIN IS POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), OMIT TEXT FROM ARTWORK (USE LAYERS).







AUTHOR: R HU	AW,RBS10NA,PLBL,V1	NETGEAL	R
SHEET: 1 of 1	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.	P/N: AW-14284-01	REV: 01