



FCC RF Test Report

Product Name: Smart Phone

Model Number: MRD-LX1N

Report No.: SYBH(Z-RF)20181117006001-2005 FCC ID : QISMRD-LX1N

Autheorized	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	He Hao	M aowenli
DATE	2018-12-27	2018-12-27

Reliability Laboratory of Huawei Technologies Co., Ltd.

(Global Cmpliance and Testing Center of Huawei Technologies Co., Ltd)

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C Tel: +86 755 28780808 Fax: +86 755 89652518

X X Notice X X

 The Reliability Laboratory of Huawei Technologies Co., Ltd has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01
The Laboratory of Sporton International (Shenzhen) Inc has passed the accreditation by National Voluntary Laboratory Accreditation Program (NVLAP). The NVLAP LAB CODE is 600156-0.
The Reliability Laboratory of Huawei Technologies Co., Ltd has been recognized by the US Federal Communications Commission (FCC) to perform compliance testing subject to the Commission's Certification rules. The Designation Number is CN1173, and the Test Firm Registration Number is 294140.

4. The Laboratory of Sporton International (Shenzhen) Inc has been recognized by the US Federal Communications Commission (FCC) to perform compliance testing subject to the Commission's Certification rules. The Designation Number is CN5019, and the Test Firm Registration Number is 577730.

5. The Reliability Laboratory of Huawei Technologies Co., Ltd has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 6369A-1.

6. The Reliability Laboratory of Huawei Technologies Co., Ltd is also named "Global Compliance and Testing Center of Huawei Technologies Co., Ltd", the both names have coexisted since 2009.

7. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

8. The test report is invalid if there is any evidence of erasure and/or falsification.

9. The test report is only valid for the test samples.

10. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



MODIFICATION RECORD

No.	Report No	Modification Description
1	SYBH(Z-RF)20181117006001	First release.

DECLARATION

Туре	Description
Multiple	The present report applies to single model.
Models	The present report applies to several models. The practical measurements are
Applications	performed with the model XXXXX.
	The present report only presents the worst test case of all modes, see relevant test
	results for detailed.



1 Table of contents

1	Tab	ble of contents	4
2	Ger	neral Information	5
	1.1	Test standard/s	5
	1.2	TEST ENVIRONMENT	5
	1.3	TEST LABORATORIES	5
	1.4	Applicant and Manufacturer	5
	1.5	APPLICATION DETAILS	5
3	Sur	nmary	6
4	Pro	duct Description	7
	4.1	PRODUCT INFORMATION	7
	4.2	EUT IDENTITY	7
5	Tes	t Results	8
	5.1	BANDWIDTH MEASUREMENT	3
	5.2	IN-BAND RADIATED SPURIOUS EMISSION MEASUREMENTS)
	5.3	RADIATED SPURIOUS EMISSION MEASUREMENTS, OUT-OF-BAND	2
	5.4	FREQUENCY STABILITY	9
	5.5	AC POWER LINE CONDUCTED EMISSIONS)
6	MA	IN TEST INSTRUMENTS	2
	6.1	TEST LOCATION 1:	2
	6.2	SUB-CONTRACTED TEST LOCATION 1:	2
7	Sys	stem Measurement Uncertainty	3



2 General Information

1.1 Test standard/s

Applied Dules :	47 CFR FCC Part 02
Applied Rules :	47 CFR FCC Part 15 Subpart C (15.225)

1.2 Test Environment

Temperature :	TN 15 to 30 °C during room temperature tests		uring room temperature tests		
Ambient Relative Humidity:	20 to 85 %				
Atmospheric Pressure:	Not app	licable			
	VL	3.6	V		
Power supply :	VN	3.82	V	DC by Battery	
	VH	4.35	V		

NOTE 1: 1) VN= nominal voltage, VL= low extreme test voltage, VH= High extreme test voltage;

TN= normal temperature, TL= low extreme test temperature, TH= High extreme test temperature.

NOTE 2: The values used in the test report may be stringent than the declared.

1.3 Test Laboratories

Test Location 1 :	RELIABILITY LABORATORY OF HUAWEI TECHNOLOGIES CO., LTD.
Address of Test Location 1 :	No.2 New City Avenue Songshan Lake Sci. &Tech. Industry Park, Dongguan, Guangdong, P.R.C
Sub-contracted Test Location 1 :	Sporton International (Shenzhen) Inc.
Address of Sub-contracted Test Location 1 :	No.3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.China

1.4 Applicant and Manufacturer

Company Name :	HUAWEI TECHNOLOGIES CO., LTD
Address :	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

1.5 Application details

Date of Receipt Sample:	2018-12-04
Start of test:	2018-12-05
End of test:	2018-12-24



3 Summary

FCC Rule No.	Test Description	Test Limit	Test Condition	Test Result	Reference	Testing location
15.225 (a)	In-Band Emissions	15,848µV/m @ 30m 13.553 – 13.567 MHz		Pass	Section 5.2	Sub- contracted Test Location 1
2.1049	Bandwidth	N/A		Pass	Section 5.1	Location 1
15.225(b)	In-Band Emissions	334µV/m @ 30m 13.410 – 13.553 MHz 13.567 – 13.710 MHz		Pass	Section 5.2	Sub- contracted Test Location 1
15.225(c)	In-Band Emissions	106μV/m @ 30m 13.110 – 13.410 MHz 13.710 – 14.010 MHz	RADIATED	Pass	Section 5.2	Sub- contracted Test Location 1
15.225(d) 15.209	Out-of- Band Emissions	FCC: Emissions outside of the specified band (13.110 – 14.010 MHz) must meet the radiated limits detailed in15.209		Pass	Section 5.3	Sub- contracted Test Location 1
15.225(e)	Frequency Stability Tolerance	± 0.01% of Operating Frequency	Temperature Chamber	Pass	Section 5.4	Location 1
15.207	AC Conducted Emissions 150kHz – 30MHz	FCC: < FCC 15.207 limits	LINE CONDUCTED	Pass	Section 5.5	Location 1
NOTE: The transmitter has an integral PCB loop antenna that is enclosed within the housing of the EUT and meets the requirements of FCC 15.203						

4 Product Description

4.1 Product Information

4.1.1 General Description

MRD-LX1N is subscriber equipment in the GSM/WCDMA/LTE system. The GSM frequency bands include GSM850, GSM900, DCS1800 and PCS1900. The UMTS frequency band includes band I, band II, band V and band VIII. The LTE frequency bands include band 1, band 3, band 5, band 7, band8, band20. The Mobile Phone implements such functions as RF signal receiving/transmitting, LTE/HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS, AGPS and WIFI etc. Externally it provides one micro SD card interface, earphone port (to provide voice service), and dual SIM card interface. MRD-LX1N is dual SIM smart phone. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

Note: Only NFC test data included in this report.

4.2 EUT Identity

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

4.2.1 Board

Board					
Description	Software Version				
Main Board	HL1JATM	5.0.1.57 (SP1C900E64R1P3)			

4.2.2 Sub-Assembly

Sub-Assembly						
Sub-Assembly Name	Assembly Model Manufacturer		Description			
Adapter	HW- 050100U01	Huawei Technologies Co., Ltd.	Input Voltage: 100V-240V Output Voltage: 5V - 1A			
Li-ion Battery	HB405979ECW	Huawei Technologies Co., Ltd.	Rated capacity: 2920mAh Nominal Voltage: +3.82V Charging Voltage: +4.40V			



5 Test Results

5.1 Bandwidth Measurement

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

5.1.1 Test Setup





5.1.2 Test Result



Date: 17.DEC.2018 11:38:33

Test Environment	OBW (Hz)	FL@OBW (MHz)	FH@OBW (MHz)	Verdict
TN/VN	673.077	13.559708333	13.560381410	PASS

The result of the measurement is passed.



5.2 In-Band Radiated Spurious Emission Measurements

5.2.1 Test Setup



measurement parameters				
Detector:	Quasi Peak			
Sweep time:	-/-			
Resolution bandwidth:	10 kHz			
Video bandwidth:	10 kHz			
Span:	-/-			
Trace-Mode:	Max Hold			



5.2.2 Test Result



NOTES:

1. All measurements were performed using a loop antenna. The antenna was positioned in three orthogonal positions (X front, Y side, Z top) and the position with the highest emission level was recorded.

2. When using other measurement distance, according to the standard C63.10, If that point is closer to the EUT than $\lambda/2\pi$ and the limit distance is greater than $\lambda/2\pi$, the data was extrapolated to the specified measurement distance of 30m using extrapolation factor as specified in

§6.4.4.2. Extrapolation Factor = $40\log(\frac{d_{\text{near field}}}{d_{\text{measure}}})+20\log(\frac{d_{\text{limit}}}{d_{\text{near field}}})$.

3. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector.

4. Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain). The reading level is calculated by software which is not shown in the sheet.

The result of the measurement is passed.



5.3 Radiated Spurious Emission Measurements, Out-of-Band

5.3.1 Test Setup



Measurement parameters				
Detector:	Quasi Peak			
Sweep time:	Auto			
Resolution bandwidth:	9 kHz – 150 kHz: 200 Hz 150 kHz – 30 MHz: 9 kHz 30 MHz – 1000 MHz: 100 kHz			
Video bandwidth:	9 kHz – 150 kHz: 200 Hz 150 kHz – 30 MHz: 9 kHz 30 MHz – 1000 MHz: 100 kHz			
Span:	See Plots			
Trace-Mode:	Max Hold			



5.3.2 Test Result

9k~30MHz













Frequency (MHz)



Frequency (MHz)



NOTES:

1. All measurements were recorded using a spectrum analyzer employing a quasi-peak detector for emissions below 960MHz.

2. Both Vertical and Horizontal polarities of the receive antenna were evaluated with the worst case emissions being reported. Below 30MHz the Loop antenna was positioned in 3 separate radials.

3. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.

4. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.

5. Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain). The reading level is calculated by software which is not shown in the sheet.

The result of the measurement is passed.

Public



5.4 Frequency Stability

5.4.1 Test Setup

The EUT was placed in a Climatic Chamber. A small whip antenna was placed close to the EUT, and connected to the measuring Spectrum Analyzer. Measurement performed without modulation on TX.

5.4.2 Test Result

VOLTAGE (%)	POWER Battery	TEMP (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100%		-20	13559985	-15	-0.00011061947
100%		-10	13559979	-21	-0.00015486726
100%		0	13560023	23	0.00016961652
100%		10	13560021	21	0.00015486726
100%		20	13560007	7	0.00005162242
100%		30	13560012	12	0.00008849558
100%		40	13560018	18	0.00013274336
100%		50	13559987	-13	-0.00009587021
Battery End Point	3.6	20	13560014	14	0.00010324484
115%	4.35	20	13559985	-15	-0.00011061947

The result of the measurement is passed.

5.5 AC Power Line Conducted Emissions

5.5.1 Test Setup

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.



5.5.2 Test Result



MEASUREMENT RESULT: QP Detector

Frequency MHz	Level dBµV	Limit dBµV	Transd dB	Margin dB	Line	PE
0.242876	38.79	62.00	9.7	23.21	Ν	FLO
0.646324	43.87	56.00	9.7	12.13	Ν	FLO
1.069682	46.88	56.00	9.8	9.12	Ν	FLO
4.242518	39.61	56.00	10.0	16.39	Ν	FLO
19.717800	44.97	60.00	11.8	15.03	Ν	FLO
23.118444	45.82	60.00	12.3	14.18	Ν	FLO

MEASUREMENT RESULT: AV Detector

Frequency	Level	Limit	Transd	Margin	Line	DE
MHz	dBµV	dBµV	dB	dB	dBµV	PE
0.236839	26.59	52.21	9.7	25.62	Ν	FLO
0.641780	33.46	46.00	9.7	12.54	Ν	FLO
1.133270	35.34	46.00	9.8	10.66	Ν	FLO
4.044164	31.28	46.00	10.1	14.72	Ν	FLO
17.985460	34.44	50.00	11.6	15.56	Ν	FLO
23.588945	29.13	50.00	12.3	20.87	N	FLO

Note1:

1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)

The reading level is calculated by software which is not shown in the sheet.

2, Margin=Limit - Level

The result of the measurement is passed.

6 MAIN TEST INSTRUMENTS

6.1 Test Location 1:

Main Test Equipments(RSE test system)					
Equipment Name	Manufacturer	Model	Serial Number	Cal Date	Cal- Due
Test receiver	R&S	ESU26	100387	2018/1/20	2019/1/19
Spectrum analyzer	R&S	FSU3	200474	2018/1/20	2019/1/19
LOOP Antennas(9kHz- 30MHz)	R&S	HFH2-Z2	100262	2017/4/25	2019/4/25
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-490	2017/3/29	2019/3/29
Trilog Broadband Antenna (30M~3GHz)	SCHWARZBECK	VULB 9163	9163-521	2017/4/9	2019/4/9
Artificial Main Network	R&S	ENV4200	100134	2018/5/8	2019/5/7
Line Impedance Stabilization Network	R&S	ENV216	100382	2018/5/8	2019/5/7
Software Information					
Test Item	Software Name		Manufacturer		Version
RSE	EMC32		R&S		V8.40.0

Main Test Equipments(CE test system)					
Equipment Name	Manufacturer	Model	Serial Number	Cal Date	Cal-Due
Test receiver	R&S	ESCI	101163	2018/01/20	2019/01/19
Line Impedance Stabilization Network	R&S	ENV216	100382	2018/05/08	2019/05/07
Software Information					
Test Item	Software Name		Manufacturer		Version
CE	EMC32		R&S		V9.25.0

6.2 Sub-contracted Test Location 1:

Sub-contracted Test Location 1 :Main Test Equipments					
Equipment Name	Manufacturer	Model	Serial Number	Cal Date	Cal- Due
EMI Test Receiver&SA	Agilent	N9038A	N9038A	2018/8/30	2019/8/29
Loop Antenna	R&S	HFH2-Z2	HFH2-Z2	2018/5/30	2020/5/29
Bilog Antenna	TeseQ	CBL6112D	CBL6112D	2018/6/5	2019/6/4
LF Amplifier	Burgeon	BPA-530	BPA-530	2018/4/20	2019/4/19
Software Information					
Test Item	Software Name		Manufacturer		Version
RE	E3		AUDIX		6.2009-8- 24(sporton)



7 System Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in

accordance with the recommendations of ISO 17025 as following:

Test Item		Extended Uncertainty
Test Item	Extended Uncertainty	Test Item
All Emissions, Radiated	Field Strength [dBµV/m]	All Emissions, Radiated

-----The END------The END------