
## **SPECIFICATION**



二、原理图 SCHEMATIC DIAGRAM:

## Page 4 of 4

## 三、绕线参数 Winding Specification:

| 序号  | 端子       |   | 线径            | 圈数    | 绕线方向              |
|-----|----------|---|---------------|-------|-------------------|
| NO. | TERMINAL |   | WIRE          | Turns | Winding Direction |
| 1   | S        | F | 丝包线 0.08*105P | 10Ts  | CCW               |

## 四、电气特性 ELECTRICAL CHARACTERISTICS:

温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20%

| 序号  | 项目   | 端子       | 标准            | 测试条件           | 测试仪器            |
|-----|------|----------|---------------|----------------|-----------------|
| NO. | ITEM | TERMINAL | SPECIFICATION | TEST FREQUENCY | TEST EQUIPMENTS |
| 1   | IND. | S-F      | 3.7uH±10%单独线圈 | 100KHz/1.0V    | LCZ METER 1062B |
| 2   | IND. | S-F      | 6.4H±10%加磁片   | 100KHz/1.0V    | LCZ METER 1062B |
| 3   | DCR  | S-F      | ≤55m Ω        |                | LCZ METER 502B  |

Manufacturer: Studio Designs Limited Address: 403 The Laurels Industrial Building, 32 Tai Yau Street, San Po Kong, Hong Kong