

## FCC Part 15, Subpart C Test Report

FCC ID: 2AR2STAK4607LX

Applicant: MMD Hong Kong Holding Limited

Address: Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street,  
Kwun Tong, Kowloon, Hong Kong

Manufacturer: MMD Hong Kong Holding Limited

Address: Unit 1006, 10th Floor, C-Bons International Center, 108 Wai Yip Street,  
Kwun Tong, Kowloon, Hong Kong

Product: Wireless kids headphones

Brand(s): PHILIPS or 

Test Model(s): TAK4607LX

Series Model(s): TAK4607, TAK4607xx/yy, TAK4607LXxx/yy (xx=AA-ZZ or blank  
denoted different color; yy=00-99 denoted different country destination)

Test Date: Jun.18, 2022~ Jun. 27, 2022

Issued Date: Jul. 15, 2022

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Bld. N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town,  
Dongguan, China

Test Firm Registration No.: 915896

Designation No.: CN1255

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Tank Tan

Reviewed by :



Scott He

Approved by :



Harry Li

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into the account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the federal government. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)

Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park,](#)  
[HuangJiang Town, Dongguan, China](#)

Tel: [0769-83078199](tel:0769-83078199)

Web.: [www.hwa-hsing.com](http://www.hwa-hsing.com)

E-Mail: [customerservice.dg@hwa-hsing.com](mailto:customerservice.dg@hwa-hsing.com)

Release

[Ver. 1.5](#)



## Table of Contents

<b>Release Control Record .....</b>	<b>4</b>
<b>1. Summary of Test Results .....</b>	<b>5</b>
1.1 Measurement Uncertainty .....	5
1.2 Modification Record .....	5
<b>2. General Information .....</b>	<b>6</b>
2.1 General Description of EUT .....	6
2.2 Description of Test Channels .....	7
2.3 Test Mode Applicability and Tested Channel Detail .....	7
2.4 Description of Support Units .....	9
2.5 Configuration of System under Test .....	9
2.6 Duty Cycle of Test Signal .....	9
<b>3. Test Types and Results .....</b>	<b>10</b>
3.1 Radiated Emission and Band-edge Measurement .....	10
3.1.1 Limits of radiated emission and band-edge measurement .....	10
3.1.2 Test Instruments .....	11
3.1.3 Test Procedures .....	12
3.1.4 Deviation from Test Standard .....	13
3.1.5 Test Setup .....	14
3.1.6 EUT Operating Conditions .....	15
3.1.7 Test Results .....	16
3.2 6dB Bandwidth Measurement .....	28
3.2.1 Limits of 6dB Bandwidth Measurement .....	28
3.2.2 Test Setup .....	28
3.2.3 Test Instruments .....	28
3.2.4 Test Procedure .....	29
3.2.5 Deviation from Test Standard .....	29
3.2.6 EUT Operating Conditions .....	29
3.2.7 Test Result .....	29
3.3 Occupied Bandwidth Measurement .....	31
3.3.1 Test Setup .....	31
3.3.2 Test Instruments .....	31
3.3.3 Test Procedure .....	31
3.3.4 Deviation from Test Standard .....	31
3.3.5 EUT Operating Conditions .....	31
3.3.6 Test Results .....	31
3.4 Conducted Output Power Measurement .....	33
3.4.1 Limits of Conducted Output Power Measurement .....	33
3.4.2 Test Setup .....	33
3.4.3 Test Instruments .....	33
3.4.4 Test Procedures .....	33
3.4.5 Deviation from Test Standard .....	34
3.4.6 EUT Operating Conditions .....	34
3.4.7 Test Results .....	35
3.5 Power Spectral Density Measurement .....	38
3.5.1 Limits of Power Spectral Density Measurement .....	38
3.5.2 Test Setup .....	38
3.5.3 Test Instruments .....	38
3.5.4 Test Procedure .....	39
3.5.5 Deviation from Test Standard .....	39
3.5.6 EUT Operating Condition .....	39
3.5.7 Test Results .....	40
3.6 Conducted Out of Band Emission Measurement .....	42



3.6.1	Limits of Conducted Out of Band Emission Measurement.....	42
3.6.2	Test Setup .....	42
3.6.3	Test Instruments .....	42
3.6.4	Test Procedure .....	43
3.6.5	Deviation from Test Standard.....	43
3.6.6	EUT Operating Condition .....	43
3.6.7	Test results .....	44
<b>4.</b>	<b>Pictures of Test Arrangements .....</b>	<b>48</b>
<b>5.</b>	<b>Test Instruments.....</b>	<b>49</b>
	<b>Appendix – Information on The Testing Laboratories .....</b>	<b>50</b>



**HWA-HSING** Test Report No.: 220610KH16-RF-US-02

**Release Control Record**

Issue No.	Description	Date Issued
220610KH16-RF-US-02	Original Release	Jul. 15, 2022



## 1. Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247) KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2013			
Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit.
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	Pass	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Reference only
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used. The device is professionally installed

**Note:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

### 1.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The listed uncertainties are the worst cases uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.66 dB
Radiated Emissions up to 1 GHz	9KHz ~ 30MHz	2.16 dB
	30MHz ~ 1000MHz	3.47 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	4.84 dB
	18GHz ~ 40GHz	4.67 dB

### 1.2 Modification Record

There were no modifications required for compliance.



## 2. General Information

### 2.1 General Description of EUT

Product	Wireless kids headphones
Test Model(s)	TAK4607LX
Sample No.	HS220609-02-01
Series Model(s)	TAK4607, TAK4607xx/yy, TAK4607LXxx/yy (xx=AA-ZZ or blank denoted different color; yy=00-99 denoted different country destination)
Status of EUT	Engineering Prototype
Power Supply Rating	DC 5V from Adapter USB port, or DC 3.85V from battery
Modulation Type	GFSK for DTS
Transfer Rate	1/2 Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Maximum Output Power	5.967dBm (Peak)
Antenna Type	Chip Antenna
Antenna Gain	1.40dBi Maximum peak Gain
Antenna Connector	N/A
Accessory Device	N/A

**Note:**

1. Please refer to the EUT photo document (Reference No.: 220610KH16-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model difference: All models are identical except model name, color and country destination for marketing purpose.



## 2.2 Description of Test Channels

40 channels are provided to this EUT:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

## 2.3 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable test items	X-Axis	Y-Axis	Z-Axis	Voltage Supply
Radiated	Radiated Emissions	√	√	√	DC 3.85V from battery
Antenna Port Conducted Measurement	Band Edge Measurement	N/A	N/A	N/A	
	Antenna Port Emission	N/A	N/A	N/A	
	6dB Bandwidth	N/A	N/A	N/A	
	Occupied Bandwidth Measurement	N/A	N/A	N/A	
	Conducted power	N/A	N/A	N/A	
	Power Spectral Density	N/A	N/A	N/A	
<p>1. *: The EUT had been pre-tested on the positioned of each 3 Axis. The worst case was found when positioned on <b>Z-plane</b>.</p> <p>2. "N/A" means no effect.</p>					

### Test Condition:

Applicable test items	Environmental Conditions	Test Date	Tested by
Radiated Emissions	26.2deg. C, 51%RH	2022-6-22	Jim Xu
Antenna Port Conducted Measurement	26.2deg. C, 51%RH	2022-6-22	Dragon Long

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
- The wireless function cannot be used when charging, and the AC Power Conducted Emission item is not evaluated



**Radiated Emission Test (Above 1GHz):**

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1
-	0 to 39	0, 19, 39	GFSK	2

**Radiated Emission Test (Below 1GHz):**

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

**Power Line Conducted Emission Test:**

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	39	GFSK	2

**Antenna Port Conducted Measurement:**

\*This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1
-	0 to 39	0, 19, 39	GFSK	2





## 2.4 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	N/A	N/A	N/A	N/A	N/A

Insert Cable Connections to/from EUT provided by test team.


No.	Signal Cable Description of The Above Support Units
1.	N/A

## 2.5 Configuration of System under Test



## 2.6 Duty Cycle of Test Signal

Channel	BLE 1M Duty Cycle [%]	BLE 2M Duty Cycle [%]
2402	66.13	35.48
2440	65.08	35.48
2480	65.08	35.48





### 3. Test Types and Results

#### 3.1 Radiated Emission and Band-edge Measurement

##### 3.1.1 Limits of radiated emission and band-edge measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3
* DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable.		
* DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable		

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.1.2 Test Instruments

Radiated emission below 30MHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	100962	2023-01-13
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Test software	FARAD	FARAD	EZ_EMCV1.1.4.2	N/A
Loop Antenna	EMCI	HLA 6121	45745	2023-04-15*
Preamplifier	EMCI	EMC001340	980201	2022-09-08
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Frequency Range below 1GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	100962	2023-04-15*
Broadband antenna	Schwarzbeck	VULB 9168	00937	2023-01-13
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-09-12*
Signal Amplifier	Com-power	PAM-103	18020051	2022-09-08
Attenuator	Rohde&Schwarz	TS2GA-6dB	18101101	N/A
Test software	FARAD	FARAD	EZ_EMCV1.1.4.2	N/A

Frequency Range 1-18GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Horn Antenna	Schwarzbeck	BBHA 9170	01959	2022-09-12*
Broadband Coaxial Preamplifier	Schwarzbeck	PAM-118A	1804003	2022-09-07
Spectrum	Keysight	N9020A	MY51240612	2022-09-08
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Frequency Range 18-40GHz:

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
3m Semi-anechoic Chamber	MAORUI	9m*6m*6m	NSEMC003	2023-04-15*
Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101783	2023-01-13
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170242	2023-04-10*
Pre-Amplifier	EMCI	EMC 184045	980102	2023-01-12
Antenna Tower	MF	MFA-440H	NA	NA
Turn Table	MF	MFT-201SS	NA	NA
Antenna Tower&Turn Table Controller	MF	MF-7802	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months or 24 months (\*).

2. The test was performed in 966.



### 3.1.3 Test Procedures

#### a. Peak emission levels are measured by setting the instrument as follow:

- 1) RBW & VBW setting as a function of frequency:

Frequency	RBW	VBW
9kHz~150kHz	200Hz	600Hz
0.15MHz~30MHz	9kHz	30kHz
30MHz~1000MHz	120kHz	300kHz
>1000MHz	1MHz	3MHz

- 2) Detector = peak.  
3) Sweep time = auto.  
4) Trace mode = max hold.  
5) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Note: If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement

#### b. Average emission levels are measured by setting the instrument as follow:

##### ● Trace averaging with continuous EUT transmission at full power

If the EUT can be configured or modified to transmit continuously ( $D \geq 98\%$ ), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

- 1) RBW=1 MHz (unless otherwise specified).
- 2) VBW  $\geq 3 \times$  RBW.
- 3) Detector =RMS
- 4) Sweep time = auto.
- 5) Perform a trace average of at least 100 traces.

##### ● Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ( $D \geq 98\%$ ) cannot be achieved and the duty cycle is constant (duty cycle variations are less than  $\pm 2\%$ ), then the following procedure shall be used

- 1) The EUT shall be configured to operate at the maximum achievable duty cycle.
- 2) Measure the duty cycle D of the transmitter output signal as described in 11.6.
- 3) RBW=1 MHz (unless otherwise specified).
- 4) VBW  $\geq 3 \times$  RBW.
- 5) Detector =RMS
- 6) Sweep time = auto.
- 7) Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

\*If power averaging (rms) mode was used in step 5). then the applicable correction factor is  $[10 \log (1/D)]$ , where D is the duty cycle.

\*\*If linear voltage averaging mode was used in step f). then the applicable correction factor is  $[20 \log (1/D)]$ , where D is the duty cycle.

\*\*\*If a specific emission is demonstrated to be continuous ( $D > 98\%$ ) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that



● **Reduced VBW Averaging across ON and OFF times of the EUT transmissions with max hold**

If continuous transmission of the EUT ( $D > 98\%$ ) cannot be achieved and the duty cycle is not constant (duty cycle variations exceed  $\pm 2\%$ ), then the following procedure shall be used:

- 1) RBW = 1 MHz.
  - 2) VBW  $\geq 1/T$ .
  - 3) Detector = peak
  - 4) Sweep time = auto.
  - 5) Trace mode = max hold.
  - 6) Allow max hold to run for at least  $[50 \times (1/D)]$  traces
- c. The EUT was placed on the top of a rotating table 0.8 meters (below 1GHz) / 1.5 meters (1-18GHz) / 1.5 meters (18-40GHz) above the reference ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The EUT was set 3 meters away from the interference-receiving antenna (Below 1GHz) & (Above 1-18GHz), which was mounted on the top of a variable-height antenna tower. The EUT was set 1 meters away from the interference-receiving antenna (18-40GHz).
- e. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- f. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- g. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- h. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth = 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth =  $1/T$  for Average (Duty cycle  $< 98\%$ ) detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is = 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.1.4 Deviation from Test Standard

No deviation.




### 3.1.5 Test Setup

#### Radiated emission below 30MHz:




#### Frequency Range below 1GHz:








### Frequency Range 1-18GHz:



### Frequency Range 18-40GHz:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 3.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.




### 3.1.7 Test Results

#### 9kHz ~ 30MHz Data:

The amplitude of spurious emissions attenuated more than 20dB below the permissible value is not required to be report.

#### 30MHz ~ 1GHz Worst-Case Data:

Test Channel	Channel 0	Frequency Range	30MHz ~ 1GHz
Detector Function	Peak (PK) Quasi-peak (QP)	Tested By	Jim Xu




Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value





Test Channel	Channel 0	Frequency Range	30MHz ~ 1GHz
Detector Function	Peak (PK) Quasi-peak (QP)	Tested By	Jim Xu




Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value



Above 1GHz Data:  
BLE-1Mbps

Test channel	Channel 0	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m )	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2365.782	42.69	0.66	43.35	74.00	-30.65	peak	100	82
2	2365.782	27.95	0.66	28.61	54.00	-25.39	AVG	100	82
3 #	2401.954	99.07	0.70	99.77			peak	100	82
4 #	2401.954	88.76	0.70	89.46			AVG	100	82
5	4804.000	41.94	7.10	49.04	74.00	-24.96	peak	100	51
6	4804.000	33.86	7.10	40.96	54.00	-13.04	AVG	100	51
7	7206.000	34.75	12.08	46.83	74.00	-27.17	peak	110	223
8	7206.000	23.10	12.08	35.18	54.00	-18.82	AVG	110	223

Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)
2. Margin value = Emission level – Limit value
3. #2402MHz: Fundamental frequency.



Test channel	Channel 0	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu



Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)
2. Margin value = Emission level – Limit value
3. #2402MHz: Fundamental frequency.



Test channel	Channel 19	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

Antennal Polarity& Test Distance: Horizontal at 3m									
No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	98.92	0.77	99.69			peak	100	174
2#	2440.000	85.97	0.77	86.74			AVG	100	174
3	4880.000	40.49	7.33	47.82	74.00	-26.18	peak	207	98
4	4880.000	27.83	7.33	35.16	54.00	-18.84	AVG	207	98
5	7320.000	33.91	12.25	46.16	74.00	-27.84	peak	259	107
6	7320.000	21.95	12.25	34.20	54.00	-19.80	AVG	259	107
Antennal Polarity& Test Distance: Vertical at 3 M									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	97.48	0.77	98.25			peak	201	317
2#	2440.000	88.44	0.77	89.21			AVG	201	317
3	4880.000	41.94	7.33	49.27	74.00	-24.73	peak	100	209
4	4880.000	27.49	7.33	34.82	54.00	-19.18	AVG	100	209
5	7320.000	37.00	12.25	49.25	74.00	-24.75	peak	192	116
6	7320.000	21.60	12.25	33.85	54.00	-20.15	AVG	192	116


Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)
2. Margin value = Emission level – Limit value
3. #2440MHz: Fundamental frequency.



Test channel	Channel 39	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

Antennal Polarity&amp; Test Distance: Horizontal at 3 M




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.860	99.63	0.84	100.47			peak	100	232
2#	2479.860	89.12	0.84	89.96			AVG	100	232
3	2483.500	59.91	0.84	60.75	74.00	-13.25	peak	100	232
4	2483.500	36.58	0.84	37.42	54.00	-16.58	AVG	100	232
5	4960.000	40.86	7.56	48.42	74.00	-25.58	peak	100	51
6	4960.000	32.60	7.56	40.16	54.00	-13.84	AVG	100	51
7	7440.000	34.42	12.43	46.85	74.00	-27.15	peak	112	259
8	7440.000	21.06	12.43	33.49	54.00	-20.51	AVG	112	259

## Remarks:

1. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
2. Margin value = Emission level – Limit value
3. #2480MHz: Fundamental frequency.



Test channel	Channel 39	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.860	100.12	0.84	100.96			peak	100	110
2#	2479.860	89.97	0.84	90.81			AVG	100	110
3	2483.500	60.42	0.84	61.26	74.00	-12.74	peak	100	110
4	2483.500	36.95	0.84	37.79	54.00	-16.21	AVG	100	110
5	4960.000	43.47	7.56	51.03	74.00	-22.97	peak	142	97
6	4960.000	36.04	7.56	43.60	54.00	-10.40	AVG	142	97
7	7440.000	32.95	12.43	45.38	74.00	-28.62	peak	100	147
8	7440.000	20.85	12.43	33.28	54.00	-20.72	AVG	100	147

## Remarks:


- Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
- Margin value = Emission level – Limit value
- #2480MHz: Fundamental frequency.



## BLE-2Mbps

Test channel	Channel 0	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

Antennal Polarity&amp; Test distance: Horizontal at 3 M




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1	2378.619	43.26	0.68	43.94	74.00	-30.06	peak	100	233
2	2378.619	29.15	0.68	29.83	54.00	-24.17	AVG	100	233
3 #	2402.140	101.05	0.70	101.75			peak	100	233
4 #	2402.140	69.96	0.70	70.66			AVG	100	233
5	4804.000	40.38	7.10	47.48	74.00	-26.52	peak	118	48
6	4804.000	27.03	7.10	34.13	54.00	-19.87	AVG	118	48
7	7206.000	33.82	12.08	45.90	74.00	-28.10	peak	166	247
8	7206.000	21.37	12.08	33.45	54.00	-20.55	AVG	166	247

Remarks:

- Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
- Margin value = Emission level – Limit value
- #2402MHz: Fundamental frequency.



Test channel	Channel 0	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu



Remarks:

- Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)
- Margin value = Emission level – Limit value
- #2402MHz: Fundamental frequency.





Test channel	Channel 19	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

Antennal Polarity& Test Distance: Horizontal at 3m									
No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	96.48	0.76	97.24			peak	100	119
2#	2440.000	84.48	0.76	85.24			AVG	100	119
3	4880.000	41.88	7.33	49.21	74.00	-24.79	peak	226	86
4	4880.000	28.91	7.33	36.24	54.00	-17.76	AVG	226	86
5	7320.000	34.95	12.26	47.21	74.00	-26.79	peak	100	197
6	7320.000	22.93	12.26	35.19	54.00	-18.81	AVG	100	197
Antennal Polarity& Test Distance: Vertical at 3 M									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2440.000	97.47	0.76	98.23			peak	169	223
2#	2440.000	85.50	0.76	86.26			AVG	169	223
3	4880.000	40.80	7.33	48.13	74.00	-25.87	peak	201	98
4	4880.000	28.91	7.33	36.24	54.00	-17.76	AVG	201	98
5	7320.000	34.66	12.26	46.92	74.00	-27.08	peak	100	201
6	7320.000	21.95	12.26	34.21	54.00	-19.79	AVG	100	201


Remarks:

- Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)
- Margin value = Emission level – Limit value
- #2440MHz: Fundamental frequency.



Test channel	Channel 39	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

Antennal Polarity&amp; Test Distance: Horizontal at 3 M



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.960	99.89	0.84	100.73			peak	100	232
2#	2479.960	68.70	0.84	69.54			AVG	100	232
3	2483.500	61.23	0.84	62.07	74.00	-11.93	peak	100	232
4	2483.500	34.26	0.84	35.10	54.00	-18.90	AVG	100	232
5	4960.000	42.22	7.56	49.78	74.00	-24.22	peak	147	97
6	4960.000	28.74	7.56	36.30	54.00	-17.70	AVG	147	97
7	7440.000	32.87	12.43	45.30	74.00	-28.70	peak	144	207
8	7440.000	21.83	12.43	34.26	54.00	-19.74	AVG	144	207


## Remarks:

7. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamp Factor)
8. Margin value = Emission level – Limit value
9. #2480MHz: Fundamental frequency.



Test channel	Channel 39	Frequency Range	1GHz ~ 25GHz
Detector Function	Peak (PK) Average (AVG)	Tested By	Jim Xu

## Antennal Polarity&amp; Test Distance: Horizontal at 3 M



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Height (cm)	Table Angle (Degree)
1#	2479.960	100.39	0.84	101.23			peak	100	108
2#	2479.960	69.57	0.84	70.41			AVG	100	108
3	2483.500	61.19	0.84	62.03	74.00	-11.97	peak	100	108
4	2483.500	34.50	0.84	35.34	54.00	-18.66	AVG	100	108
5	4960.000	40.36	7.56	47.92	74.00	-26.08	peak	100	115
6	4960.000	28.10	7.56	35.66	54.00	-18.34	AVG	100	115
7	7440.000	34.66	12.43	47.09	74.00	-26.91	peak	100	117
8	7440.000	21.20	12.43	33.63	54.00	-20.37	AVG	100	117

## Remarks:

10. Emission Level = Read Level + Factor (Antenna Factor + Cable Loss - Preamplifier Factor)

11. Margin value = Emission level – Limit value

12. #2480MHz: Fundamental frequency.




### 3.2 6dB Bandwidth Measurement

#### 3.2.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

#### 3.2.2 Test Setup

Subclause 11.8 of ANSI C63.10 is applicable.



Spectrum analyzer test configuration

#### 3.2.3 Test Instruments

Refer to section 5 to get information of above instrument.



### 3.2.4 Test Procedure

#### Option 1:

- a. Set resolution bandwidth (RBW) = 30kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the dB bandwidth mode with  $X$  set to 6 dB. if the functionality described in 11.8.1 (i.e. RBW= 100 kHz. VBW  $\geq 3 \times$  RBW. and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability. care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB

### 3.2.5 Deviation from Test Standard

No deviation.

### 3.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 3.2.7 Test Result


Operation Channel	Frequency	Occupied Bandwidth (MHz)		
		BLE-1Mbps Result	BLE-2Mbps Result	Limit
0	2402MHz	0.656	1.120	>0.5
19	2440MHz	0.644	1.120	>0.5
39	2480MHz	0.668	1.172	>0.5





### 3.3 Occupied Bandwidth Measurement

#### 3.3.1 Test Setup



#### 3.3.2 Test Instruments

Refer to section 5 to get information of above instrument.

#### 3.3.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to peak. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 3.3.4 Deviation from Test Standard

No deviation.

#### 3.3.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 3.3.6 Test Results

Operation Channel	Frequency	BLE-1Mbps		
		Occupied Bandwidth (MHz)		
		BLE-1Mbps Result	BLE-2Mbps Result	Limit
0	2402MHz	1.006	1.965	2400~2483.5
19	2440MHz	1.012	1.977	2400~2483.5
39	2480MHz	1.015	1.974	2400~2483.6










### 3.4 Conducted Output Power Measurement

#### 3.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

#### 3.4.2 Test Setup

- Measurement using a spectrum analyzer (SA) Subclause 11.9.2.2 of ANSI C63.10 is applicable



Spectrum analyzer output power test configuration

#### 3.4.3 Test Instruments

Refer to section 5 to get information of above instrument.

#### 3.4.4 Test Procedures

Measurement using a spectrum analyzer (SA), Selection of test method:

The proper test method is selected based on the following criteria:

- Method AVGSA-1 or method AVGSA-1A (alternative)** shall be applied if either of the following conditions can be satisfied:
  - 1) The EUT transmits continuously (or with a  $D > 98\%$ ).
  - 2) Sweep triggering can be implemented in such a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the instrument configured as in method AVGSA-1) is equal to or shorter than the duration  $T$  of each transmission from the EUT, and if those transmissions exhibit full power throughout their durations.
- Method AVGSA-2 or method AVGSA-2A (alternative)** shall be applied if the conditions of the preceding item a) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than  $+2\%$ .
- Method AVGSA-3 or method AVGSA-3A (alternative)** shall be applied if the conditions of the preceding item a) and item b) cannot be achieved.



**Method AVGSA-3 or method AVGSA-3A:**

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c) SA Setting:
  - 1\* Set span to at least 1.5 times the OBW
  - 2\* Set sweep trigger to "free run."
  - 3\* Set RBW= 1% to 5% of the OBW. not to exceed 1MHz.
  - 4\* Set VBW  $\geq 3 \times$  RBW
  - 5\* Number of points in sweep  $\geq 2 \times$  span /RBW. (This gives bin-to-bin spacing  $\leq$  RBW / 2. so that narrowband signals are not lost between frequency bins).
  - 6\* Sweep time  $\leq$  (number of points in sweep)  $\times$  T. where T is defined in 11.6. If this gives a sweep time less than the auto sweep time of the instrument. then method AVGSA-3 shall not be used (use AVGSA-3A). The purpose of this step is so that the averaging time in each bin is less than or equal to the minimum time of a transmission.
  - 7\* Detector =RMS (power averaging).
  - 8\* Trace mode =max hold.
  - 9\* Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
  - 10\* Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function. then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

**3.4.5 Deviation from Test Standard**

No deviation.

**3.4.6 EUT Operating Conditions**

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 3.4.7 Test Results

BLE-1Mbps						
Peak Power						
Channel	Freq.	RF Output Power		Limit (mW)		Verdict
No.	(MHz)	(dBm)	(mW)	Rss-247	FCC	
0	2402	<b>5.967</b>	3.951	<125	<1000	Pass
19	2440	4.526	2.835	<125	<1000	Pass
39	2480	3.314	2.144	<125	<1000	Pass


BLE-1Mbps						
Average Power						
Channel	Freq.	RF Output Power		Limit (mW)		Verdict
No.	(MHz)	(dBm)	(mW)	Rss-247	FCC	
0	2402	-3.365	0.461	<125	<1000	Pass
19	2440	-5.512	0.281	<125	<1000	Pass
39	2480	-5.623	0.274	<125	<1000	Pass

Note: The test result had been added the duty cycle factor.


BLE-2Mbps						
Peak Power						
Channel	Freq.	RF Output Power		Limit (mW)		Verdict
No.	(MHz)	(dBm)	(mW)	Rss-247	FCC	
0	2402	5.843	3.839	<125	<1000	Pass
19	2440	4.487	2.809	<125	<1000	Pass
39	2480	3.319	2.147	<125	<1000	Pass

BLE-2Mbps						
Average Power						
Channel	Freq.	RF Output Power		Limit (mW)		Verdict
No.	(MHz)	(dBm)	(mW)	Rss-247	FCC	
0	2402	-4.701	0.338	<125	<1000	Pass
19	2440	-7.187	0.191	<125	<1000	Pass
39	2480	-5.948	0.254	<125	<1000	Pass

Note: The test result had been added the duty cycle factor.










### 3.5 Power Spectral Density Measurement

#### 3.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm/3kHz.

#### 3.5.2 Test Setup

- DTS maximum power spectral density level in the fundamental emission Subclause 11.10 of ANSI C63.10 is applicable



Spectrum analyzer test configuration

#### 3.5.3 Test Instruments

Refer to section 5 to get information of above instrument.



#### 3.5.4 Test Procedure

- a. **Method AVGPDS-1 or method AVGPDS-1A (alternative)** shall be applied if either of the following conditions can be satisfied:
- 1) The EUT transmits continuously (or with a  $D \geq 98\%$ ).
  - 2) Sweep triggering can be implemented in such a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep is equal to or shorter than the duration of each transmission from the EUT, and if those transmissions exhibit full power throughout these durations.
- b. **Method AVGPDS-2 or method AVGPDS-2A (alternative)** shall be applied if the conditions of the preceding item a) cannot be achieved. and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than  $\pm 2\%$ .
- c. **Method AVGPDS-3 or method AVGPDS-3A (alternative)** shall be applied if the conditions of the preceding paragraphs a) and b) cannot be achieved.

#### Method AVGPDS-3:

Method AVGPDS-3 uses mms detection across ON and OFE times of the EUT with max hold. The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e.  $D < 98\%$ ), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level. and when the transmission duty cycle is not constant (i.e., duty cycle variations exceed  $\pm 2\%$ ),

#### SA Setting:

- a. Set the instrument span to a minimum of 1.5 times the OBW.
  - b. Set sweep trigger to "free run."
  - c. Set the RBW = 3 kHz, VBW = 10 kHz,
  - d. Detector = RMS (power averaging).
  - e. Sweep time = Auto couple,
  - f. Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
  - g. Use the peak marker function to determine the maximum PSD level
- If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

#### 3.5.5 Deviation from Test Standard

No deviation.

#### 3.5.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




3.5.7 Test Results

<b>BLE-1Mbps</b>	Power Density		
Test Channel	Channel Frequency	Test Result (dBm/10kHz)	Limit (dBm/3kHz)
0	2402MHz	<b>-8.520</b>	<8
19	2440MHz	-8.982	<8
39	2480MHz	-8.977	<8

<b>BLE-2Mbps</b>	Power Density		
Test Channel	Channel Frequency	Test Result (dBm/10kHz)	Limit (dBm/3kHz)
0	2402MHz	<b>-8.393</b>	<8
19	2440MHz	-9.198	<8
39	2480MHz	-9.568	<8








### 3.6 Conducted Out of Band Emission Measurement

#### 3.6.1 Limits of Conducted Out of Band Emission Measurement

- a. **If the maximum peak conducted output power procedure was used to determine compliance as described in 11.9.1**, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b. **If maximum conducted (average) output power was used to determine compliance as described in 11.9.2**, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

#### 3.6.2 Test Setup

- DTS emissions in non-restricted frequency bands Subclause 11.11 of ANSI C63.10 is applicable.
- DTS emissions in restricted frequency bands Subclause 11.12 of ANSI C63.10 is applicable



Spectrum analyzer test configuration

#### 3.6.3 Test Instruments

Refer to section 5 to get information of above instrument.



#### 3.6.4 Test Procedure

a. Establish a reference level by using the following procedure:

- 1) Set instrument center frequency to DTS channel center frequency.
- 2) Set the span to 21.5 times the DTS bandwidth)
- 3) Set the RBW= 100 kHz)
- 4) Set the VBW  $\geq 3 \times$  RBW
- 5) Detector = peak
- 6) Sweep time = auto coupling
- 7) Trace mode =max hold
- 8) Allow trace to fully stabilize
- 9) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

b. Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW  $\geq 300$  kHz.
- 4) Detector = peak.
- 5) Sweep time = auto couple.
- 6) Trace mode = max hold.
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### 3.6.5 Deviation from Test Standard


No deviation.

#### 3.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 3.6.7 Test results









BLE 1Mbps  
Middle Channel  
Reference Level




BLE 2Mbps  
Middle Channel  
Reference Level




30~1000MHz Emission




30~1000MHz Emission




1000~26500MHz Emission




1000~26500MHz Emission





4.







#### **4. Pictures of Test Arrangements**

Please refer to the attached file (Test Setup Photo).





**5. Test Instruments**

Description & Manufacturer	Model No.	Serial No.	Due Date of Calibration
Spectrum Keysight	N9020A	MY51240612	2022-09-08
Spectrum Analyzer Rohde&Schwarz	FSV-40N	101783	2023-01-13
Power Meter 10Hz~18GHz Tonscend	JS0806-2	188060126	2022-09-08
Signal generator Keysight	E4421B	GB40051020	2022-09-12
Signal generator Keysight	N5182A	MY47420944	2022-09-08
Test Software Tonscend	JS0806-2	NA	NA
Hygrothermograph Yuhuaze	HTC-1	NA	2022-09-09

- Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA.
  2. The test was performed in Chamber 1.



#### **Appendix – Information on The Testing Laboratories**

We, [Hwa-Hsing \(Dongguan\) Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Bld N1, Yuyuan 2Rd, Yuyuan Industrial Park, HuangJiang Town, Dongguan, China](#)

Contact Tel: [0769-83078199](tel:0769-83078199)

Email: [Customerservice.dg@hwa-hsing.com](mailto:Customerservice.dg@hwa-hsing.com)

Web Site: [www.hwa-hsing.com](http://www.hwa-hsing.com)

--- END ---