

# Test Report

**Applicant:** FCC: NAYAX LTD  
IC: NAYAX

**Address of Applicant:** FCC: 18 Raoul Wallenberg St. building D 2 floor, Tel Aviv 6971915, Israel  
IC: 4 Hanechoshet st. TLV 69710 Israel

**Manufacturer:** FCC: NAYAX LTD  
IC: NAYAX

**Address of Manufacturer:** FCC: 18 Raoul Wallenberg St. building D 2 floor, Tel Aviv 6971915, Israel  
IC: 4 Hanechoshet st. TLV 69710 Israel

**Equipment Under Test (EUT)**

Product Name: Fusion

Model No.: Fusion

Trade Mark: Fusion

**FCC ID:** 2AK6L-FUSION

**IC:** 10840A-FUSION

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.225  
RSS-Gen Issue 5: March 2019  
RSS-210 Issue 9: August 2016

**Date of sample receipt:** September 17, 2019

**Date of Test:** September 17-October 14, 2019

**Date of report issued:** October 15, 2019

**Test Result :** PASS

Authorized Signature:




**Robinson Lo**  
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
00	October 15, 2019	Original

Prepared By:




Project Engineer

Date:

October 15, 2019

Check By:



Reviewer

Date:

October 15, 2019

## 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
4.1 MEASUREMENT UNCERTAINTY .....	4
5 GENERAL INFORMATION .....	5
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	6
5.3 TEST FACILITY .....	6
5.4 TEST LOCATION.....	6
5.5 DESCRIPTION OF SUPPORT UNITS .....	6
6 TEST INSTRUMENTS LIST .....	7
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT: .....	9
7.2 CONDUCTED EMISSIONS .....	10
7.3 FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK MEASUREMENT .....	13
7.4 RADIATED EMISSION .....	15
7.5 20dB EMISSION BANDWIDTH.....	20
7.6 FREQUENCY STABILITY MEASUREMENT .....	22
8 TEST SETUP PHOTO .....	24
9 EUT CONSTRUCTIONAL DETAILS .....	24

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Field Strength of Fundamental Emissions and Mask Measurement	15.225(a)(b)(c)	Pass
Radiated Emission	15.225(d)&15.209	Pass
20dB Emission Bandwidth	15.225&15.215	Pass
Frequency Stability Measurement	15.225(e)	Pass

Test Item	Section	Result
Antenna requirement	RSS-Gen 6.8	Pass
AC Power Line Conducted Emission	RSS-Gen 8.8	Pass
Field strength of the fundamental signal	RSS-210 B.6	Pass
Spurious emissions	RSS-210 B.6& RSS-Gen Clause 8.9&8.10	Pass
Band edge	RSS-210 B.6 & RSS-Gen Clause 8.9&8.10	Pass
99% Occupied Bandwidth	RSS-Gen 6.7	Pass
Frequency Stability Measurement	RSS-210 B.6	Pass

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.

### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 3.8039\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 3.9679\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.29\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.44\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

Product Name:	Fusion
Model No.:	Fusion
Serial No.:	000136
Hardware Version:	N/A
Software Version:	N/A
Sample(s) Status	Engineered sample
Operation Frequency:	13.56MHz
Channel Number:	1
Modulation:	ASK
Antenna type:	Internal antenna
Antenna gain:	0dBi(declare by applicant)
Power supply:	AC ADAPTER MODEL: RS-025/24-S335 INPUT: AC 100-240V, 50/60Hz, 1.2A MAX OUTPUT: DC 24V, 2.5A

## 5.2 Test mode

Transmitter mode	Keep the EUT in continuously transmitting.		
Pre-test mode.			
GTS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:			
Axis	X	Y	Z
Field Strength(dBuV/m)	50.44	52.65	51.81
Final Test Mode:			
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”: Y axis (see the test setup photo)			

## 5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

- **IC —Registration No.: 9079A**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. Has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A

## 5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number
Apple	PC	A1278	C1MN99ERDTY3

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020




## 7 Test results and Measurement Data

### 7.1 Antenna requirement:

<b>Standard requirement:</b>	FCC Part15 C Section 15.203
<b>15.203 requirement:</b> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>E.U.T Antenna:</b> <i>The NFC antenna is internal antenna; the best case gain of the antenna is 0dBi. reference to the appendix II for details</i>	

<b>Standard requirement:</b>	RSS-Gen Section 6.8
A transmitter can only be sold or operated with antennas with which it was approved. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. For transmitters of RF output power of 10 milliwatts or less, only the portion of the antenna gain that is in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power to demonstrate compliance with the radiated power limits specified in the applicable standard. For transmitters of output power greater than 10 milliwatts, the total antenna gain shall be added to the measured RF output power to demonstrate compliance to the specified radiated power	
<b>EUT Antenna:</b> <i>The NFC antenna is Internal antenna; the best case gain of the antenna is 0dBi. reference to the appendix II for details</i>	


## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207 RSS-Gen Section 8.8															
Test Method:	ANSI C63.10:2013															
Test Frequency Range:	150KHz to 30MHz															
Class / Severity:	Class B															
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto															
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>		Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)															
	Quasi-peak	Average														
0.15-0.5	66 to 56*	56 to 46*														
0.5-5	56	46														
5-30	60	50														
Test setup:	 <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>															
Test Instruments:	Refer to section 6.0 for details															
Test mode:	Refer to section 5.2 for details															
Test voltage:	AC120V 60Hz															
Test results:	Pass															

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


## Measurement data:

Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	48.24	0.40	0.07	48.71	65.74	-17.03	QP
0.15	30.41	0.40	0.07	30.88	55.74	-24.86	Average
0.32	32.46	0.39	0.10	32.95	59.80	-26.85	QP
0.32	25.13	0.39	0.10	25.62	49.80	-24.18	Average
0.42	38.72	0.34	0.11	39.17	57.42	-18.25	QP
0.42	32.85	0.34	0.11	33.30	47.42	-14.12	Average
0.94	27.43	0.21	0.15	27.79	56.00	-28.21	QP
0.94	25.65	0.21	0.15	26.01	46.00	-19.99	Average
3.29	24.72	0.20	0.19	25.11	56.00	-30.89	QP
3.29	15.94	0.20	0.19	16.33	46.00	-29.67	Average
10.34	36.75	0.20	0.20	37.15	60.00	-22.85	QP
10.34	33.56	0.20	0.20	33.96	50.00	-16.04	Average

## Neutral:




Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	49.27	0.40	0.07	49.74	65.91	-16.17	QP
0.15	31.70	0.40	0.07	32.17	55.91	-23.74	Average
0.42	37.86	0.34	0.11	38.31	57.42	-19.11	QP
0.42	31.41	0.34	0.11	31.86	47.42	-15.56	Average
0.63	31.34	0.28	0.12	31.74	56.00	-24.26	QP
0.63	22.19	0.28	0.12	22.59	46.00	-23.41	Average
0.95	25.98	0.21	0.15	26.34	56.00	-29.66	QP
0.95	23.79	0.21	0.15	24.15	46.00	-21.85	Average
3.31	23.84	0.20	0.19	24.23	56.00	-31.77	QP
3.31	14.03	0.20	0.19	14.42	46.00	-31.58	Average
10.34	35.22	0.20	0.20	35.62	60.00	-24.38	QP
10.34	32.12	0.20	0.20	32.52	50.00	-17.48	Average

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

## 7.3 Field Strength of Fundamental Emissions and Mask Measurement


Test Requirement:	FCC Part15 C Section 15.225(a)(b)(c) RSS-210 b.6& RSS-Gen 8.9& RSS-Gen 8.10
Test Method:	ANSI C63.10:2013 & ANSI C63.4: 2014 &RSS-Gen
Test site:	Measurement Distance: 3m
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=Auto
limit:	FCC Part 15.225 & 15.209 RSS-210, Annex B.6 RSS-Gen, Section 8.9
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

**Measurement data:**


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Remark
13.56	29.08	23.06	0.51	52.65	64	-11.35	QP


**Test plot as follows:**

Test data combines x, y, z-axis



## 7.4 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.225(d) and 15.209 RSS-210 B.6& RSS-Gen 8.9& RSS-Gen 8.10				
Test Method:	ANSI C63.10: 2013 & ANSI C63.4: 2014 &RSS-Gen				
Test Frequency Range:	9KHz to 1000MHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Limit:	All out of band emissions appearing in a restricted band as specified in Section 15.225 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.				
	Frequency (MHz)		Field strength (micorvolts/meter)	Measurement distance (meters)	
	0.009~0.490		2400/F(KHz)	300	
	0.490~1.705		24000/F(KHz)	30	
	1.705~30		30	30	
	30~88		100	3	
	88~216		150	3	
	216~960		200	3	
	960~1000		500	3	
Test setup:	Below 30MHz				
					
	Above 30MHz				


	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass



**Measurement data:**


■ 9kHz~30MHz

Test data combines x, y, z-axis; the radiation emission more than 20dB below the limit




## ■ 30MHz~1GHz

Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
47.826	51.65	12.28	0.75	36.08	28.60	40.00	-11.40	QP
95.427	58.10	11.52	1.16	36.68	34.10	43.50	-9.40	QP
189.739	60.89	9.90	1.79	37.28	35.30	43.50	-8.20	QP
239.987	61.87	11.85	2.07	37.37	38.42	46.00	-7.58	QP
244.232	64.72	11.96	2.09	37.37	41.40	46.00	-4.60	QP
250.301	63.01	12.18	2.12	37.38	39.93	46.00	-6.07	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
47.826	57.00	12.28	0.75	36.08	33.95	40.00	-6.05	QP
50.409	56.48	12.25	0.77	36.19	33.31	40.00	-6.69	QP
56.395	53.00	11.65	0.83	36.27	29.21	40.00	-10.79	QP
67.913	56.29	8.31	0.92	36.42	29.10	40.00	-10.90	QP
143.830	62.28	7.47	1.53	37.04	34.24	43.50	-9.26	QP
239.987	57.63	11.85	2.07	37.37	34.18	46.00	-11.82	QP


## 7.5 Occupied Bandwidth

Test Requirement:	FCC Part15 C Section 15.225 and 15.215 RSS-Gen 6.7
Test Method:	ANSI C63.10:2013 & RSS-Gen
Limit:	N/A
Test Procedure:	<ol style="list-style-type: none"> <li>1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT.</li> <li>2. Set the EUT to proper test channel.</li> <li>3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points.</li> <li>4. Read 20dB bandwidth &amp; 99%bandwidth.</li> </ol>
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


## Measurement Data

Test frequency(MHz)	20dB bandwidth(KHz)	99% bandwidth(KHz)	Result
13.56	2.837	2.4029	Pass

Test plot as follows:



## 7.6 Frequency Stability Measurement

Test Requirement:	FCC Part15 C Section 15.225 (e) RSS-210, B.6
Test Method:	ANSI C63.10: 2013
Receiver setup:	RBW=1KHz, VBW=1KHz, Sweep time=Auto
Limit:	<p>The frequency tolerance of the carrier signal shall be maintained within <math>\pm 0.01\%</math> of the operating frequency over a temperature variation of <math>-20</math> degrees to <math>+50</math> degrees C at normal supply voltage,</p> <p>for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.</p> <p>For battery operated equipment, the equipment tests shall be performed using a new battery.</p>
Test setup:	 <p>The diagram illustrates the test setup. On the left is a green Spectrum Analyzer. A cable connects its output to a yellow test equipment unit (EUT) located inside a blue oven. The oven is labeled 'OVEN' at the bottom. The EUT is labeled 'EUT' in the center.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Reference Frequency: 13.56MHz					
Power supplied (Vac)	Temperature (°C)	Frequency error		Limit	Result
		Hz	%		
120	-20	91	0.0007	+/- 0.01%	Pass
	-10	82	0.0006		
	0	68	0.0005		
	10	59	0.0004		
	20	49	0.0004		
	30	58	0.0004		
	40	74	0.0005		
	50	79	0.0006		

Reference Frequency: 13.56MHz					
Temperature (°C)	Power supplied (Vac)	Frequency error		Limit	Result
		Hz	ppm		
20	102	172	0.0013	+/- 0.01%	Pass
	120	156	0.0012		
	138	128	0.0009		

## 8 Test Setup Photo

Reference to the **appendix I** for details.

## 9 EUT Constructional Details

Reference to the **appendix II** for details.

----- End -----