

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID # CFS8DL5805BDV

Date : ____ 9/20/2003 Tested by: Greg Barbato

Approved by: Ken Addy

Test Sample (model) : _____ 5805BDV

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30								729
345	V	69.99	1.2	17.91	28510.2	10%	2851.0	7292
690	V	47.00	2	22.81	3894.9	10%	389.5	729
1035	H	41.20	2.6	25.69	2981.9	10%	298.2	500
1380	H	30.00	3	25.51	842.4	10%	84.2	500
1725	V	30.00	3.5	26.25	971.6	10%	97.2	729
2070	H	25.17	3.9	28.31	739.6	10%	74.0	729
2415	V	25.17	4.3	28.57	798.0	10%	79.8	729
2760	H	25.17	4.7	29.52	932.2	10%	93.2	729
3105	H	25.17	4.9	30.83	1109.2	10%	110.9	729
3450	H	25.17	5.1	32.4	1359.9	10%	136.0	729
4000								