



深圳锐锋电子技术有限公司

SPECIFICATION FOR APPROVAL

客 户:

CUSTOMER: Actions Microelectronics Co., Ltd.

客户料号:

CUSTOMER PART No.: ANT-524-DPB001

型 号:

RF10007

Model Number:

品名/规格:

Item description/ Rod antenna length 178MM 2.4~2.5GHz&5.15~5.85GHz

Specification: SMA ROHS

本厂料号:

PART No.: C009-10007-A

制造地址:

Production address: Floor 4, Building B5, Xinfu Industrial Zone, Fuyong Heping
Chongqing Road, Bao 'an District, Shenzhen City, Guangdong
Province

日 期:

DATE: 2020.12.14

出样签章Sample signature

核准 APPROVED BY	确认 CHECKED BY	制作 DRAWED BY

客户承认签章The customer acknowledges the seal

核准 APPROVED BY	确认 CHECKED BY	检查 TESTED BY



深圳锐锋电子技术有限公司

1. Contents 项目表

No.	content 内容	Pages 页数
0	Admission cover承认书封面	1
1	Item list项目表	2
2	Change of resume变更履历	2
3	Specification sheet规格表	3
4	Electrical test report电性测试报告	4-6
5	2D Product drawing	

2. Revision history变更履历

Revision 版本	Date 日期	Change the content 变更内容
X0	2020.12.14	


深圳锐锋电子技术有限公司

3. 规格表 Specification

A. Electrical Properties	
Frequency Rang 频段范围	2.40-2.50GHz 5.15-5.85GHz
Impedance 特性阻抗	50 Ω Nominal
VSWR 电压驻波比	2.0Max.
Gain(peak) 增益 (峰值)	5.0dBi
Out of roundness 不圆度	3.0dB(Max.)
Radiation 辐射方式	Omni-Directional/全向
Polarization 极化方式	Linear Vertical/垂直
B. Physical Properties	
4	
Connector Type 连接方式	SMA
Cable 线材	RG-178
Antenna Radiator 天线振子体	PCB FR
Antenna Plastic 天线塑胶	Body:TPE Hinge:PC+PBT Holder:PC+PBT
C. Environmental	
Storage Temp 存储环境范围	-40°C~+85°C
Operating Temp 工作环境	-10°C~+65°C
Storage humidity 存储湿度	95%
Working humidity 工作湿度	5%~95%

4. 电性测试报告Electrical Test Report

4.1 网络分析仪测试报告Network analyzer test report




4.2 暗室无源测试数据Dark room passive test data


Frequency	2.4GHz	2.41GHz	2.42GHz	2.43GHz	2.44GHz	2.45GHz	2.46GHz	2.47GHz	2.48GHz	2.49GHz	2.5GHz
Efficiency (%)	74.3	77.09	82.04	79.25	76.21	77.8	77.98	82.79	84.72	87.3	88.31
Gain (dBi)	1.87	2.02	2.46	2.44	2.34	2.48	2.54	2.8	3	3.18	3.16

Frequency	5.15GHz	5.2GHz	5.25GHz	5.3GHz	5.35GHz	5.4GHz	5.45GHz	5.5GHz	5.55GHz	5.6GHz	5.65GHz	5.7GHz	5.75GHz	5.8GHz	5.85GHz
Efficiency (%)	63.83	59.43	61.09	62.37	61.38	60.53	67.61	63.97	63.24	67.76	67.45	75.34	77.62	80.35	76.56
Gain (dBi)	2.1	5	2.52	3.29	3.3	2.79	3.66	3.38	3.4	3.73	3.55	3.71	3.7	5	3.1

4.3 暗室2D、3DRaditation Pattern



2. 4G





工程图

SIGN	DATE	DESCRIPTION	APPROVER
X0	20.12.18	New drawing	JOHN.LIU



6	P40-02002-R	PCB板	FR-4	双面覆铜 OSP 绿油 PCB009	1
5	P20-01002-R	SMA公头母针	BRASS	黑色POM外壳	1
4	P50-03003-R	下固定座	PC+PBT	黑色 CD-13 免打铆钉 小圆孔	1
3	P10-04001-R	RG-178 CABLE	镀锡铜	50 Ω 棕色 L:61mm	1
2	P50-02003-R	上固定座	PC+PBT	黑色 CD-374 免打铆钉	1
1	—	杆套	TPE	黑色 刀锋	1
No.	Part Number	Name	Material	Describe	Q'ty

NOTE:
1. 带“*”为重点管制尺寸;
2. 电测:
Frequency Rang:2.4&5.8GHz
Impedance:50 Ω
VSWR:2.0MAX
Gain(Peak):2.0dBi
3. 工作环境:-10℃~+65℃;
4. 环保要求: RoHS 2.0;

TITLE:		外置可拧天线		深圳锐锋电子技术有限公司			
P/N:		---					
CUSTOMER:		锐锋					
DRAW NO.:		C009-10007-A				APPROVED	
DIMENSIONS TOLERANCES UNLESS OTHERWISE NOTED						CHECKED	
一般公差 TOLERANCE	.XXX	±0.1	XX, ±5	SHEET: 1/1	SCALE: NONE	DRAWED	JOHN. LIU
	.XX	±0.3					
	.X	±1.0					
	X	±3.0					
				UNIT: mm	REV.X0		