



FCC CERTIFICATION TEST REPORT

Applicant	:	Shenzhen Romoss Technology Co., Ltd.
Address of Applicant	:	Room1601, BLOCK B, Building 7, Shenzhen International Innovation Valley, Dashi 1st Road Xili community, Xili Street, Nanshan, Shenzhen, Guangdong, P.R.China
Manufacturer	:	Jiangmen Romoss Technology Co., Ltd.
Address of Manufacturer	:	Room 01-2, First floor, Building 8, No. 80, Renhe Road, Tangxia Town, Pengjiang District, Jiangmen City
Equipment under Test	:	Portable Power Station
Model No.	:	RM300
FCC ID	:	2A6QM-RM300
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10:2013
Report No.	:	DDT-RE24032913-2E01
Issue Date	:	2024/04/19
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	6
2.	General Test Information.....	7
2.1.	Description of EUT.....	7
2.2.	Accessories of EUT	7
2.3.	Block diagram of EUT configuration for test.....	7
2.4.	Decision of final test mode	7
2.5.	Deviations of test standard	8
2.6.	Test environment conditions.....	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty	9
3.	20 dB Bandwidth.....	10
3.1.	Test equipment	10
3.2.	Block diagram of test setup	10
3.3.	Limits.....	10
3.4.	Assistant equipment used for test	10
3.5.	Test procedure	10
3.6.	Test result	11
3.7.	Test data	11
4.	Radiated Emission.....	12
4.1.	Test equipment	12
4.2.	Block diagram of test setup	13
4.3.	Limits.....	13
4.4.	Assistant equipment used for test	14
4.5.	Test procedure.....	14
4.6.	Test result	15
4.7.	Test data	16
5.	Antenna Requirement.....	24
5.1.	Limits.....	24
5.2.	Assess result.....	24
6.	Power Line Conducted Emissions.....	25
6.1.	Test equipment	25
6.2.	Block diagram of test setup	25
6.3.	Limits.....	25
6.4.	Assistant equipment used for test	25
6.5.	Test procedure.....	25
6.6.	Test result	26

6.7. Test data..... 27

7. Test Setup Photograph..... 29

8. Photos of the EUT 31

Test Report Declare

Applicant	:	Shenzhen Romoss Technology Co., Ltd.
Address of Applicant	:	Room1601, BLOCK B, Building 7, Shenzhen International Innovation Valley, Dashi 1st Road Xili community, Xili Street, Nanshan, Shenzhen, Guangdong, P.R.China
Equipment under Test	:	Portable Power Station
Model No.	:	RM300
Manufacturer	:	Jiangmen Romoss Technology Co., Ltd.
Address of Manufacturer	:	Room 01-2, First floor, Building 8, No. 80, Renhe Road, Tangxia Town, Pengjiang District, Jiangmen City

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10:2013

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24032913-2E01		
Date of Receipt:	2024/04/01	Date of Test:	2024/04/01~2024/04/18

Prepared By:**Approved By:****Bobo Chen/Engineer****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/04/19	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	20 dB Bandwidth	FCC Part 15: 15.215	/	Pass
2	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209	/	Pass
3	Antenna Requirement	FCC Part 15: 15.203	/	Pass
4	Power Line Conducted Emissions	FCC Part 15: 15.207(a)	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Portable Power Station
Model Number	: RM300
EUT Function Description	: Please reference user manual of this device
Power Supply	Type-C Input/Output(x1): DC 5V/3A, DC 9V/3A, DC 12V/3A, DC 15V/3A, DC 20V/3A (60W Max) USB-A Output(x2): DC 5V/3A, DC 9V/2A, DC 12V/1.5A (Dual-Port:36W Max) AC Input: AC 110-130V, 50Hz/60Hz 4A Max DC Input(XT60): DC 12-30V/8A(100W Max) AC Output(x1): AC 110-130V, 50Hz/60Hz 2.73A(Total:300W) Car Charger Output(x1): DC 12V/10A(120W Max) Wireless Charging Output: 15W
Wireless charging Operation frequency	: 110.5-205 kHz
Antenna Type	: Inductive loop coil antenna


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
AC cable	N/A	N/A	Length: 1 m
Car Charger cable	N/A	N/A	Length: 1 m

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

For mode 1: Tx mode (5W load, 7.5W load, 10W load, 15W load)

For mode 2: Standby mode

Note: Scan with mode 1 and mode 2, the worst case is mode 1 Tx mode (15W load) and recorded in this report

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15℃ to +35 ℃
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. 20 dB Bandwidth

3.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2024/07/11
Digital Multimeter	FLUKE	15B PRO	DDT-ZC02062	2024/07/14
AVG POWER SENSOR	R&S	NRP-Z22	DDT-ZC02301	2024/07/11

3.2. Block diagram of test setup



3.3. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

3.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Dummy load	N/A	N/A	N/A	N/A

3.5. Test procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300 Hz RBW and 1 kHz VBW. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

3.6. Test result

Test Site: 2#EMC Shield Room	Test Date: 2024/04/17
Condition: 24.5°C,56.0%	Test Engineer: Zora Zhang
Sample No.: S24032913-002	Test Mode: Charging

Freq. (kHz)	20 dB bandwidth Result (Hz)	Conclusion
146.378	673.077	Pass

3.7. Test data




4. Radiated Emission

4.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2024/04/26
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2024/04/20
Hochgewinn- Hornantenne	Schwarzbeck Mess-Elektronik	BBHA 9120 D	DDT-ZC02129	2025/09/17
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2024/04/25
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2024/05/14
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ- 1.5M	DDT-ZC02762	2024/04/20
High Pass filter	XIANXINGBO	XBLBQ-GTA67	DDT-ZC02179	2024/05/14
RF cable	Yuhu Technology	JCTB810-NJ-NJ- 9M	DDT-ZC02538	2024/04/22
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2024/05/14
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2024/04/20
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/10
RF cable	Yuhu Technology	ZT26S-SMAJ- SMAJ-1M	DDT-ZC02037	2024/04/22
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2024/04/22
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2024/04/22

4.2. Block diagram of test setup



4.3. Limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~ 88	3	100	40.0
88~ 216	3	150	43.5
216~ 960	3	200	46.0
960~ 1000	3	500	54.0

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 40\text{Log}(300\text{m}/3\text{m}) = \text{Limit}_{300\text{m}}(\text{dBuV/m}) + 80$$

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40$$

4.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Dummy load	N/A	N/A	N/A	N/A

4.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

4.6. Test result

PASS. (See below detailed test result)

4.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010251_H

Memo:

X Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.010	66.38	20.50	0.07	-29.30	57.65	127.59	69.94	PK	Vertical
2	0.024	61.48	20.46	0.07	-29.33	52.68	119.99	67.31	PK	Vertical
3	0.040	62.48	20.40	0.07	-29.35	53.60	115.56	61.96	PK	Vertical
4	0.056	67.24	20.40	0.07	-29.38	58.33	112.65	54.32	PK	Vertical
5	0.061	65.99	20.40	0.07	-29.39	57.07	111.84	54.77	PK	Vertical
6	0.135	107.72	20.17	0.07	-29.52	98.44	104.98	6.54	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.010	60.23	20.50	0.07	-29.30	51.50	127.60	76.10	AV	Vertical
2	0.024	57.12	20.46	0.07	-29.33	48.32	119.99	71.67	AV	Vertical
3	0.040	58.63	20.40	0.07	-29.35	49.75	115.56	65.81	AV	Vertical
4	0.056	61.03	20.40	0.07	-29.38	52.12	112.65	60.53	AV	Vertical
5	0.061	60.18	20.40	0.07	-29.39	51.26	111.85	60.59	AV	Vertical
6	0.135	102.76	20.17	0.07	-29.52	93.48	104.98	11.50	AV	Vertical

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010346_H

Memo:

Y Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.016	61.42	20.50	0.07	-29.31	52.68	123.26	70.58	PK	Vertical
2	0.024	63.88	20.46	0.07	-29.33	55.08	120.01	64.93	PK	Vertical
3	0.040	63.18	20.40	0.07	-29.35	54.30	115.57	61.27	PK	Vertical
4	0.056	64.23	20.40	0.07	-29.38	55.32	112.65	57.33	PK	Vertical
5	0.061	65.91	20.40	0.07	-29.39	56.99	111.84	54.85	PK	Vertical
6	0.136	107.76	20.17	0.07	-29.52	98.48	104.95	6.47	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.016	55.23	20.50	0.07	-29.31	46.49	123.25	76.76	AV	Vertical
2	0.024	58.92	20.46	0.07	-29.33	50.12	120.03	69.91	AV	Vertical
3	0.040	58.14	20.40	0.07	-29.35	49.26	115.58	66.32	AV	Vertical
4	0.056	59.74	20.40	0.07	-29.38	50.83	112.65	61.82	AV	Vertical
5	0.061	60.38	20.40	0.07	-29.39	51.46	111.85	60.39	AV	Vertical
6	0.136	104.52	20.17	0.07	-29.52	95.24	104.95	9.71	AV	Vertical

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010438_H

Memo:

Z Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.015	61.67	20.50	0.07	-29.31	52.93	124.03	71.10	PK	Vertical
2	0.024	63.77	20.46	0.07	-29.33	54.97	120.01	65.04	PK	Vertical
3	0.040	61.94	20.40	0.07	-29.35	53.06	115.57	62.51	PK	Vertical
4	0.056	68.23	20.40	0.07	-29.38	59.32	112.65	53.33	PK	Vertical
5	0.061	66.22	20.40	0.07	-29.39	57.30	111.83	54.53	PK	Vertical
6	0.136	108.18	20.17	0.07	-29.52	98.90	104.95	6.05	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.015	57.41	20.50	0.07	-29.31	48.67	124.02	75.35	AV	Vertical
2	0.024	59.10	20.46	0.07	-29.33	50.30	120.03	69.73	AV	Vertical
3	0.040	57.32	20.40	0.07	-29.35	48.44	115.58	67.14	AV	Vertical
4	0.056	62.23	20.40	0.07	-29.38	53.32	112.65	59.33	AV	Vertical
5	0.061	61.74	20.40	0.07	-29.39	52.82	111.84	59.02	AV	Vertical
6	0.136	103.41	20.17	0.07	-29.52	94.13	104.95	10.82	AV	Vertical

Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010551_H

Memo:

Z Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.281	73.01	20.17	0.08	-29.77	63.49	98.63	35.14	PK	Vertical
2	0.424	60.67	20.26	0.08	-30.10	50.91	95.07	44.16	PK	Vertical
3	2.470	50.98	20.40	0.13	-31.47	40.04	69.54	29.50	PK	Vertical
4	5.841	46.57	20.54	0.16	-31.39	35.88	69.54	33.66	PK	Vertical
5	9.814	44.82	20.46	0.20	-31.30	34.18	69.54	35.36	PK	Vertical
6	18.382	45.92	20.17	0.37	-31.17	35.29	69.54	34.25	PK	Vertical


Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	0.281	70.12	20.17	0.08	-29.77	60.60	98.63	38.03	AV	Vertical
2	0.424	56.21	20.26	0.08	-30.10	46.45	95.07	48.62	AV	Vertical
3	2.470	47.16	20.40	0.13	-31.47	36.22	69.54	33.32	QP	Vertical
4	5.841	42.75	20.54	0.16	-31.39	32.06	69.54	37.48	QP	Vertical
5	9.814	41	20.46	0.20	-31.30	30.36	69.54	39.18	QP	Vertical
6	18.382	42.82	20.17	0.37	-31.17	32.19	69.54	37.35	QP	Vertical

Note:

- Level = Reading + Cable Loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-04-16 Tested By: Junchang Du
EUT: Portable Power Station Model Number: RM300
Test Mode: Operating mode Power Supply: Battery
Condition: Temp:24.9°C;Humi:61.5% Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010635_H
Memo: Y Sample Number:S24032913-002




Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.279	72.91	20.17	0.08	-29.76	63.40	98.68	35.28	PK	Vertical
2	0.421	60.94	20.26	0.08	-30.09	51.19	95.11	43.92	PK	Vertical
3	2.503	52.10	20.40	0.13	-31.47	41.16	69.54	28.38	PK	Vertical
4	4.228	50.06	20.46	0.15	-31.43	39.24	69.54	30.30	PK	Vertical
5	7.571	45.49	20.57	0.18	-31.35	34.89	69.54	34.65	PK	Vertical
6	18.333	46.28	20.17	0.37	-31.18	35.64	69.54	33.90	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.279	69.23	20.17	0.08	-29.76	59.72	98.68	38.96	AV	Vertical
2	0.421	57.13	20.26	0.08	-30.09	47.38	95.11	47.73	AV	Vertical
3	2.503	47.38	20.40	0.13	-31.47	36.44	69.54	33.10	QP	Vertical
4	4.228	45.34	20.46	0.15	-31.43	34.52	69.54	35.02	QP	Vertical
5	7.571	41.49	20.57	0.18	-31.35	30.89	69.54	38.65	QP	Vertical
6	18.333	42.28	20.17	0.37	-31.18	31.64	69.54	37.90	QP	Vertical

Note:
1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-04-16 **Tested By:** Junchang Du
EUT: Portable Power Station **Model Number:** RM300
Test Mode: Operating mode **Power Supply:** Battery
Condition: Temp:24.9°C;Humi:61.5% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-010714_H
Memo: X Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.281	72.65	20.17	0.08	-29.77	63.13	98.63	35.50	PK	Vertical
2	0.424	60.33	20.26	0.08	-30.10	50.57	95.07	44.50	PK	Vertical
3	1.765	49.94	20.40	0.13	-31.48	38.99	69.54	30.55	PK	Vertical
4	3.253	50.47	20.41	0.14	-31.45	39.57	69.54	29.97	PK	Vertical
5	10.824	45.00	20.41	0.22	-31.29	34.34	69.54	35.20	PK	Vertical
6	15.475	45.34	20.25	0.31	-31.22	34.68	69.54	34.86	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	0.281	69.02	20.17	0.08	-29.77	59.50	98.63	39.13	AV	Vertical
2	0.424	56.2	20.26	0.08	-30.10	46.44	95.07	48.63	AV	Vertical
3	1.765	46.76	20.40	0.13	-31.48	35.81	69.54	33.73	QP	Vertical
4	3.253	47.29	20.41	0.14	-31.45	36.39	69.54	33.15	QP	Vertical
5	10.824	41.5	20.41	0.22	-31.29	30.84	69.54	38.70	QP	Vertical
6	15.475	41.84	20.25	0.31	-31.22	31.18	69.54	38.36	QP	Vertical

Note:

1. Level = Reading + Cable Loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: 9kHz-150kHz RBW: 300Hz, VBW: 1 kHz, Sweep time: auto.
150kHz-30MHz RBW: 10kHz, VBW: 30kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-005657_H

Memo:

Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	30.021	33.17	10.30	4.47	-31.00	16.94	40.00	23.06	QP	Horizontal
2	53.051	26.8	13.53	4.74	-30.68	14.39	40.00	25.61	QP	Horizontal
3	118.902	31.29	9.75	5.16	-30.84	15.36	43.50	28.14	QP	Horizontal
4	143.986	29.94	9.30	5.29	-30.77	13.76	43.50	29.74	QP	Horizontal
5	265.374	43.92	11.76	6.00	-30.40	31.28	46.00	14.72	QP	Horizontal
6	686.721	26.35	19.30	7.70	-29.90	23.45	46.00	22.55	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-16

Tested By:

Junchang Du

EUT:

Portable Power Station

Model Number:

RM300

Test Mode:

Operating mode

Power Supply:

Battery

Condition:

Temp:24.9°C;Humi:61.5%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032913-2E\FCC BELOW 1G\20240416-005745_V

Memo:

Sample Number:S24032913-002



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	44.709	34.76	13.14	4.66	-30.78	21.78	40.00	18.22	QP	Vertical
2	59.977	37.06	12.79	4.76	-30.63	23.98	40.00	16.02	QP	Vertical
3	72.223	39.24	9.51	4.80	-30.55	23.00	40.00	17.00	QP	Vertical
4	119.906	43.95	9.98	5.17	-30.84	28.26	43.50	15.24	QP	Vertical
5	264.445	36.52	11.68	6.00	-30.41	23.79	46.00	22.21	QP	Vertical
6	900.166	24.67	21.90	8.34	-29.00	25.91	46.00	20.09	QP	Vertical

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

5. Antenna Requirement

5.1. Limits

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

5.2. Assess result


Conclusion: The antenna used for this product is inductive loop coil antenna and that no antenna other than that furnished by the responsible party shall be used with the device.

6. Power Line Conducted Emissions

6.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Software	Audix/TW	e3	DDT-ZC01252	/
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2024/07/11
EMI Test Receiver	R&S	ESCI	DDT-ZC00235	2024/07/10
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2024/07/14
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2024/07/10
Pulse Limiter	SCHWARZBEC K	ESH3-Z2	DDT-ZC00539	2024/07/14

6.2. Block diagram of test setup



6.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

6.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
Dummy load	N/A	N/A	N/A	N/A
AC cable	N/A	N/A	Length: 1 m	/

6.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

6.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “-----” means Peak detection; “-----” means Average detection.


Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

6.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2024 CE report data\Q24032913-1E\RF-FCC.EM6**
Test Date : 2024-04-17 **Tested By** : Gen liu
EUT : Portable Power Station **Model Number** : RM300
Power Supply : AC 120V/60Hz **Test Mode** : Operating mode
Condition : TEMP:22.5°C, RH:46.2% **ISN** : 2023 1# ENV216/LINE
Memo : Sample Number:S24032913-002

Data: 2



Item	Freq.	Read Level	ISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)	
1	0.61	7.62	9.78	0.81	9.72	27.93	56.00	-28.07	QP
2	0.61	0.59	9.78	0.81	9.72	20.90	46.00	-25.10	Average
3	1.07	10.51	9.65	0.67	9.73	30.56	56.00	-25.44	QP
4	1.07	-2.03	9.65	0.67	9.73	18.02	46.00	-27.98	Average
5	3.21	-2.36	9.63	0.58	9.78	17.63	56.00	-38.37	QP
6	3.21	-11.90	9.63	0.58	9.78	8.09	46.00	-37.91	Average
7	6.32	6.13	9.69	0.47	9.80	26.09	60.00	-33.91	QP
8	6.32	-2.93	9.69	0.47	9.80	17.03	50.00	-32.97	Average
9	11.38	5.88	9.80	0.17	9.84	25.69	60.00	-34.31	QP
10	11.38	0.27	9.80	0.17	9.84	20.08	50.00	-29.92	Average
11	18.33	17.88	9.87	0.32	9.91	37.98	60.00	-22.02	QP
12	18.33	12.25	9.87	0.32	9.91	32.35	50.00	-17.65	Average


Note:

1. Result Level = Read Level + ISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2024 CE report data\Q24032913-1E\RF-FCC.EM6**
Test Date : 2024-04-17 **Tested By** : Gen liu
EUT : Portable Power Station **Model Number** : RM300
Power Supply : AC 120V/60Hz **Test Mode** : Operating mode
Condition : TEMP:22.5°C, RH:46.2% **ISN** : 2023 1# ENV216/NEUTRAL
Memo : Sample Number:S24032913-002

Data: 4



Item	Freq.	Read Level	ISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)	
1	0.62	2.85	9.83	0.81	9.72	23.21	56.00	-32.79	QP
2	0.62	-3.72	9.83	0.81	9.72	16.64	46.00	-29.36	Average
3	1.06	3.60	9.74	0.67	9.73	23.74	56.00	-32.26	QP
4	1.06	-3.16	9.74	0.67	9.73	16.98	46.00	-29.02	Average
5	3.24	-1.44	9.72	0.58	9.78	18.64	56.00	-37.36	QP
6	3.24	-11.09	9.72	0.58	9.78	8.99	46.00	-37.01	Average
7	6.42	7.51	9.80	0.47	9.80	27.58	60.00	-32.42	QP
8	6.42	-4.50	9.80	0.47	9.80	15.57	50.00	-34.43	Average
9	11.26	6.63	9.78	0.17	9.84	26.42	60.00	-33.58	QP
10	11.26	0.85	9.78	0.17	9.84	20.64	50.00	-29.36	Average
11	18.33	17.93	9.85	0.32	9.91	38.01	60.00	-21.99	QP
12	18.33	12.02	9.85	0.32	9.91	32.10	50.00	-17.90	Average

Note:

- Result Level = Read Level + ISN Factor + Pulse Limiter Factor + Cable loss.
- If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
- Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

8. Photos of the EUT

Please refer to DDT-Q24032913-1E appendix I

-----End Report-----