

RF EXPOSURE EVALUATION

EUT Specification

EUT	LED Security Light
Model Number	MK-SC0118, ES00931G
FCC ID	2APP3MK-SC0118
Antenna gain (Max)	1.3dBi
Operation Frequency	BT:2.402-2.480GHz WLAN: 2.412GHz ~ 2.462GHz
Input Rating	AC 120V, 50/60Hz
Max. output power	BT:-0.06dBm WLAN: 802.11b: 9.86dBm 802.11g: 7.68dBm 802.11n(HT20): 6.42dBm 802.11n(HT40): 4.83dBm

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1416$

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, $1\text{mW}/\text{cm}^2$. If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 1.3 dBi

BT:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm^2)	Power density Limits (mW/cm^2)
GFSK	2402	-0.06	0 ± 1	1	1.349	0.000338	1
GFSK	2440	-0.87	-1 ± 1	0	1.349	0.000268	1
GFSK	2480	-1.77	-2 ± 1	-1	1.349	0.000213	1

WIFI:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power (dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
802.11b	1	10 ± 1	11	12.589	1.3	1.349	0.003379	1
	6	9 ± 1	10	10.000	1.3	1.349	0.002684	1
	11	9 ± 1	10	10.000	1.3	1.349	0.002684	1
802.11g	1	7 ± 1	8	6.310	1.3	1.349	0.001693	1
	6	7 ± 1	8	6.310	1.3	1.349	0.001693	1
	11	8 ± 1	9	7.943	1.3	1.349	0.002132	1
802.11n (HT20)	1	6 ± 1	7	5.012	1.3	1.349	0.001345	1
	6	6 ± 1	7	5.012	1.3	1.349	0.001345	1
	11	6 ± 1	7	5.012	1.3	1.349	0.001345	1
802.11n (HT40)	3	5 ± 1	6	3.981	1.3	1.349	0.001068	1
	6	5 ± 1	6	3.981	1.3	1.349	0.001068	1
	9	5 ± 1	6	3.981	1.3	1.349	0.001068	1

Signature:

A handwritten signature in black ink, which appears to read "Alan He". The signature is fluid and cursive, with a long, sweeping underline that extends to the left.

Alan He

Date: 2021-12-17