

RF Exposure Report

Report No.: SABDBO-WTW-P20090055A

FCC ID: P4Q-N594

Test Model: N594

Received Date: 2021/8/23

Test Date: 2021/9/2 ~2021/9/6

Issued Date: 2021/9/16

Applicant: MiTAC Digital Technology Corporation

Address: 4F., No. 1, R&D Road 2, Hsinchu Science Park, Hsinchu 30076, Taiwan,

R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration /

Designation Number: 198487 / TW2021





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: SABDBO-WTW-P20090055A Pa Reference No.: BDBO-WTW-P21080882

Page No. 1 / 6

Report Format Version: 6.1.1



Table of Contents

Rele	elease Control Record	3
1	Certificate of Conformity	4
2	·	
2.	2.1 Limits For Maximum Permissible Exposure (MPE)	5
2.	2.2 MPE Calculation Formula	5
2.	2.3 Classification	5
	2.4 Antenna Gain	
2.	2.5 Calculation Result Of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SABDBO-WTW-P20090055A	Original release.	2021/9/16

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SABDBO-WTW-P20090055A Reference No.: BDBO-WTW-P21080882



1	Certificate	of Conformity	,
---	-------------	---------------	---

Product: Driving Recorder

Brand: Mio

Test Model: N594

Sample Status: Engineering sample

Applicant: MiTAC Digital Technology Corporation

Test Date: 2021/9/2 ~2021/9/6

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Jessica Cheng / Senior Specialist

Approved by : , Date: 2021/9/16

Rex Lai / Associate Technical Manager



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)			Average Time (minutes)				
	Limits For General Population / Uncontrolled Exposure						
0.3-1.34	614	1.63	(100)*	30			
1.34-30	824/f	2.19/f (180/f²)*		30			
30-300	27.5	0.073 0.2		30			
300-1500			f/1500	30			
1500-100,000	0-100,000 1.0		1.0	30			

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Function	Frequency (MHz)	Peak Gain (dBi)	Antenna Type	Connector
WLAN	2412-2462	-1.58	PIFA	N/A

Note: The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Report No.: SABDBO-WTW-P20090055A Reference No.: BDBO-WTW-P21080882



2.5 Calculation Result Of Maximum Conducted Power

Function	Frequency Band (MHz)	Max AV Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
WLAN	2412-2462	14.46	-1.58	20	0.0039	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

	N	n	
	IVI	u	

Report No.: SABDBO-WTW-P20090055A Reference No.: BDBO-WTW-P21080882