

FCC Test Report

Report No.: RFBDGD-WTW-P24060412

FCC ID: Q3N-NUHF

Test Model: RS36 NUHF

Received Date: 2024/6/18

Test Date: 2024/8/1 ~ 2024/8/13

Issued Date: 2024/11/6

Applicant: CIPHERLAB CO., LTD

Address: 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 106

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration /
Designation Number: 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

| | |
|---|-----------|
| Release Control Record | 4 |
| 1 Certificate of Conformity | 5 |
| 2 Summary of Test Results | 6 |
| 2.1 Measurement Uncertainty | 6 |
| 2.2 Modification Record | 6 |
| 3 General Information | 7 |
| 3.1 General Description of EUT | 7 |
| 3.2 Description of Test Modes | 8 |
| 3.2.1 Test Mode Applicability and Tested Channel Detail | 9 |
| 3.3 Description of Support Units | 10 |
| 3.3.1 Configuration of System under Test | 10 |
| 3.4 General Description of Applied Standards and References | 11 |
| 4 Test Types and Results | 12 |
| 4.1 Radiated Emission and Bandedge Measurement | 12 |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 12 |
| 4.1.2 Test Instruments | 13 |
| 4.1.3 Test Procedures | 14 |
| 4.1.4 Deviation from Test Standard | 14 |
| 4.1.5 Test Setup | 15 |
| 4.1.6 EUT Operating Conditions | 16 |
| 4.1.7 Test Results | 17 |
| 4.2 Conducted Emission Measurement | 29 |
| 4.2.1 Limits of Conducted Emission Measurement | 29 |
| 4.2.2 Test Instruments | 29 |
| 4.2.3 Test Procedures | 30 |
| 4.2.4 Deviation from Test Standard | 30 |
| 4.2.5 Test Setup | 30 |
| 4.2.6 EUT Operating Conditions | 30 |
| 4.2.7 Test Results | 31 |
| 4.3 Number of Hopping Frequency Used | 33 |
| 4.3.1 Limits of Hopping Frequency Used Measurement | 33 |
| 4.3.2 Test Setup | 33 |
| 4.3.3 Test Instruments | 33 |
| 4.3.4 Test Procedure | 33 |
| 4.3.5 Deviation from Test Standard | 33 |
| 4.3.6 Test Results | 33 |
| 4.4 Dwell Time on Each Channel | 34 |
| 4.4.1 Limits of Dwell Time on Each Channel Measurement | 34 |
| 4.4.2 Test Setup | 34 |
| 4.4.3 Test Instruments | 34 |
| 4.4.4 Test Procedures | 34 |
| 4.4.5 Deviation from Test Standard | 34 |
| 4.4.6 Test Results | 35 |
| 4.5 Channel Bandwidth | 36 |
| 4.5.1 Limits of Channel Bandwidth Measurement | 36 |
| 4.5.2 Test Setup | 36 |
| 4.5.3 Test Instruments | 36 |
| 4.5.4 Test Procedure | 36 |
| 4.5.5 Deviation from Test Standard | 36 |
| 4.5.6 EUT Operating Condition | 36 |
| 4.5.7 Test Results | 37 |
| 4.6 Hopping Channel Separation | 38 |
| 4.6.1 Limits of Hopping Channel Separation Measurement | 38 |

| | | |
|----------|---|-----------|
| 4.6.2 | Test Setup | 38 |
| 4.6.3 | Test Instruments | 38 |
| 4.6.4 | Test Procedure | 38 |
| 4.6.5 | Deviation from Test Standard | 38 |
| 4.6.6 | Test Results | 39 |
| 4.7 | Maximum Output Power | 40 |
| 4.7.1 | Limits of Maximum Output Power Measurement | 40 |
| 4.7.2 | Test Setup | 40 |
| 4.7.3 | Test Instruments | 40 |
| 4.7.4 | Test Procedure | 40 |
| 4.7.5 | Deviation from Test Standard | 40 |
| 4.7.6 | EUT Operating Condition | 40 |
| 4.7.7 | Test Results | 41 |
| 4.8 | Conducted Out of Band Emission Measurement | 42 |
| 4.8.1 | Limits Of Conducted Out Of Band Emission Measurement | 42 |
| 4.8.2 | Test Instruments | 42 |
| 4.8.3 | Test Procedure | 42 |
| 4.8.4 | Deviation from Test Standard | 42 |
| 4.8.5 | EUT Operating Condition | 42 |
| 4.8.6 | Test Results | 42 |
| 5 | Pictures of Test Arrangements | 44 |
| | Appendix – Information of the Testing Laboratories | 45 |

Release Control Record

| Issue No. | Description | Date Issued |
|----------------------|------------------|-------------|
| RFBDGD-WTW-P24060412 | Original release | 2024/11/6 |

1 Certificate of Conformity

Product: UHF reader

Brand: CIPHERLAB

Test Model: RS36 NUHF

Sample Status: Engineering sample

Applicant: CIPHERLAB CO., LTD

Test Date: 2024/8/1 ~ 2024/8/13

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Gina Liu , **Date:** 2024/11/6
Gina Liu / Specialist

Approved by : Jeremy Lin , **Date:** 2024/11/6
Jeremy Lin / Project Engineer

2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) | | | |
|--|---|--------|--|
| FCC Clause | Test Item | Result | Remarks |
| 15.207 | AC Power Conducted Emission | Pass | Meet the requirement of limit. Minimum passing margin is -11.41dB at 0.59655MHz. |
| 15.247(a)(1)(i) | Number of Hopping Frequency Used | Pass | Meet the requirement of limit. |
| 15.247(a)(1)(i) | Dwell Time on Each Channel | Pass | Meet the requirement of limit. |
| 15.247(a)(1)(i) | 1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System | Pass | Meet the requirement of limit. |
| 15.247(b)(2) | Maximum Peak Output Power | Pass | Meet the requirement of limit. |
| 15.205 & 209 & 15.247(d) | Radiated Emissions & Band Edge Measurement | Pass | Meet the requirement of limit. Minimum passing margin is -0.1dB at 7318.00MHz. |
| 15.247(d) | Antenna Port Emission | Pass | Meet the requirement of limit. |
| 15.203 | Antenna Requirement | Pass | No antenna connector is used. |

Note:

- 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement | Frequency | Expanded Uncertainty (k=2) (±) |
|------------------------------------|----------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 2.79 dB |
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz | 2.60 dB |
| | 30MHz ~1000MHz | 4.47 dB |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz | 2.29 dB |
| | 18GHz ~ 40GHz | 2.29 dB |

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

| | |
|---------------------|--------------------|
| Product | UHF reader |
| Brand | CIPHERLAB |
| Test Model | RS36 NUHF |
| Sample Status | Engineering sample |
| Power Supply Rating | 5 Vdc (Adapter) |
| Modulation Type | ASK |
| Operating Frequency | 902.75 ~ 927.25MHz |
| Number of Channel | 50 |
| Channel Spacing | 500kHz |
| Output Power | 341.193mW |
| Antenna Type | Refer to note |
| Antenna Connector | Refer to note |
| Accessory Device | Refer to note |
| Cable Supplied | NA |

Note:

1. The EUT uses following accessories.

| AC Adapter (Support Unit) | | |
|---------------------------|--------------|--|
| Brand | Model | Specification |
| Sunny Electronics CORP | SYS1561-1005 | AC Input : 100-240V, 50/60Hz, 0.35A DC Output : 5.0V=2.0A |

2. The antenna information is listed as below.

| Brand | Model | Antenna Type | Connector Type | Gain (dBi) |
|-------------|--|--------------|----------------|------------|
| FAVEPC INC. | KZURUPA363101 (RS36 Short Range UHFRFID Antenna US FAVEPC) | Patch | MMCX | 0.23 |

*Detail antenna specification please refer to antenna photos/or drawings, including antenna dimensions.

3.2 Description of Test Modes

50 channels are provided to this EUT:

| Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|
| 0 | 902.75 | 25 | 915.25 |
| 1 | 903.25 | 26 | 915.75 |
| 2 | 903.75 | 27 | 916.25 |
| 3 | 904.25 | 28 | 916.75 |
| 4 | 904.75 | 29 | 917.25 |
| 5 | 905.25 | 30 | 917.75 |
| 6 | 905.75 | 31 | 918.25 |
| 7 | 906.25 | 32 | 918.75 |
| 8 | 906.75 | 33 | 919.25 |
| 9 | 907.25 | 34 | 919.75 |
| 10 | 907.75 | 35 | 920.25 |
| 11 | 908.25 | 36 | 920.75 |
| 12 | 908.75 | 37 | 921.25 |
| 13 | 909.25 | 38 | 921.75 |
| 14 | 909.75 | 39 | 922.25 |
| 15 | 910.25 | 40 | 922.75 |
| 16 | 910.75 | 41 | 923.25 |
| 17 | 911.25 | 42 | 923.75 |
| 18 | 911.75 | 43 | 924.25 |
| 19 | 912.25 | 44 | 924.75 |
| 20 | 912.75 | 45 | 925.25 |
| 21 | 913.25 | 46 | 925.75 |
| 22 | 913.75 | 47 | 926.25 |
| 23 | 914.25 | 48 | 926.75 |
| 24 | 914.75 | 49 | 927.25 |

3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to | | | | Description |
|--------------------|---------------|-------|-----|------|-------------|
| | RE \geq 1G | RE<1G | PLC | APCM | |
| - | √ | √ | √ | √ | - |

Where RE \geq 1G: Radiated Emission above 1GHz & Bandedge Measurement
 RE<1G: Radiated Emission below 1GHz
 PLC: Power Line Conducted Emission
 APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type |
|--------------------|-------------------|----------------|-----------------|
| - | 0 to 49 | 0, 24, 49 | ASK |

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type |
|--------------------|-------------------|----------------|-----------------|
| - | 0 to 49 | 0, 24, 49 | ASK |

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type |
|--------------------|-------------------|----------------|-----------------|
| - | 0 to 49 | 49 | ASK |

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type |
|--------------------|-------------------|----------------|-----------------|
| - | 0 to 49 | 0, 24, 49 | ASK |

Test Condition:

| Applicable to | Environmental Conditions | Input Power | Tested by |
|---------------|--------------------------|----------------|-----------|
| RE \geq 1G | 20.6 deg. C, 73.3% RH | 120 Vac, 60 Hz | Rex Wang |
| RE<1G | 20.6 deg. C, 73.3% RH | 120 Vac, 60 Hz | Rex Wang |
| PLC | 25 deg. C, 75% RH | 120 Vac, 60 Hz | Greg Lin |
| APCM | 25 deg. C, 60% RH | 120 Vac, 60 Hz | Chris Lin |

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %, duty factor is not required.




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|-----------------|------------------------|--------------|------------|--------|-----------------------|
| A | Adapter | Sunny Electronics CORP | SYS1561-1005 | N/A | N/A | Supplied by applicant |
| B | Mobile computer | CIPHERLAB | RS36 | N/A | N/A | Supplied by applicant |

| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------------|------|------------|--------------------|--------------|-----------------------|
| 1 | Snapon | 1 | 1.0 | No | 0 | Supplied by applicant |

3.4.1 Configuration of System under Test



Under Table

Remote Site

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---------------------------------------|-----------------------------------|---------------------------------|--------------------|---------------------|
| Antenna Tower & Turn BV ADT | AT100 | AT93021705 | N/A | N/A |
| Bi_Log Antenna Schwarzbeck | VULB 9168 | 9168-160 | 2023/10/17 | 2024/10/16 |
| Loop Antenna Electro-Metrics | EM-6879 | 269 | 2023/9/23 | 2024/9/22 |
| Loop Antenna TESEQ | HLA 6121 | 64095 | 2023/9/23 | 2024/9/22 |
| MXE EMI Receiver Keysight | N9038B | MY60180018 | 2024/3/13 | 2025/3/12 |
| Preamplifier Agilent | 8447D | 2944A10638 | 2024/5/1 | 2025/4/30 |
| Preamplifier EMCI | EMC001340 | 980201 | 2023/9/27 | 2024/9/26 |
| RF Coaxial Cable Woken | 8D-FB | Cable-CH9-01 | 2024/5/1 | 2025/4/30 |
| Signal & Spectrum Analyzer R&S | FSW43 | 101867 | 2023/12/29 | 2024/12/28 |
| Software BV ADT | ADT_Radiated_ V7.6.15.9.5 | N/A | N/A | N/A |
| Turn Table BV ADT | TT100 | TT93021705 | N/A | N/A |
| Turn Table Controller BV ADT | SC100 | SC93021705 | N/A | N/A |
| Boresight antenna tower fixture BV | BAF-02 | 5 | N/A | N/A |
| Horn Antenna Schwarzbeck | BBHA 9120D | 9120D-1169 | 2023/11/12 | 2024/11/11 |
| | BBHA 9170 | 9170-480 | 2023/11/12 | 2024/11/11 |
| | | BBHA9170243 | 2023/11/12 | 2024/11/11 |
| Preamplifier Agilent | 8449B | 3008A02367 | 2024/1/6 | 2025/1/5 |
| Preamplifier EMCI | EMC 184045 | 980116 | 2023/9/27 | 2024/9/26 |
| RF Coaxial Cable EMCI | EMC102-KM-KM-600 | 150928 | 2024/7/6 | 2025/7/5 |
| | EMC102-KM-KM-3000 | 150929 | 2024/7/6 | 2025/7/5 |
| RF Coaxial Cable HUBER+SUHNER | SUCOFLEX 104 | CABLE-CH9-(250795/4) | 2024/1/6 | 2025/1/5 |
| RF Coaxial Cable HUBER+SUHNER&EMCI | SUCOFLEX 104& EMC104-SM-SM8000 | CABLE-CH9-02 (248780+171006) | 2024/1/6 | 2025/1/5 |
| Spectrum Analyzer ROHDE & SCHWARZ | FSV40 | 100980 | 2024/5/6 | 2025/5/5 |
| Peak Power Analyzer KEYSIGHT | 8990B | MY51000485 | 2024/1/21 | 2025/1/20 |
| Wideband Power Sensor KEYSIGHT | N1923A | MY58020002 | 2024/1/18 | 2025/1/17 |

Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HY- 966 chamber 4.
3. Tested date: 2024/8/1-2024/8/13

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (RMS AV) at frequency above 1GHz. The instrument settings are as follows: Sweep time: Auto; Trace count: trace average of at least 100 traces.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

| | | | |
|-----------------|-----------------|-------------------|------------------------------|
| Channel | TX Channel 0 | Detector Function | Quasi-Peak (QP) Peak (PK) |
| Frequency Range | 902MHz ~ 928MHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 902.00 | 57.2 QP | 81.7 | -24.5 | 1.60 H | 217 | 24.5 | 32.7 |
| 2 | *902.75 | 101.7 QP | | | 1.60 H | 217 | 69.0 | 32.7 |
| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 902.00 | 59.4 QP | 93.9 | -34.5 | 1.00 V | 184 | 26.7 | 32.7 |
| 2 | *902.75 | 113.9 QP | | | 1.00 V | 184 | 81.2 | 32.7 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value.
5. " * ": Fundamental frequency.

| | | | |
|-----------------|-----------------|-------------------|------------------------------|
| Channel | TX Channel 24 | Detector Function | Quasi-Peak (QP) Peak (PK) |
| Frequency Range | 902MHz ~ 928MHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | *914.75 | 110.5 QP | | | 1.89 H | 227 | 77.6 | 32.9 |
| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | *914.75 | 120.9 QP | | | 1.00 V | 181 | 88.0 | 32.9 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value.
5. " * ": Fundamental frequency.

| | | | |
|-----------------|-----------------|-------------------|------------------------------|
| Channel | TX Channel 49 | Detector Function | Quasi-Peak (QP) Peak (PK) |
| Frequency Range | 902MHz ~ 928MHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | *927.25 | 114.1 QP | | | 2.13 H | 235 | 81.0 | 33.1 |
| 2 | 928.00 | 59.5 QP | 94.1 | -34.6 | 2.13 H | 235 | 26.4 | 33.1 |
| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | *927.25 | 121.8 QP | | | 1.00 V | 183 | 88.7 | 33.1 |
| 2 | 928.00 | 64.8 QP | 101.8 | -37.0 | 1.00 V | 183 | 31.7 | 33.1 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value.
5. " * ": Fundamental frequency.

Above 1GHz Data

| | | | |
|-----------------|--------------|-------------------|---------------------------|
| Channel | TX Channel 0 | Detector Function | Peak (PK) Average (AV) |
| Frequency Range | 1GHz ~ 10GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2708.25 | 45.3 PK | 74.0 | -28.7 | 2.41 H | 260 | 46.6 | -1.3 |
| 2 | 2708.25 | 39.3 AV | 54.0 | -14.7 | 2.41 H | 260 | 40.6 | -1.3 |
| 3 | 4513.75 | 51.5 PK | 74.0 | -22.5 | 1.49 H | 166 | 48.4 | 3.1 |
| 4 | 4513.75 | 47.9 AV | 54.0 | -6.1 | 1.49 H | 166 | 44.8 | 3.1 |
| 5 | 8124.75 | 53.8 PK | 74.0 | -20.2 | 1.76 H | 242 | 42.5 | 11.3 |
| 6 | 8124.75 | 45.1 AV | 54.0 | -8.9 | 1.76 H | 242 | 33.8 | 11.3 |
| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2708.30 | 46.2 PK | 74.0 | -27.8 | 2.35 V | 222 | 47.5 | -1.3 |
| 2 | 2708.30 | 39.8 AV | 54.0 | -14.2 | 2.35 V | 222 | 41.1 | -1.3 |
| 3 | 4513.75 | 54.4 PK | 74.0 | -19.6 | 1.39 V | 145 | 51.3 | 3.1 |
| 4 | 4513.75 | 53.0 AV | 54.0 | -1.0 | 1.39 V | 145 | 49.9 | 3.1 |
| 5 | 8124.75 | 52.4 PK | 74.0 | -21.6 | 2.51 V | 160 | 41.1 | 11.3 |
| 6 | 8124.75 | 40.7 AV | 54.0 | -13.3 | 2.51 V | 160 | 29.4 | 11.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.

| | | | |
|-----------------|---------------|-------------------|---------------------------|
| Channel | TX Channel 24 | Detector Function | Peak (PK) Average (AV) |
| Frequency Range | 1GHz ~ 10GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2744.25 | 50.3 PK | 74.0 | -23.7 | 2.44 H | 176 | 51.4 | -1.1 |
| 2 | 2744.25 | 46.7 AV | 54.0 | -7.3 | 2.44 H | 176 | 47.8 | -1.1 |
| 3 | 4573.75 | 54.3 PK | 74.0 | -19.7 | 1.58 H | 190 | 51.0 | 3.3 |
| 4 | 4573.75 | 51.1 AV | 54.0 | -2.9 | 1.58 H | 190 | 47.8 | 3.3 |
| 5 | 7318.00 | 57.9 PK | 74.0 | -16.1 | 1.37 H | 229 | 47.5 | 10.4 |
| 6 | 7318.00 | 53.9 AV | 54.0 | -0.1 | 1.37 H | 229 | 43.5 | 10.4 |
| 7 | 8232.75 | 56.9 PK | 74.0 | -17.1 | 1.42 H | 210 | 45.9 | 11.0 |
| 8 | 8232.75 | 52.4 AV | 54.0 | -1.6 | 1.42 H | 210 | 41.4 | 11.0 |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2744.25 | 50.9 PK | 74.0 | -23.1 | 2.31 V | 219 | 52.0 | -1.1 |
| 2 | 2744.25 | 47.9 AV | 54.0 | -6.1 | 2.31 V | 219 | 49.0 | -1.1 |
| 3 | 4573.75 | 53.0 PK | 74.0 | -21.0 | 3.05 V | 199 | 49.7 | 3.3 |
| 4 | 4573.75 | 49.4 AV | 54.0 | -4.6 | 3.05 V | 199 | 46.1 | 3.3 |
| 5 | 7318.00 | 55.9 PK | 74.0 | -18.1 | 2.56 V | 256 | 45.5 | 10.4 |
| 6 | 7318.00 | 48.9 AV | 54.0 | -5.1 | 2.56 V | 256 | 38.5 | 10.4 |
| 7 | 8232.75 | 56.5 PK | 74.0 | -17.5 | 2.26 V | 173 | 45.5 | 11.0 |
| 8 | 8232.75 | 52.0 AV | 54.0 | -2.0 | 2.26 V | 173 | 41.0 | 11.0 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.

| | | | |
|-----------------|---------------|-------------------|---------------------------|
| Channel | TX Channel 49 | Detector Function | Peak (PK) Average (AV) |
| Frequency Range | 1GHz ~ 10GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2781.75 | 45.2 PK | 74.0 | -28.8 | 1.70 H | 218 | 46.5 | -1.3 |
| 2 | 2781.75 | 40.0 AV | 54.0 | -14.0 | 1.70 H | 218 | 41.3 | -1.3 |
| 3 | 4636.25 | 46.3 PK | 74.0 | -27.7 | 1.63 H | 220 | 42.8 | 3.5 |
| 4 | 4636.25 | 37.2 AV | 54.0 | -16.8 | 1.63 H | 220 | 33.7 | 3.5 |
| 5 | 7418.00 | 54.0 PK | 74.0 | -20.0 | 1.37 H | 228 | 43.6 | 10.4 |
| 6 | 7418.00 | 46.9 AV | 54.0 | -7.1 | 1.37 H | 228 | 36.5 | 10.4 |
| 7 | 8345.25 | 51.9 PK | 74.0 | -22.1 | 1.65 H | 242 | 41.3 | 10.6 |
| 8 | 8345.25 | 40.5 AV | 54.0 | -13.5 | 1.65 H | 242 | 29.9 | 10.6 |
| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 2781.75 | 51.9 PK | 74.0 | -22.1 | 1.97 V | 252 | 53.2 | -1.3 |
| 2 | 2781.75 | 48.6 AV | 54.0 | -5.4 | 1.97 V | 252 | 49.9 | -1.3 |
| 3 | 4636.25 | 47.1 PK | 74.0 | -26.9 | 2.06 V | 199 | 43.6 | 3.5 |
| 4 | 4636.25 | 39.7 AV | 54.0 | -14.3 | 2.06 V | 199 | 36.2 | 3.5 |
| 5 | 7418.00 | 52.4 PK | 74.0 | -21.6 | 2.00 V | 199 | 42.0 | 10.4 |
| 6 | 7418.00 | 43.2 AV | 54.0 | -10.8 | 2.00 V | 199 | 32.8 | 10.4 |
| 7 | 8345.25 | 51.8 PK | 74.0 | -22.2 | 2.54 V | 161 | 41.2 | 10.6 |
| 8 | 8345.25 | 40.2 AV | 54.0 | -13.8 | 2.54 V | 161 | 29.6 | 10.6 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " # ": The radiated frequency is out of the restricted band, the limit was restricted at the Conducted Out of Band Emissions.


Below 1GHz worst-case data:

| | | | |
|-----------------|--------------|-------------------|-----------------|
| Channel | TX Channel 0 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 30.00 | 30.6 QP | 40.0 | -9.4 | 1.49 H | 9 | 41.1 | -10.5 |
| 2 | 55.22 | 32.6 QP | 40.0 | -7.4 | 1.00 H | 184 | 41.7 | -9.1 |
| 3 | 86.26 | 28.3 QP | 40.0 | -11.7 | 1.99 H | 22 | 42.5 | -14.2 |
| 4 | 142.52 | 28.3 QP | 43.5 | -15.2 | 1.49 H | 138 | 37.1 | -8.8 |
| 5 | 187.14 | 28.0 QP | 43.5 | -15.5 | 1.00 H | 144 | 38.6 | -10.6 |
| 6 | 276.38 | 25.7 QP | 46.0 | -20.3 | 1.49 H | 226 | 33.1 | -7.4 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




| | | | |
|-----------------|--------------|-------------------|-----------------|
| Channel | TX Channel 0 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 31.94 | 23.7 QP | 40.0 | -16.3 | 1.99 V | 201 | 34.3 | -10.6 |
| 2 | 57.16 | 29.8 QP | 40.0 | -10.2 | 1.00 V | 7 | 39.2 | -9.4 |
| 3 | 83.35 | 27.1 QP | 40.0 | -12.9 | 1.50 V | 258 | 41.0 | -13.9 |
| 4 | 167.74 | 25.7 QP | 43.5 | -17.8 | 1.99 V | 13 | 34.2 | -8.5 |
| 5 | 614.91 | 28.4 QP | 46.0 | -17.6 | 1.00 V | 7 | 29.0 | -0.6 |
| 6 | 946.65 | 35.7 QP | 46.0 | -10.3 | 1.50 V | 6 | 30.4 | 5.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




| | | | |
|-----------------|---------------|-------------------|-----------------|
| Channel | TX Channel 24 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 30.00 | 27.0 QP | 40.0 | -13.0 | 1.00 H | 178 | 37.5 | -10.5 |
| 2 | 57.16 | 23.7 QP | 40.0 | -16.3 | 2.00 H | 7 | 33.1 | -9.4 |
| 3 | 99.84 | 23.6 QP | 43.5 | -19.9 | 1.00 H | 176 | 36.8 | -13.2 |
| 4 | 186.17 | 28.0 QP | 43.5 | -15.5 | 2.00 H | 145 | 38.5 | -10.5 |
| 5 | 261.83 | 31.1 QP | 46.0 | -14.9 | 1.50 H | 6 | 39.3 | -8.2 |
| 6 | 922.40 | 37.4 QP | 46.0 | -8.6 | 1.00 H | 151 | 32.1 | 5.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




| | | | |
|-----------------|---------------|-------------------|-----------------|
| Channel | TX Channel 24 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 57.16 | 29.8 QP | 40.0 | -10.2 | 1.50 V | 180 | 39.2 | -9.4 |
| 2 | 96.93 | 27.1 QP | 43.5 | -16.4 | 1.00 V | 15 | 40.8 | -13.7 |
| 3 | 151.25 | 23.9 QP | 43.5 | -19.6 | 2.00 V | 15 | 32.2 | -8.3 |
| 4 | 187.14 | 22.0 QP | 43.5 | -21.5 | 1.00 V | 7 | 32.6 | -10.6 |
| 5 | 464.56 | 27.7 QP | 46.0 | -18.3 | 2.00 V | 237 | 31.2 | -3.5 |
| 6 | 940.83 | 33.5 QP | 46.0 | -12.5 | 1.00 V | 113 | 28.2 | 5.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




| | | | |
|-----------------|---------------|-------------------|-----------------|
| Channel | TX Channel 49 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Horizontal at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 30.00 | 27.5 QP | 40.0 | -12.5 | 1.00 H | 169 | 38.0 | -10.5 |
| 2 | 67.83 | 24.7 QP | 40.0 | -15.3 | 2.00 H | 97 | 35.2 | -10.5 |
| 3 | 99.84 | 24.0 QP | 43.5 | -19.5 | 1.50 H | 145 | 37.2 | -13.2 |
| 4 | 189.08 | 27.9 QP | 43.5 | -15.6 | 1.50 H | 145 | 38.7 | -10.8 |
| 5 | 266.68 | 33.0 QP | 46.0 | -13.0 | 1.00 H | 204 | 40.9 | -7.9 |
| 6 | 922.40 | 39.5 QP | 46.0 | -6.5 | 1.00 H | 100 | 34.2 | 5.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




| | | | |
|-----------------|---------------|-------------------|-----------------|
| Channel | TX Channel 49 | Detector Function | Quasi-Peak (QP) |
| Frequency Range | 9kHz ~ 1GHz | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 57.16 | 30.3 QP | 40.0 | -9.7 | 1.00 V | 326 | 39.7 | -9.4 |
| 2 | 75.59 | 25.9 QP | 40.0 | -14.1 | 1.00 V | 350 | 38.1 | -12.2 |
| 3 | 151.25 | 23.4 QP | 43.5 | -20.1 | 1.50 V | 298 | 31.7 | -8.3 |
| 4 | 167.74 | 22.8 QP | 43.5 | -20.7 | 1.00 V | 253 | 31.3 | -8.5 |
| 5 | 548.95 | 27.0 QP | 46.0 | -19.0 | 2.00 V | 30 | 29.3 | -2.3 |
| 6 | 922.40 | 34.5 QP | 46.0 | -11.5 | 1.00 V | 4 | 29.2 | 5.3 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) | |
|-----------------|------------------------|---------|
| | Quasi-peak | Average |
| 0.15 - 0.5 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 56 | 46 |
| 5.0 - 30.0 | 60 | 50 |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

| Description & Manufacturer | Model No. | Serial No. | Cal. Date | Cal. Due |
|-------------------------------------|----------------------|----------------|-----------|-----------|
| LISN R&S | ESH2-Z5 | 100100 | 2024/3/6 | 2025/3/5 |
| LISN Schwarzbeck | NNLK 8121 | 8121-731 | 2024/6/12 | 2025/6/11 |
| Receiver R&S | ESCI | 100412 | 2023/8/23 | 2024/8/22 |
| RF Coaxial Cable WORKEN | 5D-FB | Cable-cond2-01 | 2023/9/2 | 2024/9/1 |
| Software BVADT | BVADT_Conc_ V7.3.7.4 | N/A | N/A | N/A |
| Temperature&Humidity Meter Lufft | 5098.00 | Lf11015 | 2024/1/4 | 2025/1/3 |
| V-LISN Schwarzbeck | NNBL 8226-2 | 8226-142 | 2023/8/31 | 2024/8/30 |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2 (Conduction 2).

3. The VCCI Site Registration No. is C-12047.

4. Tested date: 2024/8/9

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|---------|---------------|-------------------|--------------------------------|
| Channel | TX Channel 49 | | |

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|----------------|-------------------------|----------------------------|--------------|-----------------------------|--------------|--------------------|--------------|----------------|---------------|
| | | | | | | | | | | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.16932 | 10.40 | 19.43 | 11.67 | 29.83 | 22.07 | 64.99 | 54.99 | -35.16 | -32.92 |
| 2 | 0.32200 | 10.47 | 19.70 | 11.79 | 30.17 | 22.26 | 59.66 | 49.66 | -29.49 | -27.40 |
| 3 | 0.41000 | 10.51 | 18.75 | 9.76 | 29.26 | 20.27 | 57.65 | 47.65 | -28.39 | -27.38 |
| 4 | 0.59655 | 10.53 | 29.09 | 24.06 | 39.62 | 34.59 | 56.00 | 46.00 | -16.38 | -11.41 |
| 5 | 1.92600 | 10.57 | 18.19 | 11.93 | 28.76 | 22.50 | 56.00 | 46.00 | -27.24 | -23.50 |
| 6 | 4.15800 | 10.67 | 19.20 | 10.45 | 29.87 | 21.12 | 56.00 | 46.00 | -26.13 | -24.88 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




| | | | |
|---------|---------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Channel | TX Channel 49 | | |

| No | Freq. [MHz] | Corr. Factor (dB) | Reading Value [dB (uV)] | | Emission Level [dB (uV)] | | Limit [dB (uV)] | | Margin (dB) | |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
| | | | | | | | | | | |
| | | | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. | Q.P. | AV. |
| 1 | 0.19013 | 10.46 | 23.33 | 12.66 | 33.79 | 23.12 | 64.03 | 54.03 | -30.24 | -30.91 |
| 2 | 0.35594 | 10.54 | 13.28 | 4.17 | 23.82 | 14.71 | 58.82 | 48.82 | -35.00 | -34.11 |
| 3 | 0.44600 | 10.56 | 13.97 | 4.67 | 24.53 | 15.23 | 56.95 | 46.95 | -32.42 | -31.72 |
| 4 | 0.58719 | 10.57 | 24.94 | 15.41 | 35.51 | 25.98 | 56.00 | 46.00 | -20.49 | -20.02 |
| 5 | 1.75800 | 10.61 | 12.93 | 3.36 | 23.54 | 13.97 | 56.00 | 46.00 | -32.46 | -32.03 |
| 6 | 4.33400 | 10.76 | 19.75 | 5.98 | 30.51 | 16.74 | 56.00 | 46.00 | -25.49 | -29.26 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

The 20 dB bandwidth of the hopping channel is less than 250 kHz, at least 50 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure


- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- Set the SA on View mode and then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 50 hopping frequencies in the hopping mode. On the plots, it shows that the hopping frequencies are equally spaced.



4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period. (If the 20 dB bandwidth of the hopping channel is less than 250 kHz)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard


No deviation.

4.4.6 Test Results

| Number of transmission in a period | Length of transmission time (msec) | Result (msec) | Limit (msec) |
|------------------------------------|------------------------------------|---------------|--------------|
| 2 time | 197.6 | 395.2 | 400 |

Note:

- Test plots of the transmitting time slot are shown as below.
- Calculator Result = 2 time * 197.6 = 395.2



4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

The maximum allowed 20 dB bandwidth of the hopping channel is 250 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.


4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) | Limit (MHz) |
|---------|-----------------|----------------------|-------------|
| 0 | 902.75 | 0.06 | 0.25 |
| 24 | 914.75 | 0.06 | 0.25 |
| 49 | 927.25 | 0.06 | 0.25 |

Note: 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period.




4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF


- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- By using the MaxHold function record the separation of two adjacent channels.
- Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

| Channel | Frequency (MHz) | Adjacent Channel Separation (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|-----------------------------------|---------------------|-------------|
| 0 | 902.75 | 0.506 | 0.06 | Pass |
| 24 | 914.75 | 0.500 | 0.06 | Pass |
| 49 | 927.25 | 0.503 | 0.06 | Pass |




4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

For Peak Power

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

For Average Power

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

For Peak Power

| Channel | Frequency (MHz) | Output Power (mW) | Output Power (dBm) | Power Limit (dBm) | Pass / Fail |
|---------|-----------------|-------------------|--------------------|-------------------|-------------|
| 0 | 902.75 | 144.877 | 21.61 | 30 | Pass |
| 24 | 914.75 | 337.287 | 25.28 | 30 | Pass |
| 49 | 927.25 | 341.193 | 25.33 | 30 | Pass |

For Average Power

| Channel | Frequency (MHz) | Average Power (mW) | Average Power (dBm) |
|---------|-----------------|--------------------|---------------------|
| 0 | 902.75 | 143.549 | 21.57 |
| 24 | 914.75 | 334.195 | 25.24 |
| 49 | 927.25 | 338.065 | 25.29 |

4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits Of Conducted Out Of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.



4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.



4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.



Hopping disabled Low Channel



Hopping disabled High Channel



Hopping enabled



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---