

TABLE OF CONTENTS

APPLICANT:  RADIOSHACK, A DIV.OF TANDY CORP.

FCC ID:       AAO6004269

TEST REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST AND TEST PROCEDURE  
PAGE 2.....TEST PROCEDURE AND CIRCUIT DESCRIPTION  
PAGE 3.....RADIATION INTERFERENCE TEST DATA  
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER  
EXHIBIT 2.....BLOCK DIAGRAM  
EXHIBIT 3.....SCHEMATIC  
EXHIBIT 4A-4E.....INSTRUCTION MANUAL  
EXHIBIT 5.....SAMPLE OF FCC ID LABEL  
EXHIBIT 6.....LOCATION OF FCC ID LABEL  
EXHIBIT 7.....EXTERNAL PHOTO - FRONT SIDE  
EXHIBIT 8.....EXTERNAL PHOTO - BACK SIDE  
EXHIBIT 9.....INTERNAL PHOTO - COMPONENT SIDE  
EXHIBIT 10.....INTERNAL PHOTO - COPPER SIDE  
EXHIBIT 11.....OCCUPIED BANDWIDTH PLOT  
EXHIBIT 12.....OCCUPIED BAND EDGE PLOT

APPLICANT:  RADIOSHACK, A DIV.OF TANDY CORP.

FCC ID:  AAO6004269

REPORT #:  T:\CUS\R\RADSHACK\RAD154H0\RAD154H0.RPT

PAGE:  TABLE OF CONTENTS LIST

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID: AAO6004269

#### TEST EQUIPMENT LIST

- 1.\_X\_Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/  
preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter  
HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02,  
S/N 3008A00372 Cal. 10/17/99
- 2.\_X\_Biconnical Antenna: Eaton Model 94455-1, S/N 1057
- 3.\_X\_Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
- 4.\_\_\_Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180,  
1-18 GHz, S/N 2319 Cal. 4/27/99
- 5.\_\_\_Horn 40-60GHz: ATM Part #19-443-6R
- 6.\_\_\_Line Impedance Stabilization Network: Electro-Metrics Model  
ANS-25/2, S/N 2604 Cal. 2/9/00
- 7.\_\_\_Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
- 8.\_\_\_Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
- 9.\_\_\_Peak Power Meter: HP Model 8900C, S/N 2131A00545 Cal 7/19/99
- 10.\_\_\_Open Area Test Site #1-3meters Cal. 12/22/99
- 11.\_\_\_Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
- 12.\_\_\_Signal Generator: HP 8614A, S/N 2015A07428 Cal. 5/29/99
- 13.\_\_\_Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N  
9706-1211 Cal. 6/23/97
- 14.\_\_\_Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153  
Cal. 11/24/99
- 15.\_\_\_AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
- 16.\_\_\_Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
- 17.\_\_\_Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
- 18.\_\_\_Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

#### TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 72o with a humidity of 75%.

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID: AAO6004269  
REPORT #: T:\CUS\R\RADSHACK\RAD154H0\RAD154H0.RPT  
PAGE #: 1

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID: AAO6004269

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

#### CIRCUIT DESCRIPTION:

In the transmit mode the momentary switches SW-L, SW-R, SW-B, & SW-F provide input to the encoder intergrated circuit U1. The output of U1 modulated the RF oscillator Q1 by varing the emitter current of that stage. The RF frequency is determined by the crystal Y1. The output of Q1 is coupled through C10 to the base of the RF amplifier Q2. From Q2 the signal is fed into the tuned circuit made up of L3/C5 & then to the low pass filter made up of C7/L2/C8 and is then fed to the antenna.

#### ANTENNA AND GROUND CIRCUITRY

This unit makes use of a short, antenna. The antenna is inductively coupled. The antenna is self contained, no provision is made for an external antenna. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID: AAO6004269  
REPORT #: T:\CUS\R\RADSHACK\RAD154H0\RAD154H0.RPT  
PAGE #: 2

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.

FCC ID: AAO6004269

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.227

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.  
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M
216 - 960 MHz	46.0 dBuV/M
ABOVE 960 MHz	54.0 dBuV/M

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR dB	PEAK FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
27.15	59.50	0.20	11.75	71.45	8.55	V
54.29	15.40	0.80	9.61	25.81	14.19	V
108.58	10.20	0.80	8.38	19.38	24.12	V
190.02	2.90	0.90	13.67	17.47	26.03	V
244.31	5.40	1.20	13.21	19.81	26.19	V
271.45	9.80	1.40	14.00	25.20	20.80	V
298.60	13.10	1.40	15.61	30.11	15.89	V
325.74	14.90	1.40	14.85	31.15	14.85	V
352.89	9.50	1.40	15.63	26.53	19.47	V

SAMPLE CALCULATION:  $FSdBuV/m = MR(dBuV) + ACFdB$ .

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: \_\_\_\_\_ DATE: MAY 15, 2000

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.

FCC ID: AAO6004269

REPORT #: T:\CUS\R\RADSHACK\RAD154H0\RAD154H0.RPT

PAGE #: 3

APPLICANT:               RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID:                 AAO6004269  
NAME OF TEST:           Occupied Bandwidth  
RULES PART NO.:        15.227  
REQUIREMENTS:         The field strength of any emissions appearing  
                          outside the 26.96-27.28 MHz band shall not  
                          exceed 100 uV/m (15.209).

THE GRAPH IN EXHIBIT 11 & 12 REPRESENTS THE WORSE CASE OCCUPIED  
BANDWIDTH EMISSIONS FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output  
was fed into the spectrum analyzer and the attached plot was  
taken. The vertical scale is set to -10 dBm per division. The  
horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: \_\_\_\_\_ MAY 15, 2000

APPLICANT: RADIOSHACK, A DIV.OF TANDY CORP.  
FCC ID: AAO6004269  
REPORT #: T:\CUS\R\RADSHACK\RAD154H0\RAD154H0.RPT  
PAGE #: 4