

Page : 1 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

# **Maximum Permissible Exposure Report**

**Product**: Wireless Headset

**Model Name** : A00151

**FCC ID** : JNZA00151

**Test Regulation** : 47 CFR FCC Part 2.1093

**Received Date** : 2021/11/15

**Test Date** : 2021/11/10 ~ 2021/11/18

**Issued Date** : 2021/12/20

**Applicant** : Logitech Far East Ltd.

#2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan,

R.O.C.

**Issued By** : Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd.,

Zhudong Township, Hsinchu County, Taiwan





The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948

Doc No: 17-EM-F0864 / 5.0



Page : 2 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

# **REVISION HISTORY**

Original Test Report No.: 4790181997-US-R2-V0

Rev.	Test report No. 4790181997-US-R2-V0	Date	Page revised	Contents
Original	4790181997-US-R2-V0	2021/12/20	-	Initial issue
<u> </u>				
-				
-				



Doc No: 17-EM-F0864 / 5.0

Page : 3 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

# **Table of Contents**

1.	Attestation of Test Results	4
2.	Test Methodology and Reference Procedures	5
3.	Facilities and Accreditation	5
4.	Equipment Under Test	6
4	1.1. Description of EUT	6
5.	Requirement	9
6.	Radio Frequency SAR Test Exclusion Thresholds	10



Page : 4 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

### 1. Attestation of Test Results

**APPLICANT:** Logitech Far East Ltd.

#2 Creation Rd. 4, Science-Based Ind. Park Hsinchu Taiwan, R.O.C.

**MANUFACTURER:** Logitech Europe S.A.

EPFL – Quartier de I'Innovation, Daniel Borel Innovation Center,

1015 Lausanne, Switzerland

**EUT DESCRIPTION:** Wireless Headset

**BRAND:** logitech G

**MODEL:** A00151

**SAMPLE STAGE:** Engineering Verification Test sample

#### APPLICABLE STANDARDS

**STANDARD** 

**Test Results** 

47 CFR FCC PART 2.1093

**PASS** 

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By: Approved and Authorized By:

Sally Lu Date: 2021/12/20 Waternil Guan Date: 2021/12/20

Project Handler Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX): +886-3-583-7948 Doc No: 17-EM-F0864 / 5.0



Doc No: 17-EM-F0864 / 5.0

Page : 5 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

## 2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

### 3. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.	
Address	Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan	
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.	



Page : 6 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

# 4. Equipment Under Test

## 4.1. Description of EUT

Product Name	Wireless Headset			
Brand Name	logitech G			
Model Name	A00151			
O 41 F	Bluetooth EDR	2402MHz ~ 2480MHz		
Operating Frequency	SRD	2403.35MHz ~ 2477.35MHz		
M. J. J. J. C.	Bluetooth EDR	GFSK, π/4-DQPSK and 8DPSK		
Modulation	SRD	GFSK		
N. 1 0.01	Bluetooth EDR	79		
Number of Channel	SRD	38		
Normal Voltage	3.7Vdc from battery			
Normal Voltage	5Vdc from host			
S/N	2141LZ05QFW8			
Comple ID	Conducted Test: 4383734			
Sample ID	Radiated Test: 4383731			



Page : 7 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

#### Note:

1. The EUT contains following accessory devices:

	The Bet contains following decessory devices.						
Product Brand		Model	Description				
USB Cable	logitech G	USB-C to USB-A Charging Cable	Length: 1.9m				
MIC	logitech G	A00166	-				
Extender USB adapter	logitech G	502-001387	-				

2. The EUT could be option supplied with rechargeable battery as the following table:

Brand Name	Model No.	Spec.	
HIGHPOWER	533-000181 / 604050	1500mAh 3.7V 5.55Wh	

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.



Page : 8 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

## 4.2. Description of Available Antennas

#### **Bluetooth EDR**

Ant. No.	Transmitter Circuit	Ant. Type	Maximum Gain (dBi)	
BT	Chain (0)	Wire	0.71	

### **SRD**

Ant. No.	Transmitter Circuit	Ant. Type	Maximum Gain (dBi)	
Ant0	Chain (0)	PCB	-4.7	
Ant1	Chain (1)	PCB	-8	

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



Page : 9 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

## 5. Requirement

Following FCC KDB 447498 D01 "General SAR test exclusion guidance"

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- ► f(GHz) is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance 50mm)·( f(MHz)/150)] mW, at 100MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)  $\cdot$  10] mW at > 1500 MHz and  $\leq$  6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(MHz))]$  for test separation distances > 50 mm and < 200 mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 5.0



Page : 10 of 10 Issued date : 2021/12/20 FCC ID : JNZA00151

## 6. Radio Frequency SAR Test Exclusion Thresholds

Operating Mode	Evaluation Frequency	Max. Average power	Antenna Gain	Min. test separation distance	SAR test exclusion calculation	1-g SAR test exclusion thresholds	Result
	(MHz)	(mW)	(dBi)	(mm)	value	uiresnoias	
BT-GFSK	2480	1.824	0.71	5	0.574	3	PASS
SRD	2477.35	1.038	-4.71	5	0.327	3	PASS

#### Note:

### **Conclusion:**

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

**END OF REPORT** 

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 5.0

<sup>1.</sup> Calculate SAR test exclusion thresholds from section 5.1 formulas.