

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DLLYNXREN-4**

Date : 6/30/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : LYNXR-EN_ver13.1

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	72.20	1.2	14.78	25644.8	15.0%	3846.7	7292
690	H	36.00	1.8	19.10	699.8	15.0%	105.0	729
1035	H	31.00	2.2	22.70	623.7	15.0%	93.6	500
1380	H	30.00	2.5	24.96	746.4	15.0%	112.0	500
1725	H	25.00	2.8	27.55	585.5	15.0%	87.8	729
2070	H	25.00	3.0	29.52	751.6	15.0%	112.7	729
2415	H	25.00	3.3	31.13	936.5	15.0%	140.5	729
2760	H	25.00	3.7	31.50	1023.3	15.0%	153.5	500
3105	H	25.00	4.1	31.61	1085.2	15.0%	162.8	729
3450	H	25.00	4.4	32.22	1205.0	15.0%	180.8	729
4000			CABLE "A"	BICONILOG				