

产品规格承认书

SPECIFICATIONS

客户:

CUSTOMER: _____

产品名称:

DESCRIPTION: _____ Chip Antenna

客户型号:

CUSTOMER PART NO: _____

产品型号:

OUR MODEL NO: _____ PBX2012MA01

日期:

DATE: _____ 2020/12/22

PBX2012MA01 Specification

Operating Temp. : -40°C~+85°C


1. FEATURES:

- Light weight, compact
- Wide bandwidth, low cost
- Built-in antenna with high gain

2. APPLICATIONS:

- Bluetooth, Wireless LAN, Mobile TV
- Home RF System, etc


3. PRODUCT IDENTIFICATION



(1) Product type: Multilayer chip Antenna

(2) External Dimensions (L×W) (mm): 2.0×1.2

4. SHAPE AND DIMENSIONS:




SHAPE AND DIMENSIONS

L	W	H	A
2.0±0.2	1.2±0.2	0.55±0.1	0.4±0.1


TERMINAL-CONFIGURATION



EVALUATION BOARD



APPLICATION GUIDE



5. SPECIFICATIONS:


ITEM	SPECIFICATION
Frequency Band	2400MHz~2483MHz
VSWR	Less than 3
Polarization	Linear
*Peak Gain	2.48 dBi Typ.
*Peak Efficiency	72.6% Typ.
Impedance	50 Ω Typ.

* Test condition: Test board size 98*65 mm

Matching circuit: Pi matching circuit will be required

6. Electrical Characteristics :


VSWR




Mark	Frequency	VSWR
1	2400 MHz	3.04
2	2450 MHz	1.15
3	2500 MHz	2.57

Radiation Pattern

The Gain pattern is measured in INPAQ's FAR-field chamber. DUT is placed on the table of rotator,a standard horn antenna and Vector Network Analyzer is used to collect data.



© **3D Gain Pattern (2400 MHz)**



© **2D Gain Pattern (2400 MHz)**

