

承认书

SPECIFICATION FOR APPROVAL

客户名称 (CUSTOMER) 深圳市立景科技有限公司

客户料号 (CUSTOMER P/N) : 磁吸线圈

品名 (DESCRIPTION) : DATE:2023/11/8

规格 (SPECIFICATION) : G43开槽+背胶 0.07*100 10UH 30长 REV.NO.:A0

鸿日昇威科技承认签核、盖章

部门	确认/日期	审核/日期	批准/日期	(盖公司公章)
品质	董晚红	吕惠	韦函满	
工程	何伟华	韦红	韦红	

备注:

立景科技承认签核、盖章

部门	确认/日期	审核/日期	批准/日期	(盖公司公
----	-------	-------	-------	-------

开发工程				章
采购				
品质				
备注：				
深圳市鸿日昇威科技有限公司 HRSW ELECTRONICS CO.,LTD ADD: 深圳市龙华新区观澜环观中路48号1栋2楼 TEL: 13682412162 page:1/2				

SPECIFICATION FOR APPROVAL

1.MECHANICAL DIMENSION (UNIT:mm)

2. SCHEMATICS:

- 1.Coil attached magnetic sheet, magnetic sheet size:43.5mm±0.5MM, thickness:0.8±0.05mm, open L-line slot.
2. Coil outlet position wrap adhesive tape 1-2Ts;
3. The bottom of the magnet insulation sheet should be glued.

	A	B	C	D2	E	H	I		F	
	41.5±0.3	13.5±0.3	0.8±0.05	30±2	3±1	2.3MAX	5±1		43.3+0-0.3	
3.WINDING:										
STE P	START-FINISH		WIRE TYPE				TURNS		TAPE	REMAR K
N1	S-F		silk covered wireø0.07* 100mm 2UEW				15TS (Ref)			
4. ELECTRICAL SPECIFICATION:										
ITEM	L		DCR		L				HI-POT	
TES T CON	Coil+ magnetic sheet		S-F		Individual coil					
	100KHz, 0.25V		AT 25℃		100KHz, 0.25V					
SPEC	10uH+0-1		80mΩ Max		6.2uH±10%					
5.BILF OF MATERIAL:										
NO.	ITEM		MATERIAL SPECIFICATION				MANUFACTURER		SGS NO.	
1	silk covered wire 0.07* 100 strand		Acetone silk covered wire 0.07* 100 strand				NANJINGJINNINGCO,LTD			
2	Lead-free tin strip		Lead-free tin strip				QIAODO			
3	Magnetic sheet		Ø 44*0.8 Manganese-zinc hard magnetic sheet with L slot				TAIYI CO.,LTD			
4	Adhesive		Chloroprene Adhesive9999				LIANCHENG CO.,LTD			
5	High temperature adhesive tape		7mm wide high temperature adhesive tape				CUDAK CO.,LTD			
6	Back Adhesive		Ø 41.5*0.1/3M				CUDAK CO.,LTD			
HRSW ELECTRONICS CO.,LTD						PART NO		G43.5 with slot + Back adhesive 10UH		
						TITLE				

DRAWN BY	CHECKED BY	APPROVED BY
He weihua	Wei lihong	Wei lihong